

# TenarisHydril Wedge 511® and TenarisHydril Wedge 511® Dopeless® Blanking Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, recopied, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections B.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request therefore. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyrighted 2021 as an unpublished work. ALL RIGHTS RESERVED.

CONNECTION							PIN						BOX							
SIZE (IN)	WEIGHT (LB/FT)	WALL (IN)	PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH	RECUT LENGTH	INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH	RECUT LENGTH	INSIDE DIAMETER		OUTSIDE DIAMETER - MACHINED OD		OUTSIDE DIAMETER - AS ROLLED	
							MIN	MIN	MIN	MAX	MIN	MAX	MIN	MIN	MIN	MAX	MIN	MAX*	MIN	MAX*
2.063	3.25	0.156	TenarisHydril Wedge 511®	Standard	1.657	Standard API Drift	2.99 in (76.0 mm)	1.63 in (41.4 mm)	1.676 in (42.58 mm)	1.696 in (43.06 mm)	2.053 in (52.16 mm)	2.073 in (52.64 mm)	2.99 in (76.0 mm)	1.63 in (41.4 mm)	1.741 in (44.24 mm)	1.761 in (44.72 mm)	2.116 in (53.76 mm)	2.136 in (54.24 mm)	N/A	N/A
2.063	4.50	0.225	TenarisHydril Wedge 511®	Standard	1.519	Standard API Drift	2.99 in (76.0 mm)	1.63 in (41.4 mm)	1.538 in (39.08 mm)	1.558 in (39.56 mm)	2.053 in (52.16 mm)	2.073 in (52.64 mm)	2.99 in (76.0 mm)	1.63 in (41.4 mm)	1.603 in (40.72 mm)	1.623 in (41.22 mm)	2.116 in (53.76 mm)	2.136 in (54.24 mm)	N/A	N/A
2.375	4.60	0.190	TenarisHydril Wedge 511®	Standard	1.901	Standard API Drift	2.99 in (76.0 mm)	1.63 in (41.4 mm)	1.920 in (48.78 mm)	1.940 in (49.26 mm)	2.365 in (60.08 mm)	2.385 in (60.56 mm)	2.99 in (76.0 mm)	1.63 in (41.4 mm)	2.005 in (50.92 mm)	2.025 in (51.42 mm)	2.396 in (60.86 mm)	2.416 in (61.36 mm)	N/A	N/A
2.375	5.10	0.218	TenarisHydril Wedge 511®	Standard	1.845	Standard API Drift	2.99 in (76.0 mm)	1.63 in (41.4 mm)	1.877 in (47.68 mm)	1.897 in (48.18 mm)	2.365 in (60.08 mm)	2.385 in (60.56 mm)	2.99 in (76.0 mm)	1.63 in (41.4 mm)	1.949 in (49.00 mm)	1.929 in (49.50 mm)	2.396 in (60.86 mm)	2.416 in (61.36 mm)	N/A	N/A
2.375	6.30	0.280	TenarisHydril Wedge 511®	Standard	1.721	Standard API Drift	3.96 in (100.6 mm)	1.72 in (43.6 mm)	1.740 in (44.20 mm)	1.760 in (44.70 mm)	2.365 in (60.08 mm)	2.385 in (60.56 mm)	3.96 in (100.6 mm)	1.72 in (43.6 mm)	1.805 in (45.86 mm)	1.825 in (46.34 mm)	2.396 in (60.86 mm)	2.416 in (61.36 mm)	N/A	N/A
2.875	6.40	0.217	TenarisHydril Wedge 511®	Standard	2.347	Standard API Drift	2.99 in (76.0 mm)	1.63 in (41.4 mm)	2.367 in (60.14 mm)	2.387 in (60.62 mm)	2.865 in (72.78 mm)	2.885 in (73.26 mm)	2.99 in (76.0 mm)	1.63 in (41.4 mm)	2.431 in (61.76 mm)	2.451 in (62.24 mm)	N/A	N/A	2.875 in (73.04 mm)	2.906 in (73.80 mm)
2.875	6.40	0.217	TenarisHydril Wedge 511®	ExxonMobil CTP ALL	2.347	Standard API Drift	2.99 in (76.0 mm)	1.63 in (41.4 mm)	2.367 in (60.14 mm)	2.387 in (60.62 mm)	2.865 in (72.78 mm)	2.885 in (73.26 mm)	2.99 in (76.0 mm)	1.63 in (41.4 mm)	2.431 in (61.76 mm)	2.451 in (62.24 mm)	N/A	N/A	2.875 in (73.04 mm)	2.906 in (73.80 mm)
3.500	7.70	0.216	TenarisHydril Wedge 511®	Standard	2.943	Standard API Drift	3.47 in (88.0 mm)	1.63 in (41.4 mm)	2.963 in (75.28 mm)	2.983 in (75.76 mm)	3.490 in (88.66 mm)	3.510 in (89.14 mm)	3.47 in (88.0 mm)	1.63 in (41.4 mm)	3.058 in (77.68 mm)	3.078 in (78.18 mm)	N/A	N/A	3.500 in (88.90 mm)	3.531 in (89.68 mm)
3.500	7.70	0.216	TenarisHydril Wedge 511®	SPR.0049	2.943	Standard API Drift	3.47 in (88.0 mm)	1.63 in (41.4 mm)	2.998 in (75.66 mm)	2.998 in (76.14 mm)	3.490 in (88.66 mm)	3.510 in (89.14 mm)	3.47 in (88.0 mm)	1.63 in (41.4 mm)	3.058 in (77.68 mm)	3.078 in (78.18 mm)	N/A	N/A	3.500 in (88.90 mm)	3.531 in (89.68 mm)
3.500	9.20	0.254	TenarisHydril Wedge 511®	Standard	2.867	Standard API Drift	3.47 in (88.0 mm)	1.63 in (41.4 mm)	2.887 in (73.34 mm)	2.907 in (73.82 mm)	3.490 in (88.66 mm)	3.510 in (89.14 mm)	3.47 in (88.0 mm)	1.63 in (41.4 mm)	2.982 in (75.76 mm)	3.002 in (76.24 mm)	N/A	N/A	3.500 in (88.90 mm)	3.531 in (89.68 mm)
3.500	9.20	0.254	TenarisHydril Wedge 511®	ExxonMobil CTP ALL	2.867	Standard API Drift	3.47 in (88.0 mm)	1.63 in (41.4 mm)	2.887 in (73.34 mm)	2.907 in (73.82 mm)	3.490 in (88.66 mm)	3.510 in (89.14 mm)	3.47 in (88.0 mm)	1.63 in (41.4 mm)	2.982 in (75.76 mm)	3.002 in (76.24 mm)	N/A	N/A	3.500 in (88.90 mm)	3.531 in (89.68 mm)
3.500	9.20	0.254	TenarisHydril Wedge 511®	Shell Level A,B	2.867	Standard API Drift	3.47 in (88.0 mm)	1.63 in (41.4 mm)	2.887 in (73.34 mm)	2.907 in (73.82 mm)	3.490 in (88.66 mm)	3.510 in (89.14 mm)	3.47 in (88.0 mm)	1.63 in (41.4 mm)	2.982 in (75.76 mm)	3.002 in (76.24 mm)	N/A	N/A	3.500 in (88.90 mm)	3.531 in (89.68 mm)
3.500	10.20	0.289	TenarisHydril Wedge 511®	Standard	2.797	Standard API Drift	3.47 in (88.0 mm)	1.63 in (41.4 mm)	2.817 in (71.56 mm)	2.837 in (72.04 mm)	3.490 in (88.66 mm)	3.510 in (89.14 mm)	3.47 in (88.0 mm)	1.63 in (41.4 mm)	2.912 in (73.98 mm)	2.932 in (74.46 mm)	N/A	N/A	3.500 in (88.90 mm)	3.531 in (89.68 mm)
4.000	9.50	0.226	TenarisHydril Wedge 511®	Standard	3.423	Standard API Drift	3.47 in (88.0 mm)	1.63 in (41.4 mm)	3.444 in (87.48 mm)	3.464 in (87.98 mm)	3.990 in (101.36 mm)	4.010 in (101.84 mm)	3.47 in (88.0 mm)	1.63 in (41.4 mm)	3.538 in (89.88 mm)	3.558 in (90.36 mm)	N/A	N/A	4.000 in (101.60 mm)	4.031 in (102.38 mm)
4.000	11.00	0.262	TenarisHydril Wedge 511®	Standard	3.351	Standard API Drift	3.47 in (88.0 mm)	1.63 in (41.4 mm)	3.372 in (85.66 mm)	3.392 in (86.14 mm)	3.990 in (101.36 mm)	4.010 in (101.84 mm)	3.47 in (88.0 mm)	1.63 in (41.4 mm)	3.466 in (88.04 mm)	3.486 in (88.54 mm)	N/A	N/A	4.000 in (101.60 mm)	4.031 in (102.38 mm)
4.000	11.60	0.286	TenarisHydril Wedge 511®	Standard	3.303	Standard API Drift	3.47 in (88.0 mm)	1.63 in (41.4 mm)	3.324 in (84.44 mm)	3.344 in (84.92 mm)	3.990 in (101.36 mm)	4.010 in (101.84 mm)	3.47 in (88.0 mm)	1.63 in (41.4 mm)	3.418 in (86.82 mm)	3.438 in (87.32 mm)	4.021 in (102.14 mm)	4.041 in (102.64 mm)	N/A	N/A
4.000	11.60	0.286	TenarisHydril Wedge 511®	Exxon Mobil CTP ALL	3.303	Standard API Drift	3.47 in (88.0 mm)	1.63 in (41.4 mm)	3.324 in (84.44 mm)	3.344 in (84.92 mm)	3.990 in (101.36 mm)	4.010 in (101.84 mm)	3.47 in (88.0 mm)	1.63 in (41.4 mm)	3.418 in (86.82 mm)	3.438 in (87.32 mm)	4.021 in (102.14 mm)	4.041 in (102.64 mm)	N/A	N/A
4.000	16.10	0.415	TenarisHydril Wedge 511®	Standard	3.045	Standard API Drift	4.43 in (112.6 mm)	2.01 in (51.0 mm)	3.067 in (77.92 mm)	3.087 in (78.40 mm)	3.990 in (101.36 mm)	4.010 in (101.84 mm)	4.43 in (112.6 mm)	2.01 in (51.0 mm)	3.160 in (80.28 mm)	3.180 in (80.76 mm)	N/A	N/A	4.000 in (101.60 mm)	4.031 in (102.38 mm)
4.500	10.50	0.224	TenarisHydril Wedge 511®	Standard	3.927	Standard API Drift	3.47 in (88.0 mm)	1.63 in (41.4 mm)	3.949 in (100.32 mm)	3.969 in (100.80 mm)	4.490 in (114.06 mm)	4.510 in (114.54 mm)	3.47 in (88.0 mm)	1.63 in (41.4 mm)	4.042 in (102.68 mm)	4.062 in (103.16 mm)	N/A	N/A	4.500 in (114.30 mm)	4.545 in (115.44 mm)
4.500	11.00	0.237	TenarisHydril Wedge 511®	Standard	3.901	Standard API Drift	3.47 in (88.0 mm)	1.63 in (41.4 mm)	3.924 in (99.68 mm)	3.944 in (100.16 mm)	4.490 in (114.06 mm)	4.510 in (114.54 mm)	3.47 in (88.0 mm)	1.63 in (41.4 mm)	4.016 in (102.02 mm)	4.036 in (102.50 mm)	N/A	N/A	4.500 in (114.30 mm)	4.545 in (115.44 mm)
4.500	11.60	0.250	TenarisHydril Wedge 511®	Standard	3.875	Standard API Drift	3.47 in (88.0 mm)	1.63 in (41.4 mm)	3.898 in (99.02 mm)	3.918 in (99.50 mm)	4.490 in (114.06 mm)	4.510 in (114.54 mm)	3.47 in (88.0 mm)	1.63 in (41.4 mm)	3.990 in (101.36 mm)	4.010 in (101.84 mm)	N/A	N/A	4.500 in (114.30 mm)	4.545 in (115.44 mm)
4.500	12.60	0.271	TenarisHydril Wedge 511®	Standard	3.833	Standard API Drift	3.40 in (86.2 mm)	1.72 in (43.6 mm)	3.855 in (97.92 mm)	3.875 in (98.42 mm)	4.490 in (114.06 mm)	4.510 in (114.54 mm)	3.40 in (86.2 mm)	1.72 in (43.6 mm)	3.948 in (100.28 mm)	3.968 in (100.78 mm)	N/A	N/A	4.500 in (114.30 mm)	4.545 in (115.44 mm)
4.500	13.50	0.290	TenarisHydril Wedge 511®	ExxonMobil CTP ALL	3.795	Standard API Drift	3.40 in (86.2 mm)	1.72 in (43.6 mm)	3.817 in (96.96 mm)	3.837 in (97.44 mm)	4.490 in (114.06 mm)	4.510 in (114.54 mm)	3.40 in (86.2 mm)	1.72 in (43.6 mm)	3.910 in (99.32 mm)	3.930 in (99.82 mm)	N/A	N/A	4.500 in (114.30 mm)	4.545 in (115.44 mm)
4.500	13.50	0.290	TenarisHydril Wedge 511®	Standard	3.795	Standard API Drift	3.40 in (86.2 mm)	1.72 in (43.6 mm)	3.817 in (96.96 mm)	3.837 in (97.44 mm)	4.490 in (114.06 mm)	4.510 in (114.54 mm)	3.40 in (86.2 mm)	1.72 in (43.6 mm)	3.910 in (99.32 mm)	3.930 in (99.82 mm)	N/A	N/A	4.500 in (114.30 mm)	4.545 in (115.44 mm)
4.500	15.10	0.337	TenarisHydril Wedge 511®	Standard	3.701	Standard API Drift	3.76 in (95.4 mm)	1.77 in (45.0 mm)	3.723 in (94.58 mm)	3.743 in (95.06 mm)	4.490 in (114.06 mm)	4.510 in (114.54 mm)	3.76 in (95.4 mm)	1.77 in (45.0 mm)	3.816 in (96.94 mm)	3.836 in (97.42 mm)	N/A	N/A	4.500 in (114.30 mm)	4.545 in (115.44 mm)
5.000	15.00	0.296	TenarisHydril Wedge 511®	Standard	4.283	Standard API Drift	3.40 in (86.2 mm)	1.74 in (44.2 mm)	4.307 in (109.40 mm)	4.327 in (109.90 mm)	4.990 in (126.76 mm)	5.010 in (127.24 mm)	3.40 in (86.2 mm)	1.74 in (44.2 mm)	4.398 in (111.72 mm)	4.418 in (112.20 mm)	N/A	N/A	5.000 in (127.00 mm)	5.050 in (128.26 mm)

# TenarisHydril Wedge 511® and TenarisHydril Wedge 511® Dopeless® Blanking Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, recopied, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections B.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request therefore. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyrighted 2021 as an unpublished work. ALL RIGHTS RESERVED.

SIZE (IN)	WEIGHT (LB/FT)	WALL (IN)	CONNECTION				PIN								BOX							
			PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH	RECUT LENGTH	INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH	RECUT LENGTH	INSIDE DIAMETER		OUTSIDE DIAMETER - MACHINED OD		OUTSIDE DIAMETER - AS ROLLED			
									MIN	MAX	MIN	MAX			MIN	MAX	MIN	MAX*	MIN	MAX*		
5.000	18.00	0.362	TenarisHydril Wedge 511®	Standard	4.151	Standard API Drift	4.34 in (110.2 mm)	1.79 in (45.6 mm)	4.175 in (106.06 mm)	4.195 in (106.54 mm)	4.990 in (126.76 mm)	5.010 in (127.24 mm)	4.34 in (110.2 mm)	1.79 in (45.6 mm)	4.266 in (108.36 mm)	4.286 in (108.86 mm)	N/A	N/A	5.000 in (127.00 mm)	5.050 in (128.26 mm)		
5.500	15.50	0.275	TenarisHydril Wedge 511®	Standard	4.825	Standard API Drift	3.40 in (86.2 mm)	1.74 in (44.2 mm)	4.850 in (123.20 mm)	4.870 in (123.68 mm)	5.490 in (139.46 mm)	5.510 in (139.94 mm)	3.40 in (86.2 mm)	1.74 in (44.2 mm)	4.940 in (125.48 mm)	4.960 in (125.98 mm)	N/A	N/A	5.500 in (139.70 mm)	5.555 in (141.08 mm)		
5.500	17.00	0.304	TenarisHydril Wedge 511®	Standard	4.767	Standard API Drift	3.40 in (86.2 mm)	1.74 in (44.2 mm)	4.792 in (121.72 mm)	4.812 in (122.22 mm)	5.490 in (139.46 mm)	5.510 in (139.94 mm)	3.40 in (86.2 mm)	1.74 in (44.2 mm)	4.882 in (124.02 mm)	4.902 in (124.50 mm)	N/A	N/A	5.500 in (139.70 mm)	5.555 in (141.08 mm)		
5.500	20.00	0.361	TenarisHydril Wedge 511®	Standard	4.653	Standard API Drift	3.96 in (100.6 mm)	1.74 in (44.2 mm)	4.678 in (118.84 mm)	4.698 in (119.32 mm)	5.490 in (139.46 mm)	5.510 in (139.94 mm)	3.96 in (100.6 mm)	1.74 in (44.2 mm)	4.768 in (121.12 mm)	4.788 in (121.60 mm)	N/A	N/A	5.500 in (139.70 mm)	5.555 in (141.08 mm)		
5.500	32.60	0.625	TenarisHydril Wedge 511®	Standard	4.125	Standard API Drift	5.52 in (140.2 mm)	1.63 in (41.4 mm)	4.150 in (105.42 mm)	4.170 in (105.90 mm)	5.490 in (139.46 mm)	5.510 in (139.94 mm)	5.52 in (140.2 mm)	1.63 in (41.4 mm)	4.240 in (107.70 mm)	4.260 in (108.20 mm)	N/A	N/A	5.500 in (139.70 mm)	5.555 in (141.08 mm)		
5.750	18.00	0.312	TenarisHydril Wedge 511®	Standard	5.001	Standard API Drift	3.40 in (86.2 mm)	1.74 in (44.2 mm)	5.026 in (127.68 mm)	5.046 in (128.16 mm)	5.740 in (145.80 mm)	5.760 in (146.30 mm)	3.40 in (86.2 mm)	1.74 in (44.2 mm)	5.116 in (129.96 mm)	5.136 in (130.44 mm)	N/A	N/A	5.750 in (146.06 mm)	5.808 in (147.52 mm)		
5.750	21.80	0.375	TenarisHydril Wedge 511®	Standard	4.875	Standard API Drift	4.43 in (112.6 mm)	2.03 in (51.6 mm)	4.900 in (124.46 mm)	4.920 in (124.96 mm)	5.740 in (145.80 mm)	5.760 in (146.30 mm)	4.43 in (112.6 mm)	2.03 in (51.6 mm)	4.990 in (126.76 mm)	5.010 in (127.24 mm)	N/A	N/A	5.750 in (146.06 mm)	5.808 in (147.52 mm)		
5.750	24.20	0.420	TenarisHydril Wedge 511®	Standard	4.785	Standard API Drift	4.43 in (112.6 mm)	2.03 in (51.6 mm)	4.810 in (122.18 mm)	4.830 in (122.68 mm)	5.740 in (145.80 mm)	5.760 in (146.30 mm)	4.43 in (112.6 mm)	2.03 in (51.6 mm)	4.900 in (124.46 mm)	4.920 in (124.96 mm)	N/A	N/A	5.750 in (146.06 mm)	5.808 in (147.52 mm)		
6.000	20.00	0.324	TenarisHydril Wedge 511®	Standard	5.227	Standard API Drift	3.76 in (95.4 mm)	1.79 in (45.6 mm)	5.253 in (133.44 mm)	5.273 in (133.92 mm)	5.990 in (152.16 mm)	6.010 in (152.64 mm)	3.76 in (95.4 mm)	1.79 in (45.6 mm)	5.342 in (135.70 mm)	5.362 in (136.18 mm)	N/A	N/A	6.000 in (152.40 mm)	6.060 in (153.92 mm)		
6.000	23.00	0.380	TenarisHydril Wedge 511®	Standard	5.115	Standard API Drift	3.83 in (97.2 mm)	1.78 in (45.2 mm)	5.141 in (130.60 mm)	5.161 in (131.08 mm)	5.990 in (152.16 mm)	6.010 in (152.64 mm)	3.83 in (97.2 mm)	1.78 in (45.2 mm)	5.230 in (132.86 mm)	5.250 in (133.34 mm)	N/A	N/A	6.000 in (152.40 mm)	6.060 in (153.92 mm)		
6.625	24.00	0.352	TenarisHydril Wedge 511®	Standard	5.796	Standard API Drift	4.34 in (110.2 mm)	1.79 in (45.6 mm)	5.822 in (147.88 mm)	5.842 in (148.38 mm)	6.615 in (168.04 mm)	6.635 in (168.52 mm)	4.34 in (110.2 mm)	1.79 in (45.6 mm)	5.911 in (150.14 mm)	5.931 in (150.64 mm)	N/A	N/A	6.625 in (168.28 mm)	6.691 in (169.94 mm)		
6.625	28.00	0.417	TenarisHydril Wedge 511®	Standard	5.666	Standard API Drift	4.43 in (112.6 mm)	2.03 in (51.6 mm)	5.692 in (144.58 mm)	5.712 in (145.08 mm)	6.615 in (168.04 mm)	6.635 in (168.52 mm)	4.43 in (112.6 mm)	2.03 in (51.6 mm)	5.781 in (146.84 mm)	5.801 in (147.34 mm)	N/A	N/A	6.625 in (168.28 mm)	6.691 in (169.94 mm)		
7.000	23.00	0.317	TenarisHydril Wedge 511®	Standard	6.250	Alternative API Drift	3.76 in (95.4 mm)	1.79 in (45.6 mm)	6.276 in (159.42 mm)	6.296 in (159.90 mm)	6.990 in (177.56 mm)	7.010 in (178.04 mm)	3.76 in (95.4 mm)	1.79 in (45.6 mm)	6.356 in (161.46 mm)	6.376 in (161.94 mm)	N/A	N/A	7.000 in (177.80 mm)	7.070 in (179.56 mm)		
7.000	26.00	0.362	TenarisHydril Wedge 511®	Standard	6.151	Standard API Drift	4.43 in (112.6 mm)	2.03 in (51.6 mm)	6.177 in (156.90 mm)	6.197 in (157.40 mm)	6.990 in (177.56 mm)	7.010 in (178.04 mm)	4.43 in (112.6 mm)	2.03 in (51.6 mm)	6.266 in (159.16 mm)	6.286 in (159.66 mm)	N/A	N/A	7.000 in (177.80 mm)	7.070 in (179.56 mm)		
7.000	29.00	0.408	TenarisHydril Wedge 511®	Standard	6.059	Standard API Drift	4.42 in (112.6 mm)	1.78 in (45.2 mm)	6.085 in (154.56 mm)	6.105 in (155.06 mm)	6.990 in (177.56 mm)	7.010 in (178.04 mm)	4.42 in (112.6 mm)	1.78 in (45.2 mm)	6.174 in (156.82 mm)	6.194 in (157.32 mm)	N/A	N/A	7.000 in (177.80 mm)	7.070 in (179.56 mm)		
7.625	26.40	0.328	TenarisHydril Wedge 511®	Standard	6.844	Standard API Drift	3.76 in (95.4 mm)	1.79 in (45.6 mm)	6.871 in (174.54 mm)	6.891 in (175.02 mm)	7.615 in (193.44 mm)	7.635 in (193.92 mm)	3.76 in (95.4 mm)	1.79 in (45.6 mm)	6.959 in (176.76 mm)	6.979 in (177.26 mm)	N/A	N/A	7.625 in (193.68 mm)	7.701 in (195.60 mm)		
7.625	29.70	0.375	TenarisHydril Wedge 511®	Standard	6.750	Standard API Drift	4.43 in (112.6 mm)	2.03 in (51.6 mm)	6.777 in (172.14 mm)	6.797 in (172.64 mm)	7.615 in (193.44 mm)	7.635 in (193.92 mm)	4.43 in (112.6 mm)	2.03 in (51.6 mm)	6.865 in (174.38 mm)	6.885 in (174.86 mm)	N/A	N/A	7.625 in (193.68 mm)	7.701 in (195.60 mm)		
7.625	33.70	0.430	TenarisHydril Wedge 511®	Standard	6.640	Standard API Drift	4.87 in (123.6 mm)	2.19 in (55.6 mm)	6.667 in (169.36 mm)	6.687 in (169.84 mm)	7.615 in (193.44 mm)	7.635 in (193.92 mm)	4.87 in (123.6 mm)	2.19 in (55.6 mm)	6.755 in (171.58 mm)	6.775 in (172.08 mm)	N/A	N/A	7.625 in (193.68 mm)	7.701 in (195.60 mm)		
7.625	51.20	0.687	TenarisHydril Wedge 511®	Standard	6.126	Standard API Drift	6.34 in (161.2 mm)	2.33 in (59.2 mm)	6.153 in (156.30 mm)	6.173 in (156.78 mm)	7.615 in (193.44 mm)	7.635 in (193.92 mm)	6.34 in (161.2 mm)	2.33 in (59.2 mm)	6.241 in (158.54 mm)	6.261 in (159.02 mm)	N/A	N/A	7.625 in (193.68 mm)	7.701 in (195.60 mm)		
8.000	31.00	0.375	TenarisHydril Wedge 511®	Standard	7.125	Standard API Drift	4.43 in (112.6 mm)	2.03 in (51.6 mm)	7.158 in (181.82 mm)	7.178 in (182.32 mm)	7.990 in (202.96 mm)	8.010 in (203.44 mm)	4.43 in (112.6 mm)	2.03 in (51.6 mm)	7.240 in (183.90 mm)	7.260 in (184.40 mm)	N/A	N/A	8.000 in (203.20 mm)	8.080 in (205.22 mm)		
8.125	32.50	0.375	TenarisHydril Wedge 511®	Standard	7.250	Standard API Drift	4.43 in (112.6 mm)	2.03 in (51.6 mm)	7.283 in (185.00 mm)	7.303 in (185.48 mm)	8.115 in (206.14 mm)	8.135 in (206.62 mm)	4.43 in (112.6 mm)	2.03 in (51.6 mm)	7.365 in (187.08 mm)	7.385 in (187.56 mm)	N/A	N/A	8.125 in (206.38 mm)	8.206 in (208.42 mm)		
8.125	32.50	0.375	TenarisHydril Wedge 511®	ExxonMobil CTP ALL	7.250	Standard API Drift	4.43 in (112.6 mm)	2.03 in (51.6 mm)	7.283 in (185.00 mm)	7.303 in (185.48 mm)	8.115 in (206.14 mm)	8.135 in (206.62 mm)	4.43 in (112.6 mm)	2.03 in (51.6 mm)	7.365 in (187.08 mm)	7.385 in (187.56 mm)	N/A	N/A	8.125 in (206.38 mm)	8.206 in (208.42 mm)		
8.125	35.50	0.420	TenarisHydril Wedge 511®	Standard	7.160	Standard API Drift	4.42 in (112.2 mm)	1.78 in (45.2 mm)	7.193 in (182.72 mm)	7.213 in (183.20 mm)	8.115 in (206.14 mm)	8.135 in (206.62 mm)	4.42 in (112.2 mm)	1.78 in (45.2 mm)	7.275 in (184.80 mm)	7.295 in (185.28 mm)	N/A	N/A	8.125 in (206.38 mm)	8.206 in (208.42 mm)		
8.125	39.50	0.470	TenarisHydril Wedge 511®	Standard	7.060	Standard API Drift	4.87 in (123.6 mm)	2.19 in (55.6 mm)	7.093 in (180.18 mm)	7.113 in (180.66 mm)	8.115 in (206.14 mm)	8.135 in (206.62 mm)	4.87 in (123.6 mm)	2.19 in (55.6 mm)	7.175 in (182.26 mm)	7.195 in (182.74 mm)	N/A	N/A	8.125 in (206.38 mm)	8.206 in (208.42 mm)		
8.625	32.00	0.352	TenarisHydril Wedge 511®	Standard	7.875	Alternative API Drift	3.96 in (100.6 mm)	1.74 in (44.2 mm)	7.908 in (200.88 mm)	7.928 in (201.36 mm)	8.615 in (218.84 mm)	8.635 in (219.32 mm)	3.96 in (100.6 mm)	1.74 in (44.2 mm)	7.911 in (200.94 mm)	7.931 in (201.44 mm)	N/A	N/A	8.625 in (219.08 mm)	8.711 in (221.24 mm)		
8.625	36.00	0.400	TenarisHydril Wedge 511®	Standard	7.700	Standard API Drift	4.42 in (112.2 mm)	1.78 in (45.2 mm)	7.733 in (196.42 mm)	7.753 in (196.92 mm)	8.615 in (218.84 mm)	8.635 in (219.32 mm)	4.42 in (112.2 mm)	1.78 in (45.2 mm)	7.815 in (198.52 mm)	7.835 in (199.00 mm)	N/A	N/A	8.625 in (219.08 mm)	8.711 in (221.24 mm)		

# TenarisHydril Wedge 511® and TenarisHydril Wedge 511® Dopeless® Blanking Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, recopied, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections B.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request therefore. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyrighted 2021 as an unpublished work. ALL RIGHTS RESERVED.

SIZE (IN)	WEIGHT (LB/FT)	WALL (IN)	CONNECTION				PIN								BOX					
			PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH	RECUT LENGTH	INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH	RECUT LENGTH	INSIDE DIAMETER		OUTSIDE DIAMETER - MACHINED OD		OUTSIDE DIAMETER - AS ROLLED	
									MIN	MAX	MIN	MAX			MIN	MAX	MIN	MAX*	MIN	MAX*
8.625	40.00	0.450	TenarisHydril Wedge 511®	Standard	7.625	Alternative API Drift	4.87 in (123.6 mm)	2.19 in (55.6 mm)	7.658 in (194.52 mm)	7.678 in (195.02 mm)	8.615 in (218.84 mm)	8.635 in (219.32 mm)	4.87 in (123.6 mm)	2.19 in (55.6 mm)	7.715 in (195.98 mm)	7.735 in (196.46 mm)	N/A	N/A	8.625 in (219.08 mm)	8.711 in (221.24 mm)
9.000	40.00	0.425	TenarisHydril Wedge 511®	Standard	8.025	Standard API Drift	4.42 in (112.2 mm)	1.78 in (45.2 mm)	8.059 in (204.70 mm)	8.079 in (205.20 mm)	8.990 in (228.36 mm)	9.010 in (228.84 mm)	4.42 in (112.2 mm)	1.78 in (45.2 mm)	8.140 in (206.76 mm)	8.160 in (207.26 mm)	N/A	N/A	9.000 in (228.60 mm)	9.090 in (230.88 mm)
9.625	40.00	0.395	TenarisHydril Wedge 511®	Standard	8.750	Alternative API Drift	4.43 in (112.6 mm)	2.03 in (51.6 mm)	8.784 in (223.12 mm)	8.804 in (223.62 mm)	9.615 in (244.24 mm)	9.635 in (244.72 mm)	4.43 in (112.6 mm)	2.03 in (51.6 mm)	8.825 in (224.16 mm)	8.845 in (224.66 mm)	N/A	N/A	9.625 in (244.48 mm)	9.721 in (246.90 mm)
9.625	43.50	0.435	TenarisHydril Wedge 511®	Standard	8.625	Special Drift	4.42 in (112.2 mm)	1.78 in (45.2 mm)	8.659 in (219.94 mm)	8.679 in (220.44 mm)	9.615 in (244.24 mm)	9.635 in (244.72 mm)	4.42 in (112.2 mm)	1.78 in (45.2 mm)	8.745 in (222.14 mm)	8.765 in (222.62 mm)	N/A	N/A	9.625 in (244.48 mm)	9.721 in (246.90 mm)
9.625	47.00	0.472	TenarisHydril Wedge 511®	Standard	8.525	Standard API Drift	4.87 in (123.6 mm)	2.19 in (55.6 mm)	8.559 in (217.40 mm)	8.579 in (217.90 mm)	9.615 in (244.24 mm)	9.635 in (244.72 mm)	4.87 in (123.6 mm)	2.19 in (55.6 mm)	8.671 in (220.26 mm)	8.691 in (220.74 mm)	N/A	N/A	9.625 in (244.48 mm)	9.721 in (246.90 mm)
10.750	45.50	0.400	TenarisHydril Wedge 511®	Standard	9.875	Alternative API Drift	4.43 in (112.6 mm)	2.06 in (52.2 mm)	9.912 in (251.78 mm)	9.932 in (252.26 mm)	10.740 in (272.80 mm)	10.760 in (273.30 mm)	4.43 in (112.6 mm)	2.06 in (52.2 mm)	9.940 in (252.48 mm)	9.960 in (252.98 mm)	N/A	N/A	10.750 in (273.06 mm)	10.858 in (275.78 mm)
10.750	51.00	0.450	TenarisHydril Wedge 511®	Standard	9.694	Standard API Drift	4.87 in (123.6 mm)	2.22 in (56.2 mm)	9.731 in (247.38 mm)	9.751 in (247.66 mm)	10.740 in (272.80 mm)	10.760 in (273.30 mm)	4.87 in (123.6 mm)	2.22 in (56.2 mm)	9.840 in (249.94 mm)	9.860 in (250.44 mm)	N/A	N/A	10.750 in (273.06 mm)	10.858 in (275.78 mm)
10.750	55.50	0.495	TenarisHydril Wedge 511®	Standard	9.625	Alternative API Drift	4.87 in (123.6 mm)	2.22 in (56.2 mm)	9.662 in (245.42 mm)	9.682 in (245.92 mm)	10.740 in (272.80 mm)	10.760 in (273.30 mm)	4.87 in (123.6 mm)	2.22 in (56.2 mm)	9.750 in (247.66 mm)	9.770 in (248.14 mm)	N/A	N/A	10.750 in (273.06 mm)	10.858 in (275.78 mm)
10.750	60.70	0.545	TenarisHydril Wedge 511®	Standard	9.504	Standard API Drift	5.71 in (145.0 mm)	1.95 in (49.6 mm)	9.541 in (242.36 mm)	9.561 in (242.84 mm)	10.740 in (272.80 mm)	10.760 in (273.30 mm)	5.71 in (145.0 mm)	1.95 in (49.6 mm)	9.650 in (245.12 mm)	9.670 in (245.60 mm)	N/A	N/A	10.750 in (273.06 mm)	10.858 in (275.78 mm)
10.750	65.70	0.595	TenarisHydril Wedge 511®	Standard	9.500	Special Drift	5.71 in (145.0 mm)	1.95 in (49.6 mm)	9.537 in (242.24 mm)	9.557 in (242.74 mm)	10.740 in (272.80 mm)	10.760 in (273.30 mm)	5.71 in (145.0 mm)	1.95 in (49.6 mm)	9.550 in (242.58 mm)	9.570 in (243.06 mm)	N/A	N/A	10.750 in (273.06 mm)	10.858 in (275.78 mm)
11.500	51.00	0.425	TenarisHydril Wedge 511®	Standard	10.625	Special Drift	4.43 in (112.6 mm)	2.06 in (52.2 mm)	10.640 in (270.26 mm)	10.660 in (270.76 mm)	11.490 in (291.86 mm)	11.510 in (292.34 mm)	4.43 in (112.6 mm)	2.06 in (52.2 mm)	10.640 in (270.26 mm)	10.660 in (270.76 mm)	N/A	N/A	11.500 in (292.10 mm)	11.615 in (295.02 mm)
11.750	60.00	0.489	TenarisHydril Wedge 511®	Standard	10.625	Alternative API Drift	5.38 in (136.8 mm)	2.51 in (63.8 mm)	10.664 in (270.88 mm)	10.684 in (271.36 mm)	11.740 in (298.20 mm)	11.760 in (298.70 mm)	5.38 in (136.8 mm)	2.51 in (63.8 mm)	10.762 in (273.36 mm)	10.782 in (273.86 mm)	N/A	N/A	11.750 in (298.46 mm)	11.868 in (301.44 mm)
11.750	65.00	0.534	TenarisHydril Wedge 511®	Standard	10.625	Alternative API Drift	5.38 in (136.8 mm)	2.51 in (63.8 mm)	10.664 in (270.88 mm)	10.684 in (271.36 mm)	11.740 in (298.20 mm)	11.760 in (298.70 mm)	5.38 in (136.8 mm)	2.51 in (63.8 mm)	10.672 in (271.08 mm)	10.692 in (271.56 mm)	N/A	N/A	11.750 in (298.46 mm)	11.868 in (301.44 mm)
11.875	58.80	0.470	TenarisHydril Wedge 511®	Standard	10.875	Special Drift	4.87 in (123.6 mm)	2.22 in (56.2 mm)	10.916 in (277.28 mm)	10.936 in (277.76 mm)	11.865 in (301.38 mm)	11.885 in (301.86 mm)	4.87 in (123.6 mm)	2.22 in (56.2 mm)	10.925 in (277.50 mm)	10.945 in (278.00 mm)	N/A	N/A	11.875 in (301.64 mm)	11.994 in (304.64 mm)
11.875	58.80	0.470	TenarisHydril Wedge 511®	ExxonMobil CTP ALL	10.875	Special Drift	4.87 in (123.6 mm)	2.22 in (56.2 mm)	10.916 in (277.28 mm)	10.936 in (277.76 mm)	11.865 in (301.38 mm)	11.885 in (301.86 mm)	4.87 in (123.6 mm)	2.22 in (56.2 mm)	10.925 in (277.50 mm)	10.945 in (278.00 mm)	N/A	N/A	11.875 in (301.64 mm)	11.994 in (304.64 mm)
11.875	71.80	0.582	TenarisHydril Wedge 511®	Standard	10.625	Special Drift	5.71 in (145.0 mm)	1.95 in (49.6 mm)	10.665 in (270.90 mm)	10.685 in (271.38 mm)	11.865 in (301.38 mm)	11.885 in (301.86 mm)	5.71 in (145.0 mm)	1.95 in (49.6 mm)	10.701 in (271.82 mm)	10.721 in (272.30 mm)	N/A	N/A	11.875 in (301.64 mm)	11.994 in (304.64 mm)
16.000	84.00	0.495	TenarisHydril Wedge 511®	Standard	14.822	Standard API Drift	4.96 in (126.0 mm)	1.99 in (50.6 mm)	14.871 in (377.74 mm)	14.891 in (378.22 mm)	15.990 in (406.16 mm)	16.010 in (406.64 mm)	4.96 in (126.0 mm)	1.99 in (50.6 mm)	15.000 in (381.00 mm)	15.020 in (381.50 mm)	N/A	N/A	16.000 in (406.40 mm)	16.160 in (410.46 mm)
16.000	95.00	0.566	TenarisHydril Wedge 511®	Standard	14.750	Special Drift	5.71 in (145.0 mm)	1.99 in (50.6 mm)	14.797 in (375.86 mm)	14.817 in (376.34 mm)	15.990 in (406.16 mm)	16.010 in (406.64 mm)	5.71 in (145.0 mm)	1.99 in (50.6 mm)	14.858 in (377.40 mm)	14.878 in (377.90 mm)	N/A	N/A	16.000 in (406.40 mm)	16.160 in (410.46 mm)
16.000	96.00	0.575	TenarisHydril Wedge 511®	Standard	14.750	Special Drift	5.71 in (145.0 mm)	1.99 in (50.6 mm)	14.797 in (375.86 mm)	14.817 in (376.34 mm)	15.990 in (406.16 mm)	16.010 in (406.64 mm)	5.71 in (145.0 mm)	1.99 in (50.6 mm)	14.840 in (376.94 mm)	14.860 in (377.44 mm)	N/A	N/A	16.000 in (406.40 mm)	16.160 in (410.46 mm)
16.000	96.00	0.575	TenarisHydril Wedge 511®	ExxonMobil CTP ALL	14.750	Special Drift	5.71 in (145.0 mm)	1.99 in (50.6 mm)	14.797 in (375.86 mm)	14.817 in (376.34 mm)	15.990 in (406.16 mm)	16.010 in (406.64 mm)	5.71 in (145.0 mm)	1.99 in (50.6 mm)	14.840 in (376.94 mm)	14.860 in (377.44 mm)	N/A	N/A	16.000 in (406.40 mm)	16.160 in (410.46 mm)
16.000	102.90	0.625	TenarisHydril Wedge 511®	Standard	14.562	Standard API Drift	6.34 in (161.2 mm)	2.39 in (60.6 mm)	14.611 in (371.12 mm)	14.631 in (371.62 mm)	15.990 in (406.16 mm)	16.010 in (406.64 mm)	6.34 in (161.2 mm)	2.39 in (60.6 mm)	14.740 in (374.40 mm)	14.760 in (374.90 mm)	N/A	N/A	16.000 in (406.40 mm)	16.160 in (410.46 mm)
16.000	109.00	0.656	TenarisHydril Wedge 511®	Standard	14.500	Standard API Drift	6.34 in (161.2 mm)	2.39 in (60.6 mm)	14.549 in (369.56 mm)	14.569 in (370.04 mm)	15.990 in (406.16 mm)	16.010 in (406.64 mm)	6.34 in (161.2 mm)	2.39 in (60.6 mm)	14.678 in (372.84 mm)	14.698 in (373.32 mm)	N/A	N/A	16.000 in (406.40 mm)	16.160 in (410.46 mm)
18.000	105.00	0.562	TenarisHydril Wedge 511®	Standard	16.688	Standard API Drift	5.38 in (136.8 mm)	2.61 in (66.2 mm)	16.741 in (425.24 mm)	16.761 in (425.72 mm)	17.990 in (456.96 mm)	18.010 in (457.44 mm)	5.38 in (136.8 mm)	2.61 in (66.2 mm)	16.866 in (428.40 mm)	16.886 in (428.90 mm)	N/A	N/A	18.000 in (457.20 mm)	18.180 in (461.76 mm)
18.000	117.00	0.625	TenarisHydril Wedge 511®	Standard	16.562	Standard API Drift	6.34 in (161.2 mm)	2.42 in (61.6 mm)	16.615 in (422.04 mm)	16.635 in (422.52 mm)	17.990 in (456.96 mm)	18.010 in (457.44 mm)	6.34 in (161.2 mm)	2.42 in (61.6 mm)	16.740 in (425.20 mm)	16.760 in (425.70 mm)	N/A	N/A	18.000 in (457.20 mm)	18.180 in (461.76 mm)
18.000	119.00	0.640	TenarisHydril Wedge 511®	Standard	16.532	Standard API Drift	6.34 in (161.2 mm)	2.42 in (61.6 mm)	16.585 in (421.26 mm)	16.605 in (421.76 mm)	17.990 in (456.96 mm)	18.010 in (457.44 mm)	6.34 in (161.2 mm)	2.42 in (61.6 mm)	16.710 in (424.44 mm)	16.730 in (424.94 mm)	N/A	N/A	18.000 in (457.20 mm)	18.180 in (461.76 mm)
18.000	126.00	0.677	TenarisHydril Wedge 511®	Standard	16.500	Special Drift	6.34 in (161.2 mm)	2.42 in (61.6 mm)	16.553 in (420.46 mm)	16.573 in (420.94 mm)	17.990 in (456.96 mm)	18.010 in (457.44 mm)	6.34 in (161.2 mm)	2.42 in (61.6 mm)	16.636 in (422.56 mm)	16.656 in (423.06 mm)	N/A	N/A	18.000 in (457.20 mm)	18.180 in (461.76 mm)

# TenarisHydril Wedge 511® and TenarisHydril Wedge 511® Dopeless® Blanking Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections B.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request therefore. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyrighted 2021 as an unpublished work. ALL RIGHTS RESERVED.

CONNECTION							PIN				BOX									
SIZE (IN)	WEIGHT (LB/FT)	WALL (IN)	PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH	RECUT LENGTH	INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH	RECUT LENGTH	INSIDE DIAMETER		OUTSIDE DIAMETER - MACHINED OD		OUTSIDE DIAMETER - AS ROLLED	
							MIN	MIN	MIN	MAX	MIN	MAX	MIN	MIN	MIN	MAX	MIN	MAX*	MIN	MAX*
18.000	128.00	0.688	TenarisHydril Wedge 511®	Standard	16.500	Special Drift	6.34 in (161.2 mm)	2.42 in (61.6 mm)	16.553 in (420.46 mm)	16.573 in (420.94 mm)	17.990 in (456.96 mm)	18.010 in (457.44 mm)	6.34 in (161.2 mm)	2.42 in (61.6 mm)	16.614 in (422.00 mm)	16.634 in (422.50 mm)	N/A	N/A	18.000 in (457.20 mm)	18.180 in (461.76 mm)
18.000	162.00	0.875	TenarisHydril Wedge 511®	Standard	16.062	Standard API Drift	6.62 in (168.2 mm)	2.05 in (52.0 mm)	16.115 in (409.34 mm)	16.135 in (409.82 mm)	17.990 in (456.96 mm)	18.010 in (457.44 mm)	6.62 in (168.2 mm)	2.05 in (52.0 mm)	16.240 in (412.50 mm)	16.260 in (413.00 mm)	N/A	N/A	18.000 in (457.20 mm)	18.180 in (461.76 mm)
18.625	123.40	0.625	TenarisHydril Wedge 511®	Standard	17.187	Standard API Drift	6.34 in (161.2 mm)	2.42 in (61.6 mm)	17.244 in (438.00 mm)	17.264 in (438.50 mm)	18.615 in (472.84 mm)	18.635 in (473.32 mm)	6.34 in (161.2 mm)	2.42 in (61.6 mm)	17.365 in (441.08 mm)	17.385 in (441.56 mm)	N/A	N/A	18.625 in (473.08 mm)	18.811 in (477.78 mm)
18.625	123.40	0.625	TenarisHydril Wedge 511®	ExxonMobil CTP ALL	17.187	Standard API Drift	6.34 in (161.2 mm)	2.42 in (61.6 mm)	17.244 in (438.00 mm)	17.264 in (438.50 mm)	18.615 in (472.84 mm)	18.635 in (473.32 mm)	6.34 in (161.2 mm)	2.42 in (61.6 mm)	17.365 in (441.08 mm)	17.385 in (441.56 mm)	N/A	N/A	18.625 in (473.08 mm)	18.811 in (477.78 mm)
18.625	136.00	0.693	TenarisHydril Wedge 511®	Standard	17.051	Standard API Drift	6.34 in (161.2 mm)	2.42 in (61.6 mm)	17.108 in (434.56 mm)	17.128 in (435.04 mm)	18.615 in (472.84 mm)	18.635 in (473.32 mm)	6.34 in (161.2 mm)	2.42 in (61.6 mm)	17.229 in (437.62 mm)	17.249 in (438.12 mm)	N/A	N/A	18.625 in (473.08 mm)	18.811 in (477.78 mm)
18.625	139.00	0.720	TenarisHydril Wedge 511®	Standard	16.997	Standard API Drift	6.34 in (161.2 mm)	2.42 in (61.6 mm)	17.054 in (433.18 mm)	17.074 in (433.66 mm)	18.615 in (472.84 mm)	18.635 in (473.32 mm)	6.34 in (161.2 mm)	2.42 in (61.6 mm)	17.175 in (436.26 mm)	17.195 in (436.74 mm)	N/A	N/A	18.625 in (473.08 mm)	18.811 in (477.78 mm)

Dimensions provided do not include length required for tongs for making up assemblies. Please take this into consideration when designing and machining your accessory.

BLANK OD and ID: The nominal blank ODs and IDs in the Pin Diameters and Box Diameters columns are finished product dimensions. When this minimum material is supplied, the blank OD and the blank ID must be true to each other within 0.010" TIR (Total Indicator Reading).

BLANK Min Length includes 0.02" (0.5mm) extra material for facing.

Contact Tenaris Manufacturing Services at blankingdimensions@tenaris.com for details.

These Blanking Dimensions are NOT applicable For Handling & lifting plug, HydroTest Caps & HydroTest Plugs.

N/A: Not Applicable

\*For OEM Max OD is not restricted.

  Yellow - Shaded corresponds to modified from previous document revision.