

TenarisHydril Blue® Dopeless® Blanking Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, recopied, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections B.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request therefore. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyrighted 2021 as an unpublished work. ALL RIGHTS RESERVED.

CONNECTION					PIN												BOX								
SIZE (IN)	WEIGHT (LB/FT)	WALL (IN)	PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH	RECUT LENGTH	INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH	RECUT LENGTH	COUPLING LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER - REGULAR		OUTSIDE DIAMETER - MATCHED STRENGTH		OUTSIDE DIAMETER - SPECIAL CLEARANCE #1		
							MIN	MIN	MIN	MAX	MIN	MAX	MIN	MIN	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN
3.500	7.70	0.216	TenarisHydril Blue® Dopeless®	Standard	2.943	Standard API Drift	4.27 in (108.4 mm)	1.55 in (39.4 mm)	3.020 in (76.70 mm)	3.043 in (77.30 mm)	3.500 in (88.90 mm)	3.531 in (89.68 mm)	4.27 in (108.4 mm)	2.09 in (53.2 mm)	8.130 in (206.50 mm)	8.326 in (211.50 mm)	3.004 in (76.30 mm)	3.027 in (76.90 mm)	3.918 in (99.50 mm)	3.956 in (100.50 mm)	3.843 in (97.60 mm)	3.881 in (98.60 mm)	85.0	3.772 in (95.80 mm)	3.811 in (96.80 mm)

TenarisHydril Blue[®] Dopeless[®] Blanking Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, recopied, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections B.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request therefore. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyrighted 2021 as an unpublished work. ALL RIGHTS RESERVED.

CONNECTION					PIN										BOX										
SIZE (IN)	WEIGHT (LB/FT)	WALL (IN)	PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH	RECUT LENGTH	INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH	RECUT LENGTH	COUPLING LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER - REGULAR		OUTSIDE DIAMETER - MATCHED STRENGTH		OUTSIDE DIAMETER - SPECIAL CLEARANCE #1		
									MIN	MAX	MIN	MAX			MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN
9.625	47.00	0.472	TenarisHydril Blue [®] Dopeless [®]	Standard	8.540	Special Drift	5.72 (145.2 mm)	1.60 (40.8 mm)	8.670 (220.20 mm)	8.692 (220.80 mm)	9.625 (244.48 mm)	9.721 (246.90 mm)	5.72 (145.2 mm)	2.10 (53.4 mm)	11.595 (294.50 mm)	11.791 (299.50 mm)	8.648 (219.66 mm)	8.671 (220.24 mm)	10.607 (269.40 mm)	10.645 (270.40 mm)	10.378 (263.60 mm)	10.417 (264.60 mm)	85.0	10.217 (259.50 mm)	10.255 (260.50 mm)
9.625	47.00	0.472	TenarisHydril Blue [®] Dopeless [®]	Standard	8.614	Special Drift	5.72 (145.2 mm)	1.60 (40.8 mm)	8.670 (220.20 mm)	8.692 (220.80 mm)	9.625 (244.48 mm)	9.721 (246.90 mm)	5.72 (145.2 mm)	2.10 (53.4 mm)	11.595 (294.50 mm)	11.791 (299.50 mm)	8.648 (219.66 mm)	8.671 (220.24 mm)	10.607 (269.40 mm)	10.645 (270.40 mm)	10.378 (263.60 mm)	10.417 (264.60 mm)	85.0	10.217 (259.50 mm)	10.255 (260.50 mm)
9.625	53.50	0.545	TenarisHydril Blue [®] Dopeless [®]	Standard	8.379	Standard API Drift	5.72 (145.2 mm)	1.60 (40.8 mm)	8.524 (216.50 mm)	8.546 (217.08 mm)	9.625 (244.48 mm)	9.721 (246.90 mm)	5.72 (145.2 mm)	2.10 (53.4 mm)	11.595 (294.50 mm)	11.791 (299.50 mm)	8.534 (216.76 mm)	8.557 (217.34 mm)	10.607 (269.40 mm)	10.645 (270.40 mm)	10.504 (266.80 mm)	10.543 (267.80 mm)	85.0	10.323 (262.20 mm)	10.362 (263.20 mm)
9.625	47.00	0.472	TenarisHydril Blue [®] Dopeless [®]	Standard	8.540	Special Drift	5.72 (145.2 mm)	1.60 (40.8 mm)	8.670 (220.20 mm)	8.692 (220.80 mm)	9.625 (244.48 mm)	9.721 (246.90 mm)	5.72 (145.2 mm)	2.10 (53.4 mm)	11.595 (294.50 mm)	11.791 (299.50 mm)	8.648 (219.66 mm)	8.671 (220.24 mm)	10.607 (269.40 mm)	10.645 (270.40 mm)	10.378 (263.60 mm)	10.417 (264.60 mm)	85.0	10.217 (259.50 mm)	10.255 (260.50 mm)
9.625	60.70	0.545	TenarisHydril Blue [®] Dopeless [®]	Standard	8.540	Special Drift	5.72 (145.2 mm)	1.60 (40.8 mm)	8.670 (220.20 mm)	8.692 (220.80 mm)	9.625 (244.48 mm)	9.721 (246.90 mm)	5.72 (145.2 mm)	2.10 (53.4 mm)	11.595 (294.50 mm)	11.791 (299.50 mm)	8.648 (219.66 mm)	8.671 (220.24 mm)	10.607 (269.40 mm)	10.645 (270.40 mm)	10.378 (263.60 mm)	10.417 (264.60 mm)	85.0	10.217 (259.50 mm)	10.255 (260.50 mm)
9.625	60.70	0.545	TenarisHydril Blue [®] Dopeless [®]	Standard	8.540	Special Drift	5.72 (145.2 mm)	1.60 (40.8 mm)	8.670 (220.20 mm)	8.692 (220.80 mm)	9.625 (244.48 mm)	9.721 (246.90 mm)	5.72 (145.2 mm)	2.10 (53.4 mm)	11.595 (294.50 mm)	11.791 (299.50 mm)	8.648 (219.66 mm)	8.671 (220.24 mm)	10.607 (269.40 mm)	10.645 (270.40 mm)	10.378 (263.60 mm)	10.417 (264.60 mm)	85.0	10.217 (259.50 mm)	10.255 (260.50 mm)

