

## TenarisHydril Wedge™ 613 Dopeless® Blanking Dimensions



DESIGNATION					PIN and BOX		PIN				BOX			
					GENERAL		REGULAR		GENERAL		REGULAR		GENERAL	
DIAMETER	WALL THICKNESS	WEIGHT	PRODUCT	DRIFT	MINIMUM LENGTH	ADD. LENGTH 1 RECUT	OUTSIDE DIAMETER min	OUTSIDE DIAMETER max	INSIDE DIAMETER min	INSIDE DIAMETER max	OUTSIDE DIAMETER min	OUTSIDE DIAMETER max	INSIDE DIAMETER min	INSIDE DIAMETER max
in.	in.	lb/ft	---	inch (mm)	inch (mm)	inch (mm)	inch (mm)	inch (mm)	inch (mm)	inch (mm)	inch (mm)	inch (mm)	inch (mm)	inch (mm)
14.150	0.895	127.00	TSH WEDGE 613™ & TSH WEDGE 613™ DOPELESS®	12.250" ( 311.15 mm)	9.259" ( 235.18 mm)	2.100" ( 53.34 mm)	14.150" ( 359.41 mm)	14.292" ( 363.00 mm)	12.279" ( 311.89 mm)	12.299" ( 312.39 mm)	14.277" ( 362.64 mm)	14.292" ( 363.02 mm)	12.350" ( 313.69 mm)	12.370" ( 314.20 mm)
16.000	0.495	84.00	TSH WEDGE 613™ & TSH WEDGE 613™ DOPELESS®	14.822" ( 376.48 mm)	7.220" ( 183.39 mm)	1.800" ( 45.72 mm)	16.000" ( 406.40 mm)	16.160" ( 410.46 mm)	14.851" ( 377.22 mm)	14.871" ( 377.72 mm)	16.150" ( 410.21 mm)	16.170" ( 410.72 mm)	15.000" ( 381.00 mm)	15.020" ( 381.51 mm)
16.000	0.575	96.00	TSH WEDGE 613™ & TSH WEDGE 613™ DOPELESS®	14.750" ( 374.65 mm)	7.366" ( 187.10 mm)	1.800" ( 45.72 mm)	16.000" ( 406.40 mm)	16.160" ( 410.46 mm)	14.780" ( 375.41 mm)	14.800" ( 375.92 mm)	16.145" ( 410.08 mm)	16.160" ( 410.46 mm)	14.840" ( 376.94 mm)	14.860" ( 377.44 mm)
16.250	0.825	136.50	TSH WEDGE 613™ & TSH WEDGE 613™ DOPELESS®	14.501" ( 368.33 mm)	8.665" ( 220.09 mm)	1.800" ( 45.72 mm)	16.250" ( 412.75 mm)	16.413" ( 416.88 mm)	14.531" ( 369.09 mm)	14.551" ( 369.60 mm)	16.382" ( 416.10 mm)	16.402" ( 416.61 mm)	14.590" ( 370.59 mm)	14.610" ( 371.09 mm)

BLANK OD and ID: The nominal blank ODs and IDs in the Pin Diameters and Box Diameters columns are finished product dimensions. When this minimum material is supplied, the blank OD and the blank ID must be true to each other within 0.010" TIR (Total Indicator Reading).

na: Not Applicable.  
Blank spaces indicate product not currently available.

Contact Tenaris Manufacturing Services at [licensees@oilfield.tenaris.com](mailto:licensees@oilfield.tenaris.com) for details.  
These Blanking Dimensions are NOT applicable For Handling & lifting plug, HydroTest Caps & HydroTest Plugs.

Yellow - Shaded corresponds to modified from previous document revision.