

TenarisHydril Blue® /A Blanking Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, recopied, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections B.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request therefore. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyrighted 2020 as an unpublished work. ALL RIGHTS RESERVED.

SIZE (IN)	WEIGHT (LB/FT)	WALL (IN)	CONNECTION				PIN						BOX									
			PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH	RECUT LENGTH	INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH	RECUT LENGTH	COUPLING LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER - REGULAR		OUTSIDE DIAMETER - MATCHED STRENGTH	
									MIN	MAX	MIN	MAX			MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX
5.500	17.00	0.304	TenarisHydril Blue® /A	ExxonMobil CTP ALL GB3	4.767	Standard API Drift	5.33 in (135.4 mm)	1.55 in (39.4 mm)	4.871 in (123.70 mm)	4.893 in (124.30 mm)	5.500 in (139.70 mm)	5.555 in (141.08 mm)	5.33 in (135.4 mm)	2.12 in (53.8 mm)	10.650 in (270.50 mm)	10.846 in (275.50 mm)	4.849 in (123.16 mm)	4.872 in (123.74 mm)	6.044 in (153.50 mm)	6.082 in (154.50 mm)	N/A	N/A
5.500	20.00	0.361	TenarisHydril Blue® /A	ExxonMobil CTP1 GB2 & GB3	4.653	Standard API Drift	5.33 in (135.4 mm)	1.55 in (39.4 mm)	4.767 in (121.06 mm)	4.789 in (121.66 mm)	5.500 in (139.70 mm)	5.555 in (141.08 mm)	5.33 in (135.4 mm)	2.12 in (53.8 mm)	10.650 in (270.50 mm)	10.846 in (275.50 mm)	4.778 in (121.36 mm)	4.801 in (121.94 mm)	6.083 in (154.50 mm)	6.122 in (155.50 mm)	N/A	N/A
5.500	23.00	0.415	TenarisHydril Blue® /A	ExxonMobil CTP ALL GB3	4.545	Standard API Drift	5.33 in (135.4 mm)	1.55 in (39.4 mm)	4.659 in (118.32 mm)	4.681 in (118.92 mm)	5.500 in (139.70 mm)	5.555 in (141.08 mm)	5.33 in (135.4 mm)	2.12 in (53.8 mm)	10.650 in (270.50 mm)	10.846 in (275.50 mm)	4.684 in (118.96 mm)	4.706 in (119.54 mm)	6.162 in (156.50 mm)	6.200 in (157.50 mm)	N/A	N/A
6.625	32.00	0.475	TenarisHydril Blue® /A	ExxonMobil CTP ALL GB3	5.550	Standard API Drift	5.13 in (130.4 mm)	1.60 in (40.8 mm)	5.664 in (143.86 mm)	5.687 in (144.44 mm)	6.625 in (168.28 mm)	6.691 in (169.94 mm)	5.13 in (130.4 mm)	2.05 in (52.0 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	5.667 in (144.52 mm)	5.689 in (144.52 mm)	7.390 in (187.70 mm)	7.429 in (188.70 mm)	N/A	N/A
6.625	32.00	0.475	TenarisHydril Blue® /A	ExxonMobil CTP ALL GB3 CRA	5.550	Standard API Drift	5.13 in (130.4 mm)	1.60 in (40.8 mm)	5.664 in (143.86 mm)	5.687 in (144.44 mm)	6.625 in (168.28 mm)	6.691 in (169.94 mm)	5.13 in (130.4 mm)	2.05 in (52.0 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	5.667 in (143.92 mm)	5.689 in (144.52 mm)	7.390 in (187.70 mm)	7.429 in (188.70 mm)	N/A	N/A
7.000	23.00	0.317	TenarisHydril Blue® /A	ExxonMobil CTP ALL GB2	6.241	Standard API Drift	5.13 in (130.4 mm)	1.60 in (40.8 mm)	6.300 in (160.00 mm)	6.322 in (160.60 mm)	7.000 in (177.80 mm)	7.070 in (179.56 mm)	5.13 in (130.4 mm)	2.09 in (53.0 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	6.276 in (159.40 mm)	6.299 in (160.00 mm)	7.658 in (194.50 mm)	7.696 in (195.50 mm)	N/A	N/A
7.000	23.00	0.317	TenarisHydril Blue® /A	ExxonMobil CTP ALL GB3	6.241	Standard API Drift	5.13 in (130.4 mm)	1.60 in (40.8 mm)	6.300 in (160.00 mm)	6.322 in (160.60 mm)	7.000 in (177.80 mm)	7.070 in (179.56 mm)	5.13 in (130.4 mm)	2.09 in (53.0 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	6.276 in (159.40 mm)	6.299 in (160.00 mm)	7.658 in (194.50 mm)	7.696 in (195.50 mm)	N/A	N/A
7.000	23.00	0.317	TenarisHydril Blue® /A	ExxonMobil CTP ALL GB2	6.250	Alternative API Drift	5.13 in (130.4 mm)	1.60 in (40.8 mm)	6.300 in (160.00 mm)	6.322 in (160.60 mm)	7.000 in (177.80 mm)	7.070 in (179.56 mm)	5.13 in (130.4 mm)	2.09 in (53.0 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	6.276 in (159.40 mm)	6.299 in (160.00 mm)	7.658 in (194.50 mm)	7.696 in (195.50 mm)	N/A	N/A
7.000	23.00	0.317	TenarisHydril Blue® /A	ExxonMobil CTP ALL GB3	6.250	Alternative API Drift	5.13 in (130.4 mm)	1.60 in (40.8 mm)	6.300 in (160.00 mm)	6.322 in (160.60 mm)	7.000 in (177.80 mm)	7.070 in (179.56 mm)	5.13 in (130.4 mm)	2.09 in (53.0 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	6.276 in (159.40 mm)	6.299 in (160.00 mm)	7.658 in (194.50 mm)	7.696 in (195.50 mm)	N/A	N/A
7.000	26.00	0.362	TenarisHydril Blue® /A	ExxonMobil CTP ALL GB2	6.151	Standard API Drift	5.13 in (130.4 mm)	1.60 in (40.8 mm)	6.201 in (157.50 mm)	6.224 in (158.10 mm)	7.000 in (177.80 mm)	7.070 in (179.56 mm)	5.13 in (130.4 mm)	2.09 in (53.0 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	6.178 in (156.90 mm)	6.200 in (157.50 mm)	7.658 in (194.50 mm)	7.696 in (195.50 mm)	N/A	N/A
7.000	26.00	0.362	TenarisHydril Blue® /A	ExxonMobil CTP ALL GB3	6.151	Standard API Drift	5.13 in (130.4 mm)	1.60 in (40.8 mm)	6.201 in (157.50 mm)	6.224 in (158.10 mm)	7.000 in (177.80 mm)	7.070 in (179.56 mm)	5.13 in (130.4 mm)	2.09 in (53.0 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	6.178 in (156.90 mm)	6.200 in (157.50 mm)	7.658 in (194.50 mm)	7.696 in (195.50 mm)	N/A	N/A
7.000	29.00	0.408	TenarisHydril Blue® /A	ExxonMobil CTP ALL GB2	6.059	Standard API Drift	5.13 in (130.4 mm)	1.60 in (40.8 mm)	6.130 in (155.70 mm)	6.153 in (156.30 mm)	7.000 in (177.80 mm)	7.070 in (179.56 mm)	5.13 in (130.4 mm)	2.09 in (53.0 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	6.107 in (155.10 mm)	6.129 in (155.70 mm)	7.658 in (194.50 mm)	7.696 in (195.50 mm)	N/A	N/A
7.000	29.00	0.408	TenarisHydril Blue® /A	ExxonMobil CTP ALL GB3	6.059	Standard API Drift	5.13 in (130.4 mm)	1.60 in (40.8 mm)	6.130 in (155.70 mm)	6.153 in (156.30 mm)	7.000 in (177.80 mm)	7.070 in (179.56 mm)	5.13 in (130.4 mm)	2.09 in (53.0 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	6.107 in (155.10 mm)	6.129 in (155.70 mm)	7.658 in (194.50 mm)	7.696 in (195.50 mm)	N/A	N/A
7.000	32.00	0.453	TenarisHydril Blue® /A	ExxonMobil CTP ALL GB2	5.969	Standard API Drift	5.13 in (130.4 mm)	1.60 in (40.8 mm)	6.075 in (154.90 mm)	6.098 in (155.90 mm)	7.000 in (177.80 mm)	7.070 in (179.56 mm)	5.13 in (130.4 mm)	2.09 in (53.0 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	6.052 in (153.70 mm)	6.074 in (154.30 mm)	7.713 in (195.90 mm)	7.751 in (196.90 mm)	N/A	N/A
7.000	32.00	0.453	TenarisHydril Blue® /A	ExxonMobil CTP ALL GB3	5.969	Standard API Drift	5.13 in (130.4 mm)	1.60 in (40.8 mm)	6.075 in (154.90 mm)	6.098 in (155.90 mm)	7.000 in (177.80 mm)	7.070 in (179.56 mm)	5.13 in (130.4 mm)	2.09 in (53.0 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	6.052 in (153.70 mm)	6.074 in (154.30 mm)	7.713 in (195.90 mm)	7.751 in (196.90 mm)	N/A	N/A
7.000	32.00	0.453	TenarisHydril Blue® /A	ExxonMobil CTP ALL GB2	6.000	Alternative API Drift	5.13 in (130.4 mm)	1.60 in (40.8 mm)	6.075 in (154.90 mm)	6.098 in (155.90 mm)	7.000 in (177.80 mm)	7.070 in (179.56 mm)	5.13 in (130.4 mm)	2.09 in (53.0 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	6.052 in (153.70 mm)	6.074 in (154.30 mm)	7.713 in (195.90 mm)	7.751 in (196.90 mm)	N/A	N/A
7.000	32.00	0.453	TenarisHydril Blue® /A	ExxonMobil CTP ALL GB3	6.000	Alternative API Drift	5.13 in (130.4 mm)	1.60 in (40.8 mm)	6.075 in (154.90 mm)	6.098 in (155.90 mm)	7.000 in (177.80 mm)	7.070 in (179.56 mm)	5.13 in (130.4 mm)	2.09 in (53.0 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	6.052 in (153.70 mm)	6.074 in (154.30 mm)	7.713 in (195.90 mm)	7.751 in (196.90 mm)	N/A	N/A
7.000	35.00	0.498	TenarisHydril Blue® /A	ExxonMobil CTP ALL GB3	5.879	Standard API Drift	5.13 in (130.4 mm)	1.60 in (40.8 mm)	5.993 in (152.20 mm)	6.015 in (152.80 mm)	7.000 in (177.80 mm)	7.070 in (179.56 mm)	5.13 in (130.4 mm)	2.09 in (53.0 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	6.000 in (152.40 mm)	6.023 in (153.00 mm)	7.788 in (197.80 mm)	7.826 in (198.80 mm)	N/A	N/A
7.625	29.70	0.375	TenarisHydril Blue® /A	ExxonMobil CTP ALL GB2 & GB3	6.750	Standard API Drift	5.21 in (132.2 mm)	1.60 in (40.8 mm)	6.815 in (173.10 mm)	6.838 in (173.70 mm)	7.625 in (193.68 mm)	7.701 in (195.60 mm)	5.21 in (132.2 mm)	2.09 in (53.0 mm)	10.571 in (268.50 mm)	10.767 in (273.50 mm)	6.790 in (172.46 mm)	6.812 in (173.04 mm)	8.406 in (213.50 mm)	8.444 in (214.50 mm)	N/A	N/A
7.625	33.70	0.430	TenarisHydril Blue® /A	ExxonMobil CTP ALL GB2 & GB3	6.640	Standard API Drift	5.21 in (132.2 mm)	1.60 in (40.8 mm)	6.713 in (170.50 mm)	6.736 in (171.10 mm)	7.625 in (193.68 mm)	7.701 in (195.60 mm)	5.21 in (132.2 mm)	2.09 in (53.0 mm)	10.571 in (268.50 mm)	10.767 in (273.50 mm)	6.688 in (169.86 mm)	6.710 in (170.44 mm)	8.445 in (214.50 mm)	8.484 in (215.50 mm)	8.296 in (210.70 mm)	8.334 in (211.70 mm)
7.625	35.80	0.465	TenarisHydril Blue® /A	ExxonMobil CTP ALL GB2 & GB3	6.570	Standard API Drift	5.21 in (132.2 mm)	1.60 in (40.8 mm)	6.674 in (169.50 mm)	6.696 in (170.10 mm)	7.625 in (193.68 mm)	7.701 in (195.60 mm)	5.21 in (132.2 mm)	2.09 in (53.0 mm)	10.571 in (268.50 mm)	10.767 in (273.50 mm)	6.648 in (168.86 mm)	6.671 in (169.44 mm)	8.445 in (214.50 mm)	8.484 in (215.50 mm)	N/A	N/A
7.625	39.00	0.500	TenarisHydril Blue® /A	ExxonMobil CTP ALL GB2 & GB3	6.500	Standard API Drift	5.21 in (132.2 mm)	1.60 in (40.8 mm)	6.614 in (167.98 mm)	6.637 in (168.58 mm)	7.625 in (193.68 mm)	7.701 in (195.60 mm)	5.21 in (132.2 mm)	2.09 in (53.0 mm)	10.571 in (268.50 mm)	10.767 in (273.50 mm)	6.593 in (167.46 mm)	6.616 in (168.04 mm)	8.477 in (215.30 mm)	8.515 in (216.30 mm)	N/A	N/A
8.625	36.00	0.400	TenarisHydril Blue® /A	ExxonMobil CTP ALL GB2 & GB3	7.700	Standard API Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	7.804 in (198.20 mm)	7.826 in (198.80 mm)	8.625 in (219.08 mm)	8.711 in (221.24 mm)	5.72 in (145.2 mm)	2.08 in (52.8 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	7.776 in (197.50 mm)	7.799 in (198.10 mm)	9.469 in (240.50 mm)	9.507 in (241.50 mm)	N/A	N/A
8.625	40.00	0.450	TenarisHydril Blue® /A	ExxonMobil CTP ALL GB2 & GB3	7.600	Standard API Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	7.714 in (195.92 mm)	7.737 in (196.52 mm)	8.625 in (219.08 mm)	8.711 in (221.24 mm)	5.72 in (145.2 mm)	2.08 in (52.8 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	7.697 in (195.50 mm)	7.720 in (196.10 mm)	9.469 in (240.50 mm)	9.507 in (241.50 mm)	N/A	N/A
8.625	44.00	0.500	TenarisHydril Blue® /A	ExxonMobil CTP ALL GB2 & GB3	7.500	Standard API Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	7.614 in (193.38 mm)	7.637 in (193.98 mm)	8.625 in (219.08 mm)	8.711 in (221.24 mm)	5.72 in (145.2 mm)	2.08 in (52.8 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	7.638 in (194.00 mm)	7.661 in (194.60 mm)	9.469 in (240.50 mm)	9.507 in (241.50 mm)	N/A	N/A
8.625	49.00	0.557	TenarisHydril Blue® /A	ExxonMobil CTP ALL GB2 & GB3	7.386	Standard API Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	7.500 in (190.48 mm)	7.522 in (191.08 mm)	8.625 in (219.08 mm)	8.711 in (221.24 mm)	5.72 in (145.2 mm)	2.08 in (52.8 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	7.524 in (191.10 mm)	7.547 in (191.70 mm)	9.607 in (244.00 mm)	9.645 in (245.00 mm)	N/A	N/A
8.625	52.00	0.595	TenarisHydril Blue® /A	ExxonMobil CTP ALL GB2	7.310	Standard API Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	7.424 in (188.56 mm)	7.446 in (189.14 mm)	8.625 in (219.08 mm)	8.711 in (221.24 mm)	5.72 in (145.2 mm)	2.08 in (52.8 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	7.485 in (190.10 mm)	7.507 in (190.70 mm)	9.607 in (244.00 mm)	9.645 in (245.00 mm)	N/A	N/A
9.625	40.00	0.395	TenarisHydril Blue® /A	ExxonMobil CTP ALL GB2 & GB3	8.679	Standard API Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	8.800 in (223.50 mm)	8.822 in (224.10 mm)	9.625 in (244.48 mm)	9.721 in (246.90 mm)	5.72 in (145.2 mm)	2.10 in (53.4 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	8.770 in (222.76 mm)	8.793 in (223.34 mm)	10.607 in (269.40 mm)	10.645 in (270.40 mm)	N/A	N/A
9.625	43.50	0.435	TenarisHydril Blue® /A	ExxonMobil CTP ALL GB2 & GB3	8.599	Standard API Drift	5.72 in (145.2 mm)</															

TenarisHydril Blue® /A Blanking Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, recopied, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections B.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request therefore. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyrighted 2020 as an unpublished work. ALL RIGHTS RESERVED.

SIZE (IN)	WEIGHT (LB/FT)	WALL (IN)	CONNECTION				PIN								BOX							
			PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH	RECUT LENGTH	INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH	RECUT LENGTH	COUPLING LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER - REGULAR		OUTSIDE DIAMETER - MATCHED STRENGTH	
									MIN	MAX	MIN	MAX			MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX
13.375	72.00	0.514	TenarisHydril Blue® /A	HS ExxonMobil CTP ALL GB3	12.250	Special Drift	6.37 in (161.8 mm)	1.60 in (40.8 mm)	12.325 in (313.06 mm)	12.348 in (313.64 mm)	13.375 in (339.74 mm)	13.509 in (343.12 mm)	6.37 in (161.8 mm)	1.96 in (49.8 mm)	12.934 in (328.50 mm)	13.129 in (333.50 mm)	12.284 in (312.00 mm)	12.307 in (312.60 mm)	14.359 in (364.70 mm)	14.397 in (365.70 mm)	N/A	N/A
13.375	77.00	0.550	TenarisHydril Blue® /A	ExxonMobil CTP ALL GB2	12.119	Standard API Drift	6.37 in (161.8 mm)	1.60 in (40.8 mm)	12.264 in (311.50 mm)	12.287 in (312.08 mm)	13.375 in (339.74 mm)	13.509 in (343.12 mm)	6.37 in (161.8 mm)	2.08 in (53.0 mm)	12.934 in (328.50 mm)	13.129 in (333.50 mm)	12.249 in (311.12 mm)	12.272 in (311.72 mm)	14.280 in (362.70 mm)	14.318 in (363.70 mm)	N/A	N/A
13.375	77.00	0.550	TenarisHydril Blue® /A	HS ExxonMobil CTP ALL GB3	12.119	Standard API Drift	6.37 in (161.8 mm)	1.60 in (40.8 mm)	12.231 in (310.66 mm)	12.253 in (311.24 mm)	13.375 in (339.74 mm)	13.509 in (343.12 mm)	6.37 in (161.8 mm)	1.96 in (49.8 mm)	12.934 in (328.50 mm)	13.129 in (333.50 mm)	12.189 in (309.60 mm)	12.212 in (310.20 mm)	14.367 in (364.90 mm)	14.405 in (365.90 mm)	N/A	N/A
13.375	80.70	0.580	TenarisHydril Blue® /A	ExxonMobil CTP ALL GB2	12.059	Standard API Drift	6.37 in (161.8 mm)	1.60 in (40.8 mm)	12.204 in (309.96 mm)	12.226 in (310.56 mm)	13.375 in (339.74 mm)	13.509 in (343.12 mm)	6.37 in (161.8 mm)	2.08 in (53.0 mm)	12.934 in (328.50 mm)	13.129 in (333.50 mm)	12.210 in (310.12 mm)	12.233 in (310.72 mm)	14.335 in (364.10 mm)	14.374 in (365.10 mm)	N/A	N/A
13.375	80.70	0.580	TenarisHydril Blue® /A	HS ExxonMobil CTP ALL GB3	12.059	Standard API Drift	6.37 in (161.8 mm)	1.60 in (40.8 mm)	12.188 in (309.56 mm)	12.210 in (310.14 mm)	13.375 in (339.74 mm)	13.509 in (343.12 mm)	6.37 in (161.8 mm)	1.96 in (49.8 mm)	12.934 in (328.50 mm)	13.129 in (333.50 mm)	12.146 in (308.50 mm)	12.169 in (309.10 mm)	14.426 in (366.40 mm)	14.464 in (367.40 mm)	N/A	N/A
13.375	85.00	0.608	TenarisHydril Blue® /A	ExxonMobil CTP ALL GB2	12.003	Standard API Drift	6.37 in (161.8 mm)	1.60 in (40.8 mm)	12.148 in (308.54 mm)	12.170 in (309.14 mm)	13.375 in (339.74 mm)	13.509 in (343.12 mm)	6.37 in (161.8 mm)	2.08 in (53.0 mm)	12.934 in (328.50 mm)	13.129 in (333.50 mm)	12.171 in (309.12 mm)	12.193 in (309.72 mm)	14.382 in (365.30 mm)	14.421 in (366.30 mm)	N/A	N/A
13.375	85.00	0.608	TenarisHydril Blue® /A	HS ExxonMobil CTP ALL GB3	12.003	Standard API Drift	6.37 in (161.8 mm)	1.60 in (40.8 mm)	12.148 in (308.54 mm)	12.170 in (309.14 mm)	13.375 in (339.74 mm)	13.509 in (343.12 mm)	6.37 in (161.8 mm)	1.96 in (49.8 mm)	12.934 in (328.50 mm)	13.129 in (333.50 mm)	12.107 in (307.50 mm)	12.129 in (308.10 mm)	14.477 in (367.70 mm)	14.515 in (368.70 mm)	N/A	N/A
13.375	86.00	0.625	TenarisHydril Blue® /A	ExxonMobil CTP ALL GB2	11.969	Standard API Drift	6.37 in (161.8 mm)	1.60 in (40.8 mm)	12.114 in (307.68 mm)	12.137 in (308.28 mm)	13.375 in (339.74 mm)	13.509 in (343.12 mm)	6.37 in (161.8 mm)	2.08 in (53.0 mm)	12.934 in (328.50 mm)	13.129 in (333.50 mm)	12.163 in (308.92 mm)	12.185 in (309.52 mm)	14.414 in (366.10 mm)	14.452 in (367.10 mm)	N/A	N/A
13.375	86.00	0.625	TenarisHydril Blue® /A	HS ExxonMobil CTP ALL GB3	11.969	Standard API Drift	6.37 in (161.8 mm)	1.60 in (40.8 mm)	12.114 in (307.68 mm)	12.137 in (308.28 mm)	13.375 in (339.74 mm)	13.509 in (343.12 mm)	6.37 in (161.8 mm)	1.96 in (49.8 mm)	12.934 in (328.50 mm)	13.129 in (333.50 mm)	12.095 in (307.20 mm)	12.118 in (307.80 mm)	14.512 in (366.60 mm)	14.551 in (369.60 mm)	N/A	N/A
13.500	81.40	0.580	TenarisHydril Blue® /A	ExxonMobil CTP ALL GB2 & GB3	12.153	Standard API Drift	6.37 in (161.8 mm)	1.60 in (40.8 mm)	12.329 in (313.14 mm)	12.351 in (313.74 mm)	13.500 in (342.90 mm)	13.635 in (346.32 mm)	6.37 in (161.8 mm)	2.36 in (59.8 mm)	12.894 in (327.50 mm)	13.090 in (332.50 mm)	12.388 in (314.66 mm)	12.411 in (315.24 mm)	14.469 in (367.50 mm)	14.507 in (368.50 mm)	N/A	N/A
13.625	88.20	0.625	TenarisHydril Blue® /A	ExxonMobil CTP ALL GB2 & GB3	12.188	Standard API Drift	6.37 in (161.8 mm)	1.60 in (40.8 mm)	12.364 in (314.04 mm)	12.387 in (314.62 mm)	13.625 in (346.08 mm)	13.761 in (349.52 mm)	6.37 in (161.8 mm)	1.97 in (50.0 mm)	12.894 in (327.50 mm)	13.090 in (332.50 mm)	12.411 in (315.22 mm)	12.433 in (315.82 mm)	14.646 in (372.00 mm)	14.685 in (373.00 mm)	N/A	N/A
13.625	88.20	0.625	TenarisHydril Blue® /A	ExxonMobil CTP ALL GB2 & GB3	12.250	Special Drift	6.37 in (161.8 mm)	1.60 in (40.8 mm)	12.364 in (314.04 mm)	12.387 in (314.62 mm)	13.625 in (346.08 mm)	13.761 in (349.52 mm)	6.37 in (161.8 mm)	1.97 in (50.0 mm)	12.894 in (327.50 mm)	13.090 in (332.50 mm)	12.411 in (315.22 mm)	12.433 in (315.82 mm)	14.646 in (372.00 mm)	14.685 in (373.00 mm)	N/A	N/A

Dimensions provided do not include length required for tongs for making up assemblies. Please take this into consideration when designing and machining your accessory.

BLANK OD and ID: The nominal blank ODs and IDs in the Pin Diameters and Box Diameters columns are finished product dimensions. When this minimum material is supplied, the blank OD and the blank ID must be true to each other within 0.010" TIR (Total Indicator Reading).

BLANK Min Length includes 0.02" (0.5mm) extra material for facing.

Contact Tenaris Manufacturing Services at blankingdimensions@tenaris.com for details.

These Blanking Dimensions are NOT applicable For Handling & lifting plug, HydroTest Caps & HydroTest Plugs.

N/A: Not Applicable

Yellow - Shaded corresponds to modified from previous document revision.