

TenarisHydril Wedge 441™ Blanking Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, recopied, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections B.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request therefore. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyrighted 2020 as an unpublished work. ALL RIGHTS RESERVED.

CONNECTION							PIN						BOX							
SIZE (IN)	WEIGHT (LB/FT)	WALL (IN)	PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH	RECUT LENGTH	INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH	RECUT LENGTH	COUPLING LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER - MACHINED OD	
							MIN	MIN	MIN	MAX	MIN	MAX	MIN	MIN	MIN	MAX	MIN	MAX	MIN	MAX
5.000	18.00	0.362	TenarisHydril Wedge 441™	Standard	4.151	Standard API Drift	4.19 in (106.4 mm)	1.79 in (45.4 mm)	4.266 in (108.36 mm)	4.286 in (108.86 mm)	5.000 in (127.00 mm)	5.050 in (128.26 mm)	4.51 in (114.4 mm)	1.86 in (47.2 mm)	8.684 in (220.58 mm)	8.904 in (226.16 mm)	4.266 in (108.36 mm)	4.286 in (108.86 mm)	5.339 in (135.62 mm)	5.379 in (136.62 mm)
5.500	20.00	0.361	TenarisHydril Wedge 441™	Standard	4.653	Standard API Drift	4.19 in (106.4 mm)	1.79 in (45.4 mm)	4.768 in (121.12 mm)	4.788 in (121.60 mm)	5.500 in (139.70 mm)	5.555 in (141.08 mm)	4.51 in (114.4 mm)	1.86 in (47.2 mm)	8.684 in (220.58 mm)	8.904 in (226.16 mm)	4.768 in (121.12 mm)	4.788 in (121.60 mm)	5.832 in (148.14 mm)	5.872 in (149.14 mm)
7.625	29.70	0.375	TenarisHydril Wedge 441™	Standard	6.750	Standard API Drift	4.16 in (105.6 mm)	1.29 in (32.8 mm)	6.865 in (174.38 mm)	6.885 in (174.86 mm)	7.625 in (193.68 mm)	7.701 in (195.60 mm)	4.48 in (113.8 mm)	1.58 in (40.0 mm)	8.636 in (219.36 mm)	8.856 in (224.94 mm)	6.865 in (174.38 mm)	6.885 in (174.86 mm)	7.890 in (200.42 mm)	7.910 in (200.90 mm)

Dimensions provided do not include length required for tongs for making up assemblies. Please take this into consideration when designing and machining your accessory.

BLANK OD and ID: The nominal blank ODs and IDs in the Pin Diameters and Box Diameters columns are finished product dimensions. When this minimum material is supplied, the blank OD and the blank ID must be true to each other within 0.010" TIR (Total Indicator Reading).

BLANK Min Length includes 0.02" (0.5mm) extra material for facing.

Contact Tenaris Manufacturing Services at blankingdimensions@tenaris.com for details.

These Blanking Dimensions are NOT applicable For Handling & lifting plug, HydroTest Caps & HydroTest Plugs.

N/A: Not Applicable

Yellow - Shaded corresponds to modified from previous document revision.