

# TenarisHydril Wedge 625 RF Blanking Dimensions

DESIGNATION					PIN & BOX		PIN				BOX			
DIAMETER	WALL THICKNESS	WEIGHT	PRODUCT	DRIFT	ADD. LENGTH 1 RECUT	MINIMUM LENGTH	OUTSIDE DIAMETER min	OUTSIDE DIAMETER max	INSIDE DIAMETER min	INSIDE DIAMETER max	INSIDE DIAMETER min	INSIDE DIAMETER max	OUTSIDE DIAMETER min	OUTSIDE DIAMETER max
in.	in.	lb/ft	---	inch (mm)	inch (mm)	inch (mm)	inch (mm)	inch (mm)	inch (mm)	inch (mm)	inch (mm)	inch (mm)	inch (mm)	inch (mm)
4.000	0.286	11.60	TSH WEDGE 625® RF	3.325" ( 84.46 mm)	1.700" ( 43.50 mm)	5.549" ( 140.94 mm)	4.000" ( 101.60 mm)	4.040" ( 102.62 mm)	3.370" ( 85.60 mm)	3.390" ( 86.11 mm)	3.418" ( 86.82 mm)	3.438" ( 87.33 mm)	4.140" ( 105.16 mm)	4.160" ( 105.66 mm)

When this minimum material is supplied, the blank OD and the blank ID must be true to each other within 0.010" TIR (Total Indicator Reading).

na: Not Applicable.

Blank spaces indicate product not currently available.

Dopeless® refers to all Dopeless® versions available for this connection

Contact Tenaris Manufacturing Services at [licensees@oilfield.tenaris.com](mailto:licensees@oilfield.tenaris.com) for details.

These Blanking Dimensions are NOT applicable For Handling & lifting plug, HydroTest Caps & HydroTest Plugs.

Yellow - Shaded corresponds to modified from previous document revision.