

ULTRA™ DQX Blanking Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, recopied, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections B.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request therefore. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyrighted 2020 as an unpublished work. ALL RIGHTS RESERVED.

SIZE (IN)	CONNECTION						PIN						BOX											
	WEIGHT (LB/FT)	WALL (IN)	PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH	RECUT LENGTH	INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH	RECUT LENGTH	COUPLING LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER - REGULAR API 9		OUTSIDE DIAMETER - REGULAR API 10		OUTSIDE DIAMETER - REGULAR	
							MIN	MIN	MIN	MAX	MIN	MAX	MIN	MIN	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX
4.500	10.50	0.224	ULTRA DQX	Standard	3.927	Standard API Drift	N/A	2.25 in (57.2 mm)	4.036 in (102.52 mm)	4.097 in (104.06 mm)	4.484 in (113.90 mm)	4.545 in (115.44 mm)	N/A	N/A	7.514 in (190.86 mm)	7.574 in (192.36 mm)	4.239 in (107.68 mm)	4.271 in (108.48 mm)	4.969 in (126.22 mm)	5.050 in (128.26 mm)	5.219 in (132.58 mm)	5.300 in (134.62 mm)	N/A	N/A
4.500	10.50	0.224	ULTRA DQX	Accessory	3.927	Standard API Drift	4.30 in (109.2 mm)	2.25 in (57.2 mm)	4.036 in (102.52 mm)	4.068 in (103.32 mm)	4.484 in (113.90 mm)	4.516 in (114.70 mm)	4.30 in (109.2 mm)	2.25 in (57.2 mm)	N/A	N/A	4.036 in (102.52 mm)	4.068 in (103.32 mm)	4.969 in (126.22 mm)	5.050 in (128.26 mm)	5.219 in (132.58 mm)	5.300 in (134.62 mm)	N/A	N/A
4.500	11.60	0.250	ULTRA DQX	Standard	3.875	Standard API Drift	N/A	2.25 in (57.2 mm)	3.984 in (101.20 mm)	4.045 in (102.74 mm)	4.484 in (113.90 mm)	4.545 in (115.44 mm)	N/A	N/A	7.514 in (190.86 mm)	7.574 in (192.36 mm)	4.239 in (107.68 mm)	4.271 in (108.48 mm)	4.969 in (126.22 mm)	5.050 in (128.26 mm)	5.219 in (132.58 mm)	5.300 in (134.62 mm)	N/A	N/A
4.500	11.60	0.250	ULTRA DQX	Accessory	3.875	Standard API Drift	4.30 in (109.2 mm)	2.25 in (57.2 mm)	3.984 in (101.20 mm)	4.016 in (102.00 mm)	4.484 in (113.90 mm)	4.516 in (114.70 mm)	4.30 in (109.2 mm)	2.25 in (57.2 mm)	N/A	N/A	3.984 in (101.20 mm)	4.016 in (102.00 mm)	4.969 in (126.22 mm)	5.050 in (128.26 mm)	5.219 in (132.58 mm)	5.300 in (134.62 mm)	N/A	N/A
4.500	13.50	0.290	ULTRA DQX	Standard	3.795	Standard API Drift	N/A	2.25 in (57.2 mm)	3.904 in (99.18 mm)	3.965 in (100.70 mm)	4.484 in (113.90 mm)	4.545 in (115.44 mm)	N/A	N/A	7.514 in (190.86 mm)	7.574 in (192.36 mm)	4.239 in (107.68 mm)	4.271 in (108.48 mm)	4.969 in (126.22 mm)	5.050 in (128.26 mm)	5.219 in (132.58 mm)	5.300 in (134.62 mm)	N/A	N/A
4.500	13.50	0.290	ULTRA DQX	Accessory	3.795	Standard API Drift	4.30 in (109.2 mm)	2.25 in (57.2 mm)	3.904 in (99.18 mm)	3.936 in (99.96 mm)	4.484 in (113.90 mm)	4.516 in (114.70 mm)	4.30 in (109.2 mm)	2.25 in (57.2 mm)	N/A	N/A	3.904 in (99.18 mm)	3.936 in (99.96 mm)	4.969 in (126.22 mm)	5.050 in (128.26 mm)	5.219 in (132.58 mm)	5.300 in (134.62 mm)	N/A	N/A
4.500	15.10	0.337	ULTRA DQX	Standard	3.701	Standard API Drift	N/A	2.25 in (57.2 mm)	3.810 in (96.78 mm)	3.871 in (98.32 mm)	4.484 in (113.90 mm)	4.545 in (115.44 mm)	N/A	N/A	7.514 in (190.86 mm)	7.574 in (192.36 mm)	4.239 in (107.68 mm)	4.271 in (108.48 mm)	4.969 in (126.22 mm)	5.050 in (128.26 mm)	5.219 in (132.58 mm)	5.300 in (134.62 mm)	N/A	N/A
4.500	15.10	0.337	ULTRA DQX	Accessory	3.701	Standard API Drift	4.30 in (109.2 mm)	2.25 in (57.2 mm)	3.810 in (96.78 mm)	3.842 in (97.58 mm)	4.484 in (113.90 mm)	4.516 in (114.70 mm)	4.30 in (109.2 mm)	2.25 in (57.2 mm)	N/A	N/A	3.810 in (96.78 mm)	3.842 in (97.58 mm)	4.969 in (126.22 mm)	5.050 in (128.26 mm)	5.219 in (132.58 mm)	5.300 in (134.62 mm)	N/A	N/A
5.000	15.00	0.296	ULTRA DQX	Standard	4.283	Standard API Drift	N/A	2.63 in (66.8 mm)	4.392 in (111.56 mm)	4.458 in (113.22 mm)	4.984 in (126.60 mm)	5.050 in (128.26 mm)	N/A	N/A	8.164 in (207.38 mm)	8.224 in (208.88 mm)	4.713 in (119.72 mm)	4.745 in (120.52 mm)	5.532 in (140.52 mm)	5.672 in (144.06 mm)	5.769 in (146.54 mm)	5.909 in (150.08 mm)	N/A	N/A
5.000	15.00	0.296	ULTRA DQX	Accessory	4.283	Standard API Drift	4.62 in (117.4 mm)	2.63 in (66.8 mm)	4.392 in (111.56 mm)	4.424 in (112.36 mm)	4.984 in (126.60 mm)	5.016 in (127.40 mm)	4.62 in (117.4 mm)	2.38 in (60.4 mm)	N/A	N/A	4.392 in (111.56 mm)	4.424 in (112.36 mm)	5.532 in (140.52 mm)	5.672 in (144.06 mm)	5.769 in (146.54 mm)	5.909 in (150.08 mm)	N/A	N/A
5.000	18.00	0.362	ULTRA DQX	Standard	4.151	Standard API Drift	N/A	2.63 in (66.8 mm)	4.260 in (108.22 mm)	4.326 in (109.00 mm)	4.984 in (126.60 mm)	5.050 in (128.26 mm)	N/A	N/A	8.164 in (207.38 mm)	8.224 in (208.88 mm)	4.713 in (119.72 mm)	4.745 in (120.52 mm)	5.532 in (140.52 mm)	5.672 in (144.06 mm)	5.769 in (146.54 mm)	5.909 in (150.08 mm)	N/A	N/A
5.000	18.00	0.362	ULTRA DQX	Accessory	4.151	Standard API Drift	4.62 in (117.4 mm)	2.63 in (66.8 mm)	4.260 in (108.22 mm)	4.292 in (109.00 mm)	4.984 in (126.60 mm)	5.016 in (127.40 mm)	4.62 in (117.4 mm)	2.38 in (60.4 mm)	N/A	N/A	4.260 in (108.22 mm)	4.292 in (109.00 mm)	5.532 in (140.52 mm)	5.672 in (144.06 mm)	5.769 in (146.54 mm)	5.909 in (150.08 mm)	N/A	N/A
5.000	21.40	0.437	ULTRA DQX	Standard	4.001	Standard API Drift	N/A	2.63 in (66.8 mm)	4.110 in (104.40 mm)	4.176 in (106.06 mm)	4.984 in (126.60 mm)	5.050 in (128.26 mm)	N/A	N/A	8.164 in (207.38 mm)	8.224 in (208.88 mm)	4.713 in (119.72 mm)	4.745 in (120.52 mm)	5.532 in (140.52 mm)	5.672 in (144.06 mm)	5.769 in (146.54 mm)	5.909 in (150.08 mm)	N/A	N/A
5.000	21.40	0.437	ULTRA DQX	Accessory	4.001	Standard API Drift	4.62 in (117.4 mm)	2.63 in (66.8 mm)	4.110 in (104.40 mm)	4.142 in (105.20 mm)	4.984 in (126.60 mm)	5.016 in (127.40 mm)	4.62 in (117.4 mm)	2.38 in (60.4 mm)	N/A	N/A	4.110 in (104.40 mm)	4.142 in (105.20 mm)	5.532 in (140.52 mm)	5.672 in (144.06 mm)	5.769 in (146.54 mm)	5.909 in (150.08 mm)	N/A	N/A
5.000	23.20	0.478	ULTRA DQX	Standard	3.919	Standard API Drift	N/A	2.63 in (66.8 mm)	4.028 in (102.32 mm)	4.094 in (103.98 mm)	4.984 in (126.60 mm)	5.050 in (128.26 mm)	N/A	N/A	8.164 in (207.38 mm)	8.224 in (208.88 mm)	4.713 in (119.72 mm)	4.745 in (120.52 mm)	5.532 in (140.52 mm)	5.672 in (144.06 mm)	5.769 in (146.54 mm)	5.909 in (150.08 mm)	N/A	N/A
5.000	23.20	0.478	ULTRA DQX	Accessory	3.919	Standard API Drift	4.62 in (117.4 mm)	2.63 in (66.8 mm)	4.028 in (102.32 mm)	4.060 in (103.12 mm)	4.984 in (126.60 mm)	5.016 in (127.40 mm)	4.62 in (117.4 mm)	2.38 in (60.4 mm)	N/A	N/A	4.028 in (102.32 mm)	4.060 in (103.12 mm)	5.532 in (140.52 mm)	5.672 in (144.06 mm)	5.769 in (146.54 mm)	5.909 in (150.08 mm)	N/A	N/A
5.500	15.50	0.275	ULTRA DQX	Standard	4.825	Standard API Drift	N/A	2.63 in (66.8 mm)	4.934 in (125.34 mm)	5.005 in (127.12 mm)	5.484 in (139.30 mm)	5.555 in (141.08 mm)	N/A	N/A	8.214 in (208.64 mm)	8.274 in (210.14 mm)	5.211 in (132.36 mm)	5.243 in (133.16 mm)	6.019 in (152.90 mm)	6.159 in (156.42 mm)	6.269 in (159.24 mm)	6.409 in (162.78 mm)	N/A	N/A
5.500	15.50	0.275	ULTRA DQX	Accessory	4.825	Standard API Drift	4.65 in (118.0 mm)	2.63 in (66.8 mm)	4.934 in (125.34 mm)	4.966 in (126.12 mm)	5.484 in (139.30 mm)	5.516 in (140.10 mm)	4.65 in (118.0 mm)	2.38 in (60.4 mm)	N/A	N/A	4.934 in (125.34 mm)	4.966 in (126.12 mm)	6.019 in (152.90 mm)	6.159 in (156.42 mm)	6.269 in (159.24 mm)	6.409 in (162.78 mm)	N/A	N/A
5.500	17.00	0.304	ULTRA DQX	Standard	4.767	Standard API Drift	N/A	2.63 in (66.8 mm)	4.876 in (123.86 mm)	4.947 in (125.64 mm)	5.484 in (139.30 mm)	5.555 in (141.08 mm)	N/A	N/A	8.214 in (208.64 mm)	8.274 in (210.14 mm)	5.211 in (132.36 mm)	5.243 in (133.16 mm)	6.019 in (152.90 mm)	6.159 in (156.42 mm)	6.269 in (159.24 mm)	6.409 in (162.78 mm)	N/A	N/A
5.500	17.00	0.304	ULTRA DQX	Accessory	4.767	Standard API Drift	4.65 in (118.0 mm)	2.63 in (66.8 mm)	4.876 in (123.86 mm)	4.908 in (124.66 mm)	5.484 in (139.30 mm)	5.516 in (140.10 mm)	4.65 in (118.0 mm)	2.38 in (60.4 mm)	N/A	N/A	4.876 in (123.86 mm)	4.908 in (124.66 mm)	6.019 in (152.90 mm)	6.159 in (156.42 mm)	6.269 in (159.24 mm)	6.409 in (162.78 mm)	N/A	N/A
5.500	20.00	0.361	ULTRA DQX	Standard	4.653	Standard API Drift	N/A	2.63 in (66.8 mm)	4.762 in (120.96 mm)	4.833 in (122.74 mm)	5.484 in (139.30 mm)	5.555 in (141.08 mm)	N/A	N/A	8.214 in (208.64 mm)	8.274 in (210.14 mm)	5.211 in (132.36 mm)	5.243 in (133.16 mm)	6.019 in (152.90 mm)	6.159 in (156.42 mm)	6.269 in (159.24 mm)	6.409 in (162.78 mm)	N/A	N/A
5.500	20.00	0.361	ULTRA DQX	Accessory	4.653	Standard API Drift	4.65 in (118.0 mm)	2.63 in (66.8 mm)	4.762 in (120.96 mm)	4.794 in (121.76 mm)	5.484 in (139.30 mm)	5.516 in (140.10 mm)	4.65 in (118.0 mm)	2.38 in (60.4 mm)	N/A	N/A	4.762 in (120.96 mm)	4.794 in (121.76 mm)	6.019 in (152.90 mm)	6.159 in (156.42 mm)	6.269 in (159.24 mm)	6.409 in (162.78 mm)	N/A	N/A
5.500	23.00	0.415	ULTRA DQX	Standard	4.545	Standard API Drift	N/A	2.63 in (66.8 mm)	4.654 in (118.22 mm)	4.725 in (120.00 mm)	5.484 in (139.30 mm)	5.555 in (141.08 mm)	N/A	N/A	8.214 in (208.64 mm)	8.274 in (210.14 mm)	5.211 in (132.36 mm)	5.243 in (133.16 mm)	6.019 in (152.90 mm)	6.159 in (156.42 mm)	6.269 in (159.24 mm)	6.409 in (162.78 mm)	N/A	N/A
5.500	23.00	0.415	ULTRA DQX	Accessory	4.545	Standard API Drift	4.65 in (118.0 mm)	2.63 in (66.8 mm)	4.654 in (118.22 mm)	4.686 in (119.02 mm)	5.484 in (139.30 mm)	5.516 in (140.10 mm)	4.65 in (118.0 mm)	2.38 in (60.4 mm)	N/A	N/A	4.654 in (118.22 mm)	4.686 in (119.02 mm)	6.019 in (152.90 mm)	6.159 in (156.42 mm)	6.269 in (159.24 mm)	6.409 in (162.78 mm)	N/A	N/A
5.500	26.00	0.476	ULTRA DQX	Standard	4.423	Standard API Drift	N/A	2.63 in (66.8 mm)	4.532 in (115.12 mm)	4.603 in (116.90 mm)	5.484 in (139.30 mm)	5.555 in (141.08 mm)	N/A	N/A	8.214 in (208.64 mm)	8.274 in (210.14 mm)	5.211 in (132.36 mm)	5.243 in (133.16 mm)	6.019 in (152.90 mm)	6.159 in (156.42 mm)	6.269 in (159.24 mm)	6.409 in (162.78 mm)	N/A	N/A
5.500	26.00	0.476	ULTRA DQX	Accessory	4.423	Standard API Drift	4.65 in (118.0 mm)	2.63 in (66.8 mm)	4.532 in (115.12 mm)	4.564 in (115.92 mm)	5.484 in (139.30 mm)	5.516 in (140.10 mm)	4.65 in (118.0 mm)	2.38 in (60.4 mm)	N/A	N/A	4.532 in (115.12 mm)	4.564 in (115.92 mm)	6.019 in (152.90 mm)	6.159 in (156.42 mm)	6.269 in (159.24 mm)	6.409 in (162.78 mm)	N/A	N/A
6.000	24.50	0.400	ULTRA DQX	Standard	5.075	Standard API Drift	N/A	2.88 in (73.2 mm)	5.184 in (131.68 mm)	5.260 in (133.60 mm)	5.984 in (152.00 mm)	6.060 in (153.92 mm)	N/A	N/A	8.364 in (212.46 mm)	8.424 in (213.96 mm)	5.705 in (144.92 mm)	5.737 in (145.70 mm)	N/A	N/A	N/A	N/A	6.762 in (171.76 mm)	6.898 in (175.20 mm)
6.000	24.50	0.400	ULTRA DQX	Accessory	5.075	Standard API Drift	4.72 in (120.0 mm)	2.88 in (73.2 mm)	5.184 in (131.68 mm)	5.216 in (132.48 mm)	5.984 in (152.00 mm)	6.016 in (152.80 mm)	4.72 in (120.0 mm)	2.50 in (63.6 mm)	N/A	N/A	5.184 in (131.68 mm)	5.216 in (132.48 mm)	N/A	N/A	N/A	N/A	6.762 in (171.76 mm)	6.898 in (175.20 mm)

ULTRA™ DQX Blanking Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, recopied, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections B.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request therefore. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyrighted 2020 as an unpublished work. ALL RIGHTS RESERVED.

SIZE (IN)	CONNECTION						PIN						BOX											
	WEIGHT (LB/FT)	WALL (IN)	PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH	RECUT LENGTH	INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH	RECUT LENGTH	COUPLING LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER - REGULAR API 9		OUTSIDE DIAMETER - REGULAR API 10		OUTSIDE DIAMETER - REGULAR	
									MIN	MAX	MIN	MAX			MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX
7.000	23.00	0.317	ULTRA DQX	Standard	6.250	Standard API Drift	N/A	3.13 in (79.4 mm)	6.350 in (161.30 mm)	6.436 in (163.46 mm)	6.984 in (177.40 mm)	7.070 in (179.56 mm)	N/A	N/A	8.892 in (225.86 mm)	8.952 in (227.38 mm)	6.684 in (169.78 mm)	6.716 in (170.58 mm)	N/A	N/A	7.844 in (199.24 mm)	7.984 in (202.78 mm)	N/A	N/A
7.000	23.00	0.317	ULTRA DQX	Accessory	6.250	Standard API Drift	4.99 in (126.6 mm)	3.13 in (79.4 mm)	6.350 in (161.30 mm)	6.382 in (162.10 mm)	6.984 in (177.40 mm)	7.016 in (178.20 mm)	4.99 in (126.6 mm)	2.50 in (63.6 mm)	N/A	N/A	6.350 in (161.30 mm)	6.382 in (162.10 mm)	N/A	N/A	7.844 in (199.24 mm)	7.984 in (202.78 mm)	N/A	N/A
7.000	26.00	0.362	ULTRA DQX	Standard	6.151	Standard API Drift	N/A	3.13 in (79.4 mm)	6.260 in (159.02 mm)	6.346 in (161.18 mm)	6.984 in (177.40 mm)	7.070 in (179.56 mm)	N/A	N/A	8.892 in (225.86 mm)	8.952 in (227.38 mm)	6.684 in (169.78 mm)	6.716 in (170.58 mm)	N/A	N/A	7.844 in (199.24 mm)	7.984 in (202.78 mm)	N/A	N/A
7.000	26.00	0.362	ULTRA DQX	Accessory	6.151	Standard API Drift	4.99 in (126.6 mm)	3.13 in (79.4 mm)	6.260 in (159.02 mm)	6.292 in (159.80 mm)	6.984 in (177.40 mm)	7.016 in (178.20 mm)	4.99 in (126.6 mm)	2.50 in (63.6 mm)	N/A	N/A	6.260 in (159.02 mm)	6.292 in (159.80 mm)	N/A	N/A	7.844 in (199.24 mm)	7.984 in (202.78 mm)	N/A	N/A
7.000	29.00	0.408	ULTRA DQX	Standard	6.125	Standard API Drift	N/A	3.13 in (79.4 mm)	6.168 in (156.68 mm)	6.254 in (158.84 mm)	6.984 in (177.40 mm)	7.070 in (179.56 mm)	N/A	N/A	8.892 in (225.86 mm)	8.952 in (227.38 mm)	6.684 in (169.78 mm)	6.716 in (170.58 mm)	N/A	N/A	7.844 in (199.24 mm)	7.984 in (202.78 mm)	N/A	N/A
7.000	29.00	0.408	ULTRA DQX	Accessory	6.125	Standard API Drift	4.99 in (126.6 mm)	3.13 in (79.4 mm)	6.168 in (156.68 mm)	6.200 in (157.48 mm)	6.984 in (177.40 mm)	7.016 in (178.20 mm)	4.99 in (126.6 mm)	2.50 in (63.6 mm)	N/A	N/A	6.168 in (156.68 mm)	6.200 in (157.48 mm)	N/A	N/A	7.844 in (199.24 mm)	7.984 in (202.78 mm)	N/A	N/A
7.000	32.00	0.453	ULTRA DQX	Standard	6.000	Standard API Drift	N/A	3.13 in (79.4 mm)	6.078 in (154.40 mm)	6.164 in (156.56 mm)	6.984 in (177.40 mm)	7.070 in (179.56 mm)	N/A	N/A	8.892 in (225.86 mm)	8.952 in (227.38 mm)	6.684 in (169.78 mm)	6.716 in (170.58 mm)	N/A	N/A	7.844 in (199.24 mm)	7.984 in (202.78 mm)	N/A	N/A
7.000	32.00	0.453	ULTRA DQX	Accessory	6.000	Standard API Drift	4.99 in (126.6 mm)	3.13 in (79.4 mm)	6.078 in (154.40 mm)	6.110 in (155.18 mm)	6.984 in (177.40 mm)	7.016 in (178.20 mm)	4.99 in (126.6 mm)	2.50 in (63.6 mm)	N/A	N/A	6.078 in (154.40 mm)	6.110 in (155.18 mm)	N/A	N/A	7.844 in (199.24 mm)	7.984 in (202.78 mm)	N/A	N/A
7.625	26.40	0.328	ULTRA DQX	Standard	6.844	Standard API Drift	N/A	3.38 in (85.8 mm)	6.953 in (176.62 mm)	7.045 in (178.94 mm)	7.609 in (193.28 mm)	7.701 in (195.60 mm)	N/A	N/A	9.267 in (235.40 mm)	9.327 in (236.90 mm)	7.294 in (185.28 mm)	7.326 in (186.08 mm)	N/A	N/A	8.469 in (215.12 mm)	8.609 in (218.66 mm)	N/A	N/A
7.625	26.40	0.328	ULTRA DQX	Accessory	6.844	Standard API Drift	5.17 in (131.4 mm)	3.38 in (85.8 mm)	6.953 in (176.62 mm)	6.985 in (177.40 mm)	7.609 in (193.28 mm)	7.641 in (194.08 mm)	5.17 in (131.4 mm)	2.63 in (66.8 mm)	N/A	N/A	6.953 in (176.62 mm)	6.985 in (177.40 mm)	N/A	N/A	8.469 in (215.12 mm)	8.609 in (218.66 mm)	N/A	N/A
7.625	29.70	0.375	ULTRA DQX	Standard	6.750	Standard API Drift	N/A	3.38 in (85.8 mm)	6.859 in (174.22 mm)	6.951 in (176.76 mm)	7.609 in (193.28 mm)	7.701 in (195.60 mm)	N/A	N/A	9.267 in (235.40 mm)	9.327 in (236.90 mm)	7.294 in (185.28 mm)	7.326 in (186.08 mm)	N/A	N/A	8.469 in (215.12 mm)	8.609 in (218.66 mm)	N/A	N/A
7.625	29.70	0.375	ULTRA DQX	Accessory	6.750	Standard API Drift	5.17 in (131.4 mm)	3.38 in (85.8 mm)	6.859 in (174.22 mm)	6.891 in (175.02 mm)	7.609 in (193.28 mm)	7.641 in (194.08 mm)	5.17 in (131.4 mm)	2.63 in (66.8 mm)	N/A	N/A	6.859 in (174.22 mm)	6.891 in (175.02 mm)	N/A	N/A	8.469 in (215.12 mm)	8.609 in (218.66 mm)	N/A	N/A
7.625	33.70	0.430	ULTRA DQX	Standard	6.640	Standard API Drift	N/A	3.38 in (85.8 mm)	6.749 in (171.44 mm)	6.841 in (173.76 mm)	7.609 in (193.28 mm)	7.701 in (195.60 mm)	N/A	N/A	9.267 in (235.40 mm)	9.327 in (236.90 mm)	7.294 in (185.28 mm)	7.326 in (186.08 mm)	N/A	N/A	8.469 in (215.12 mm)	8.609 in (218.66 mm)	N/A	N/A
7.625	33.70	0.430	ULTRA DQX	Accessory	6.640	Standard API Drift	5.17 in (131.4 mm)	3.38 in (85.8 mm)	6.749 in (171.44 mm)	6.781 in (172.22 mm)	7.609 in (193.28 mm)	7.641 in (194.08 mm)	5.17 in (131.4 mm)	2.63 in (66.8 mm)	N/A	N/A	6.749 in (171.44 mm)	6.781 in (172.22 mm)	N/A	N/A	8.469 in (215.12 mm)	8.609 in (218.66 mm)	N/A	N/A
9.625	36.00	0.352	ULTRA DQX	Standard	8.765	Standard API Drift	N/A	3.50 in (89.0 mm)	8.905 in (226.20 mm)	9.017 in (229.02 mm)	9.609 in (244.08 mm)	9.721 in (246.90 mm)	N/A	N/A	9.455 in (240.16 mm)	9.515 in (241.68 mm)	9.268 in (235.42 mm)	9.300 in (236.22 mm)	N/A	N/A	10.594 in (269.10 mm)	10.734 in (272.64 mm)	N/A	N/A
9.625	36.00	0.352	ULTRA DQX	Accessory	8.765	Standard API Drift	5.27 in (133.8 mm)	3.50 in (89.0 mm)	8.905 in (226.20 mm)	8.937 in (226.98 mm)	9.609 in (244.08 mm)	9.641 in (244.88 mm)	5.27 in (133.8 mm)	2.63 in (66.8 mm)	N/A	N/A	8.905 in (226.20 mm)	8.937 in (226.98 mm)	N/A	N/A	10.594 in (269.10 mm)	10.734 in (272.64 mm)	N/A	N/A
9.625	40.00	0.395	ULTRA DQX	Standard	8.750	Standard API Drift	N/A	3.50 in (89.0 mm)	8.819 in (224.02 mm)	8.931 in (226.84 mm)	9.609 in (244.08 mm)	9.721 in (246.90 mm)	N/A	N/A	9.455 in (240.16 mm)	9.515 in (241.68 mm)	9.268 in (235.42 mm)	9.300 in (236.22 mm)	N/A	N/A	10.594 in (269.10 mm)	10.734 in (272.64 mm)	N/A	N/A
9.625	40.00	0.395	ULTRA DQX	Accessory	8.750	Standard API Drift	5.27 in (133.8 mm)	3.50 in (89.0 mm)	8.819 in (224.02 mm)	8.851 in (224.80 mm)	9.609 in (244.08 mm)	9.641 in (244.88 mm)	5.27 in (133.8 mm)	2.63 in (66.8 mm)	N/A	N/A	8.819 in (224.02 mm)	8.851 in (224.80 mm)	N/A	N/A	10.594 in (269.10 mm)	10.734 in (272.64 mm)	N/A	N/A
9.625	43.50	0.435	ULTRA DQX	Standard	8.599	Standard API Drift	N/A	3.50 in (89.0 mm)	8.739 in (221.98 mm)	8.851 in (224.80 mm)	9.609 in (244.08 mm)	9.721 in (246.90 mm)	N/A	N/A	9.455 in (240.16 mm)	9.515 in (241.68 mm)	9.268 in (235.42 mm)	9.300 in (236.22 mm)	N/A	N/A	10.594 in (269.10 mm)	10.734 in (272.64 mm)	N/A	N/A
9.625	43.50	0.435	ULTRA DQX	Accessory	8.599	Standard API Drift	5.27 in (133.8 mm)	3.50 in (89.0 mm)	8.739 in (221.98 mm)	8.771 in (222.78 mm)	9.609 in (244.08 mm)	9.641 in (244.88 mm)	5.27 in (133.8 mm)	2.63 in (66.8 mm)	N/A	N/A	8.739 in (221.98 mm)	8.771 in (222.78 mm)	N/A	N/A	10.594 in (269.10 mm)	10.734 in (272.64 mm)	N/A	N/A
9.625	47.00	0.472	ULTRA DQX	Standard	8.525	Standard API Drift	N/A	3.50 in (89.0 mm)	8.665 in (220.10 mm)	8.777 in (222.92 mm)	9.609 in (244.08 mm)	9.721 in (246.90 mm)	N/A	N/A	9.455 in (240.16 mm)	9.515 in (241.68 mm)	9.268 in (235.42 mm)	9.300 in (236.22 mm)	N/A	N/A	10.594 in (269.10 mm)	10.734 in (272.64 mm)	N/A	N/A
9.625	47.00	0.472	ULTRA DQX	Accessory	8.525	Standard API Drift	5.27 in (133.8 mm)	3.50 in (89.0 mm)	8.665 in (220.10 mm)	8.697 in (220.90 mm)	9.609 in (244.08 mm)	9.641 in (244.88 mm)	5.27 in (133.8 mm)	2.63 in (66.8 mm)	N/A	N/A	8.665 in (220.10 mm)	8.697 in (220.90 mm)	N/A	N/A	10.594 in (269.10 mm)	10.734 in (272.64 mm)	N/A	N/A
9.625	53.50	0.545	ULTRA DQX	Standard	8.500	Standard API Drift	N/A	3.50 in (89.0 mm)	8.519 in (216.40 mm)	8.631 in (219.22 mm)	9.609 in (244.08 mm)	9.721 in (246.90 mm)	N/A	N/A	9.455 in (240.16 mm)	9.515 in (241.68 mm)	9.268 in (235.42 mm)	9.300 in (236.22 mm)	N/A	N/A	10.594 in (269.10 mm)	10.734 in (272.64 mm)	N/A	N/A
9.625	53.50	0.545	ULTRA DQX	Accessory	8.500	Standard API Drift	5.27 in (133.8 mm)	3.50 in (89.0 mm)	8.519 in (216.40 mm)	8.551 in (217.18 mm)	9.609 in (244.08 mm)	9.641 in (244.88 mm)	5.27 in (133.8 mm)	2.63 in (66.8 mm)	N/A	N/A	8.519 in (216.40 mm)	8.551 in (217.18 mm)	N/A	N/A	10.594 in (269.10 mm)	10.734 in (272.64 mm)	N/A	N/A

Dimensions provided do not include length required for tongs for making up assemblies. Please take this into consideration when designing and machining your accessory.

BLANK OD and ID: The nominal blank ODs and IDs in the Pin Diameters and Box Diameters columns are finished product dimensions. When this minimum material is supplied, the blank OD and the blank ID must be true to each other within 0.010" TIR (Total Indicator Reading).

BLANK Min Length includes 0.02" (0.5mm) extra material for facing.

Contact Tenaris Manufacturing Services at blankingdimensions@tenaris.com for details.

These Blanking Dimensions are NOT applicable For Handling & lifting plug, HydroTest Caps & HydroTest Plugs.

N/A: Not Applicable

Yellow - Shaded corresponds to modified from previous document revision.