



# TenarisHydril Blue® Dopeless® 3.0 Blanking Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, recycled, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections B.V. and/or (Hydril) Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyright© 2021 as an unpublished work. ALL RIGHTS RESERVED.

SIZE (IN)	WEIGHT (LB/FT)	WALL (IN)	CONNECTION				PIN						BOX						EFFICIENCY		OUTSIDE DIAMETER - SPECIAL CLEARANCE #1		OUTSIDE DIAMETER - SPECIAL CLEARANCE #2		OUTSIDE DIAMETER - SPECIAL CLEARANCE #3							
			PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH		RECUR LENGTH		COUPLING LENGTH										INSIDE DIAMETER		OUTSIDE DIAMETER - REGULAR		OUTSIDE DIAMETER - MATCHED STRENGTH	
							MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX
5.00	26.00	0.476	TenarisHydril Blue® Dopeless® 3.0	Standard	4.423	Standard API Drift	5.33 (135.4 mm)	1.55 (39.4 mm)	4.537 (115.22 mm)	4.559 (115.82 mm)	5.500 (139.70 mm)	5.555 (141.08 mm)	5.33 (135.4 mm)	2.12 (53.8 mm)	10.650 (270.50 mm)	10.846 (275.50 mm)	4.544 (115.40 mm)	4.566 (116.00 mm)	6.288 (159.70 mm)	6.326 (160.70 mm)	6.221 (158.00 mm)	6.259 (159.00 mm)	85.0	6.103 (155.00 mm)	6.141 (156.00 mm)	N/A	N/A	N/A	N/A	N/A	N/A	N/A



TenarisHydril Blue® Dopeless® 3.0 Blanking Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, recycled, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections B.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request hereafter. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyright © 2021 by an unpublished work. ALL RIGHTS RESERVED.

Table with columns: CONNECTION (SIZE, WEIGHT, WALL, PRODUCT, TAG, DRIFT, DRIFT TYPE), PIN (LENGTH, RECUR LENGTH, INSIDE DIAMETER, OUTSIDE DIAMETER), BOX (LENGTH, RECUR LENGTH, COUPLING LENGTH, INSIDE DIAMETER, OUTSIDE DIAMETER - REGULAR, OUTSIDE DIAMETER - MATCHED STRENGTH, OUTSIDE DIAMETER - SPECIAL CLEARANCE #1, OUTSIDE DIAMETER - SPECIAL CLEARANCE #2, OUTSIDE DIAMETER - SPECIAL CLEARANCE #3), EFFICIENCY, MIN, MAX for various diameters and lengths.

# TenarisHydril Blue® Dopeless® 3.0 Blanking Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, recopied, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections B.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request therefore. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyrighted 2021 as an unpublished work. ALL RIGHTS RESERVED.

CONNECTION							PIN								BOX																			
SIZE (IN)	WEIGHT (LB/FT)	WALL (IN)	PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH		RECUR LENGTH		COUPLING LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER - REGULAR		OUTSIDE DIAMETER - MATCHED STRENGTH		OUTSIDE DIAMETER - SPECIAL CLEARANCE #1			OUTSIDE DIAMETER - SPECIAL CLEARANCE #2			OUTSIDE DIAMETER - SPECIAL CLEARANCE #3			
							MIN	MIN	MIN	MAX	MIN	MAX	MIN	MIN	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	EFFICIENCY	MIN	MAX	EFFICIENCY	MIN	MAX
14.000	114.00	0.800	TenarisHydril Blue® Dopeless® 3.0	Standard	12.213	Standard API Drift	7.10 in (180.2 mm)	1.60 in (40.8 mm)	12.389 in (314.66 mm)	12.411 in (315.26 mm)	14.000 in (355.60 mm)	14.140 in (359.14 mm)	7.10 in (180.2 mm)	2.80 in (71.2 mm)	14.359 in (364.70 mm)	14.555 in (369.70 mm)	12.662 in (321.60 mm)	12.684 in (322.18 mm)	15.284 in (388.20 mm)	15.322 in (389.20 mm)	15.241 in (387.10 mm)	15.279 in (388.10 mm)	85.0	15.032 in (381.80 mm)	15.070 in (382.80 mm)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
14.000	114.00	0.800	TenarisHydril Blue® Dopeless® 3.0	Standard	12.250	Special Drift	7.10 in (180.2 mm)	1.60 in (40.8 mm)	12.389 in (314.66 mm)	12.411 in (315.26 mm)	14.000 in (355.60 mm)	14.140 in (359.14 mm)	7.10 in (180.2 mm)	2.80 in (71.2 mm)	14.359 in (364.70 mm)	14.555 in (369.70 mm)	12.662 in (321.60 mm)	12.684 in (322.18 mm)	15.284 in (388.20 mm)	15.322 in (389.20 mm)	15.241 in (387.10 mm)	15.279 in (388.10 mm)	85.0	15.032 in (381.80 mm)	15.070 in (382.80 mm)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

Dimensions provided do not include length required for tongs for making up assemblies. Please take this into consideration when designing and machining your accessory.  
 BLANK OD and ID: The nominal blank ODs and IDs in the Pin Diameters and Box Diameters columns are finished product dimensions. When this minimum material is supplied, the blank OD and the blank ID must be true to each other within 0.010" TIR (Total Indicator Reading).  
 BLANK Min Length includes 0.02" (0.5mm) extra material for facing.  
 Contact Tenaris Manufacturing Services at [blankingdimensions@tenaris.com](mailto:blankingdimensions@tenaris.com) for details.  
 These Blanking Dimensions are NOT applicable For Handling & lifting plug, HydroTest Caps & HydroTest Plugs.  
 N/A: Not Applicable

Yellow - Shaded corresponds to modified from previous document revision.