

# TORQ® DQW™ Blanking Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, recopied, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections B.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request therefore. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyrighted 2020 as an unpublished work. ALL RIGHTS RESERVED.

SIZE (IN)	WEIGHT (LB/FT)	WALL (IN)	CONNECTION				PIN						BOX											
			PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH	RECUR LENGTH	INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH	RECUR LENGTH	COUPLING LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER - REGULAR API 9		OUTSIDE DIAMETER - REGULAR API 10		OUTSIDE DIAMETER - REGULAR	
									MIN	MAX	MIN	MAX			MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX
4.500	11.60	0.250	TORQ DQW	Standard	3.875	Standard API Drift	N/A	2.25 in (57.2 mm)	3.984 in (101.20 mm)	4.045 in (102.74 mm)	4.484 in (113.90 mm)	4.545 in (115.44 mm)	N/A	N/A	7.682 in (195.14 mm)	7.702 in (195.62 mm)	4.206 in (106.84 mm)	4.238 in (107.64 mm)	4.947 in (125.66 mm)	5.053 in (128.34 mm)	5.197 in (132.02 mm)	5.303 in (134.68 mm)	N/A	N/A
4.500	11.60	0.250	TORQ DQW	Accessory	3.875	Standard API Drift	4.48 in (113.8 mm)	2.25 in (57.2 mm)	3.984 in (101.20 mm)	4.016 in (102.00 mm)	4.484 in (113.90 mm)	4.516 in (114.70 mm)	4.37 in (111.0 mm)	2.25 in (57.2 mm)	N/A	N/A	3.984 in (101.20 mm)	4.016 in (102.00 mm)	4.947 in (125.66 mm)	5.053 in (128.34 mm)	5.197 in (132.02 mm)	5.303 in (134.68 mm)	N/A	N/A
4.500	12.60	0.271	TORQ DQW	Standard	3.833	Standard API Drift	N/A	2.25 in (57.2 mm)	3.942 in (100.14 mm)	4.003 in (101.66 mm)	4.484 in (113.90 mm)	4.545 in (115.44 mm)	N/A	N/A	7.682 in (195.14 mm)	7.702 in (195.62 mm)	4.206 in (106.84 mm)	4.238 in (107.64 mm)	4.947 in (125.66 mm)	5.053 in (128.34 mm)	5.197 in (132.02 mm)	5.303 in (134.68 mm)	N/A	N/A
4.500	12.60	0.271	TORQ DQW	Accessory	3.833	Standard API Drift	4.48 in (113.8 mm)	2.25 in (57.2 mm)	3.942 in (100.14 mm)	3.974 in (100.92 mm)	4.484 in (113.90 mm)	4.516 in (114.70 mm)	4.37 in (111.0 mm)	2.25 in (57.2 mm)	N/A	N/A	3.942 in (100.14 mm)	3.974 in (100.92 mm)	4.947 in (125.66 mm)	5.053 in (128.34 mm)	5.197 in (132.02 mm)	5.303 in (134.68 mm)	N/A	N/A
4.500	13.50	0.290	TORQ DQW	Standard	3.795	Standard API Drift	N/A	2.25 in (57.2 mm)	3.904 in (99.18 mm)	3.965 in (100.70 mm)	4.484 in (113.90 mm)	4.545 in (115.44 mm)	N/A	N/A	7.682 in (195.14 mm)	7.702 in (195.62 mm)	4.206 in (106.84 mm)	4.238 in (107.64 mm)	4.947 in (125.66 mm)	5.053 in (128.34 mm)	5.197 in (132.02 mm)	5.303 in (134.68 mm)	N/A	N/A
4.500	13.50	0.290	TORQ DQW	Accessory	3.795	Standard API Drift	4.48 in (113.8 mm)	2.25 in (57.2 mm)	3.904 in (99.18 mm)	3.936 in (99.96 mm)	4.484 in (113.90 mm)	4.516 in (114.70 mm)	4.37 in (111.0 mm)	2.25 in (57.2 mm)	N/A	N/A	3.904 in (99.18 mm)	3.936 in (99.96 mm)	4.947 in (125.66 mm)	5.053 in (128.34 mm)	5.197 in (132.02 mm)	5.303 in (134.68 mm)	N/A	N/A
4.500	15.10	0.337	TORQ DQW	Standard	3.701	Standard API Drift	N/A	2.25 in (57.2 mm)	3.810 in (96.78 mm)	3.871 in (98.32 mm)	4.484 in (113.90 mm)	4.545 in (115.44 mm)	N/A	N/A	7.682 in (195.14 mm)	7.702 in (195.62 mm)	4.206 in (106.84 mm)	4.238 in (107.64 mm)	4.947 in (125.66 mm)	5.053 in (128.34 mm)	5.197 in (132.02 mm)	5.303 in (134.68 mm)	N/A	N/A
4.500	15.10	0.337	TORQ DQW	Accessory	3.701	Standard API Drift	4.48 in (113.8 mm)	2.25 in (57.2 mm)	3.810 in (96.78 mm)	3.842 in (97.58 mm)	4.484 in (113.90 mm)	4.516 in (114.70 mm)	4.37 in (111.0 mm)	2.25 in (57.2 mm)	N/A	N/A	3.810 in (96.78 mm)	3.842 in (97.58 mm)	4.947 in (125.66 mm)	5.053 in (128.34 mm)	5.197 in (132.02 mm)	5.303 in (134.68 mm)	N/A	N/A
5.000	18.00	0.362	TORQ DQW	Standard	4.151	Standard API Drift	N/A	2.25 in (57.2 mm)	4.260 in (108.22 mm)	4.326 in (109.88 mm)	4.984 in (126.60 mm)	5.050 in (128.26 mm)	N/A	N/A	8.557 in (217.36 mm)	8.577 in (217.84 mm)	4.671 in (118.66 mm)	4.703 in (119.44 mm)	5.505 in (139.84 mm)	5.621 in (142.76 mm)	5.742 in (145.86 mm)	5.858 in (148.78 mm)	N/A	N/A
5.000	18.00	0.362	TORQ DQW	Accessory	4.151	Standard API Drift	4.92 in (125.0 mm)	2.25 in (57.2 mm)	4.260 in (108.22 mm)	4.292 in (109.00 mm)	4.984 in (126.60 mm)	5.016 in (127.40 mm)	4.81 in (122.2 mm)	2.25 in (57.2 mm)	N/A	N/A	4.260 in (108.22 mm)	4.292 in (109.00 mm)	5.505 in (139.84 mm)	5.621 in (142.76 mm)	5.742 in (145.86 mm)	5.858 in (148.78 mm)	N/A	N/A
5.000	21.40	0.437	TORQ DQW	Standard	4.001	Standard API Drift	N/A	2.25 in (57.2 mm)	4.110 in (104.40 mm)	4.176 in (106.06 mm)	4.984 in (126.60 mm)	5.050 in (128.26 mm)	N/A	N/A	8.557 in (217.36 mm)	8.577 in (217.84 mm)	4.671 in (118.66 mm)	4.703 in (119.44 mm)	5.505 in (139.84 mm)	5.621 in (142.76 mm)	5.742 in (145.86 mm)	5.858 in (148.78 mm)	N/A	N/A
5.000	21.40	0.437	TORQ DQW	Accessory	4.001	Standard API Drift	4.92 in (125.0 mm)	2.25 in (57.2 mm)	4.110 in (104.40 mm)	4.142 in (105.20 mm)	4.984 in (126.60 mm)	5.016 in (127.40 mm)	4.81 in (122.2 mm)	2.25 in (57.2 mm)	N/A	N/A	4.110 in (104.40 mm)	4.142 in (105.20 mm)	5.505 in (139.84 mm)	5.621 in (142.76 mm)	5.742 in (145.86 mm)	5.858 in (148.78 mm)	N/A	N/A
5.000	23.20	0.478	TORQ DQW	Standard	3.919	Standard API Drift	N/A	2.25 in (57.2 mm)	4.028 in (102.32 mm)	4.094 in (103.98 mm)	4.984 in (126.60 mm)	5.050 in (128.26 mm)	N/A	N/A	8.557 in (217.36 mm)	8.577 in (217.84 mm)	4.671 in (118.66 mm)	4.703 in (119.44 mm)	5.505 in (139.84 mm)	5.621 in (142.76 mm)	5.742 in (145.86 mm)	5.858 in (148.78 mm)	N/A	N/A
5.000	23.20	0.478	TORQ DQW	Accessory	3.919	Standard API Drift	4.92 in (125.0 mm)	2.25 in (57.2 mm)	4.028 in (102.32 mm)	4.060 in (103.12 mm)	4.984 in (126.60 mm)	5.016 in (127.40 mm)	4.81 in (122.2 mm)	2.25 in (57.2 mm)	N/A	N/A	4.028 in (102.32 mm)	4.060 in (103.12 mm)	5.505 in (139.84 mm)	5.621 in (142.76 mm)	5.742 in (145.86 mm)	5.858 in (148.78 mm)	N/A	N/A
5.500	17.00	0.304	TORQ DQW	Standard	4.767	Standard API Drift	N/A	2.25 in (57.2 mm)	4.876 in (123.86 mm)	4.947 in (125.64 mm)	5.484 in (139.30 mm)	5.555 in (141.08 mm)	N/A	N/A	8.637 in (219.38 mm)	8.657 in (219.88 mm)	5.157 in (131.00 mm)	5.189 in (131.80 mm)	5.987 in (152.08 mm)	6.113 in (155.26 mm)	6.237 in (158.42 mm)	6.363 in (161.62 mm)	N/A	N/A
5.500	17.00	0.304	TORQ DQW	Accessory	4.767	Standard API Drift	4.96 in (126.0 mm)	2.25 in (57.2 mm)	4.876 in (123.86 mm)	4.908 in (124.66 mm)	5.484 in (139.30 mm)	5.516 in (140.10 mm)	4.85 in (123.2 mm)	2.25 in (57.2 mm)	N/A	N/A	4.876 in (123.86 mm)	4.908 in (124.66 mm)	5.987 in (152.08 mm)	6.113 in (155.26 mm)	6.237 in (158.42 mm)	6.363 in (161.62 mm)	N/A	N/A
5.500	20.00	0.361	TORQ DQW	Standard	4.653	Standard API Drift	N/A	2.25 in (57.2 mm)	4.762 in (120.96 mm)	4.833 in (122.74 mm)	5.484 in (139.30 mm)	5.555 in (141.08 mm)	N/A	N/A	8.637 in (219.38 mm)	8.657 in (219.88 mm)	5.157 in (131.00 mm)	5.189 in (131.80 mm)	5.987 in (152.08 mm)	6.113 in (155.26 mm)	6.237 in (158.42 mm)	6.363 in (161.62 mm)	N/A	N/A
5.500	20.00	0.361	TORQ DQW	Accessory	4.653	Standard API Drift	4.96 in (126.0 mm)	2.25 in (57.2 mm)	4.762 in (120.96 mm)	4.794 in (121.76 mm)	5.484 in (139.30 mm)	5.516 in (140.10 mm)	4.85 in (123.2 mm)	2.25 in (57.2 mm)	N/A	N/A	4.762 in (120.96 mm)	4.794 in (121.76 mm)	5.987 in (152.08 mm)	6.113 in (155.26 mm)	6.237 in (158.42 mm)	6.363 in (161.62 mm)	N/A	N/A

# TORQ® DQW™ Blanking Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, recopied, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections B.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request therefore. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyrighted 2020 as an unpublished work. ALL RIGHTS RESERVED.

SIZE (IN)	CONNECTION						PIN						BOX											
	WEIGHT (LB/FT)	WALL (IN)	PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH	RECUR LENGTH	INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH	RECUR LENGTH	COUPLING LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER - REGULAR API 9		OUTSIDE DIAMETER - REGULAR API 10		OUTSIDE DIAMETER - REGULAR	
									MIN	MAX	MIN	MAX			MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX
5.500	23.00	0.415	TORQ DQW	Standard	4.545	Standard API Drift	N/A	2.25 in (57.2 mm)	4.654 in (118.22 mm)	4.725 in (120.00 mm)	5.484 in (139.30 mm)	5.555 in (141.08 mm)	N/A	N/A	8.637 in (219.38 mm)	8.657 in (219.88 mm)	5.157 in (131.00 mm)	5.189 in (131.80 mm)	5.987 in (152.08 mm)	6.113 in (155.26 mm)	6.237 in (158.42 mm)	6.363 in (161.62 mm)	N/A	N/A
5.500	23.00	0.415	TORQ DQW	Accessory	4.545	Standard API Drift	4.96 in (126.0 mm)	2.25 in (57.2 mm)	4.654 in (118.22 mm)	4.686 in (119.02 mm)	5.484 in (139.30 mm)	5.516 in (140.10 mm)	4.85 in (123.2 mm)	2.25 in (57.2 mm)	N/A	N/A	4.654 in (118.22 mm)	4.686 in (119.02 mm)	5.987 in (152.08 mm)	6.113 in (155.26 mm)	6.237 in (158.42 mm)	6.363 in (161.62 mm)	N/A	N/A
5.500	26.00	0.476	TORQ DQW	Standard	4.423	Standard API Drift	N/A	2.25 in (57.2 mm)	4.532 in (115.12 mm)	4.603 in (116.90 mm)	5.484 in (139.30 mm)	5.555 in (141.08 mm)	N/A	N/A	8.637 in (219.38 mm)	8.657 in (219.88 mm)	5.157 in (131.00 mm)	5.189 in (131.80 mm)	5.987 in (152.08 mm)	6.113 in (155.26 mm)	6.237 in (158.42 mm)	6.363 in (161.62 mm)	N/A	N/A
5.500	26.00	0.476	TORQ DQW	Accessory	4.423	Standard API Drift	4.96 in (126.0 mm)	2.25 in (57.2 mm)	4.532 in (115.12 mm)	4.564 in (115.92 mm)	5.484 in (139.30 mm)	5.516 in (140.10 mm)	4.85 in (123.2 mm)	2.25 in (57.2 mm)	N/A	N/A	4.532 in (115.12 mm)	4.564 in (115.92 mm)	5.987 in (152.08 mm)	6.113 in (155.26 mm)	6.237 in (158.42 mm)	6.363 in (161.62 mm)	N/A	N/A
6.000	24.50	0.400	TORQ DQW	Standard	5.075	Standard API Drift	N/A	2.25 in (57.2 mm)	5.184 in (131.68 mm)	5.260 in (133.60 mm)	5.984 in (152.00 mm)	6.060 in (153.92 mm)	N/A	N/A	8.078 in (205.20 mm)	8.098 in (205.68 mm)	5.690 in (144.54 mm)	5.722 in (145.32 mm)	N/A	N/A	N/A	N/A	6.762 in (171.76 mm)	6.898 in (175.20 mm)
6.000	24.50	0.400	TORQ DQW	Accessory	5.075	Standard API Drift	4.68 in (118.8 mm)	2.25 in (57.2 mm)	5.184 in (131.68 mm)	5.216 in (132.48 mm)	5.984 in (152.00 mm)	6.016 in (152.80 mm)	4.57 in (116.0 mm)	2.25 in (57.2 mm)	N/A	N/A	5.184 in (131.68 mm)	5.216 in (132.48 mm)	N/A	N/A	N/A	N/A	6.762 in (171.76 mm)	6.898 in (175.20 mm)

Dimensions provided do not include length required for tongs for making up assemblies. Please take this into consideration when designing and machining your accessory.

BLANK OD and ID: The nominal blank ODs and IDs in the Pin Diameters and Box Diameters columns are finished product dimensions. When this minimum material is supplied, the blank OD and the blank ID must be true to each other within 0.010" TIR (Total Indicator Reading).

BLANK Min Length includes 0.02" (0.5mm) extra material for facing.

Contact Tenaris Manufacturing Services at [blankingdimensions@tenaris.com](mailto:blankingdimensions@tenaris.com) for details.

These Blanking Dimensions are NOT applicable For Handling & lifting plug, HydroTest Caps & HydroTest Plugs.

N/A: Not Applicable

Yellow - Shaded corresponds to modified from previous document revision.