

BPN Blanking Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, recopied, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections B.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request therefore. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyrighted 2020 as an unpublished work. ALL RIGHTS RESERVED.

SIZE (IN)	WEIGHT (LB/FT)	WALL (IN)	CONNECTION				PIN						BOX									
			PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH	RECU LENGTH	INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH	RECU LENGTH	COUPLING LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER - REGULAR API 9		OUTSIDE DIAMETER - REGULAR API 10	
									MIN	MAX	MIN	MAX			MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX
4.500	11.60	0.250	BPN	Standard	3.875	Standard API Drift	N/A	2.25 in (57.2 mm)	3.984 in (101.20 mm)	4.045 in (102.74 mm)	4.484 in (113.90 mm)	4.545 in (115.44 mm)	N/A	N/A	7.812 in (198.44 mm)	7.938 in (201.62 mm)	4.250 in (107.96 mm)	4.282 in (108.76 mm)	4.950 in (125.74 mm)	5.050 in (128.26 mm)	5.200 in (132.08 mm)	5.300 in (134.62 mm)
4.500	11.60	0.250	BPN	Accessory	3.875	Standard API Drift	4.46 in (113.4 mm)	2.25 in (57.2 mm)	3.984 in (101.20 mm)	4.016 in (102.00 mm)	4.484 in (113.90 mm)	4.516 in (114.70 mm)	4.46 in (113.4 mm)	2.25 in (57.2 mm)	N/A	N/A	3.984 in (101.20 mm)	4.016 in (102.00 mm)	4.950 in (125.74 mm)	5.050 in (128.26 mm)	5.200 in (132.08 mm)	5.300 in (134.62 mm)
4.500	13.50	0.290	BPN	Standard	3.795	Standard API Drift	N/A	2.25 in (57.2 mm)	3.904 in (99.18 mm)	3.965 in (100.70 mm)	4.484 in (113.90 mm)	4.545 in (115.44 mm)	N/A	N/A	7.812 in (198.44 mm)	7.938 in (201.62 mm)	4.250 in (107.96 mm)	4.282 in (108.76 mm)	4.950 in (125.74 mm)	5.050 in (128.26 mm)	5.200 in (132.08 mm)	5.300 in (134.62 mm)
4.500	13.50	0.290	BPN	Accessory	3.795	Standard API Drift	4.46 in (113.4 mm)	2.25 in (57.2 mm)	3.904 in (99.18 mm)	3.936 in (99.96 mm)	4.484 in (113.90 mm)	4.516 in (114.70 mm)	4.46 in (113.4 mm)	2.25 in (57.2 mm)	N/A	N/A	3.904 in (99.18 mm)	3.936 in (99.96 mm)	4.950 in (125.74 mm)	5.050 in (128.26 mm)	5.200 in (132.08 mm)	5.300 in (134.62 mm)
4.500	15.10	0.337	BPN	Standard	3.701	Standard API Drift	N/A	2.25 in (57.2 mm)	3.810 in (96.78 mm)	3.871 in (98.32 mm)	4.484 in (113.90 mm)	4.545 in (115.44 mm)	N/A	N/A	7.812 in (198.44 mm)	7.938 in (201.62 mm)	4.250 in (107.96 mm)	4.282 in (108.76 mm)	4.950 in (125.74 mm)	5.050 in (128.26 mm)	5.200 in (132.08 mm)	5.300 in (134.62 mm)
4.500	15.10	0.337	BPN	Accessory	3.701	Standard API Drift	4.46 in (113.4 mm)	2.25 in (57.2 mm)	3.810 in (96.78 mm)	3.842 in (97.58 mm)	4.484 in (113.90 mm)	4.516 in (114.70 mm)	4.46 in (113.4 mm)	2.25 in (57.2 mm)	N/A	N/A	3.810 in (96.78 mm)	3.842 in (97.58 mm)	4.950 in (125.74 mm)	5.050 in (128.26 mm)	5.200 in (132.08 mm)	5.300 in (134.62 mm)
5.000	18.00	0.362	BPN	Standard	4.151	Standard API Drift	N/A	2.25 in (57.2 mm)	4.260 in (108.22 mm)	4.326 in (109.88 mm)	4.984 in (126.60 mm)	5.050 in (128.26 mm)	N/A	N/A	8.062 in (204.78 mm)	8.188 in (207.96 mm)	4.736 in (120.30 mm)	4.768 in (121.10 mm)	5.505 in (139.84 mm)	5.621 in (142.76 mm)	5.742 in (145.86 mm)	5.858 in (148.78 mm)
5.000	18.00	0.362	BPN	Accessory	4.151	Standard API Drift	4.59 in (116.6 mm)	2.25 in (57.2 mm)	4.260 in (108.22 mm)	4.292 in (109.00 mm)	4.984 in (126.60 mm)	5.016 in (127.40 mm)	4.59 in (116.6 mm)	2.25 in (57.2 mm)	N/A	N/A	4.260 in (108.22 mm)	4.292 in (109.00 mm)	5.505 in (139.84 mm)	5.621 in (142.76 mm)	5.742 in (145.86 mm)	5.858 in (148.78 mm)
5.000	21.40	0.437	BPN	Standard	4.001	Standard API Drift	N/A	2.25 in (57.2 mm)	4.110 in (104.40 mm)	4.176 in (106.06 mm)	4.984 in (126.60 mm)	5.050 in (128.26 mm)	N/A	N/A	8.062 in (204.78 mm)	8.188 in (207.96 mm)	4.736 in (120.30 mm)	4.768 in (121.10 mm)	5.505 in (139.84 mm)	5.621 in (142.76 mm)	5.742 in (145.86 mm)	5.858 in (148.78 mm)
5.000	21.40	0.437	BPN	Accessory	4.001	Standard API Drift	4.59 in (116.6 mm)	2.25 in (57.2 mm)	4.110 in (104.40 mm)	4.142 in (105.20 mm)	4.984 in (126.60 mm)	5.016 in (127.40 mm)	4.59 in (116.6 mm)	2.25 in (57.2 mm)	N/A	N/A	4.110 in (104.40 mm)	4.142 in (105.20 mm)	5.505 in (139.84 mm)	5.621 in (142.76 mm)	5.742 in (145.86 mm)	5.858 in (148.78 mm)
5.000	23.20	0.478	BPN	Standard	3.919	Standard API Drift	N/A	2.25 in (57.2 mm)	4.028 in (102.32 mm)	4.094 in (103.98 mm)	4.984 in (126.60 mm)	5.050 in (128.26 mm)	N/A	N/A	8.062 in (204.78 mm)	8.188 in (207.96 mm)	4.736 in (120.30 mm)	4.768 in (121.10 mm)	5.505 in (139.84 mm)	5.621 in (142.76 mm)	5.742 in (145.86 mm)	5.858 in (148.78 mm)
5.000	23.20	0.478	BPN	Accessory	3.919	Standard API Drift	4.59 in (116.6 mm)	2.25 in (57.2 mm)	4.028 in (102.32 mm)	4.060 in (103.12 mm)	4.984 in (126.60 mm)	5.016 in (127.40 mm)	4.59 in (116.6 mm)	2.25 in (57.2 mm)	N/A	N/A	4.028 in (102.32 mm)	4.060 in (103.12 mm)	5.505 in (139.84 mm)	5.621 in (142.76 mm)	5.742 in (145.86 mm)	5.858 in (148.78 mm)
5.500	17.00	0.304	BPN	Standard	4.767	Standard API Drift	N/A	2.25 in (57.2 mm)	4.876 in (123.86 mm)	4.947 in (125.64 mm)	5.484 in (139.30 mm)	5.555 in (141.08 mm)	N/A	N/A	8.187 in (207.96 mm)	8.313 in (211.14 mm)	5.232 in (132.90 mm)	5.264 in (133.70 mm)	5.987 in (152.08 mm)	6.113 in (155.26 mm)	6.237 in (158.42 mm)	6.363 in (161.62 mm)
5.500	17.00	0.304	BPN	Accessory	4.767	Standard API Drift	4.65 in (118.0 mm)	2.25 in (57.2 mm)	4.876 in (123.86 mm)	4.908 in (124.66 mm)	5.484 in (139.30 mm)	5.516 in (140.10 mm)	4.65 in (118.0 mm)	2.25 in (57.2 mm)	N/A	N/A	4.876 in (123.86 mm)	4.908 in (124.66 mm)	5.987 in (152.08 mm)	6.113 in (155.26 mm)	6.237 in (158.42 mm)	6.363 in (161.62 mm)
5.500	20.00	0.361	BPN	Standard	4.653	Standard API Drift	N/A	2.25 in (57.2 mm)	4.762 in (120.96 mm)	4.833 in (122.74 mm)	5.484 in (139.30 mm)	5.555 in (141.08 mm)	N/A	N/A	8.187 in (207.96 mm)	8.313 in (211.14 mm)	5.232 in (132.90 mm)	5.264 in (133.70 mm)	5.987 in (152.08 mm)	6.113 in (155.26 mm)	6.237 in (158.42 mm)	6.363 in (161.62 mm)
5.500	20.00	0.361	BPN	Accessory	4.653	Standard API Drift	4.65 in (118.0 mm)	2.25 in (57.2 mm)	4.762 in (120.96 mm)	4.794 in (121.76 mm)	5.484 in (139.30 mm)	5.516 in (140.10 mm)	4.65 in (118.0 mm)	2.25 in (57.2 mm)	N/A	N/A	4.762 in (120.96 mm)	4.794 in (121.76 mm)	5.987 in (152.08 mm)	6.113 in (155.26 mm)	6.237 in (158.42 mm)	6.363 in (161.62 mm)
5.500	23.00	0.415	BPN	Standard	4.545	Standard API Drift	N/A	2.25 in (57.2 mm)	4.654 in (118.22 mm)	4.725 in (120.00 mm)	5.484 in (139.30 mm)	5.555 in (141.08 mm)	N/A	N/A	8.187 in (207.96 mm)	8.313 in (211.14 mm)	5.232 in (132.90 mm)	5.264 in (133.70 mm)	5.987 in (152.08 mm)	6.113 in (155.26 mm)	6.237 in (158.42 mm)	6.363 in (161.62 mm)
5.500	23.00	0.415	BPN	Accessory	4.545	Standard API Drift	4.65 in (118.0 mm)	2.25 in (57.2 mm)	4.654 in (118.22 mm)	4.686 in (119.02 mm)	5.484 in (139.30 mm)	5.516 in (140.10 mm)	4.65 in (118.0 mm)	2.25 in (57.2 mm)	N/A	N/A	4.654 in (118.22 mm)	4.686 in (119.02 mm)	5.987 in (152.08 mm)	6.113 in (155.26 mm)	6.237 in (158.42 mm)	6.363 in (161.62 mm)
7.000	26.00	0.362	BPN	Standard	6.151	Standard API Drift	N/A	2.25 in (57.2 mm)	6.260 in (159.02 mm)	6.346 in (161.18 mm)	6.984 in (177.40 mm)	7.070 in (179.56 mm)	N/A	N/A	8.937 in (227.00 mm)	9.063 in (230.20 mm)	6.709 in (170.42 mm)	6.741 in (171.22 mm)	N/A	N/A	7.812 in (198.44 mm)	7.938 in (201.62 mm)
7.000	26.00	0.362	BPN	Accessory	6.151	Standard API Drift	5.02 in (127.6 mm)	2.25 in (57.2 mm)	6.260 in (159.02 mm)	6.292 in (159.80 mm)	6.984 in (177.40 mm)	7.016 in (178.20 mm)	5.02 in (127.6 mm)	2.25 in (57.2 mm)	N/A	N/A	6.260 in (159.02 mm)	6.292 in (159.80 mm)	N/A	N/A	7.812 in (198.44 mm)	7.938 in (201.62 mm)
7.000	29.00	0.408	BPN	Standard	6.059	Standard API Drift	N/A	2.25 in (57.2 mm)	6.168 in (156.68 mm)	6.254 in (158.84 mm)	6.984 in (177.40 mm)	7.070 in (179.56 mm)	N/A	N/A	8.937 in (227.00 mm)	9.063 in (230.20 mm)	6.709 in (170.42 mm)	6.741 in (171.22 mm)	N/A	N/A	7.812 in (198.44 mm)	7.938 in (201.62 mm)
7.000	29.00	0.408	BPN	Accessory	6.059	Standard API Drift	5.02 in (127.6 mm)	2.25 in (57.2 mm)	6.168 in (156.68 mm)	6.200 in (157.48 mm)	6.984 in (177.40 mm)	7.016 in (178.20 mm)	5.02 in (127.6 mm)	2.25 in (57.2 mm)	N/A	N/A	6.168 in (156.68 mm)	6.200 in (157.48 mm)	N/A	N/A	7.812 in (198.44 mm)	7.938 in (201.62 mm)
7.000	32.00	0.453	BPN	Standard	5.969	Standard API Drift	N/A	2.25 in (57.2 mm)	6.078 in (154.40 mm)	6.164 in (156.56 mm)	6.984 in (177.40 mm)	7.070 in (179.56 mm)	N/A	N/A	8.937 in (227.00 mm)	9.063 in (230.20 mm)	6.709 in (170.42 mm)	6.741 in (171.22 mm)	N/A	N/A	7.812 in (198.44 mm)	7.938 in (201.62 mm)
7.000	32.00	0.453	BPN	Accessory	5.969	Standard API Drift	5.02 in (127.6 mm)	2.25 in (57.2 mm)	6.078 in (154.40 mm)	6.110 in (155.18 mm)	6.984 in (177.40 mm)	7.016 in (178.20 mm)	5.02 in (127.6 mm)	2.25 in (57.2 mm)	N/A	N/A	6.078 in (154.40 mm)	6.110 in (155.18 mm)	N/A	N/A	7.812 in (198.44 mm)	7.938 in (201.62 mm)
7.625	26.40	0.328	BPN	Standard	6.844	Standard API Drift	N/A	2.25 in (57.2 mm)	6.953 in (176.62 mm)	7.045 in (178.94 mm)	7.609 in (193.28 mm)	7.701 in (195.60 mm)	N/A	N/A	9.312 in (236.54 mm)	9.438 in (239.72 mm)	7.322 in (185.98 mm)	7.354 in (186.78 mm)	N/A	N/A	8.437 in (214.30 mm)	8.563 in (217.50 mm)

BPN Blanking Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, reprinted, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections B.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request therefore. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyrighted 2020 as an unpublished work. ALL RIGHTS RESERVED.

SIZE (IN)	WEIGHT (LB/FT)	WALL (IN)	CONNECTION				PIN						BOX									
			PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH	RECUT LENGTH	INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH	RECUT LENGTH	COUPLING LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER - REGULAR API 9		OUTSIDE DIAMETER - REGULAR API 10	
									MIN	MAX	MIN	MAX			MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX
7.625	26.40	0.328	BPN	Accessory	6.844	Standard API Drift	5.21 in (132.4 mm)	2.25 in (57.2 mm)	6.953 in (176.62 mm)	6.985 in (177.40 mm)	7.609 in (193.28 mm)	7.641 in (194.08 mm)	5.21 in (132.4 mm)	2.25 in (57.2 mm)	N/A	N/A	6.953 in (176.62 mm)	6.985 in (177.40 mm)	N/A	N/A	8.437 in (214.30 mm)	8.563 in (217.50 mm)
7.625	29.70	0.375	BPN	Standard	6.750	Standard API Drift	N/A	2.25 in (57.2 mm)	6.859 in (174.22 mm)	6.951 in (176.54 mm)	7.609 in (193.28 mm)	7.701 in (195.60 mm)	N/A	N/A	9.312 in (236.54 mm)	9.438 in (239.72 mm)	7.322 in (185.98 mm)	7.354 in (186.78 mm)	N/A	N/A	8.437 in (214.30 mm)	8.563 in (217.50 mm)
7.625	29.70	0.375	BPN	Accessory	6.750	Standard API Drift	5.21 in (132.4 mm)	2.25 in (57.2 mm)	6.859 in (174.22 mm)	6.891 in (175.02 mm)	7.609 in (193.28 mm)	7.641 in (194.08 mm)	5.21 in (132.4 mm)	2.25 in (57.2 mm)	N/A	N/A	6.859 in (174.22 mm)	6.891 in (175.02 mm)	N/A	N/A	8.437 in (214.30 mm)	8.563 in (217.50 mm)
7.625	33.70	0.430	BPN	Standard	6.640	Standard API Drift	N/A	2.25 in (57.2 mm)	6.749 in (171.44 mm)	6.841 in (173.76 mm)	7.609 in (193.28 mm)	7.701 in (195.60 mm)	N/A	N/A	9.312 in (236.54 mm)	9.438 in (239.72 mm)	7.322 in (185.98 mm)	7.354 in (186.78 mm)	N/A	N/A	8.437 in (214.30 mm)	8.563 in (217.50 mm)
7.625	33.70	0.430	BPN	Accessory	6.640	Standard API Drift	5.21 in (132.4 mm)	2.25 in (57.2 mm)	6.749 in (171.44 mm)	6.781 in (172.22 mm)	7.609 in (193.28 mm)	7.641 in (194.08 mm)	5.21 in (132.4 mm)	2.25 in (57.2 mm)	N/A	N/A	6.749 in (171.44 mm)	6.781 in (172.22 mm)	N/A	N/A	8.437 in (214.30 mm)	8.563 in (217.50 mm)
9.625	36.00	0.352	BPN	Standard	8.765	Standard API Drift	N/A	2.25 in (57.2 mm)	8.905 in (226.20 mm)	9.017 in (229.02 mm)	9.609 in (244.08 mm)	9.721 in (246.90 mm)	N/A	N/A	9.562 in (242.88 mm)	9.688 in (246.06 mm)	9.314 in (236.58 mm)	9.346 in (237.38 mm)	N/A	N/A	10.562 in (268.28 mm)	10.688 in (271.46 mm)
9.625	36.00	0.352	BPN	Accessory	8.765	Standard API Drift	5.34 in (135.6 mm)	2.25 in (57.2 mm)	8.905 in (226.20 mm)	8.937 in (226.98 mm)	9.609 in (244.08 mm)	9.641 in (244.88 mm)	5.34 in (135.6 mm)	2.25 in (57.2 mm)	N/A	N/A	8.905 in (226.20 mm)	8.937 in (226.98 mm)	N/A	N/A	10.562 in (268.28 mm)	10.688 in (271.46 mm)
9.625	40.00	0.395	BPN	Standard	8.679	Standard API Drift	N/A	2.25 in (57.2 mm)	8.819 in (224.02 mm)	8.931 in (226.84 mm)	9.609 in (244.08 mm)	9.721 in (246.90 mm)	N/A	N/A	9.562 in (242.88 mm)	9.688 in (246.06 mm)	9.314 in (236.58 mm)	9.346 in (237.38 mm)	N/A	N/A	10.562 in (268.28 mm)	10.688 in (271.46 mm)
9.625	40.00	0.395	BPN	Accessory	8.679	Standard API Drift	5.34 in (135.6 mm)	2.25 in (57.2 mm)	8.819 in (224.02 mm)	8.851 in (224.80 mm)	9.609 in (244.08 mm)	9.641 in (244.88 mm)	5.34 in (135.6 mm)	2.25 in (57.2 mm)	N/A	N/A	8.819 in (224.02 mm)	8.851 in (224.80 mm)	N/A	N/A	10.562 in (268.28 mm)	10.688 in (271.46 mm)
9.625	43.50	0.435	BPN	Standard	8.599	Standard API Drift	N/A	2.25 in (57.2 mm)	8.739 in (221.98 mm)	8.851 in (224.80 mm)	9.609 in (244.08 mm)	9.721 in (246.90 mm)	N/A	N/A	9.562 in (242.88 mm)	9.688 in (246.06 mm)	9.314 in (236.58 mm)	9.346 in (237.38 mm)	N/A	N/A	10.562 in (268.28 mm)	10.688 in (271.46 mm)
9.625	43.50	0.435	BPN	Accessory	8.599	Standard API Drift	5.34 in (135.6 mm)	2.25 in (57.2 mm)	8.739 in (221.98 mm)	8.771 in (222.78 mm)	9.609 in (244.08 mm)	9.641 in (244.88 mm)	5.34 in (135.6 mm)	2.25 in (57.2 mm)	N/A	N/A	8.739 in (221.98 mm)	8.771 in (222.78 mm)	N/A	N/A	10.562 in (268.28 mm)	10.688 in (271.46 mm)
9.625	47.00	0.472	BPN	Standard	8.525	Standard API Drift	N/A	2.25 in (57.2 mm)	8.665 in (220.10 mm)	8.777 in (222.92 mm)	9.609 in (244.08 mm)	9.721 in (246.90 mm)	N/A	N/A	9.562 in (242.88 mm)	9.688 in (246.06 mm)	9.314 in (236.58 mm)	9.346 in (237.38 mm)	N/A	N/A	10.562 in (268.28 mm)	10.688 in (271.46 mm)
9.625	47.00	0.472	BPN	Accessory	8.525	Standard API Drift	5.34 in (135.6 mm)	2.25 in (57.2 mm)	8.665 in (220.10 mm)	8.697 in (220.90 mm)	9.609 in (244.08 mm)	9.641 in (244.88 mm)	5.34 in (135.6 mm)	2.25 in (57.2 mm)	N/A	N/A	8.665 in (220.10 mm)	8.697 in (220.90 mm)	N/A	N/A	10.562 in (268.28 mm)	10.688 in (271.46 mm)
10.750	40.50	0.350	BPN	Standard	9.894	Standard API Drift	N/A	2.25 in (57.2 mm)	10.034 in (254.88 mm)	10.158 in (258.00 mm)	10.734 in (272.66 mm)	10.858 in (275.78 mm)	N/A	N/A	9.562 in (242.88 mm)	9.688 in (246.06 mm)	10.439 in (265.16 mm)	10.471 in (265.96 mm)	N/A	N/A	11.687 in (296.86 mm)	11.813 in (300.04 mm)
10.750	40.50	0.350	BPN	Accessory	9.894	Standard API Drift	5.34 in (135.6 mm)	2.25 in (57.2 mm)	10.034 in (254.88 mm)	10.066 in (255.66 mm)	10.734 in (272.66 mm)	10.766 in (273.44 mm)	5.34 in (135.6 mm)	2.25 in (57.2 mm)	N/A	N/A	10.034 in (254.88 mm)	10.066 in (255.66 mm)	N/A	N/A	11.687 in (296.86 mm)	11.813 in (300.04 mm)
10.750	45.50	0.400	BPN	Standard	9.794	Standard API Drift	N/A	2.25 in (57.2 mm)	9.934 in (252.34 mm)	10.058 in (255.46 mm)	10.734 in (272.66 mm)	10.858 in (275.78 mm)	N/A	N/A	9.562 in (242.88 mm)	9.688 in (246.06 mm)	10.439 in (265.16 mm)	10.471 in (265.96 mm)	N/A	N/A	11.687 in (296.86 mm)	11.813 in (300.04 mm)
10.750	45.50	0.400	BPN	Accessory	9.794	Standard API Drift	5.34 in (135.6 mm)	2.25 in (57.2 mm)	9.934 in (252.34 mm)	9.966 in (253.12 mm)	10.734 in (272.66 mm)	10.766 in (273.44 mm)	5.34 in (135.6 mm)	2.25 in (57.2 mm)	N/A	N/A	9.934 in (252.34 mm)	9.966 in (253.12 mm)	N/A	N/A	11.687 in (296.86 mm)	11.813 in (300.04 mm)
10.750	51.00	0.450	BPN	Standard	9.694	Standard API Drift	N/A	2.25 in (57.2 mm)	9.834 in (249.80 mm)	9.958 in (252.92 mm)	10.734 in (272.66 mm)	10.858 in (275.78 mm)	N/A	N/A	9.562 in (242.88 mm)	9.688 in (246.06 mm)	10.439 in (265.16 mm)	10.471 in (265.96 mm)	N/A	N/A	11.687 in (296.86 mm)	11.813 in (300.04 mm)
10.750	51.00	0.450	BPN	Accessory	9.694	Standard API Drift	5.34 in (135.6 mm)	2.25 in (57.2 mm)	9.834 in (249.80 mm)	9.866 in (250.58 mm)	10.734 in (272.66 mm)	10.766 in (273.44 mm)	5.34 in (135.6 mm)	2.25 in (57.2 mm)	N/A	N/A	9.834 in (249.80 mm)	9.866 in (250.58 mm)	N/A	N/A	11.687 in (296.86 mm)	11.813 in (300.04 mm)
10.750	55.50	0.495	BPN	Standard	9.604	Standard API Drift	N/A	2.25 in (57.2 mm)	9.744 in (247.50 mm)	9.868 in (250.64 mm)	10.734 in (272.66 mm)	10.858 in (275.78 mm)	N/A	N/A	9.562 in (242.88 mm)	9.688 in (246.06 mm)	10.439 in (265.16 mm)	10.471 in (265.96 mm)	N/A	N/A	11.687 in (296.86 mm)	11.813 in (300.04 mm)
10.750	55.50	0.495	BPN	Accessory	9.604	Standard API Drift	5.34 in (135.6 mm)	2.25 in (57.2 mm)	9.744 in (247.50 mm)	9.776 in (248.30 mm)	10.734 in (272.66 mm)	10.766 in (273.44 mm)	5.34 in (135.6 mm)	2.25 in (57.2 mm)	N/A	N/A	9.744 in (247.50 mm)	9.776 in (248.30 mm)	N/A	N/A	11.687 in (296.86 mm)	11.813 in (300.04 mm)

Dimensions provided do not include length required for tongs for making up assemblies. Please take this into consideration when designing and machining your accessory.

BLANK OD and ID: The nominal blank ODs and IDs in the Pin Diameters and Box Diameters columns are finished product dimensions. When this minimum material is supplied, the blank OD and the blank ID must be true to each other within 0.010" TIR (Total Indicator Reading).

BLANK Min Length includes 0.02" (0.5mm) extra material for facing.

Contact Tenaris Manufacturing Services at blankingdimensions@tenaris.com for details.

These Blanking Dimensions are NOT applicable For Handling & lifting plug, HydroTest Caps & HydroTest Plugs.

N/A: Not Applicable

Yellow - Shaded corresponds to modified from previous document revision.