

TenarisHydril Wedge 461® Blanking and Accessory Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, recopied, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections B.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request therefore. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyrighted 2021 as an unpublished work. ALL RIGHTS RESERVED.

SIZE (IN)	WEIGHT (LB/FT)	WALL (IN)	CONNECTION				PIN						BOX											
			PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH	RECU LENGTH	COUPLING LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER - MATCHED STRENGTH		OUTSIDE DIAMETER - MACHINED OD		OUTSIDE DIAMETER - AS ROLLED	
							MIN	MIN	MIN	MAX	MIN	MAX			MIN	MIN	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX
4.500	11.60	0.250	TenarisHydril Wedge 461®	Standard	3.875	Standard API Drift	3.90 in (99.0 mm)	1.79 in (45.4 mm)	3.990 in (101.36 mm)	4.010 in (101.84 mm)	4.500 in (114.30 mm)	4.545 in (115.44 mm)	N/A	1.79 in (45.4 mm)	7.684 in (195.18 mm)	7.744 in (196.68 mm)	4.188 in (106.38 mm)	4.208 in (106.88 mm)	4.871 in (123.74 mm)	4.969 in (126.20 mm)	N/A	N/A	5.198 in (132.04 mm)	5.302 in (134.66 mm)
4.500	11.60	0.250	TenarisHydril Wedge 461®	Accessory	3.875	Standard API Drift	3.90 in (99.0 mm)	1.79 in (45.4 mm)	3.990 in (101.36 mm)	4.010 in (101.84 mm)	4.500 in (114.30 mm)	4.545 in (115.44 mm)	4.51 in (114.4 mm)	1.97 in (50.0 mm)	N/A	N/A	4.188 in (106.38 mm)	4.208 in (106.88 mm)	N/A	N/A	5.230 in (132.86 mm)	5.270 in (133.84 mm)	N/A	N/A
4.500	13.50	0.290	TenarisHydril Wedge 461®	Standard	3.795	Standard API Drift	4.19 in (106.4 mm)	1.79 in (45.4 mm)	3.910 in (99.32 mm)	3.930 in (99.82 mm)	4.500 in (114.30 mm)	4.545 in (115.44 mm)	N/A	1.79 in (45.4 mm)	7.684 in (195.18 mm)	7.744 in (196.68 mm)	4.188 in (106.38 mm)	4.208 in (106.88 mm)	4.910 in (124.72 mm)	5.010 in (127.24 mm)	N/A	N/A	5.198 in (132.04 mm)	5.302 in (134.66 mm)
4.500	13.50	0.290	TenarisHydril Wedge 461®	Accessory	3.795	Standard API Drift	4.19 in (106.4 mm)	1.79 in (45.4 mm)	3.910 in (99.32 mm)	3.930 in (99.82 mm)	4.500 in (114.30 mm)	4.545 in (115.44 mm)	4.51 in (114.4 mm)	1.97 in (50.0 mm)	N/A	N/A	3.910 in (99.32 mm)	3.930 in (99.82 mm)	N/A	N/A	5.230 in (132.86 mm)	5.270 in (133.84 mm)	N/A	N/A
4.500	15.20	0.337	TenarisHydril Wedge 461®	Standard	3.701	Standard API Drift	4.19 in (106.4 mm)	1.79 in (45.4 mm)	3.816 in (96.94 mm)	3.836 in (97.42 mm)	4.500 in (114.30 mm)	4.545 in (115.44 mm)	N/A	1.79 in (45.4 mm)	7.684 in (195.18 mm)	7.744 in (196.68 mm)	4.188 in (106.38 mm)	4.208 in (106.88 mm)	4.990 in (126.76 mm)	5.090 in (129.28 mm)	N/A	N/A	5.198 in (132.04 mm)	5.302 in (134.66 mm)
4.500	15.20	0.337	TenarisHydril Wedge 461®	Accessory	3.701	Standard API Drift	4.19 in (106.4 mm)	1.79 in (45.4 mm)	3.816 in (96.94 mm)	3.836 in (97.42 mm)	4.500 in (114.30 mm)	4.545 in (115.44 mm)	4.51 in (114.4 mm)	1.97 in (50.0 mm)	N/A	N/A	3.816 in (96.94 mm)	3.836 in (97.42 mm)	N/A	N/A	5.230 in (132.86 mm)	5.270 in (133.84 mm)	N/A	N/A
4.500	16.60	0.375	TenarisHydril Wedge 461®	Standard	3.625	Standard API Drift	4.19 in (106.4 mm)	1.79 in (45.4 mm)	3.740 in (95.00 mm)	3.760 in (95.50 mm)	4.500 in (114.30 mm)	4.545 in (115.44 mm)	N/A	1.79 in (45.4 mm)	7.684 in (195.18 mm)	7.744 in (196.68 mm)	4.188 in (106.38 mm)	4.208 in (106.88 mm)	5.049 in (128.26 mm)	5.151 in (130.82 mm)	N/A	N/A	5.198 in (132.04 mm)	5.302 in (134.66 mm)
4.500	16.60	0.375	TenarisHydril Wedge 461®	Accessory	3.625	Standard API Drift	4.19 in (106.4 mm)	1.79 in (45.4 mm)	3.740 in (95.00 mm)	3.760 in (95.50 mm)	4.500 in (114.30 mm)	4.545 in (115.44 mm)	4.51 in (114.4 mm)	1.97 in (50.0 mm)	N/A	N/A	3.740 in (95.00 mm)	3.760 in (95.50 mm)	N/A	N/A	5.230 in (132.86 mm)	5.270 in (133.84 mm)	N/A	N/A
5.000	18.00	0.362	TenarisHydril Wedge 461®	Standard	4.151	Standard API Drift	4.19 in (106.4 mm)	1.79 in (45.4 mm)	4.266 in (108.36 mm)	4.286 in (108.86 mm)	5.000 in (127.00 mm)	5.050 in (128.26 mm)	N/A	1.79 in (45.4 mm)	7.684 in (195.18 mm)	7.744 in (196.68 mm)	4.637 in (117.78 mm)	4.657 in (118.28 mm)	5.494 in (139.56 mm)	5.606 in (142.38 mm)	N/A	N/A	5.742 in (145.86 mm)	5.858 in (148.78 mm)
5.000	18.00	0.362	TenarisHydril Wedge 461®	Accessory	4.151	Standard API Drift	4.19 in (106.4 mm)	1.79 in (45.4 mm)	4.266 in (108.36 mm)	4.286 in (108.86 mm)	5.000 in (127.00 mm)	5.050 in (128.26 mm)	4.51 in (114.4 mm)	1.97 in (50.0 mm)	N/A	N/A	4.266 in (108.36 mm)	4.286 in (108.86 mm)	N/A	N/A	5.780 in (146.82 mm)	5.820 in (147.82 mm)	N/A	N/A
5.000	20.30	0.408	TenarisHydril Wedge 461®	Standard	4.059	Standard API Drift	4.19 in (106.4 mm)	1.79 in (45.4 mm)	4.174 in (106.02 mm)	4.194 in (106.52 mm)	5.000 in (127.00 mm)	5.050 in (128.26 mm)	N/A	1.79 in (45.4 mm)	7.684 in (195.18 mm)	7.744 in (196.68 mm)	4.637 in (117.78 mm)	4.657 in (118.28 mm)	5.564 in (141.34 mm)	5.676 in (144.16 mm)	N/A	N/A	5.742 in (145.86 mm)	5.858 in (148.78 mm)
5.000	20.30	0.408	TenarisHydril Wedge 461®	Accessory	4.059	Standard API Drift	4.19 in (106.4 mm)	1.79 in (45.4 mm)	4.174 in (106.02 mm)	4.194 in (106.52 mm)	5.000 in (127.00 mm)	5.050 in (128.26 mm)	4.51 in (114.4 mm)	1.97 in (50.0 mm)	N/A	N/A	4.174 in (106.02 mm)	4.194 in (106.52 mm)	N/A	N/A	5.780 in (146.82 mm)	5.820 in (147.82 mm)	N/A	N/A
5.000	20.80	0.422	TenarisHydril Wedge 461®	Standard	4.031	Standard API Drift	4.19 in (106.4 mm)	1.79 in (45.4 mm)	4.166 in (105.32 mm)	4.186 in (105.80 mm)	5.000 in (127.00 mm)	5.050 in (128.26 mm)	N/A	1.79 in (45.4 mm)	7.684 in (195.18 mm)	7.744 in (196.68 mm)	4.637 in (117.78 mm)	4.657 in (118.28 mm)	5.584 in (141.84 mm)	5.696 in (144.66 mm)	N/A	N/A	5.742 in (145.86 mm)	5.858 in (148.78 mm)
5.000	20.80	0.422	TenarisHydril Wedge 461®	Accessory	4.031	Standard API Drift	4.19 in (106.4 mm)	1.79 in (45.4 mm)	4.166 in (105.32 mm)	4.186 in (105.80 mm)	5.000 in (127.00 mm)	5.050 in (128.26 mm)	4.51 in (114.4 mm)	1.97 in (50.0 mm)	N/A	N/A	4.166 in (105.32 mm)	4.186 in (105.80 mm)	N/A	N/A	5.780 in (146.82 mm)	5.820 in (147.82 mm)	N/A	N/A
5.000	21.40	0.437	TenarisHydril Wedge 461®	Standard	4.001	Standard API Drift	4.19 in (106.4 mm)	1.79 in (45.4 mm)	4.116 in (104.56 mm)	4.136 in (105.04 mm)	5.000 in (127.00 mm)	5.050 in (128.26 mm)	N/A	1.79 in (45.4 mm)	7.684 in (195.18 mm)	7.744 in (196.68 mm)	4.637 in (117.78 mm)	4.657 in (118.28 mm)	5.613 in (142.58 mm)	5.727 in (145.46 mm)	N/A	N/A	5.742 in (145.86 mm)	5.858 in (148.78 mm)
5.000	21.40	0.437	TenarisHydril Wedge 461®	Accessory	4.001	Standard API Drift	4.19 in (106.4 mm)	1.79 in (45.4 mm)	4.116 in (104.56 mm)	4.136 in (105.04 mm)	5.000 in (127.00 mm)	5.050 in (128.26 mm)	4.51 in (114.4 mm)	1.97 in (50.0 mm)	N/A	N/A	4.116 in (104.56 mm)	4.136 in (105.04 mm)	N/A	N/A	5.780 in (146.82 mm)	5.820 in (147.82 mm)	N/A	N/A
5.000	23.20	0.478	TenarisHydril Wedge 461®	Standard	3.919	Standard API Drift	4.19 in (106.4 mm)	1.79 in (45.4 mm)	4.034 in (102.48 mm)	4.054 in (102.96 mm)	5.000 in (127.00 mm)	5.050 in (128.26 mm)	N/A	1.79 in (45.4 mm)	7.684 in (195.18 mm)	7.744 in (196.68 mm)	4.637 in (117.78 mm)	4.657 in (118.28 mm)	5.673 in (144.10 mm)	5.787 in (146.98 mm)	N/A	N/A	5.742 in (145.86 mm)	5.858 in (148.78 mm)
5.000	23.20	0.478	TenarisHydril Wedge 461®	Accessory	3.919	Standard API Drift	4.19 in (106.4 mm)	1.79 in (45.4 mm)	4.034 in (102.48 mm)	4.054 in (102.96 mm)	5.000 in (127.00 mm)	5.050 in (128.26 mm)	4.51 in (114.4 mm)	1.97 in (50.0 mm)	N/A	N/A	4.034 in (102.48 mm)	4.054 in (102.96 mm)	N/A	N/A	5.780 in (146.82 mm)	5.820 in (147.82 mm)	N/A	N/A
5.500	17.00	0.304	TenarisHydril Wedge 461®	Standard	4.767	Standard API Drift	4.19 in (106.4 mm)	1.79 in (45.4 mm)	4.882 in (124.02 mm)	4.902 in (124.50 mm)	5.500 in (139.70 mm)	5.555 in (141.08 mm)	N/A	1.79 in (45.4 mm)	7.684 in (195.18 mm)	7.744 in (196.68 mm)	5.135 in (130.44 mm)	5.155 in (130.92 mm)	5.900 in (149.86 mm)	6.020 in (152.90 mm)	N/A	N/A	6.237 in (158.42 mm)	6.363 in (161.62 mm)
5.500	17.00	0.304	TenarisHydril Wedge 461®	Accessory	4.767	Standard API Drift	4.19 in (106.4 mm)	1.79 in (45.4 mm)	4.882 in (124.02 mm)	4.902 in (124.50 mm)	5.500 in (139.70 mm)	5.555 in (141.08 mm)	4.51 in (114.4 mm)	1.97 in (50.0 mm)	N/A	N/A	4.882 in (124.02 mm)	4.902 in (124.50 mm)	N/A	N/A	6.280 in (159.52 mm)	6.320 in (160.52 mm)	N/A	N/A
5.500	20.00	0.361	TenarisHydril Wedge 461®	Standard	4.653	Standard API Drift	4.19 in (106.4 mm)	1.79 in (45.4 mm)	4.768 in (121.12 mm)	4.788 in (121.60 mm)	5.500 in (139.70 mm)	5.555 in (141.08 mm)	N/A	1.79 in (45.4 mm)	7.684 in (195.18 mm)	7.744 in (196.68 mm)	5.135 in (130.44 mm)	5.155 in (130.92 mm)	5.989 in (152.14 mm)	6.111 in (155.20 mm)	N/A	N/A	6.237 in (158.42 mm)	6.363 in (161.62 mm)
5.500	20.00	0.361	TenarisHydril Wedge 461®	Accessory	4.653	Standard API Drift	4.19 in (106.4 mm)	1.79 in (45.4 mm)	4.768 in (121.12 mm)	4.788 in (121.60 mm)	5.500 in (139.70 mm)	5.555 in (141.08 mm)	4.51 in (114.4 mm)	1.97 in (50.0 mm)	N/A	N/A	4.768 in (121.12 mm)	4.788 in (121.60 mm)	N/A	N/A	6.280 in (159.52 mm)	6.320 in (160.52 mm)	N/A	N/A
5.500	23.00	0.415	TenarisHydril Wedge 461®	Standard	4.545	Standard API Drift	4.19 in (106.4 mm)	1.79 in (45.4 mm)	4.660 in (118.38 mm)	4.680 in (118.86 mm)	5.500 in (139.70 mm)	5.555 in (141.08 mm)	N/A	1.79 in (45.4 mm)	7.684 in (195.18 mm)	7.744 in (196.68 mm)	5.135 in (130.44 mm)	5.155 in (130.92 mm)	6.079 in (154.42 mm)	6.201 in (157.50 mm)	N/A	N/A	6.237 in (158.42 mm)	6.363 in (161.62 mm)
5.500	23.00	0.415	TenarisHydril Wedge 461®	Accessory	4.545	Standard API Drift	4.19 in (106.4 mm)	1.79 in (45.4 mm)	4.660 in (118.38 mm)	4.680 in (118.86 mm)	5.500 in (139.70 mm)	5.555 in (141.08 mm)	4.51 in (114.4 mm)	1.97 in (50.0 mm)	N/A	N/A	4.660 in (118.38 mm)	4.680 in (118.86 mm)	N/A	N/A	6.280 in (159.52 mm)	6.320 in (160.52 mm)	N/A	N/A
5.500	26.00	0.476	TenarisHydril Wedge 461®	Standard	4.423	Standard API Drift	4.19 in (106.4 mm)	1.79 in (45.4 mm)	4.538 in (115.28 mm)	4.558 in (115.76 mm)	5.500 in (139.70 mm)	5.555 in (141.08 mm)	N/A	1.79 in (45.4 mm)	7.684 in (195.18 mm)	7.744 in (196.68 mm)	5.135 in (130.44 mm)	5.155 in (130.92 mm)	6.178 in (156.94 mm)	6.302 in (160.06 mm)	N/A	N/A	6.237 in (158.42 mm)	6.363 in (161.62 mm)
5.500	26.00	0.476	TenarisHydril Wedge 461®	Accessory	4.423	Standard API Drift	4.19 in (106.4 mm)	1.79 in (45.4 mm)	4.538 in (115.28 mm)	4.558 in (115.76 mm)	5.500 in (139.70 mm)	5.555 in (141.08 mm)	4.51 in (114.4 mm)	1.97 in (50.0 mm)	N/A	N/A	4.538 in (115.28 mm)	4.558 in (115.76 mm)	N/A	N/A	6.280 in (159.52 mm)	6.320 in (160.52 mm)	N/A	N/A
6.000	24.50	0.400	TenarisHydril Wedge 461®	Standard	5.075	Standard API Drift	4.79 in (121.6 mm)	1.79 in (45.4 mm)	5.190 in (131.84 mm)	5.210 in (132.32 mm)	6.000 in (152.40 mm)	6.060 in (153.92 mm)	N/A	1.79 in (45.4 mm)	8.884 in (225.66 mm)	8.944 in (227.16 mm)	5.617 in (142.68 mm)	5.637 in (143.16 mm)	6.544 in (166.22 mm)	6.676 in (169.56 mm)	N/A	N/A	6.732 in (171.00 mm)	6.868 in (174.44 mm)
6.000	24.50	0.400	TenarisHydril Wedge 461®	Accessory	5.075	Standard API Drift	4.79 in (121.6 mm)	1.79 in (45.4 mm)	5.190 in (131.84 mm)	5.210 in (132.32 mm)	6.000 in (152.40 mm)	6.060 in (153.92 mm)	5.11 in (129.6 mm)	1.97 in (50.0 mm)	N/A	N/A	5.190 in (131.84 mm)	5.210 in (132.32 mm)	N/A	N/A	6.780 in (172.22 mm)	6.820 in (173.22 mm)	N/A	N/A
6.000	25.10	0.415	TenarisHydril Wedge 461®	Standard	5.045	Standard API Drift	4.79 in (121.6 mm)	1.79 in (45.4 mm																

TenarisHydril Wedge 461® Blanking and Accessory Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, recopied, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections B.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request therefore. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyrighted 2021 as an unpublished work. ALL RIGHTS RESERVED.

SIZE (IN)	WEIGHT (LB/FT)	WALL (IN)	CONNECTION				PIN						BOX											
			PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH	RECUR LENGTH	COUPLING LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER - MATCHED STRENGTH		OUTSIDE DIAMETER - MACHINED OD		OUTSIDE DIAMETER - AS ROLLED	
							MIN	MIN	MIN	MAX	MIN	MAX			MIN	MIN	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX
6.000	29.80	0.500	TenarisHydril Wedge 461®	Standard	4.875	Standard API Drift	4.79 in (121.6 mm)	1.79 in (45.4 mm)	4.990 in (126.76 mm)	5.010 in (127.24 mm)	6.000 in (152.40 mm)	6.060 in (153.92 mm)	N/A	1.79 in (45.4 mm)	8.884 in (225.66 mm)	8.944 in (227.16 mm)	5.617 in (142.68 mm)	5.637 in (143.16 mm)	6.702 in (170.24 mm)	6.838 in (173.68 mm)	N/A	N/A	6.732 in (171.00 mm)	6.868 in (174.44 mm)
6.000	29.80	0.500	TenarisHydril Wedge 461®	Accessory	4.875	Standard API Drift	4.79 in (121.6 mm)	1.79 in (45.4 mm)	4.990 in (126.76 mm)	5.010 in (127.24 mm)	6.000 in (152.40 mm)	6.060 in (153.92 mm)	5.11 in (129.6 mm)	1.97 in (50.0 mm)	N/A	N/A	4.990 in (126.76 mm)	5.010 in (127.24 mm)	N/A	N/A	6.780 in (172.22 mm)	6.820 in (173.22 mm)	N/A	N/A
7.000	20.00	0.272	TenarisHydril Wedge 461®	Standard	6.331	Standard API Drift	4.50 in (114.2 mm)	1.79 in (45.4 mm)	6.454 in (163.94 mm)	6.458 in (164.02 mm)	7.000 in (177.80 mm)	7.070 in (179.56 mm)	N/A	1.79 in (45.4 mm)	8.306 in (210.98 mm)	8.366 in (212.48 mm)	6.679 in (169.66 mm)	6.699 in (170.14 mm)	N/A	N/A	N/A	N/A	7.673 in (194.90 mm)	7.827 in (198.80 mm)
7.000	20.00	0.272	TenarisHydril Wedge 461®	Accessory	6.331	Standard API Drift	4.50 in (114.2 mm)	1.79 in (45.4 mm)	6.454 in (163.94 mm)	6.458 in (164.02 mm)	7.000 in (177.80 mm)	7.070 in (179.56 mm)	4.82 in (122.4 mm)	1.97 in (50.0 mm)	N/A	N/A	6.446 in (163.74 mm)	6.466 in (164.22 mm)	N/A	N/A	7.730 in (196.36 mm)	7.770 in (197.34 mm)	N/A	N/A
7.000	23.00	0.317	TenarisHydril Wedge 461®	Standard	6.241	Standard API Drift	4.79 in (121.6 mm)	1.79 in (45.4 mm)	6.356 in (161.46 mm)	6.376 in (161.94 mm)	7.000 in (177.80 mm)	7.070 in (179.56 mm)	N/A	1.79 in (45.4 mm)	8.884 in (225.66 mm)	8.944 in (227.16 mm)	6.655 in (169.04 mm)	6.675 in (169.54 mm)	7.445 in (189.10 mm)	7.595 in (192.90 mm)	7.673 in (194.90 mm)	7.827 in (198.80 mm)	7.673 in (194.90 mm)	7.827 in (198.80 mm)
7.000	23.00	0.317	TenarisHydril Wedge 461®	Accessory	6.241	Standard API Drift	4.79 in (121.6 mm)	1.79 in (45.4 mm)	6.356 in (161.46 mm)	6.376 in (161.94 mm)	7.000 in (177.80 mm)	7.070 in (179.56 mm)	5.11 in (129.6 mm)	1.97 in (50.0 mm)	N/A	N/A	6.356 in (161.46 mm)	6.376 in (161.94 mm)	N/A	N/A	7.730 in (196.36 mm)	7.770 in (197.34 mm)	N/A	N/A
7.000	26.00	0.362	TenarisHydril Wedge 461®	Standard	6.151	Standard API Drift	4.79 in (121.6 mm)	1.79 in (45.4 mm)	6.266 in (159.16 mm)	6.286 in (159.66 mm)	7.000 in (177.80 mm)	7.070 in (179.56 mm)	N/A	1.79 in (45.4 mm)	8.884 in (225.66 mm)	8.944 in (227.16 mm)	6.655 in (169.04 mm)	6.675 in (169.54 mm)	7.524 in (191.12 mm)	7.676 in (194.96 mm)	7.673 in (194.90 mm)	7.827 in (198.80 mm)	7.673 in (194.90 mm)	7.827 in (198.80 mm)
7.000	26.00	0.362	TenarisHydril Wedge 461®	Accessory	6.151	Standard API Drift	4.79 in (121.6 mm)	1.79 in (45.4 mm)	6.266 in (159.16 mm)	6.286 in (159.66 mm)	7.000 in (177.80 mm)	7.070 in (179.56 mm)	5.11 in (129.6 mm)	1.97 in (50.0 mm)	N/A	N/A	6.266 in (159.16 mm)	6.286 in (159.66 mm)	N/A	N/A	7.730 in (196.36 mm)	7.770 in (197.34 mm)	N/A	N/A
7.000	29.00	0.408	TenarisHydril Wedge 461®	Standard	6.059	Standard API Drift	4.79 in (121.6 mm)	1.79 in (45.4 mm)	6.174 in (156.82 mm)	6.194 in (157.32 mm)	7.000 in (177.80 mm)	7.070 in (179.56 mm)	N/A	1.79 in (45.4 mm)	8.884 in (225.66 mm)	8.944 in (227.16 mm)	6.655 in (169.04 mm)	6.675 in (169.54 mm)	7.604 in (193.14 mm)	7.756 in (197.02 mm)	7.673 in (194.90 mm)	7.827 in (198.80 mm)	7.673 in (194.90 mm)	7.827 in (198.80 mm)
7.000	29.00	0.408	TenarisHydril Wedge 461®	Accessory	6.059	Standard API Drift	4.79 in (121.6 mm)	1.79 in (45.4 mm)	6.174 in (156.82 mm)	6.194 in (157.32 mm)	7.000 in (177.80 mm)	7.070 in (179.56 mm)	5.11 in (129.6 mm)	1.97 in (50.0 mm)	N/A	N/A	6.174 in (156.82 mm)	6.194 in (157.32 mm)	N/A	N/A	7.730 in (196.36 mm)	7.770 in (197.34 mm)	N/A	N/A
7.000	32.00	0.453	TenarisHydril Wedge 461®	Standard	5.969	Standard API Drift	4.79 in (121.6 mm)	1.79 in (45.4 mm)	6.084 in (154.54 mm)	6.104 in (155.04 mm)	7.000 in (177.80 mm)	7.070 in (179.56 mm)	N/A	1.79 in (45.4 mm)	8.884 in (225.66 mm)	8.944 in (227.16 mm)	6.655 in (169.04 mm)	6.675 in (169.54 mm)	N/A	N/A	7.673 in (194.90 mm)	7.827 in (198.80 mm)	7.673 in (194.90 mm)	7.827 in (198.80 mm)
7.000	32.00	0.453	TenarisHydril Wedge 461®	Accessory	5.969	Standard API Drift	4.79 in (121.6 mm)	1.79 in (45.4 mm)	6.084 in (154.54 mm)	6.104 in (155.04 mm)	7.000 in (177.80 mm)	7.070 in (179.56 mm)	5.11 in (129.6 mm)	1.97 in (50.0 mm)	N/A	N/A	6.084 in (154.54 mm)	6.104 in (155.04 mm)	N/A	N/A	7.730 in (196.36 mm)	7.770 in (197.34 mm)	N/A	N/A
7.000	32.00	0.453	TenarisHydril Wedge 461®	Standard	6.000	Alternative API Drift	4.79 in (121.6 mm)	1.79 in (45.4 mm)	6.084 in (154.54 mm)	6.104 in (155.04 mm)	7.000 in (177.80 mm)	7.070 in (179.56 mm)	N/A	1.79 in (45.4 mm)	8.884 in (225.66 mm)	8.944 in (227.16 mm)	6.655 in (169.04 mm)	6.675 in (169.54 mm)	N/A	N/A	7.673 in (194.90 mm)	7.827 in (198.80 mm)	7.673 in (194.90 mm)	7.827 in (198.80 mm)
7.000	32.00	0.453	TenarisHydril Wedge 461®	Accessory	6.000	Alternative API Drift	4.79 in (121.6 mm)	1.79 in (45.4 mm)	6.084 in (154.54 mm)	6.104 in (155.04 mm)	7.000 in (177.80 mm)	7.070 in (179.56 mm)	5.11 in (129.6 mm)	1.97 in (50.0 mm)	N/A	N/A	6.084 in (154.54 mm)	6.104 in (155.04 mm)	N/A	N/A	7.730 in (196.36 mm)	7.770 in (197.34 mm)	N/A	N/A
7.625	24.00	0.300	TenarisHydril Wedge 461®	Standard	6.900	Standard API Drift	4.77 in (121.0 mm)	1.79 in (45.4 mm)	7.023 in (178.40 mm)	7.027 in (178.48 mm)	7.625 in (193.68 mm)	7.701 in (195.60 mm)	N/A	1.79 in (45.4 mm)	8.842 in (224.60 mm)	8.902 in (226.10 mm)	7.612 in (193.36 mm)	7.632 in (193.84 mm)	8.063 in (204.80 mm)	8.206 in (208.42 mm)	N/A	N/A	N/A	N/A
7.625	24.00	0.300	TenarisHydril Wedge 461®	Accessory	6.900	Standard API Drift	4.77 in (121.0 mm)	1.79 in (45.4 mm)	7.023 in (178.40 mm)	7.027 in (178.48 mm)	7.625 in (193.68 mm)	7.701 in (195.60 mm)	5.09 in (129.2 mm)	2.02 in (51.2 mm)	N/A	N/A	7.015 in (178.20 mm)	7.035 in (178.68 mm)	8.105 in (205.88 mm)	8.145 in (206.88 mm)	N/A	N/A	N/A	N/A
7.625	26.40	0.328	TenarisHydril Wedge 461®	Standard	6.844	Standard API Drift	4.77 in (121.0 mm)	1.79 in (45.4 mm)	6.967 in (176.98 mm)	6.971 in (177.06 mm)	7.625 in (193.68 mm)	7.701 in (195.60 mm)	N/A	1.79 in (45.4 mm)	8.842 in (224.60 mm)	8.902 in (226.10 mm)	7.612 in (193.36 mm)	7.632 in (193.84 mm)	8.113 in (206.06 mm)	8.256 in (209.72 mm)	N/A	N/A	N/A	N/A

Dimensions provided do not include length required for tongs for making up assemblies. Please take this into consideration when designing and machining your accessory.
 BLANK OD and ID: The nominal blank ODs and IDs in the Pin Diameters and Box Diameters columns are finished product dimensions. When this minimum material is supplied, the blank OD and the blank ID must be true to each other within 0.010" TIR (Total Indicator Reading).
 BLANK Min Length includes 0.02" (0.5mm) extra material for facing.
 Contact Tenaris Manufacturing Services at blankingdimensions@tenaris.com for details.
 These Blanking Dimensions are NOT applicable For Handling & lifting plug, HydroTest Caps & HydroTest Plugs.
 N/A: Not Applicable

Yellow - Shaded corresponds to modified from previous document revision.