

TenarisHydril Wedge 623® - Blanking Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, recopied, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections B.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request therefore. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyrighted 2021 as an unpublished work. ALL RIGHTS RESERVED.

SIZE (IN)	WEIGHT (LB/FT)	WALL (IN)	CONNECTION				PIN						BOX					
			PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH	RECUT LENGTH	INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH	RECUT LENGTH	INSIDE DIAMETER		OUTSIDE DIAMETER - MACHINED OD	
							MIN	MIN	MIN	MAX	MIN	MAX	MIN	MIN	MIN	MAX	MIN	MAX*
5.500	29.70	0.562	TenarisHydril Wedge 623®	Standard	4.251	Standard API Drift	6.88 in (174.6 mm)	1.42 in (36.2 mm)	4.281 in (108.74 mm)	4.301 in (109.24 mm)	5.490 in (139.46 mm)	5.510 in (139.94 mm)	6.97 in (177.0 mm)	1.49 in (37.8 mm)	4.366 in (110.90 mm)	4.386 in (111.40 mm)	5.655 in (143.64 mm)	5.675 in (144.14 mm)
7.000	32.00	0.453	TenarisHydril Wedge 623®	Standard	6.000	Alternative API Drift	7.14 in (181.2 mm)	2.06 in (52.2 mm)	6.022 in (152.96 mm)	6.042 in (153.46 mm)	6.990 in (177.56 mm)	7.010 in (178.04 mm)	7.23 in (183.6 mm)	2.22 in (56.2 mm)	6.084 in (154.54 mm)	6.104 in (155.04 mm)	7.200 in (182.88 mm)	7.220 in (183.38 mm)
7.000	35.00	0.498	TenarisHydril Wedge 623®	Standard	5.879	Standard API Drift	7.14 in (181.2 mm)	2.06 in (52.2 mm)	5.901 in (149.90 mm)	5.921 in (150.38 mm)	6.990 in (177.56 mm)	7.010 in (178.04 mm)	7.23 in (183.6 mm)	2.22 in (56.2 mm)	5.994 in (152.74 mm)	6.014 in (152.74 mm)	7.200 in (182.88 mm)	7.220 in (183.38 mm)
7.000	35.00	0.498	TenarisHydril Wedge 623®	Exxon Mobil CTP ALL	5.879	Standard API Drift	7.14 in (181.2 mm)	2.06 in (52.2 mm)	5.901 in (149.90 mm)	5.921 in (150.38 mm)	6.990 in (177.56 mm)	7.010 in (178.04 mm)	7.23 in (183.6 mm)	2.22 in (56.2 mm)	5.994 in (152.26 mm)	6.014 in (152.74 mm)	7.200 in (182.88 mm)	7.220 in (183.38 mm)
7.625	55.30	0.750	TenarisHydril Wedge 623®	Standard	6.000	Standard API Drift	8.25 in (209.4 mm)	2.07 in (52.6 mm)	6.021 in (152.94 mm)	6.041 in (153.44 mm)	7.615 in (193.44 mm)	7.635 in (193.92 mm)	8.33 in (211.6 mm)	2.18 in (55.4 mm)	6.115 in (155.34 mm)	6.135 in (155.82 mm)	7.840 in (199.14 mm)	7.860 in (199.64 mm)
7.750	54.20	0.712	TenarisHydril Wedge 623®	Standard	6.250	Special Drift	7.35 in (186.6 mm)	1.40 in (35.6 mm)	6.272 in (159.32 mm)	6.292 in (159.80 mm)	7.740 in (196.60 mm)	7.760 in (197.10 mm)	7.44 in (188.8 mm)	1.49 in (37.8 mm)	6.316 in (160.44 mm)	6.336 in (160.92 mm)	7.985 in (202.82 mm)	8.005 in (203.32 mm)
9.625	47.00	0.472	TenarisHydril Wedge 623®	Standard	8.525	Standard API Drift	6.85 in (174.0 mm)	1.49 in (38.0 mm)	8.553 in (217.26 mm)	8.573 in (217.74 mm)	9.615 in (244.24 mm)	9.635 in (244.72 mm)	6.94 in (176.4 mm)	1.64 in (41.6 mm)	8.671 in (220.26 mm)	8.691 in (220.74 mm)	9.824 in (249.54 mm)	9.844 in (250.02 mm)
9.625	53.50	0.545	TenarisHydril Wedge 623®	Standard	8.500	Special Drift	6.85 in (174.0 mm)	1.49 in (38.0 mm)	8.528 in (216.62 mm)	8.548 in (217.10 mm)	9.615 in (244.24 mm)	9.635 in (244.72 mm)	6.94 in (176.4 mm)	1.64 in (41.6 mm)	8.525 in (216.54 mm)	8.545 in (217.04 mm)	9.824 in (249.54 mm)	9.844 in (250.02 mm)
9.625	53.50	0.545	TenarisHydril Wedge 623®	Shell Level B	8.500	Alternative API Drift	6.85 in (174.0 mm)	1.49 in (38.0 mm)	8.528 in (216.62 mm)	8.548 in (217.10 mm)	9.615 in (244.24 mm)	9.635 in (244.72 mm)	6.94 in (176.4 mm)	1.64 in (41.6 mm)	8.525 in (216.54 mm)	8.545 in (217.04 mm)	9.824 in (249.54 mm)	9.844 in (250.02 mm)
9.875	62.80	0.625	TenarisHydril Wedge 623®	Standard	8.500	Special Drift	7.85 in (199.2 mm)	1.70 in (43.0 mm)	8.538 in (216.88 mm)	8.558 in (217.36 mm)	9.865 in (250.58 mm)	9.885 in (251.06 mm)	7.94 in (201.6 mm)	1.83 in (46.6 mm)	8.615 in (218.84 mm)	8.635 in (219.32 mm)	10.090 in (256.30 mm)	10.110 in (256.78 mm)
9.875	65.10	0.650	TenarisHydril Wedge 623®	Standard	8.500	Special Drift	7.85 in (199.2 mm)	1.70 in (43.0 mm)	8.538 in (216.88 mm)	8.558 in (217.36 mm)	9.865 in (250.58 mm)	9.885 in (251.06 mm)	7.94 in (201.6 mm)	1.83 in (46.6 mm)	8.565 in (217.56 mm)	8.585 in (218.04 mm)	10.090 in (256.30 mm)	10.110 in (256.78 mm)
9.875	65.10	0.650	TenarisHydril Wedge 623®	SHELL Level B	8.500	Special Drift	7.85 in (199.2 mm)	1.70 in (43.0 mm)	8.538 in (216.88 mm)	8.558 in (217.36 mm)	9.865 in (250.58 mm)	9.885 in (251.06 mm)	7.94 in (201.6 mm)	1.83 in (46.6 mm)	8.529 in (216.64 mm)	8.549 in (217.14 mm)	10.090 in (256.30 mm)	10.110 in (256.78 mm)
9.875	66.90	0.668	TenarisHydril Wedge 623®	Standard	8.500	Special Drift	7.85 in (199.2 mm)	1.70 in (43.0 mm)	8.538 in (216.88 mm)	8.558 in (217.36 mm)	9.865 in (250.58 mm)	9.885 in (251.06 mm)	7.94 in (201.6 mm)	1.83 in (46.6 mm)	8.529 in (216.64 mm)	8.549 in (217.14 mm)	10.090 in (256.30 mm)	10.110 in (256.78 mm)
10.000	68.42	0.688	TenarisHydril Wedge 623®	Standard	8.500	Special Drift	7.85 in (199.2 mm)	1.70 in (43.0 mm)	8.537 in (216.84 mm)	8.557 in (217.34 mm)	9.990 in (253.76 mm)	10.010 in (254.24 mm)	7.94 in (201.6 mm)	1.83 in (46.4 mm)	8.614 in (218.80 mm)	8.634 in (219.30 mm)	10.190 in (258.84 mm)	10.210 in (259.32 mm)
10.000	68.80	0.700	TenarisHydril Wedge 623®	Standard	8.500	Special Drift	7.85 in (199.2 mm)	1.70 in (43.0 mm)	8.537 in (216.84 mm)	8.557 in (217.34 mm)	9.990 in (253.76 mm)	10.010 in (254.24 mm)	7.94 in (201.6 mm)	1.83 in (46.4 mm)	8.590 in (218.20 mm)	8.610 in (218.68 mm)	10.190 in (258.84 mm)	10.210 in (259.32 mm)
10.125	79.29	0.795	TenarisHydril Wedge 623®	Standard	8.500	Special Drift	7.86 in (199.6 mm)	1.60 in (40.6 mm)	8.537 in (216.84 mm)	8.557 in (217.34 mm)	10.115 in (256.94 mm)	10.135 in (257.42 mm)	7.95 in (202.0 mm)	1.72 in (43.6 mm)	8.525 in (216.54 mm)	8.545 in (217.04 mm)	10.365 in (263.28 mm)	10.385 in (263.76 mm)
10.125	79.29	0.795	TenarisHydril Wedge 623®	Exxon Mobil CTP ALL	8.500	Special Drift	7.86 in (199.6 mm)	1.60 in (40.6 mm)	8.537 in (216.84 mm)	8.557 in (217.34 mm)	10.115 in (256.94 mm)	10.135 in (257.42 mm)	7.95 in (202.0 mm)	1.72 in (43.6 mm)	8.525 in (216.54 mm)	8.545 in (217.04 mm)	10.365 in (263.28 mm)	10.385 in (263.76 mm)
10.750	60.70	0.545	TenarisHydril Wedge 623®	Standard	9.504	Standard API Drift	7.19 in (182.6 mm)	1.44 in (36.6 mm)	9.533 in (242.14 mm)	9.553 in (242.64 mm)	10.740 in (272.80 mm)	10.760 in (273.30 mm)	7.28 in (184.8 mm)	1.58 in (40.2 mm)	9.650 in (245.12 mm)	9.670 in (245.60 mm)	10.990 in (279.16 mm)	11.010 in (279.64 mm)
10.750	65.70	0.595	TenarisHydril Wedge 623®	Standard	9.504	Special Drift	7.19 in (182.6 mm)	1.44 in (36.6 mm)	9.533 in (242.14 mm)	9.553 in (242.64 mm)	10.740 in (272.80 mm)	10.760 in (273.30 mm)	7.28 in (184.8 mm)	1.58 in (40.2 mm)	9.550 in (242.58 mm)	9.570 in (243.06 mm)	10.990 in (279.16 mm)	11.010 in (279.64 mm)
10.750	65.70	0.595	TenarisHydril Wedge 623®	Standard	9.404	Standard API Drift	7.19 in (182.6 mm)	1.44 in (36.6 mm)	9.533 in (242.14 mm)	9.553 in (242.64 mm)	10.740 in (272.80 mm)	10.760 in (273.30 mm)	7.28 in (184.8 mm)	1.58 in (40.2 mm)	9.550 in (242.58 mm)	9.570 in (243.06 mm)	10.990 in (279.16 mm)	11.010 in (279.64 mm)
10.750	65.70	0.595	TenarisHydril Wedge 623®	Exxon Mobil CTP ALL	9.404	Standard API Drift	7.19 in (182.6 mm)	1.44 in (36.6 mm)	9.533 in (242.14 mm)	9.553 in (242.64 mm)	10.740 in (272.80 mm)	10.760 in (273.30 mm)	7.28 in (184.8 mm)	1.58 in (40.2 mm)	9.550 in (242.58 mm)	9.570 in (243.06 mm)	10.990 in (279.16 mm)	11.010 in (279.64 mm)
10.750	85.30	0.797	TenarisHydril Wedge 623®	Standard	9.000	Standard API Drift	7.84 in (199.0 mm)	1.65 in (42.0 mm)	9.040 in (229.62 mm)	9.060 in (230.12 mm)	10.740 in (272.80 mm)	10.760 in (273.30 mm)	7.93 in (201.4 mm)	1.79 in (45.6 mm)	9.146 in (232.32 mm)	9.166 in (232.80 mm)	10.956 in (278.30 mm)	10.976 in (278.78 mm)
11.500	98.20	0.860	TenarisHydril Wedge 623®	Standard	9.655	Special Drift	8.09 in (205.6 mm)	1.51 in (38.2 mm)	9.683 in (245.96 mm)	9.703 in (246.44 mm)	11.490 in (291.86 mm)	11.510 in (292.34 mm)	8.18 in (207.8 mm)	1.60 in (40.4 mm)	9.770 in (248.16 mm)	9.790 in (248.66 mm)	11.665 in (296.30 mm)	11.685 in (296.78 mm)

TenarisHydril Wedge 623® - Blanking Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, recopied, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections B.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request therefore. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyrighted 2021 as an unpublished work. ALL RIGHTS RESERVED.

SIZE (IN)	WEIGHT (LB/FT)	WALL (IN)	CONNECTION				PIN						BOX					
			PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH	RECUT LENGTH	INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH	RECUT LENGTH	INSIDE DIAMETER		OUTSIDE DIAMETER - MACHINED OD	
							MIN	MIN	MIN	MAX	MIN	MAX	MIN	MIN	MIN	MAX	MIN	MAX*
11.750	60.00	0.489	TenarisHydril Wedge 623®	Standard	10.625	Special Drift	6.89 in (175.0 mm)	1.44 in (36.6 mm)	10.653 in (270.60 mm)	10.673 in (271.08 mm)	11.740 in (298.20 mm)	11.760 in (298.70 mm)	6.98 in (177.2 mm)	1.56 in (39.8 mm)	10.762 in (273.36 mm)	10.782 in (273.86 mm)	11.955 in (303.66 mm)	11.975 in (304.16 mm)
11.750	65.00	0.534	TenarisHydril Wedge 623®	Standard	10.625	Special Drift	6.89 in (175.0 mm)	1.44 in (36.6 mm)	10.653 in (270.60 mm)	10.673 in (271.08 mm)	11.740 in (298.20 mm)	11.760 in (298.70 mm)	6.97 in (177.2 mm)	1.56 in (39.8 mm)	10.672 in (271.08 mm)	10.692 in (271.56 mm)	11.955 in (303.66 mm)	11.975 in (304.16 mm)
11.750	65.00	0.534	TenarisHydril Wedge 623®	SHELL Level B	10.625	Special Drift	6.89 in (175.0 mm)	1.44 in (36.6 mm)	10.653 in (270.60 mm)	10.673 in (271.08 mm)	11.740 in (298.20 mm)	11.760 in (298.70 mm)	6.97 in (177.2 mm)	1.56 in (39.8 mm)	10.672 in (271.08 mm)	10.692 in (271.56 mm)	11.955 in (303.66 mm)	11.975 in (304.16 mm)
11.750	80.50	0.672	TenarisHydril Wedge 623®	Standard	10.270	Special Drift	7.43 in (188.8 mm)	1.33 in (33.6 mm)	10.298 in (261.58 mm)	10.318 in (262.06 mm)	11.740 in (298.20 mm)	11.760 in (298.70 mm)	7.52 in (191.0 mm)	1.42 in (36.0 mm)	10.396 in (264.06 mm)	10.416 in (264.56 mm)	11.920 in (302.78 mm)	11.940 in (303.26 mm)
11.750	82.60	0.691	TenarisHydril Wedge 623®	Standard	10.270	Special Drift	7.43 in (188.8 mm)	1.33 in (33.6 mm)	10.298 in (261.58 mm)	10.318 in (262.06 mm)	11.740 in (298.20 mm)	11.760 in (298.70 mm)	7.52 in (191.0 mm)	1.42 in (36.0 mm)	10.358 in (263.10 mm)	10.378 in (263.60 mm)	11.920 in (302.78 mm)	11.940 in (303.26 mm)
11.750	82.60	0.691	TenarisHydril Wedge 623®	SHELL Level B	10.270	Special Drift	7.43 in (188.8 mm)	1.33 in (33.6 mm)	10.298 in (261.58 mm)	10.318 in (262.06 mm)	11.740 in (298.20 mm)	11.760 in (298.70 mm)	7.52 in (191.0 mm)	1.42 in (36.0 mm)	10.358 in (263.10 mm)	10.378 in (263.60 mm)	11.920 in (302.78 mm)	11.940 in (303.26 mm)
11.875	71.80	0.582	TenarisHydril Wedge 623®	Standard	10.625	Special Drift	7.85 in (199.4 mm)	1.95 in (49.6 mm)	10.653 in (270.60 mm)	10.673 in (271.08 mm)	11.865 in (301.38 mm)	11.885 in (301.86 mm)	7.94 in (201.8 mm)	2.11 in (53.4 mm)	10.701 in (271.82 mm)	10.721 in (272.30 mm)	12.062 in (306.38 mm)	12.082 in (306.88 mm)
11.875	71.80	0.582	TenarisHydril Wedge 623®	SHELL Level B	10.625	Special Drift	7.85 in (199.4 mm)	1.95 in (49.6 mm)	10.653 in (270.60 mm)	10.673 in (271.08 mm)	11.865 in (301.38 mm)	11.885 in (301.86 mm)	7.94 in (201.8 mm)	2.11 in (53.4 mm)	10.701 in (271.82 mm)	10.721 in (272.30 mm)	12.062 in (306.38 mm)	12.082 in (306.88 mm)
13.375	68.00	0.480	TenarisHydril Wedge 623®	Standard	12.259	Standard API Drift	6.53 in (166.0 mm)	1.51 in (38.4 mm)	12.287 in (312.10 mm)	12.307 in (312.58 mm)	13.365 in (339.48 mm)	13.385 in (339.96 mm)	6.62 in (168.2 mm)	1.67 in (42.4 mm)	12.405 in (315.10 mm)	12.425 in (315.58 mm)	13.633 in (346.28 mm)	13.653 in (346.78 mm)
13.375	72.00	0.514	TenarisHydril Wedge 623®	Standard	12.250	Special Drift	6.53 in (166.0 mm)	1.51 in (38.4 mm)	12.278 in (311.88 mm)	12.298 in (312.36 mm)	13.365 in (339.48 mm)	13.385 in (339.96 mm)	6.62 in (168.2 mm)	1.67 in (42.4 mm)	12.337 in (313.36 mm)	12.357 in (313.86 mm)	13.633 in (346.28 mm)	13.653 in (346.78 mm)
13.375	77.00	0.550	TenarisHydril Wedge 623®	Standard	12.250	Special Drift	6.53 in (166.0 mm)	1.51 in (38.4 mm)	12.278 in (311.88 mm)	12.298 in (312.36 mm)	13.365 in (339.48 mm)	13.385 in (339.96 mm)	6.62 in (168.2 mm)	1.67 in (42.4 mm)	12.265 in (311.54 mm)	12.285 in (312.02 mm)	13.685 in (347.60 mm)	13.705 in (348.10 mm)
13.625	88.20	0.625	TenarisHydril Wedge 623®	Standard	12.250	Special Drift	7.41 in (188.2 mm)	1.65 in (41.8 mm)	12.278 in (311.88 mm)	12.298 in (312.36 mm)	13.615 in (345.84 mm)	13.635 in (346.32 mm)	7.50 in (190.4 mm)	1.79 in (45.4 mm)	12.365 in (314.08 mm)	12.385 in (314.56 mm)	13.865 in (352.18 mm)	13.885 in (352.66 mm)
13.875	106.00	0.755	TenarisHydril Wedge 623®	Standard	12.250	Special Drift	8.92 in (226.4 mm)	1.99 in (50.4 mm)	12.282 in (311.98 mm)	12.302 in (312.46 mm)	13.865 in (352.18 mm)	13.885 in (352.66 mm)	9.00 in (228.6 mm)	2.17 in (55.2 mm)	12.355 in (313.82 mm)	12.375 in (314.32 mm)	14.150 in (359.42 mm)	14.170 in (359.90 mm)
14.000	113.00	0.800	TenarisHydril Wedge 623®	Standard	12.250	Special Drift	8.92 in (226.4 mm)	1.99 in (50.4 mm)	12.282 in (311.98 mm)	12.302 in (312.46 mm)	13.990 in (355.36 mm)	14.010 in (355.84 mm)	9.00 in (228.6 mm)	2.17 in (55.2 mm)	12.390 in (314.72 mm)	12.410 in (315.20 mm)	14.243 in (361.78 mm)	14.263 in (362.28 mm)
14.000	115.00	0.812	TenarisHydril Wedge 623®	Standard	12.250	Special Drift	8.92 in (226.4 mm)	1.99 in (50.4 mm)	12.282 in (311.98 mm)	12.302 in (312.46 mm)	13.990 in (355.36 mm)	14.010 in (355.84 mm)	9.00 in (228.6 mm)	2.17 in (55.2 mm)	12.366 in (314.10 mm)	12.386 in (314.60 mm)	14.243 in (361.78 mm)	14.263 in (362.28 mm)
14.000	115.00	0.812	TenarisHydril Wedge 623®	SHELL Level B	12.250	Special Drift	8.92 in (226.4 mm)	1.99 in (50.4 mm)	12.282 in (311.98 mm)	12.302 in (312.46 mm)	13.990 in (355.36 mm)	14.010 in (355.84 mm)	9.00 in (228.6 mm)	2.17 in (55.2 mm)	12.366 in (314.10 mm)	12.386 in (314.60 mm)	14.243 in (361.78 mm)	14.263 in (362.28 mm)
14.000	116.00	0.820	TenarisHydril Wedge 623®	Standard	12.250	Special Drift	8.92 in (226.4 mm)	1.99 in (50.4 mm)	12.282 in (311.98 mm)	12.302 in (312.46 mm)	13.990 in (355.36 mm)	14.010 in (355.84 mm)	9.00 in (228.6 mm)	2.17 in (55.2 mm)	12.350 in (313.70 mm)	12.370 in (314.18 mm)	14.243 in (361.78 mm)	14.263 in (362.28 mm)
16.000	109.00	0.656	TenarisHydril Wedge 623®	Standard	14.600	Special Drift	8.02 in (203.8 mm)	1.66 in (42.2 mm)	14.630 in (371.62 mm)	14.650 in (372.10 mm)	15.990 in (406.16 mm)	16.010 in (406.64 mm)	8.11 in (206.0 mm)	1.80 in (45.6 mm)	14.678 in (372.84 mm)	14.698 in (373.32 mm)	16.231 in (412.28 mm)	16.251 in (412.76 mm)
16.080	109.80	0.667	TenarisHydril Wedge 623®	Standard	14.600	Special Drift	8.02 in (203.8 mm)	1.66 in (42.2 mm)	14.630 in (371.62 mm)	14.650 in (372.10 mm)	16.070 in (408.18 mm)	16.090 in (408.68 mm)	8.11 in (206.0 mm)	1.80 in (45.6 mm)	14.736 in (374.30 mm)	14.756 in (374.80 mm)	16.231 in (412.28 mm)	16.251 in (412.76 mm)
16.080	109.80	0.667	TenarisHydril Wedge 623®	SHELL Level B	14.600	Special Drift	8.02 in (203.8 mm)	1.66 in (42.2 mm)	14.630 in (371.62 mm)	14.650 in (372.10 mm)	16.070 in (408.18 mm)	16.090 in (408.68 mm)	8.11 in (206.0 mm)	1.80 in (45.6 mm)	14.736 in (374.30 mm)	14.756 in (374.80 mm)	16.231 in (412.28 mm)	16.251 in (412.76 mm)
16.100	110.50	0.667	TenarisHydril Wedge 623®	Standard	14.600	Special Drift	8.02 in (203.8 mm)	1.66 in (42.2 mm)	14.630 in (371.62 mm)	14.650 in (372.10 mm)	16.090 in (408.70 mm)	16.110 in (409.18 mm)	8.11 in (206.0 mm)	1.80 in (45.6 mm)	14.756 in (374.82 mm)	14.776 in (375.30 mm)	16.251 in (412.78 mm)	16.271 in (413.28 mm)
16.150	120.00	0.723	TenarisHydril Wedge 623®	Standard	14.600	Special Drift	8.02 in (203.8 mm)	1.66 in (42.2 mm)	14.630 in (371.62 mm)	14.650 in (372.10 mm)	16.140 in (409.96 mm)	16.160 in (410.46 mm)	8.11 in (206.0 mm)	1.80 in (45.6 mm)	14.694 in (373.24 mm)	14.714 in (373.72 mm)	16.301 in (414.06 mm)	16.321 in (414.54 mm)
16.150	127.50	0.772	TenarisHydril Wedge 623®	Standard	14.501	Special Drift	8.40 in (213.4 mm)	1.68 in (42.6 mm)	14.531 in (369.10 mm)	14.551 in (369.58 mm)	16.140 in (409.96 mm)	16.160 in (410.46 mm)	8.49 in (215.8 mm)	1.81 in (46.0 mm)	14.596 in (370.74 mm)	14.616 in (371.24 mm)	16.382 in (416.12 mm)	16.402 in (416.60 mm)

TenarisHydril Wedge 623® - Blanking Dimensions

Document Number : TSH-BD-84.0001

Revision: 26

Effective Date : 12/Feb/2021



This document as well as the information or data contained herein are confidential and shall not be copied, recopied, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections B.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request therefore. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyrighted 2021 as an unpublished work. ALL RIGHTS RESERVED.

CONNECTION							PIN						BOX					
SIZE (IN)	WEIGHT (LB/FT)	WALL (IN)	PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH	RECUT LENGTH	INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH	RECUT LENGTH	INSIDE DIAMETER		OUTSIDE DIAMETER - MACHINED OD	
							MIN	MIN	MIN	MAX	MIN	MAX	MIN	MIN	MIN	MAX	MIN	MAX*
16.264	122.50	0.734	TenarisHydril Wedge 623®	Standard	14.609	Standard API Drift	9.06 in (230.2 mm)	2.00 in (50.8 mm)	14.639 in (371.84 mm)	14.659 in (372.32 mm)	16.254 in (412.86 mm)	16.274 in (413.34 mm)	9.15 in (232.6 mm)	2.14 in (54.4 mm)	14.786 in (375.58 mm)	14.806 in (376.06 mm)	16.470 in (418.34 mm)	16.490 in (418.84 mm)
16.264	122.50	0.734	TenarisHydril Wedge 623®	SHELL Level B	14.609	Standard API Drift	9.06 in (230.2 mm)	2.00 in (50.8 mm)	14.639 in (371.84 mm)	14.659 in (372.32 mm)	16.254 in (412.86 mm)	16.274 in (413.34 mm)	9.15 in (232.6 mm)	2.14 in (54.4 mm)	14.786 in (375.58 mm)	14.806 in (376.06 mm)	16.470 in (418.34 mm)	16.490 in (418.84 mm)

Dimensions provided do not include length required for tongs for making up assemblies. Please take this into consideration when designing and machining your accessory.

BLANK OD and ID: The nominal blank ODs and IDs in the Pin Diameters and Box Diameters columns are finished product dimensions. When this minimum material is supplied, the blank OD and the blank ID must be true to each other within 0.010" TIR (Total Indicator Reading).

BLANK Min Length includes 0.02" (0.5mm) extra material for facing.

Contact Tenaris Manufacturing Services at blankingdimensions@tenaris.com for details.

These Blanking Dimensions are NOT applicable For Handling & lifting plug, HydroTest Caps & HydroTest Plugs.

N/A: Not Applicable

*For OEM Max OD is not restricted.

Yellow - Shaded corresponds to modified from previous document revision.