

# TenarisHydril Blue® HW and TenarisHydril Blue® HW Dopeless® Blanking Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, recopied, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections B.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request therefore. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyrighted 2020 as an unpublished work. ALL RIGHTS RESERVED.

SIZE (IN)	WEIGHT (LB/FT)	WALL (IN)	CONNECTION				PIN						BOX										
			PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH	RECUT LENGTH	INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH	RECUT LENGTH	COUPLING LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER - REGULAR		OUTSIDE DIAMETER - SPECIAL CLEARANCE		
									MIN	MAX	MIN	MAX			MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN
7.625	47.10	0.625	TenarisHydril Blue® Heavy Wall	Standard	6.250	Standard API Drift	5.63 in (143.0 mm)	1.60 in (40.8 mm)	6.318 in (160.46 mm)	6.340 in (161.06 mm)	7.625 in (193.68 mm)	7.701 in (195.60 mm)	5.55 in (141.0 mm)	2.33 in (59.2 mm)	10.881 in (276.36 mm)	11.077 in (281.36 mm)	6.278 in (159.46 mm)	6.301 in (160.04 mm)	8.352 in (212.12 mm)	8.390 in (213.12 mm)	N/A	N/A	N/A
7.625	48.42	0.650	TenarisHydril Blue® Heavy Wall	Standard	6.200	Standard API Drift	5.63 in (143.0 mm)	1.60 in (40.8 mm)	6.268 in (159.20 mm)	6.290 in (159.78 mm)	7.625 in (193.68 mm)	7.701 in (195.60 mm)	5.55 in (141.0 mm)	2.33 in (59.2 mm)	10.881 in (276.36 mm)	11.077 in (281.36 mm)	6.228 in (158.18 mm)	6.251 in (158.78 mm)	8.352 in (212.12 mm)	8.390 in (213.12 mm)	N/A	N/A	N/A
7.625	51.20	0.687	TenarisHydril Blue® Heavy Wall	Standard	6.126	Standard API Drift	5.63 in (143.0 mm)	1.60 in (40.8 mm)	6.210 in (157.72 mm)	6.233 in (158.32 mm)	7.625 in (193.68 mm)	7.701 in (195.60 mm)	5.55 in (141.0 mm)	2.33 in (59.2 mm)	10.881 in (276.36 mm)	11.077 in (281.36 mm)	6.154 in (156.30 mm)	6.177 in (156.90 mm)	8.352 in (212.12 mm)	8.390 in (213.12 mm)	N/A	N/A	N/A
7.625	52.10	0.700	TenarisHydril Blue® Heavy Wall	Standard	6.100	Standard API Drift	5.63 in (143.0 mm)	1.60 in (40.8 mm)	6.179 in (156.94 mm)	6.201 in (157.52 mm)	7.625 in (193.68 mm)	7.701 in (195.60 mm)	5.55 in (141.0 mm)	2.33 in (59.2 mm)	10.881 in (276.36 mm)	11.077 in (281.36 mm)	6.128 in (155.64 mm)	6.151 in (156.24 mm)	8.352 in (212.12 mm)	8.390 in (213.12 mm)	N/A	N/A	N/A
7.625	55.30	0.750	TenarisHydril Blue® Heavy Wall	Standard	6.000	Standard API Drift	5.63 in (143.0 mm)	1.60 in (40.8 mm)	6.117 in (155.36 mm)	6.139 in (155.94 mm)	7.625 in (193.68 mm)	7.701 in (195.60 mm)	5.55 in (141.0 mm)	2.33 in (59.2 mm)	10.881 in (276.36 mm)	11.077 in (281.36 mm)	6.058 in (153.86 mm)	6.081 in (154.46 mm)	8.472 in (215.18 mm)	8.511 in (216.18 mm)	N/A	N/A	N/A
7.625	55.30	0.750	TenarisHydril Blue® Heavy Wall	KOC	6.000	Standard API Drift	5.63 in (143.0 mm)	1.60 in (40.8 mm)	6.117 in (155.36 mm)	6.139 in (155.94 mm)	7.625 in (193.68 mm)	7.701 in (195.60 mm)	5.55 in (141.0 mm)	2.33 in (59.2 mm)	10.881 in (276.36 mm)	11.077 in (281.36 mm)	6.058 in (153.86 mm)	6.081 in (154.46 mm)	8.331 in (211.60 mm)	8.350 in (212.08 mm)	70.0	8.331 in (211.60 mm)	8.350 in (212.08 mm)
7.625	58.13	0.797	TenarisHydril Blue® Heavy Wall	Standard	5.906	Standard API Drift	5.63 in (143.0 mm)	1.60 in (40.8 mm)	6.030 in (153.16 mm)	6.053 in (153.76 mm)	7.625 in (193.68 mm)	7.701 in (195.60 mm)	5.55 in (141.0 mm)	2.33 in (59.2 mm)	10.881 in (276.36 mm)	11.077 in (281.36 mm)	5.998 in (152.34 mm)	6.021 in (152.94 mm)	8.472 in (215.18 mm)	8.511 in (216.18 mm)	N/A	N/A	N/A
7.625	58.31	0.800	TenarisHydril Blue® Heavy Wall	Standard	5.900	Standard API Drift	5.63 in (143.0 mm)	1.60 in (40.8 mm)	6.025 in (153.04 mm)	6.048 in (153.62 mm)	7.625 in (193.68 mm)	7.701 in (195.60 mm)	5.55 in (141.0 mm)	2.33 in (59.2 mm)	10.881 in (276.36 mm)	11.077 in (281.36 mm)	5.994 in (152.24 mm)	6.017 in (152.84 mm)	8.472 in (215.18 mm)	8.511 in (216.18 mm)	N/A	N/A	N/A
7.625	59.20	0.812	TenarisHydril Blue® Heavy Wall	Standard	5.876	Standard API Drift	5.63 in (143.0 mm)	1.60 in (40.8 mm)	6.003 in (152.48 mm)	6.026 in (153.06 mm)	7.625 in (193.68 mm)	7.701 in (195.60 mm)	5.55 in (141.0 mm)	2.33 in (59.2 mm)	10.881 in (276.36 mm)	11.077 in (281.36 mm)	5.979 in (151.86 mm)	6.002 in (152.46 mm)	8.530 in (216.66 mm)	8.569 in (217.66 mm)	N/A	N/A	N/A
7.625	61.50	0.850	TenarisHydril Blue® Heavy Wall	Standard	5.800	Standard API Drift	5.63 in (143.0 mm)	1.60 in (40.8 mm)	5.934 in (150.72 mm)	5.957 in (151.30 mm)	7.625 in (193.68 mm)	7.701 in (195.60 mm)	5.55 in (141.0 mm)	2.33 in (59.2 mm)	10.881 in (276.36 mm)	11.077 in (281.36 mm)	5.931 in (150.64 mm)	5.954 in (151.24 mm)	8.530 in (216.66 mm)	8.569 in (217.66 mm)	N/A	N/A	N/A
7.625	64.64	0.900	TenarisHydril Blue® Heavy Wall	Standard	5.700	Standard API Drift	7.03 in (178.6 mm)	1.23 in (31.2 mm)	5.800 in (147.32 mm)	5.823 in (147.90 mm)	7.625 in (193.68 mm)	7.701 in (195.60 mm)	6.95 in (176.6 mm)	3.24 in (82.2 mm)	14.467 in (367.46 mm)	14.663 in (372.46 mm)	5.728 in (145.48 mm)	5.751 in (146.08 mm)	8.561 in (217.44 mm)	8.600 in (218.44 mm)	N/A	N/A	N/A
7.625	64.95	0.905	TenarisHydril Blue® Heavy Wall	Standard	5.690	Standard API Drift	7.03 in (178.6 mm)	1.23 in (31.2 mm)	5.791 in (147.08 mm)	5.814 in (147.68 mm)	7.625 in (193.68 mm)	7.701 in (195.60 mm)	6.95 in (176.6 mm)	3.24 in (82.2 mm)	14.467 in (367.46 mm)	14.663 in (372.46 mm)	5.718 in (145.24 mm)	5.741 in (145.82 mm)	8.567 in (217.60 mm)	8.606 in (218.60 mm)	N/A	N/A	N/A
7.625	67.72	0.950	TenarisHydril Blue® Heavy Wall	Standard	5.600	Standard API Drift	7.03 in (178.6 mm)	1.23 in (31.2 mm)	5.708 in (144.98 mm)	5.731 in (145.58 mm)	7.625 in (193.68 mm)	7.701 in (195.60 mm)	6.95 in (176.6 mm)	3.24 in (82.2 mm)	14.467 in (367.46 mm)	14.663 in (372.46 mm)	5.660 in (143.76 mm)	5.683 in (144.34 mm)	8.625 in (219.06 mm)	8.663 in (220.06 mm)	N/A	N/A	N/A
7.625	70.76	1.000	TenarisHydril Blue® Heavy Wall	Standard	5.500	Standard API Drift	7.03 in (178.6 mm)	1.23 in (31.2 mm)	5.617 in (142.66 mm)	5.640 in (143.26 mm)	7.625 in (193.68 mm)	7.701 in (195.60 mm)	6.95 in (176.6 mm)	3.24 in (82.2 mm)	14.467 in (367.46 mm)	14.663 in (372.46 mm)	5.605 in (142.36 mm)	5.627 in (142.94 mm)	8.687 in (220.64 mm)	8.725 in (221.62 mm)	N/A	N/A	N/A
7.625	73.73	1.050	TenarisHydril Blue® Heavy Wall	Standard	5.400	Standard API Drift	7.03 in (178.6 mm)	1.23 in (31.2 mm)	5.526 in (140.34 mm)	5.548 in (140.94 mm)	7.625 in (193.68 mm)	7.701 in (195.60 mm)	6.95 in (176.6 mm)	3.24 in (82.2 mm)	14.467 in (367.46 mm)	14.663 in (372.46 mm)	5.550 in (140.96 mm)	5.573 in (141.56 mm)	8.747 in (222.18 mm)	8.786 in (223.16 mm)	N/A	N/A	N/A
7.625	76.66	1.100	TenarisHydril Blue® Heavy Wall	Standard	5.300	Standard API Drift	7.03 in (178.6 mm)	1.23 in (31.2 mm)	5.434 in (138.02 mm)	5.457 in (138.62 mm)	7.625 in (193.68 mm)	7.701 in (195.60 mm)	6.95 in (176.6 mm)	3.24 in (82.2 mm)	14.467 in (367.46 mm)	14.663 in (372.46 mm)	5.495 in (139.58 mm)	5.518 in (140.16 mm)	8.807 in (223.68 mm)	8.845 in (224.68 mm)	N/A	N/A	N/A
7.625	79.53	1.150	TenarisHydril Blue® Heavy Wall	Standard	5.200	Standard API Drift	7.03 in (178.6 mm)	1.23 in (31.2 mm)	5.343 in (135.72 mm)	5.366 in (136.30 mm)	7.625 in (193.68 mm)	7.701 in (195.60 mm)	6.95 in (176.6 mm)	3.24 in (82.2 mm)	14.467 in (367.46 mm)	14.663 in (372.46 mm)	5.441 in (138.20 mm)	5.464 in (138.80 mm)	8.864 in (225.14 mm)	8.903 in (226.14 mm)	N/A	N/A	N/A
7.625	82.34	1.200	TenarisHydril Blue® Heavy Wall	Standard	5.100	Standard API Drift	7.03 in (178.6 mm)	1.23 in (31.2 mm)	5.252 in (133.40 mm)	5.275 in (134.00 mm)	7.625 in (193.68 mm)	7.701 in (195.60 mm)	6.95 in (176.6 mm)	3.24 in (82.2 mm)	14.467 in (367.46 mm)	14.663 in (372.46 mm)	5.388 in (136.86 mm)	5.411 in (137.44 mm)	8.921 in (226.58 mm)	8.959 in (227.56 mm)	N/A	N/A	N/A
7.625	85.11	1.250	TenarisHydril Blue® Heavy Wall	Standard	5.000	Standard API Drift	7.03 in (178.6 mm)	1.23 in (31.2 mm)	5.162 in (131.10 mm)	5.184 in (131.68 mm)	7.625 in (193.68 mm)	7.701 in (195.60 mm)	6.95 in (176.6 mm)	3.24 in (82.2 mm)	14.467 in (367.46 mm)	14.663 in (372.46 mm)	5.335 in (135.50 mm)	5.358 in (136.10 mm)	8.975 in (227.96 mm)	9.014 in (228.96 mm)	N/A	N/A	N/A
8.625	63.50	0.750	TenarisHydril Blue® Heavy Wall	Standard	7.000	Standard API Drift	6.56 in (166.4 mm)	1.60 in (40.8 mm)	7.097 in (180.26 mm)	7.120 in (180.86 mm)	8.625 in (219.08 mm)	8.711 in (221.24 mm)	6.48 in (164.4 mm)	2.79 in (71.0 mm)	13.515 in (343.28 mm)	13.711 in (348.26 mm)	7.117 in (180.76 mm)	7.140 in (181.36 mm)	9.524 in (241.90 mm)	9.562 in (242.90 mm)	N/A	N/A	N/A
8.625	66.86	0.800	TenarisHydril Blue® Heavy Wall	Standard	6.900	Standard API Drift	6.56 in (166.4 mm)	1.60 in (40.8 mm)	7.006 in (177.94 mm)	7.028 in (178.52 mm)	8.625 in (219.08 mm)	8.711 in (221.24 mm)	6.48 in (164.4 mm)	2.79 in (71.0 mm)	13.515 in (343.28 mm)	13.711 in (348.26 mm)	7.062 in (179.38 mm)	7.085 in (179.96 mm)	9.594 in (243.68 mm)	9.633 in (244.68 mm)	N/A	N/A	N/A
8.625	70.58	0.850	TenarisHydril Blue® Heavy Wall	Standard	6.800	Standard API Drift	6.56 in (166.4 mm)	1.60 in (40.8 mm)	6.914 in (175.60 mm)	6.937 in (176.20 mm)	8.625 in (219.08 mm)	8.711 in (221.24 mm)	6.48 in (164.4 mm)	2.79 in (71.0 mm)	13.515 in (343.28 mm)	13.711 in (348.26 mm)	7.008 in (178.00 mm)	7.031 in (178.58 mm)	9.663 in (245.44 mm)	9.701 in (246.42 mm)	N/A	N/A	N/A
8.625	72.70	0.875	TenarisHydril Blue® Heavy Wall	Standard	6.750	Standard API Drift	6.56 in (166.4 mm)	1.60 in (40.8 mm)	6.868 in (174.44 mm)	6.891 in (175.04 mm)	8.625 in (219.08 mm)	8.711 in (221.24 mm)	6.48 in (164.4 mm)	2.79 in (71.0 mm)	13.515 in (343.28 mm)	13.711 in (348.26 mm)	6.981 in (177.30 mm)	7.003 in (177.90 mm)	9.697 in (246.30 mm)	9.735 in (247.28 mm)	N/A	N/A	N/A
8.625	74.25	0.900	TenarisHydril Blue® Heavy Wall	Standard	6.700	Standard API Drift	6.56 in (166.4 mm)	1.60 in (40.8 mm)	6.822 in (173.28 mm)	6.845 in (173.86 mm)	8.625 in (219.08 mm)	8.711 in (221.24 mm)	6.48 in (164.4 mm)	2.79 in (71.0 mm)	13.515 in (343.28 mm)	13.711 in (348.26 mm)	6.954 in (176.62 mm)	6.977 in (177.22 mm)	9.730 in (247.14 mm)	9.769 in (248.14 mm)	N/A	N/A	N/A
8.625	77.87	0.950	TenarisHydril Blue® Heavy Wall	Standard	6.600	Standard API Drift	6.56 in (166.4 mm)	1.60 in (40.8 mm)	6.731 in (170.96 mm)	6.753 in (171.54 mm)	8.625 in (219.08 mm)	8.711 in (221.24 mm)	6.48 in (164.4 mm)	2.79 in (71.0 mm)	13.515 in (343.28 mm)	13.711 in (348.26 mm)	6.900 in (175.26 mm)	6.923 in (175.84 mm)	9.796 in (248.82 mm)	9.835 in (249.80 mm)	N/A	N/A	N/A
8.625	81.44	1.000	TenarisHydril Blue® Heavy Wall	Standard	6.500	Standard API Drift	7.16 in (181.8 mm)	1.23 in (31.2 mm)	6.621 in (168.16 mm)	6.644 in (168.76 mm)	8.625 in (219.08 mm)	8.711 in (221.24 mm)	7.08 in (179.8 mm)	3.08 in (78.4 mm)	14.721 in (373.90 mm)	14.916 in (378.88 mm)	6.593 in (167.46 mm)	6.616 in (168.06 mm)	9.703 in (246.44 mm)	9.741 in (247.44 mm)	N/A	N/A	N/A
8.625	83.20	1.025	TenarisHydril Blue® Heavy Wall	Standard	6.450	Standard API Drift	7.16 in (181.8 mm)	1.23 in (31.2 mm)	6.575 in (167.00 mm)	6.598 in (167.60 mm)	8.625 in (219.08 mm)	8.711 in (221.24 mm)	7.08 in (179.8 mm)	3.08 in (78.4 mm)	14.721 in (373.90 mm)	14.916 in (378.88 mm)	6.566 in (166.76 mm)	6.588 in (167.36 mm)	9.735 in (247.26 mm)	9.774 in (248.26 mm)	N/A	N/A	N/A
8.625	84.95	1.050	TenarisHydril Blue® Heavy Wall	Standard	6.400	Standard API Drift	7.16 in (181.8 mm)	1.23 in (31.2 mm)	6.530 in (165.84 mm)	6.552 in (166.44 mm)	8.625 in (219.08 mm)	8.711 in (221.24 mm)	7.08 in (179.8 mm)	3.08 in (78.4 mm)	14.721 in (373.90 mm)	14.916 in (378.88 mm)	6.538 in (166.06 mm)	6.561 in (166.66 mm)	9.767 in (248.06 mm)	9.805 in (249.05 mm)	N/A	N/A	N/A
8.625	88.40	1.100	TenarisHydril Blue® Heavy Wall	Standard	6.300	Standard API Drift	7.16 in (181.8 mm)	1.23 in (31.2 mm)	6.438 in (163.52 mm)	6.461 in (164.12 mm)	8.625 in (219.08 mm)	8.711 in (221.24 mm)	7.08 in (179.8 mm)	3.08 in (78.4 mm)	14.721 in (373.90 mm)	14.916 in (378.88 mm)	6.484 in (164.68 mm)	6.506 in (165.26 mm)	9.830 in (249.66 mm)	9.868 in (250.66 mm)	N/A	N/A	N/A
8.625	91.81	1.150	TenarisHydril Blue® Heavy Wall	Standard	6.200	Standard API Drift	7.16 in (181.8 mm)	1.23 in (31.2 mm)	6.347 in (161.20 mm)	6.370 in (161.80 mm)	8.625 in (219.08 mm)	8.711 in (221.24 mm)	7.08 in (179.8 mm)	3.08 in (78.4 mm)	14.721 in (373.90 mm)	14.916 in (378.88 mm)	6.430 in (163.30 mm)	6.452 in (163.90 mm)	9.891 in (251.22 mm)	9.929 in (252.20 mm)	N/A	N/A	N/A

# TenarisHydril Blue® HW and TenarisHydril Blue® HW Dopeless® Blanking Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, recopied, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections B.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request therefore. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyrighted 2020 as an unpublished work. ALL RIGHTS RESERVED.

SIZE (IN)	WEIGHT (LB/FT)	WALL (IN)	CONNECTION				PIN						BOX										
			PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH	RECUT LENGTH	INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH	RECUT LENGTH	COUPLING LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER - REGULAR		OUTSIDE DIAMETER - SPECIAL CLEARANCE		
									MIN	MAX	MIN	MAX			MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN
8.625	95.16	1.200	TenarisHydril Blue® Heavy Wall	Standard	6.100	Standard API Drift	7.16 in (181.8 mm)	1.23 in (31.2 mm)	6.256 in (158.90 mm)	6.279 in (159.48 mm)	8.625 in (219.08 mm)	8.711 in (221.24 mm)	7.08 in (179.8 mm)	3.08 in (78.4 mm)	14.721 in (373.90 mm)	14.916 in (378.88 mm)	6.376 in (161.94 mm)	6.398 in (162.52 mm)	9.951 in (252.74 mm)	9.989 in (253.74 mm)	N/A	N/A	N/A
8.625	98.46	1.250	TenarisHydril Blue® Heavy Wall	Standard	6.000	Standard API Drift	7.16 in (181.8 mm)	1.23 in (31.2 mm)	6.165 in (156.58 mm)	6.188 in (157.18 mm)	8.625 in (219.08 mm)	8.711 in (221.24 mm)	7.08 in (179.8 mm)	3.08 in (78.4 mm)	14.721 in (373.90 mm)	14.916 in (378.88 mm)	6.322 in (160.58 mm)	6.345 in (161.16 mm)	10.010 in (254.24 mm)	10.048 in (255.22 mm)	N/A	N/A	N/A
9.625	71.80	0.750	TenarisHydril Blue® Heavy Wall	Standard	7.969	Standard API Drift	6.62 in (168.0 mm)	1.60 in (40.8 mm)	8.069 in (204.94 mm)	8.091 in (205.52 mm)	9.625 in (244.48 mm)	9.721 in (246.90 mm)	6.54 in (166.0 mm)	2.96 in (75.2 mm)	13.639 in (346.42 mm)	13.835 in (351.40 mm)	8.093 in (205.56 mm)	8.116 in (206.16 mm)	10.515 in (267.06 mm)	10.553 in (268.06 mm)	N/A	N/A	N/A
9.625	75.60	0.797	TenarisHydril Blue® Heavy Wall	Standard	7.875	Standard API Drift	6.62 in (168.0 mm)	1.60 in (40.8 mm)	7.982 in (202.74 mm)	8.005 in (203.34 mm)	9.625 in (244.48 mm)	9.721 in (246.90 mm)	6.54 in (166.0 mm)	2.96 in (75.2 mm)	13.639 in (346.42 mm)	13.835 in (351.40 mm)	8.042 in (204.26 mm)	8.064 in (204.84 mm)	10.583 in (268.80 mm)	10.622 in (269.80 mm)	N/A	N/A	N/A
9.625	75.90	0.800	TenarisHydril Blue® Heavy Wall	Standard	7.869	Standard API Drift	6.62 in (168.0 mm)	1.60 in (40.8 mm)	7.977 in (202.60 mm)	8.000 in (203.20 mm)	9.625 in (244.48 mm)	9.721 in (246.90 mm)	6.54 in (166.0 mm)	2.96 in (75.2 mm)	13.639 in (346.42 mm)	13.835 in (351.40 mm)	8.039 in (204.18 mm)	8.061 in (204.76 mm)	10.588 in (268.92 mm)	10.626 in (269.90 mm)	N/A	N/A	N/A
9.625	79.66	0.850	TenarisHydril Blue® Heavy Wall	Standard	7.769	Standard API Drift	6.62 in (168.0 mm)	1.60 in (40.8 mm)	7.885 in (200.28 mm)	7.908 in (200.86 mm)	9.625 in (244.48 mm)	9.721 in (246.90 mm)	6.54 in (166.0 mm)	2.96 in (75.2 mm)	13.639 in (346.42 mm)	13.835 in (351.40 mm)	7.984 in (202.78 mm)	8.007 in (203.38 mm)	10.658 in (270.72 mm)	10.697 in (271.70 mm)	N/A	N/A	N/A
9.625	83.86	0.900	TenarisHydril Blue® Heavy Wall	Standard	7.669	Standard API Drift	6.62 in (168.0 mm)	1.60 in (40.8 mm)	7.793 in (197.94 mm)	7.816 in (198.54 mm)	9.625 in (244.48 mm)	9.721 in (246.90 mm)	6.54 in (166.0 mm)	2.96 in (75.2 mm)	13.639 in (346.42 mm)	13.835 in (351.40 mm)	7.930 in (202.00 mm)	7.952 in (202.00 mm)	10.728 in (272.50 mm)	10.767 in (273.48 mm)	N/A	N/A	N/A
9.625	88.02	0.950	TenarisHydril Blue® Heavy Wall	Standard	7.569	Standard API Drift	6.62 in (168.0 mm)	1.60 in (40.8 mm)	7.702 in (195.62 mm)	7.724 in (196.20 mm)	9.625 in (244.48 mm)	9.721 in (246.90 mm)	6.54 in (166.0 mm)	2.96 in (75.2 mm)	13.639 in (346.42 mm)	13.835 in (351.40 mm)	7.875 in (200.62 mm)	7.898 in (200.62 mm)	10.797 in (274.24 mm)	10.835 in (275.22 mm)	N/A	N/A	N/A
9.625	90.49	0.980	TenarisHydril Blue® Heavy Wall	Standard	7.509	Standard API Drift	6.62 in (168.0 mm)	1.60 in (40.8 mm)	7.647 in (194.22 mm)	7.669 in (194.80 mm)	9.625 in (244.48 mm)	9.721 in (246.90 mm)	6.54 in (166.0 mm)	2.96 in (75.2 mm)	13.639 in (346.42 mm)	13.835 in (351.40 mm)	7.843 in (199.20 mm)	7.866 in (199.80 mm)	10.838 in (275.26 mm)	10.876 in (276.26 mm)	N/A	N/A	N/A
9.625	90.81	0.984	TenarisHydril Blue® Heavy Wall	Standard	7.501	Standard API Drift	6.62 in (168.0 mm)	1.60 in (40.8 mm)	7.639 in (194.04 mm)	7.662 in (194.62 mm)	9.625 in (244.48 mm)	9.721 in (246.90 mm)	6.54 in (166.0 mm)	2.96 in (75.2 mm)	13.639 in (346.42 mm)	13.835 in (351.40 mm)	7.839 in (199.10 mm)	7.861 in (199.68 mm)	10.843 in (275.40 mm)	10.881 in (276.38 mm)	N/A	N/A	N/A
9.625	92.12	1.000	TenarisHydril Blue® Heavy Wall	Standard	7.469	Standard API Drift	6.62 in (168.0 mm)	1.60 in (40.8 mm)	7.610 in (193.30 mm)	7.633 in (193.88 mm)	9.625 in (244.48 mm)	9.721 in (246.90 mm)	6.54 in (166.0 mm)	2.96 in (75.2 mm)	13.639 in (346.42 mm)	13.835 in (351.40 mm)	7.822 in (199.66 mm)	7.844 in (199.66 mm)	10.864 in (275.94 mm)	10.902 in (276.92 mm)	N/A	N/A	N/A
9.625	96.16	1.050	TenarisHydril Blue® Heavy Wall	Standard	7.369	Standard API Drift	7.56 in (192.0 mm)	1.23 in (31.2 mm)	7.523 in (191.08 mm)	7.546 in (191.66 mm)	9.625 in (244.48 mm)	9.721 in (246.90 mm)	7.48 in (190.0 mm)	2.44 in (62.0 mm)	15.529 in (394.44 mm)	15.725 in (399.42 mm)	7.488 in (190.18 mm)	7.510 in (190.76 mm)	10.752 in (273.10 mm)	10.791 in (274.10 mm)	N/A	N/A	N/A
9.625	100.15	1.100	TenarisHydril Blue® Heavy Wall	Standard	7.269	Standard API Drift	7.56 in (192.0 mm)	1.23 in (31.2 mm)	7.432 in (188.76 mm)	7.454 in (189.34 mm)	9.625 in (244.48 mm)	9.721 in (246.90 mm)	7.48 in (190.0 mm)	2.44 in (62.0 mm)	15.529 in (394.44 mm)	15.725 in (399.42 mm)	7.432 in (188.78 mm)	7.455 in (189.36 mm)	10.818 in (274.78 mm)	10.857 in (275.76 mm)	N/A	N/A	N/A
9.625	104.09	1.150	TenarisHydril Blue® Heavy Wall	Standard	7.169	Standard API Drift	7.56 in (192.0 mm)	1.23 in (31.2 mm)	7.340 in (186.44 mm)	7.363 in (187.02 mm)	9.625 in (244.48 mm)	9.721 in (246.90 mm)	7.48 in (190.0 mm)	2.44 in (62.0 mm)	15.529 in (394.44 mm)	15.725 in (399.42 mm)	7.378 in (187.38 mm)	7.400 in (187.98 mm)	10.883 in (276.42 mm)	10.921 in (277.40 mm)	N/A	N/A	N/A
9.625	107.97	1.200	TenarisHydril Blue® Heavy Wall	Standard	7.069	Standard API Drift	7.56 in (192.0 mm)	1.23 in (31.2 mm)	7.249 in (184.12 mm)	7.272 in (184.72 mm)	9.625 in (244.48 mm)	9.721 in (246.90 mm)	7.48 in (190.0 mm)	2.44 in (62.0 mm)	15.529 in (394.44 mm)	15.725 in (399.42 mm)	7.323 in (186.00 mm)	7.346 in (186.60 mm)	10.946 in (278.02 mm)	10.984 in (279.00 mm)	N/A	N/A	N/A
9.625	111.81	1.250	TenarisHydril Blue® Heavy Wall	Standard	6.969	Standard API Drift	7.56 in (192.0 mm)	1.23 in (31.2 mm)	7.158 in (181.82 mm)	7.181 in (182.40 mm)	9.625 in (244.48 mm)	9.721 in (246.90 mm)	7.48 in (190.0 mm)	2.44 in (62.0 mm)	15.529 in (394.44 mm)	15.725 in (399.42 mm)	7.269 in (184.64 mm)	7.292 in (185.22 mm)	11.008 in (279.60 mm)	11.046 in (280.58 mm)	N/A	N/A	N/A
10.125	75.21	0.750	TenarisHydril Blue® Heavy Wall	Standard	8.469	Standard API Drift	6.82 in (173.2 mm)	1.51 in (38.4 mm)	8.566 in (217.56 mm)	8.588 in (218.16 mm)	10.125 in (257.18 mm)	10.226 in (259.74 mm)	6.74 in (171.2 mm)	2.03 in (51.6 mm)	14.039 in (356.58 mm)	14.235 in (361.56 mm)	8.501 in (215.92 mm)	8.524 in (216.52 mm)	10.938 in (277.82 mm)	10.976 in (278.80 mm)	N/A	N/A	N/A
10.125	79.34	0.795	TenarisHydril Blue® Heavy Wall	Standard	8.379	Standard API Drift	6.82 in (173.2 mm)	1.51 in (38.4 mm)	8.483 in (215.46 mm)	8.506 in (216.06 mm)	10.125 in (257.18 mm)	10.226 in (259.74 mm)	6.74 in (171.2 mm)	2.03 in (51.6 mm)	14.039 in (356.58 mm)	14.235 in (361.56 mm)	8.439 in (214.34 mm)	8.462 in (214.94 mm)	11.005 in (279.52 mm)	11.043 in (280.50 mm)	N/A	N/A	N/A
10.125	79.34	0.795	TenarisHydril Blue® Heavy Wall	Shell Level B	8.500	Special Drift	6.82 in (173.2 mm)	1.51 in (38.4 mm)	8.562 in (217.46 mm)	8.584 in (218.04 mm)	10.175 in (258.46 mm)	10.277 in (261.02 mm)	6.74 in (171.2 mm)	2.03 in (51.6 mm)	14.039 in (356.58 mm)	14.235 in (361.56 mm)	8.526 in (216.56 mm)	8.549 in (217.16 mm)	11.005 in (279.52 mm)	11.043 in (280.50 mm)	N/A	N/A	N/A
10.125	79.34	0.795	TenarisHydril Blue® Heavy Wall	Standard	8.500	Special Drift	6.82 in (173.2 mm)	1.51 in (38.4 mm)	8.562 in (217.46 mm)	8.584 in (218.04 mm)	10.175 in (258.46 mm)	10.277 in (261.02 mm)	6.74 in (171.2 mm)	2.03 in (51.6 mm)	14.039 in (356.58 mm)	14.235 in (361.56 mm)	8.526 in (216.56 mm)	8.549 in (217.16 mm)	11.005 in (279.52 mm)	11.043 in (280.50 mm)	N/A	N/A	N/A
10.125	79.80	0.800	TenarisHydril Blue® Heavy Wall	Standard	8.369	Standard API Drift	6.82 in (173.2 mm)	1.51 in (38.4 mm)	8.474 in (215.22 mm)	8.496 in (215.82 mm)	10.125 in (257.18 mm)	10.226 in (259.74 mm)	6.74 in (171.2 mm)	2.03 in (51.6 mm)	14.039 in (356.58 mm)	14.235 in (361.56 mm)	8.434 in (214.22 mm)	8.457 in (214.80 mm)	11.012 in (279.70 mm)	11.050 in (280.68 mm)	N/A	N/A	N/A
10.125	84.33	0.850	TenarisHydril Blue® Heavy Wall	Standard	8.269	Standard API Drift	6.82 in (173.2 mm)	1.51 in (38.4 mm)	8.382 in (212.90 mm)	8.405 in (213.48 mm)	10.125 in (257.18 mm)	10.226 in (259.74 mm)	6.74 in (171.2 mm)	2.03 in (51.6 mm)	14.039 in (356.58 mm)	14.235 in (361.56 mm)	8.384 in (212.94 mm)	8.406 in (213.52 mm)	11.085 in (281.54 mm)	11.123 in (282.54 mm)	N/A	N/A	N/A
10.125	88.81	0.900	TenarisHydril Blue® Heavy Wall	Standard	8.169	Standard API Drift	6.82 in (173.2 mm)	1.51 in (38.4 mm)	8.290 in (210.56 mm)	8.313 in (211.16 mm)	10.125 in (257.18 mm)	10.226 in (259.74 mm)	6.74 in (171.2 mm)	2.03 in (51.6 mm)	14.039 in (356.58 mm)	14.235 in (361.56 mm)	8.334 in (211.66 mm)	8.356 in (212.26 mm)	11.156 in (283.36 mm)	11.195 in (284.36 mm)	N/A	N/A	N/A
10.125	93.24	0.950	TenarisHydril Blue® Heavy Wall	Standard	8.069	Standard API Drift	6.82 in (173.2 mm)	1.51 in (38.4 mm)	8.199 in (208.24 mm)	8.221 in (208.82 mm)	10.125 in (257.18 mm)	10.226 in (259.74 mm)	6.74 in (171.2 mm)	2.03 in (51.6 mm)	14.039 in (356.58 mm)	14.235 in (361.56 mm)	8.284 in (210.40 mm)	8.307 in (211.00 mm)	11.226 in (285.14 mm)	11.265 in (286.14 mm)	N/A	N/A	N/A
10.175	80.56	0.800	TenarisHydril Blue® Heavy Wall	Standard	8.500	Special Drift	6.82 in (173.2 mm)	1.51 in (38.4 mm)	8.562 in (215.46 mm)	8.584 in (216.06 mm)	10.175 in (258.46 mm)	10.277 in (261.02 mm)	6.74 in (171.2 mm)	2.03 in (51.6 mm)	14.039 in (356.58 mm)	14.235 in (361.56 mm)	8.526 in (216.56 mm)	8.549 in (217.16 mm)	11.005 in (279.52 mm)	11.043 in (280.50 mm)	N/A	N/A	N/A
10.750	80.80	0.750	TenarisHydril Blue® Heavy Wall	Standard	9.094	Standard API Drift	6.90 in (175.2 mm)	1.51 in (38.4 mm)	9.172 in (232.96 mm)	9.195 in (233.56 mm)	10.750 in (273.06 mm)	10.858 in (275.78 mm)	6.82 in (173.2 mm)	3.75 in (95.2 mm)	13.409 in (340.58 mm)	13.605 in (345.58 mm)	9.124 in (231.74 mm)	9.146 in (232.32 mm)	11.415 in (289.94 mm)	11.453 in (290.92 mm)	N/A	N/A	N/A
10.750	85.30	0.797	TenarisHydril Blue® Heavy Wall	Standard	9.000	Standard API Drift	6.90 in (175.2 mm)	1.51 in (38.4 mm)	9.078 in (230.58 mm)	9.101 in (231.16 mm)	10.750 in (273.06 mm)	10.858 in (275.78 mm)	6.82 in (173.2 mm)	3.75 in (95.2 mm)	13.409 in (340.58 mm)	13.605 in (345.58 mm)	9.030 in (229.34 mm)	9.052 in (229.94 mm)	11.478 in (291.52 mm)	11.516 in (292.52 mm)	N/A	N/A	N/A
10.750	85.30	0.797	TenarisHydril Blue® Heavy Wall	Maersk	9.100	Special Drift	6.90 in (175.2 mm)	1.51 in (38.4 mm)	9.167 in (232.84 mm)	9.190 in (233.42 mm)	10.750 in (273.06 mm)	10.858 in (275.78 mm)	6.82 in (173.2 mm)	3.75 in (95.2 mm)	13.409 in (340.58 mm)	13.605 in (345.58 mm)	9.128 in (231.84 mm)	9.151 in (232.44 mm)	11.478 in (292.52 mm)	11.516 in (293.52 mm)	N/A	N/A	N/A
10.750	90.30	0.850	TenarisHydril Blue® Heavy Wall	Standard	8.894	Standard API Drift	6.90 in (175.2 mm)	1.51 in (38.4 mm)	8.982 in (228.12 mm)	9.004 in (228.72 mm)	10.750 in (273.06 mm)	10.858 in (275.78 mm)	6.82 in (173.2 mm)	3.75 in (95.2 mm)	13.409 in (340.58 mm)	13.605 in (345.58 mm)	8.924 in (226.66 mm)	8.946 in (227.24 mm)	11.547 in (293.28 mm)	11.585 in (294.28 mm)	N/A	N/A	N/A
10.750	91.20	0.859	TenarisHydril Blue® Heavy Wall	Standard	8.876	Standard API Drift	6.90 in (175.2 mm)	1.51 in (38.4 mm)	8.973 in (227.90 mm)	8.995 in (228.48 mm)	10.750 in (273.06 mm)	10.858 in (275.78 mm)	6.82 in (173.2 mm)	3.75 in (95.2 mm)	13.409 in (340.58 mm)	13.605 in (345.58 mm)	8.906 in (226.20 mm)	8.928 in (226.78 mm)	11.559 in (293.58 mm)	11.597 in (294.58 mm)	N/A	N/A	N/A

# TenarisHydril Blue® HW and TenarisHydril Blue® HW Dopeless® Blanking Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, recopied, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections B.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request therefore. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyrighted 2020 as an unpublished work. ALL RIGHTS RESERVED.

CONNECTION							PIN						BOX										
SIZE (IN)	WEIGHT (LB/FT)	WALL (IN)	PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH		COUPLING LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER - REGULAR		OUTSIDE DIAMETER - SPECIAL CLEARANCE		
							MIN	MIN	MIN	MAX	MIN	MAX	MIN	MIN	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	EFFICIENCY
10.750	91.20	0.859	TenarisHydril Blue® Heavy Wall	KOC - SC60	8.876	Standard API Drift	6.90 in (175.2 mm)	1.51 in (38.4 mm)	9.004 in (228.70 mm)	9.027 in (229.28 mm)	10.750 in (273.06 mm)	10.858 in (275.78 mm)	6.82 in (173.2 mm)	3.75 in (95.2 mm)	13.409 in (340.58 mm)	13.605 in (345.58 mm)	8.906 in (226.20 mm)	8.928 in (226.78 mm)	11.331 in (287.80 mm)	11.350 in (288.28 mm)	60.0	11.331 in (287.80 mm)	11.350 in (288.28 mm)
10.750	91.20	0.859	TenarisHydril Blue® Heavy Wall	KOC - SC76	8.876	Standard API Drift	6.90 in (175.2 mm)	1.51 in (38.4 mm)	9.004 in (228.70 mm)	9.027 in (229.28 mm)	10.750 in (273.06 mm)	10.858 in (275.78 mm)	6.82 in (173.2 mm)	3.75 in (95.2 mm)	13.409 in (340.58 mm)	13.605 in (345.58 mm)	8.906 in (226.20 mm)	8.928 in (226.78 mm)	11.481 in (291.60 mm)	11.500 in (292.10 mm)	76.0	11.481 in (291.60 mm)	11.500 in (292.10 mm)
10.750	94.68	0.900	TenarisHydril Blue® Heavy Wall	Standard	8.794	Standard API Drift	6.90 in (175.2 mm)	1.51 in (38.4 mm)	8.929 in (226.78 mm)	8.951 in (227.38 mm)	10.750 in (273.06 mm)	10.858 in (275.78 mm)	6.82 in (173.2 mm)	3.75 in (95.2 mm)	13.409 in (340.58 mm)	13.605 in (345.58 mm)	8.824 in (224.12 mm)	8.846 in (224.70 mm)	11.612 in (294.92 mm)	11.650 in (295.92 mm)	N/A	N/A	N/A
10.750	96.79	0.922	TenarisHydril Blue® Heavy Wall	Standard	8.750	Standard API Drift	6.90 in (175.2 mm)	1.51 in (38.4 mm)	8.888 in (225.76 mm)	8.911 in (226.34 mm)	10.750 in (273.06 mm)	10.858 in (275.78 mm)	6.82 in (173.2 mm)	3.75 in (95.2 mm)	13.409 in (340.58 mm)	13.605 in (345.58 mm)	8.797 in (223.42 mm)	8.819 in (224.02 mm)	11.639 in (295.64 mm)	11.678 in (296.62 mm)	N/A	N/A	N/A
10.750	100.40	0.960	TenarisHydril Blue® Heavy Wall	Standard	8.674	Standard API Drift	6.90 in (175.2 mm)	1.51 in (38.4 mm)	8.819 in (223.98 mm)	8.841 in (224.58 mm)	10.750 in (273.06 mm)	10.858 in (275.78 mm)	6.82 in (173.2 mm)	3.75 in (95.2 mm)	13.409 in (340.58 mm)	13.605 in (345.58 mm)	8.754 in (222.36 mm)	8.777 in (222.94 mm)	11.688 in (296.86 mm)	11.726 in (297.84 mm)	N/A	N/A	N/A
10.750	100.40	0.960	TenarisHydril Blue® Heavy Wall	Maersk	8.750	Special Drift	6.90 in (175.2 mm)	1.51 in (38.4 mm)	8.856 in (224.94 mm)	8.879 in (225.52 mm)	10.750 in (273.06 mm)	10.858 in (275.78 mm)	6.82 in (173.2 mm)	3.75 in (95.2 mm)	13.409 in (340.58 mm)	13.605 in (345.58 mm)	8.817 in (223.96 mm)	8.840 in (224.54 mm)	11.688 in (296.86 mm)	11.726 in (297.84 mm)	N/A	N/A	N/A
10.750	102.63	0.984	TenarisHydril Blue® Heavy Wall	Standard	8.626	Standard API Drift	6.90 in (175.2 mm)	1.51 in (38.4 mm)	8.775 in (222.88 mm)	8.798 in (223.46 mm)	10.750 in (273.06 mm)	10.858 in (275.78 mm)	6.82 in (173.2 mm)	3.75 in (95.2 mm)	13.409 in (340.58 mm)	13.605 in (345.58 mm)	8.728 in (221.68 mm)	8.751 in (222.28 mm)	11.717 in (297.62 mm)	11.756 in (298.60 mm)	N/A	N/A	N/A
10.750	104.13	1.000	TenarisHydril Blue® Heavy Wall	Standard	8.594	Standard API Drift	6.90 in (175.2 mm)	1.51 in (38.4 mm)	8.746 in (222.14 mm)	8.768 in (222.72 mm)	10.750 in (273.06 mm)	10.858 in (275.78 mm)	6.82 in (173.2 mm)	3.75 in (95.2 mm)	13.409 in (340.58 mm)	13.605 in (345.58 mm)	8.710 in (221.82 mm)	8.733 in (222.40 mm)	11.737 in (298.12 mm)	11.775 in (299.10 mm)	N/A	N/A	N/A
10.750	107.20	1.033	TenarisHydril Blue® Heavy Wall	Standard	8.528	Standard API Drift	6.90 in (175.2 mm)	1.51 in (38.4 mm)	8.685 in (220.60 mm)	8.708 in (221.18 mm)	10.750 in (273.06 mm)	10.858 in (275.78 mm)	6.82 in (173.2 mm)	3.75 in (95.2 mm)	13.409 in (340.58 mm)	13.605 in (345.58 mm)	8.674 in (220.30 mm)	8.696 in (220.90 mm)	11.778 in (299.14 mm)	11.816 in (300.14 mm)	N/A	N/A	N/A
10.750	108.78	1.050	TenarisHydril Blue® Heavy Wall	Standard	8.500	Special Drift	8.52 in (216.4 mm)	1.51 in (38.4 mm)	8.679 in (220.44 mm)	8.702 in (221.04 mm)	10.750 in (273.06 mm)	10.858 in (275.78 mm)	8.44 in (214.4 mm)	2.70 in (68.6 mm)	17.439 in (442.94 mm)	17.635 in (447.92 mm)	8.638 in (219.40 mm)	8.661 in (220.00 mm)	11.580 in (294.14 mm)	11.599 in (294.62 mm)	N/A	N/A	N/A
10.750	108.78	1.050	TenarisHydril Blue® Heavy Wall	Standard	8.600	Special Drift	8.52 in (216.4 mm)	1.51 in (38.4 mm)	8.679 in (220.44 mm)	8.702 in (221.04 mm)	10.750 in (273.06 mm)	10.858 in (275.78 mm)	8.44 in (214.4 mm)	2.70 in (68.6 mm)	17.439 in (442.94 mm)	17.635 in (447.92 mm)	8.638 in (219.40 mm)	8.661 in (220.00 mm)	11.580 in (294.14 mm)	11.599 in (294.62 mm)	N/A	N/A	N/A
10.875	72.00	0.656	TenarisHydril Blue® Heavy Wall	Standard	9.500	Special Drift	5.85 in (148.6 mm)	1.51 in (38.4 mm)	9.556 in (242.70 mm)	9.566 in (243.00 mm)	10.875 in (276.24 mm)	10.984 in (278.98 mm)	5.78 in (146.6 mm)	2.02 in (51.4 mm)	12.111 in (307.60 mm)	12.307 in (312.60 mm)	9.528 in (242.00 mm)	9.551 in (242.60 mm)	11.654 in (296.00 mm)	11.692 in (297.00 mm)	N/A	N/A	N/A
11.750	88.11	0.750	TenarisHydril Blue® Heavy Wall	Standard	10.094	Standard API Drift	7.12 in (181.0 mm)	1.51 in (38.4 mm)	10.172 in (258.36 mm)	10.195 in (258.96 mm)	11.750 in (298.46 mm)	11.868 in (301.44 mm)	7.05 in (179.0 mm)	3.47 in (88.2 mm)	13.866 in (352.20 mm)	14.062 in (357.18 mm)	10.124 in (257.14 mm)	10.146 in (257.72 mm)	12.417 in (315.38 mm)	12.455 in (316.36 mm)	N/A	N/A	N/A
11.750	93.23	0.797	TenarisHydril Blue® Heavy Wall	Standard	10.000	Standard API Drift	7.12 in (181.0 mm)	1.51 in (38.4 mm)	10.078 in (255.98 mm)	10.101 in (256.56 mm)	11.750 in (298.46 mm)	11.868 in (301.44 mm)	7.05 in (179.0 mm)	3.47 in (88.2 mm)	13.866 in (352.20 mm)	14.062 in (357.18 mm)	10.030 in (254.74 mm)	10.052 in (255.34 mm)	12.480 in (317.00 mm)	12.519 in (317.98 mm)	N/A	N/A	N/A
11.750	98.95	0.850	TenarisHydril Blue® Heavy Wall	Standard	9.894	Standard API Drift	7.12 in (181.0 mm)	1.51 in (38.4 mm)	9.980 in (253.48 mm)	10.003 in (254.08 mm)	11.750 in (298.46 mm)	11.868 in (301.44 mm)	7.05 in (179.0 mm)	3.47 in (88.2 mm)	13.866 in (352.20 mm)	14.062 in (357.18 mm)	9.924 in (252.06 mm)	9.946 in (252.64 mm)	12.551 in (318.80 mm)	12.590 in (319.78 mm)	N/A	N/A	N/A
11.750	99.92	0.859	TenarisHydril Blue® Heavy Wall	Standard	9.876	Standard API Drift	7.12 in (181.0 mm)	1.51 in (38.4 mm)	9.971 in (253.26 mm)	9.994 in (253.84 mm)	11.750 in (298.46 mm)	11.868 in (301.44 mm)	7.05 in (179.0 mm)	3.47 in (88.2 mm)	13.866 in (352.20 mm)	14.062 in (357.18 mm)	9.906 in (251.60 mm)	9.928 in (252.18 mm)	12.563 in (319.10 mm)	12.601 in (320.08 mm)	N/A	N/A	N/A
11.750	104.29	0.900	TenarisHydril Blue® Heavy Wall	Standard	9.794	Standard API Drift	7.12 in (181.0 mm)	1.51 in (38.4 mm)	9.929 in (252.18 mm)	9.951 in (252.78 mm)	11.750 in (298.46 mm)	11.868 in (301.44 mm)	7.05 in (179.0 mm)	3.47 in (88.2 mm)	13.866 in (352.20 mm)	14.062 in (357.18 mm)	9.824 in (249.52 mm)	9.846 in (250.10 mm)	12.617 in (320.46 mm)	12.655 in (321.46 mm)	N/A	N/A	N/A
11.750	106.62	0.922	TenarisHydril Blue® Heavy Wall	Standard	9.750	Standard API Drift	7.12 in (181.0 mm)	1.51 in (38.4 mm)	9.889 in (251.16 mm)	9.911 in (251.76 mm)	11.750 in (298.46 mm)	11.868 in (301.44 mm)	7.05 in (179.0 mm)	3.47 in (88.2 mm)	13.866 in (352.20 mm)	14.062 in (357.18 mm)	9.796 in (248.82 mm)	9.819 in (249.40 mm)	12.646 in (321.20 mm)	12.684 in (322.18 mm)	N/A	N/A	N/A
11.750	109.05	0.945	TenarisHydril Blue® Heavy Wall	Standard	9.704	Standard API Drift	7.12 in (181.0 mm)	1.51 in (38.4 mm)	9.846 in (250.08 mm)	9.869 in (250.68 mm)	11.750 in (298.46 mm)	11.868 in (301.44 mm)	7.05 in (179.0 mm)	3.47 in (88.2 mm)	13.866 in (352.20 mm)	14.062 in (357.18 mm)	9.771 in (248.16 mm)	9.793 in (248.76 mm)	12.676 in (321.96 mm)	12.714 in (322.94 mm)	N/A	N/A	N/A
11.750	118.23	1.033	TenarisHydril Blue® Heavy Wall	Standard	9.528	Standard API Drift	7.12 in (181.0 mm)	1.51 in (38.4 mm)	9.685 in (246.00 mm)	9.708 in (246.58 mm)	11.750 in (298.46 mm)	11.868 in (301.44 mm)	7.05 in (179.0 mm)	3.47 in (88.2 mm)	13.866 in (352.20 mm)	14.062 in (357.18 mm)	9.673 in (245.70 mm)	9.696 in (246.28 mm)	12.788 in (324.80 mm)	12.826 in (325.78 mm)	N/A	N/A	N/A
12.250	120.33	1.000	TenarisHydril Blue® Heavy Wall	Standard	10.094	Standard API Drift	7.64 in (194.0 mm)	1.51 in (38.4 mm)	10.212 in (259.36 mm)	10.234 in (259.96 mm)	12.250 in (311.16 mm)	12.373 in (314.26 mm)	7.56 in (192.0 mm)	3.29 in (83.6 mm)	15.688 in (398.46 mm)	15.884 in (403.46 mm)	10.140 in (257.54 mm)	10.162 in (258.14 mm)	13.396 in (340.24 mm)	13.434 in (341.24 mm)	N/A	N/A	N/A
12.250	125.78	1.050	TenarisHydril Blue® Heavy Wall	Standard	9.994	Standard API Drift	7.64 in (194.0 mm)	1.51 in (38.4 mm)	10.120 in (257.04 mm)	10.142 in (257.62 mm)	12.250 in (311.16 mm)	12.373 in (314.26 mm)	7.56 in (192.0 mm)	3.29 in (83.6 mm)	15.688 in (398.46 mm)	15.884 in (403.46 mm)	10.084 in (256.72 mm)	10.107 in (257.28 mm)	13.468 in (343.08 mm)	13.506 in (343.66 mm)	N/A	N/A	N/A
12.250	131.18	1.100	TenarisHydril Blue® Heavy Wall	Standard	9.894	Standard API Drift	7.64 in (194.0 mm)	1.51 in (38.4 mm)	10.028 in (254.70 mm)	10.051 in (255.30 mm)	12.250 in (311.16 mm)	12.373 in (314.26 mm)	7.56 in (192.0 mm)	3.29 in (83.6 mm)	15.688 in (398.46 mm)	15.884 in (403.46 mm)	10.029 in (254.74 mm)	10.052 in (255.32 mm)	13.539 in (343.88 mm)	13.577 in (344.86 mm)	N/A	N/A	N/A
12.250	133.87	1.125	TenarisHydril Blue® Heavy Wall	Standard	9.844	Standard API Drift	7.64 in (194.0 mm)	1.51 in (38.4 mm)	9.982 in (253.54 mm)	10.005 in (254.12 mm)	12.250 in (311.16 mm)	12.373 in (314.26 mm)	7.56 in (192.0 mm)	3.29 in (83.6 mm)	15.688 in (398.46 mm)	15.884 in (403.46 mm)	10.002 in (254.04 mm)	10.024 in (254.62 mm)	13.612 in (344.76 mm)	13.612 in (345.76 mm)	N/A	N/A	N/A
12.250	136.53	1.150	TenarisHydril Blue® Heavy Wall	Standard	9.794	Standard API Drift	7.64 in (194.0 mm)	1.51 in (38.4 mm)	9.936 in (252.38 mm)	9.959 in (252.96 mm)	12.250 in (311.16 mm)	12.373 in (314.26 mm)	7.56 in (192.0 mm)	3.29 in (83.6 mm)	15.688 in (398.46 mm)	15.884 in (403.46 mm)	9.974 in (253.34 mm)	9.997 in (253.92 mm)	13.609 in (345.66 mm)	13.647 in (346.64 mm)	N/A	N/A	N/A
12.250	141.83	1.200	TenarisHydril Blue® Heavy Wall	Standard	9.694	Standard API Drift	7.64 in (194.0 mm)	1.51 in (38.4 mm)	9.845 in (250.04 mm)	9.867 in (250.64 mm)	12.250 in (311.16 mm)	12.373 in (314.26 mm)	7.56 in (192.0 mm)	3.29 in (83.6 mm)	15.688 in (398.46 mm)	15.884 in (403.46 mm)	9.919 in (251.94 mm)	9.942 in (252.54 mm)	13.678 in (347.40 mm)	13.716 in (348.40 mm)	N/A	N/A	N/A
12.250	147.07	1.250	TenarisHydril Blue® Heavy Wall	Standard	9.594	Standard API Drift	7.64 in (194.0 mm)	1.51 in (38.4 mm)	9.753 in (247.72 mm)	9.776 in (248.32 mm)	12.250 in (311.16 mm)	12.373 in (314.26 mm)	7.56 in (192.0 mm)	3.29 in (83.6 mm)	15.688 in (398.46 mm)	15.884 in (403.46 mm)	9.865 in (250.56 mm)	9.888 in (251.16 mm)	13.745 in (349.12 mm)	13.784 in (350.12 mm)	N/A	N/A	N/A
14.000	106.00	0.750	TenarisHydril Blue® Heavy Wall	Standard	12.313	Standard API Drift	6.77 in (171.8 mm)	1.51 in (38.4 mm)	12.426 in (315.62 mm)	12.449 in (316.22 mm)	14.000 in (355.60 mm)	14.140 in (359.14 mm)	6.69 in (169.8 mm)	2.82 in (71.8 mm)	13.154 in (334.10 mm)	13.350 in (339.08 mm)	12.347 in (313.60 mm)	12.370 in (314.20 mm)	14.760 in (374.88 mm)	14.798 in (375.88 mm)	N/A	N/A	N/A
14.000	114.00	0.800	TenarisHydril Blue® Heavy Wall	Standard	12.213	Standard API Drift	6.77 in (171.8 mm)	1.51 in (38.4 mm)	12.334 in (313.28 mm)	12.357 in (313.88 mm)	14.000 in (355.60 mm)	14.140 in (359.14 mm)	6.69 in (169.8 mm)	2.82 in (71.8 mm)	13.154 in (334.10 mm)	13.350 in (339.08 mm)	12.280 in (311.92 mm)	12.303 in (312.50 mm)	14.760 in (374.88 mm)	14.798 in (375.88 mm)	N/A	N/A	N/A
14.000	120.00	0.850	TenarisHydril Blue® Heavy Wall	Standard	12.113	Standard API Drift	6.77 in (171.8 mm)	1.51 in (38.4 mm)	12.243 in (310.96 mm)	12.265 in (311.54 mm)	14.000 in (355.60 mm)	14.140 in (359.14 mm)	6.69 in (169.8 mm)	2.82 in (71.8 mm)	13.154 in (334.10 mm)	13.350 in (339.08 mm)	12.230 in (310.64 mm)	12.253 in (311.22 mm)	14.965 in (380.10 mm)	15.003 in (381.08 mm)	N/A	N/A	N/A

# TenarisHydril Blue® HW and TenarisHydril Blue® HW Dopeless® Blanking Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, recopied, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections B.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request therefore. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyrighted 2020 as an unpublished work. ALL RIGHTS RESERVED.

CONNECTION							PIN								BOX								
SIZE (IN)	WEIGHT (LB/FT)	WALL (IN)	PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH	RECUT LENGTH	INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH	RECUT LENGTH	COUPLING LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER - REGULAR		OUTSIDE DIAMETER - SPECIAL CLEARANCE		
							MIN	MIN	MIN	MAX	MIN	MAX	MIN	MIN	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	EFFICIENCY
14.000	125.92	0.900	TenarisHydril Blue® Heavy Wall	Standard	12.013	Standard API Drift	6.77 in (171.8 mm)	1.51 in (38.4 mm)	12.150 in (308.62 mm)	12.173 in (309.20 mm)	14.000 in (355.60 mm)	14.140 in (359.14 mm)	6.69 in (169.8 mm)	2.82 in (71.8 mm)	13.154 in (334.10 mm)	13.350 in (339.08 mm)	12.180 in (309.36 mm)	12.202 in (309.94 mm)	14.965 in (380.10 mm)	15.003 in (381.08 mm)	N/A	N/A	N/A
14.000	132.41	0.950	TenarisHydril Blue® Heavy Wall	Standard	11.913	Standard API Drift	6.77 in (171.8 mm)	1.51 in (38.4 mm)	12.059 in (306.28 mm)	12.081 in (306.88 mm)	14.000 in (355.60 mm)	14.140 in (359.14 mm)	6.69 in (169.8 mm)	2.82 in (71.8 mm)	13.154 in (334.10 mm)	13.350 in (339.08 mm)	12.130 in (308.10 mm)	12.153 in (308.68 mm)	14.965 in (380.10 mm)	15.003 in (381.08 mm)	N/A	N/A	N/A

Dimensions provided do not include length required for tongs for making up assemblies. Please take this into consideration when designing and machining your accessory.

BLANK OD and ID: The nominal blank ODs and IDs in the Pin Diameters and Box Diameters columns are finished product dimensions. When this minimum material is supplied, the blank OD and the blank ID must be true to each other within 0.010" TIR (Total Indicator Reading).

BLANK Min Length includes 0.02" (0.5mm) extra material for facing.

Contact Tenaris Manufacturing Services at blankingdimensions@tenaris.com for details.

These Blanking Dimensions are NOT applicable For Handling & lifting plug, HydroTest Caps & HydroTest Plugs.

N/A: Not Applicable

Yellow - Shaded corresponds to modified from previous document revision.