

TenarisHydril MS XT/XC™ Blanking Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, recopied, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections B.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request therefore. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyrighted 2019 as an unpublished work. ALL RIGHTS RESERVED.

CONNECTION						PIN						BOX														
SIZE (IN)	WEIGHT (LB/FT)	WALL (IN)	PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH	RECUT LENGTH		COUPLING LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER - REGULAR		OUTSIDE DIAMETER - MATCHED STRENGTH		OUTSIDE DIAMETER - SPECIAL CLEARANCE		EFFICIENCY
							MIN	MIN	MIN	MAX	MIN	MAX		MIN	MIN	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	
3.500	9.20	0.254	TenarisHydril MS XT/XC™	Standard	2.867	API Standard Drift	4.04 in (102.6 mm)	1.84 in (46.8 mm)	2.983 in (75.76 mm)	3.001 in (76.24 mm)	3.500 in (88.90 mm)	3.531 in (89.68 mm)	4.04 in (102.6 mm)	1.96 in (49.8 mm)	7.953 in (202.00 mm)	8.149 in (207.00 mm)	2.917 in (74.08 mm)	2.935 in (74.56 mm)	3.898 in (99.00 mm)	3.937 in (100.00 mm)	3.867 in (98.20 mm)	3.905 in (99.20 mm)	N/A	3.831 in (97.30 mm)	3.862 in (98.10 mm)	
4.500	10.50	0.224	TenarisHydril MS XT/XC™	Standard	3.927	API Standard Drift	4.67 in (118.6 mm)	1.84 in (46.8 mm)	4.038 in (102.56 mm)	4.057 in (103.06 mm)	4.500 in (114.30 mm)	4.545 in (115.44 mm)	4.67 in (118.6 mm)	1.96 in (49.8 mm)	9.804 in (249.00 mm)	10.000 in (254.00 mm)	3.977 in (101.00 mm)	3.996 in (101.50 mm)	4.902 in (124.50 mm)	4.940 in (125.50 mm)	4.875 in (123.80 mm)	4.913 in (124.80 mm)	N/A	4.859 in (123.40 mm)	4.889 in (124.20 mm)	
4.500	11.60	0.250	TenarisHydril MS XT/XC™	Standard	3.875	API Standard Drift	4.67 in (118.6 mm)	1.84 in (46.8 mm)	3.991 in (101.36 mm)	4.009 in (101.84 mm)	4.500 in (114.30 mm)	4.545 in (115.44 mm)	4.67 in (118.6 mm)	1.96 in (49.8 mm)	9.804 in (249.00 mm)	10.000 in (254.00 mm)	3.925 in (99.68 mm)	3.944 in (100.18 mm)	4.902 in (124.50 mm)	4.940 in (125.50 mm)	4.875 in (123.80 mm)	4.913 in (124.80 mm)	N/A	4.859 in (123.40 mm)	4.889 in (124.20 mm)	
4.500	12.60	0.271	TenarisHydril MS XT/XC™	Standard	3.833	API Standard Drift	4.67 in (118.6 mm)	1.84 in (46.8 mm)	3.949 in (100.28 mm)	3.967 in (100.78 mm)	4.500 in (114.30 mm)	4.545 in (115.44 mm)	4.67 in (118.6 mm)	1.96 in (49.8 mm)	9.804 in (249.00 mm)	10.000 in (254.00 mm)	3.902 in (99.12 mm)	3.921 in (99.60 mm)	4.902 in (124.50 mm)	4.940 in (125.50 mm)	4.875 in (123.80 mm)	4.913 in (124.80 mm)	N/A	4.859 in (123.40 mm)	4.889 in (124.20 mm)	
4.500	13.50	0.290	TenarisHydril MS XT/XC™	Standard	3.795	API Standard Drift	4.67 in (118.6 mm)	1.84 in (46.8 mm)	3.911 in (99.32 mm)	3.929 in (99.82 mm)	4.500 in (114.30 mm)	4.545 in (115.44 mm)	4.67 in (118.6 mm)	1.96 in (49.8 mm)	9.804 in (249.00 mm)	10.000 in (254.00 mm)	3.865 in (98.16 mm)	3.883 in (98.64 mm)	4.941 in (125.50 mm)	4.980 in (126.50 mm)	4.902 in (124.50 mm)	4.940 in (125.50 mm)	N/A	4.859 in (123.40 mm)	4.889 in (124.20 mm)	
4.500	15.10	0.337	TenarisHydril MS XT/XC™	Standard	3.701	API Standard Drift	4.67 in (118.6 mm)	1.84 in (46.8 mm)	3.817 in (96.94 mm)	3.835 in (97.42 mm)	4.500 in (114.30 mm)	4.545 in (115.44 mm)	4.67 in (118.6 mm)	1.96 in (49.8 mm)	9.804 in (249.00 mm)	10.000 in (254.00 mm)	3.817 in (97.42 mm)	3.835 in (97.90 mm)	5.060 in (128.50 mm)	5.098 in (129.50 mm)	4.977 in (126.40 mm)	5.015 in (127.40 mm)	N/A	4.859 in (123.40 mm)	4.889 in (124.20 mm)	
4.500	17.00	0.380	TenarisHydril MS XT/XC™	Standard	3.615	API Standard Drift	4.67 in (118.6 mm)	1.84 in (46.8 mm)	3.731 in (94.76 mm)	3.750 in (95.24 mm)	4.500 in (114.30 mm)	4.545 in (115.44 mm)	4.67 in (118.6 mm)	1.96 in (49.8 mm)	9.804 in (249.00 mm)	10.000 in (254.00 mm)	3.731 in (94.76 mm)	3.750 in (95.24 mm)	5.060 in (128.50 mm)	5.098 in (129.50 mm)	5.040 in (128.00 mm)	5.078 in (129.00 mm)	N/A	4.859 in (123.40 mm)	4.889 in (124.20 mm)	
4.500	23.70	0.560	TenarisHydril MS XT/XC™	Standard	3.255	API Standard Drift	4.67 in (118.6 mm)	1.84 in (46.8 mm)	3.371 in (85.60 mm)	3.389 in (86.10 mm)	4.500 in (114.30 mm)	4.545 in (115.44 mm)	4.67 in (118.6 mm)	1.96 in (49.8 mm)	9.804 in (249.00 mm)	10.000 in (254.00 mm)	3.534 in (89.75 mm)	3.553 in (90.24 mm)	5.280 in (134.10 mm)	5.318 in (135.10 mm)	5.288 in (134.30 mm)	5.326 in (135.30 mm)	N/A	4.859 in (123.40 mm)	4.889 in (124.20 mm)	
5.000	13.00	0.253	TenarisHydril MS XT/XC™	Standard	4.369	API Standard Drift	4.91 in (124.6 mm)	2.00 in (50.8 mm)	4.485 in (113.90 mm)	4.503 in (114.40 mm)	5.000 in (127.00 mm)	5.050 in (128.26 mm)	4.91 in (124.6 mm)	2.12 in (53.8 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	4.438 in (112.72 mm)	4.457 in (113.22 mm)	5.540 in (140.70 mm)	5.586 in (141.90 mm)	5.375 in (136.50 mm)	5.413 in (137.50 mm)	N/A	5.359 in (136.10 mm)	5.405 in (137.30 mm)	
5.000	15.00	0.296	TenarisHydril MS XT/XC™	Standard	4.283	API Standard Drift	4.91 in (124.6 mm)	2.00 in (50.8 mm)	4.399 in (111.72 mm)	4.417 in (112.20 mm)	5.000 in (127.00 mm)	5.050 in (128.26 mm)	4.91 in (124.6 mm)	2.12 in (53.8 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	4.352 in (110.54 mm)	4.371 in (111.04 mm)	5.540 in (140.70 mm)	5.586 in (141.90 mm)	5.430 in (137.90 mm)	5.468 in (138.90 mm)	N/A	5.359 in (136.10 mm)	5.405 in (137.30 mm)	
5.000	18.00	0.362	TenarisHydril MS XT/XC™	Standard	4.151	API Standard Drift	4.91 in (124.6 mm)	2.00 in (50.8 mm)	4.267 in (108.36 mm)	4.285 in (108.86 mm)	5.000 in (127.00 mm)	5.050 in (128.26 mm)	4.91 in (124.6 mm)	2.12 in (53.8 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	4.240 in (107.70 mm)	4.259 in (108.18 mm)	5.540 in (140.70 mm)	5.586 in (141.90 mm)	5.536 in (140.60 mm)	5.574 in (141.60 mm)	N/A	5.359 in (136.10 mm)	5.405 in (137.30 mm)	
5.000	20.30	0.408	TenarisHydril MS XT/XC™	Standard	4.059	API Standard Drift	4.91 in (124.6 mm)	2.00 in (50.8 mm)	4.175 in (106.02 mm)	4.193 in (106.52 mm)	5.000 in (127.00 mm)	5.050 in (128.26 mm)	4.91 in (124.6 mm)	2.12 in (53.8 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	4.175 in (106.02 mm)	4.193 in (106.52 mm)	5.540 in (140.70 mm)	5.586 in (141.90 mm)	5.536 in (140.60 mm)	5.574 in (141.60 mm)	N/A	5.359 in (136.10 mm)	5.405 in (137.30 mm)	
5.000	20.80	0.422	TenarisHydril MS XT/XC™	Standard	4.031	API Standard Drift	4.91 in (124.6 mm)	2.00 in (50.8 mm)	4.147 in (105.32 mm)	4.165 in (105.80 mm)	5.000 in (127.00 mm)	5.050 in (128.26 mm)	4.91 in (124.6 mm)	2.12 in (53.8 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	4.147 in (105.32 mm)	4.165 in (105.80 mm)	5.540 in (140.70 mm)	5.586 in (141.90 mm)	5.536 in (140.60 mm)	5.574 in (141.60 mm)	N/A	5.359 in (136.10 mm)	5.405 in (137.30 mm)	
5.000	21.40	0.437	TenarisHydril MS XT/XC™	Standard	4.001	API Standard Drift	4.91 in (124.6 mm)	2.00 in (50.8 mm)	4.117 in (104.56 mm)	4.135 in (105.04 mm)	5.000 in (127.00 mm)	5.050 in (128.26 mm)	4.91 in (124.6 mm)	2.12 in (53.8 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	4.117 in (104.56 mm)	4.135 in (105.04 mm)	5.540 in (140.70 mm)	5.586 in (141.90 mm)	5.650 in (143.50 mm)	5.688 in (144.50 mm)	N/A	5.359 in (136.10 mm)	5.405 in (137.30 mm)	
5.000	23.20	0.478	TenarisHydril MS XT/XC™	Standard	3.919	API Standard Drift	4.91 in (124.6 mm)	2.00 in (50.8 mm)	4.035 in (102.48 mm)	4.053 in (102.96 mm)	5.000 in (127.00 mm)	5.050 in (128.26 mm)	4.91 in (124.6 mm)	2.12 in (53.8 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	4.035 in (102.48 mm)	4.053 in (102.96 mm)	5.540 in (140.70 mm)	5.586 in (141.90 mm)	5.709 in (145.00 mm)	5.748 in (146.00 mm)	N/A	5.359 in (136.10 mm)	5.405 in (137.30 mm)	
5.000	24.10	0.500	TenarisHydril MS XT/XC™	Standard	3.875	API Standard Drift	4.91 in (124.6 mm)	2.00 in (50.8 mm)	3.991 in (101.36 mm)	4.009 in (101.84 mm)	5.000 in (127.00 mm)	5.050 in (128.26 mm)	4.91 in (124.6 mm)	2.12 in (53.8 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	3.991 in (101.36 mm)	4.009 in (101.84 mm)	5.540 in (140.70 mm)	5.586 in (141.90 mm)	5.737 in (145.70 mm)	5.775 in (146.70 mm)	N/A	5.359 in (136.10 mm)	5.405 in (137.30 mm)	
5.500	15.50	0.275	TenarisHydril MS XT/XC™	Standard	4.825	API Standard Drift	4.91 in (124.6 mm)	2.00 in (50.8 mm)	4.941 in (125.48 mm)	4.959 in (125.98 mm)	5.500 in (139.70 mm)	5.555 in (141.08 mm)	4.91 in (124.6 mm)	2.12 in (53.8 mm)	10.650 in (270.50 mm)	10.846 in (275.50 mm)	4.875 in (123.82 mm)	4.894 in (124.30 mm)	6.028 in (153.10 mm)	6.074 in (154.30 mm)	5.902 in (149.90 mm)	5.940 in (150.90 mm)	N/A	5.859 in (148.80 mm)	5.905 in (150.00 mm)	
5.500	17.00	0.304	TenarisHydril MS XT/XC™	Standard	4.767	API Standard Drift	4.91 in (124.6 mm)	2.00 in (50.8 mm)	4.883 in (124.02 mm)	4.901 in (124.50 mm)	5.500 in (139.70 mm)	5.555 in (141.08 mm)	4.91 in (124.6 mm)	2.12 in (53.8 mm)	10.650 in (270.50 mm)	10.846 in (275.50 mm)	4.836 in (122.84 mm)	4.855 in (123.32 mm)	6.028 in (153.10 mm)	6.074 in (154.30 mm)	5.949 in (151.10 mm)	5.988 in (152.10 mm)	N/A	5.859 in (148.80 mm)	5.905 in (150.00 mm)	
5.500	20.00	0.361	TenarisHydril MS XT/XC™	Standard	4.653	API Standard Drift	4.91 in (124.6 mm)	2.00 in (50.8 mm)	4.769 in (121.12 mm)	4.787 in (121.60 mm)	5.500 in (139.70 mm)	5.555 in (141.08 mm)	4.91 in (124.6 mm)	2.12 in (53.8 mm)	10.650 in (270.50 mm)	10.846 in (275.50 mm)	4.769 in (121.12 mm)	4.787 in (121.60 mm)	6.028 in (153.10 mm)	6.074 in (154.30 mm)	6.040 in (153.40 mm)	6.078 in (154.40 mm)	N/A	5.859 in (148.80 mm)	5.905 in (150.00 mm)	
5.500	23.00	0.415	TenarisHydril MS XT/XC™	Standard	4.545	API Standard Drift	4.91 in (124.6 mm)	2.00 in (50.8 mm)	4.661 in (118.38 mm)	4.679 in (118.86 mm)	5.500 in (139.70 mm)	5.555 in (141.08 mm)	4.91 in (124.6 mm)	2.12 in (53.8 mm)	10.650 in (270.50 mm)	10.846 in (275.50 mm)	4.661 in (118.38 mm)	4.679 in (118.86 mm)	6.028 in (153.10 mm)	6.074 in (154.30 mm)	6.123 in (155.50 mm)	6.161 in (156.50 mm)	N/A	5.859 in (148.80 mm)	5.905 in (150.00 mm)	
5.500	26.80	0.500	TenarisHydril MS XT/XC™	Standard	4.375	API Standard Drift	4.91 in (124.6 mm)	2.00 in (50.8 mm)	4.491 in (114.06 mm)	4.509 in (114.54 mm)	5.500 in (139.70 mm)	5.555 in (141.08 mm)	4.91 in (124.6 mm)	2.12 in (53.8 mm)	10.650 in (270.50 mm)	10.846 in (275.50 mm)	4.491 in (114.06 mm)	4.509 in (114.54 mm)	6.028 in (153.10 mm)	6.074 in (154.30 mm)	6.252 in (158.80 mm)	6.291 in (159.80 mm)	N/A	5.859 in (148.80 mm)	5.905 in (150.00 mm)	
6.625	24.00	0.352	TenarisHydril MS XT/XC™	Standard	5.796	API Standard Drift	4.91 in (124.6 mm)	1.92 in (48.6 mm)	5.910 in (150.10 mm)	5.932 in (150.68 mm)	6.625 in (168.28 mm)	6.691 in (169.94 mm)	4.91 in (124.6 mm)	2.03 in (51.6 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	5.863 in (148.92 mm)	5.886 in (149.52 mm)	7.367 in (187.10 mm)	7.413 in (188.30 mm)	7.130 in (181.10 mm)	7.169 in (182.10 mm)	N/A	6.985 in (177.40 mm)	7.031 in (178.60 mm)	
6.625	28.00	0.417	TenarisHydril MS XT/XC™	Standard	5.666	API Standard Drift	4.91 in (124.6 mm)	1.92 in (48.6 mm)	5.780 in (146.80 mm)	5.802 in (147.38 mm)	6.625 in (168.28 mm)	6.691 in (169.94 mm)	4.91 in (124.6 mm)	2.03 in (51.6 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	5.781 in (146.82 mm)	5.803 in (147.42 mm)	7.367 in (187.10 mm)	7.413 in (188.30 mm)	7.237 in (183.80 mm)	7.275 in (184.80 mm)	N/A	6.985 in (177.40 mm)	7.031 in (178.60 mm)	
6.625	32.00	0.475	TenarisHydril MS XT/XC™	Standard	5.550	API Standard Drift	4.91 in (124.6 mm)	1.92 in (48.6 mm)	5.664 in (143.86 mm)	5.687 in (144.44 mm)	6.625 in (168.28 mm)	6.691 in (169.94 mm)	4.91 in (124.6 mm)	2.03 in (51.6 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	5.665 in (143.88 mm)	5.688 in (144.48 mm)	7.367 in (187.10 mm)	7.413 in (188.30 mm)	7.327 in (186.10 mm)	7.366 in (187.10 mm)	N/A	6.985 in (177.40 mm)	7.031 in (178.60 mm)	
7.000																										

TenarisHydril MS XT/XC™ Blanking Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, recopied, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections B.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request therefore. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyrighted 2019 as an unpublished work. ALL RIGHTS RESERVED.

CONNECTION							PIN							BOX											
SIZE (IN)	WEIGHT (LB/FT)	WALL (IN)	PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH	RECUT LENGTH	INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH	RECUT LENGTH	COUPLING LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER - REGULAR		OUTSIDE DIAMETER - MATCHED STRENGTH		OUTSIDE DIAMETER - SPECIAL CLEARANCE		
							MIN	MIN	MIN	MAX	MIN	MAX	MIN	MIN	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN
7.000	35.00	0.498	TenarisHydril MS XT/XC™	Standard	5.879	API Standard Drift	5.06 in (128.6 mm)	1.92 in (48.6 mm)	5.993 in (152.20 mm)	6.015 in (152.80 mm)	7.000 in (177.80 mm)	7.070 in (179.56 mm)	5.06 in (128.6 mm)	2.03 in (51.6 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	5.993 in (152.20 mm)	6.015 in (152.80 mm)	7.634 in (193.90 mm)	7.681 in (195.10 mm)	7.729 in (196.30 mm)	7.767 in (197.30 mm)	N/A	7.359 in (186.90 mm)	7.405 in (188.10 mm)
7.000	38.00	0.540	TenarisHydril MS XT/XC™	Standard	5.795	API Standard Drift	5.06 in (128.6 mm)	1.92 in (48.6 mm)	5.909 in (150.08 mm)	5.931 in (150.66 mm)	7.000 in (177.80 mm)	7.070 in (179.56 mm)	5.06 in (128.6 mm)	2.03 in (51.6 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	5.908 in (150.06 mm)	5.931 in (150.66 mm)	7.634 in (193.90 mm)	7.681 in (195.10 mm)	7.796 in (198.00 mm)	7.834 in (199.00 mm)	N/A	7.359 in (186.90 mm)	7.405 in (188.10 mm)
7.000	41.00	0.590	TenarisHydril MS XT/XC™	Standard	5.695	API Standard Drift	5.06 in (128.6 mm)	1.92 in (48.6 mm)	5.809 in (147.54 mm)	5.831 in (148.12 mm)	7.000 in (177.80 mm)	7.070 in (179.56 mm)	5.06 in (128.6 mm)	2.03 in (51.6 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	5.808 in (147.52 mm)	5.831 in (148.12 mm)	7.634 in (193.90 mm)	7.681 in (195.10 mm)	7.871 in (199.90 mm)	7.909 in (200.90 mm)	N/A	7.359 in (186.90 mm)	7.405 in (188.10 mm)
7.625	26.40	0.328	TenarisHydril MS XT/XC™	Standard	6.844	API Standard Drift	5.26 in (133.6 mm)	1.92 in (48.6 mm)	6.958 in (176.72 mm)	6.980 in (177.30 mm)	7.625 in (193.68 mm)	7.701 in (195.60 mm)	5.26 in (133.6 mm)	2.03 in (51.6 mm)	10.571 in (268.50 mm)	10.767 in (273.50 mm)	6.892 in (175.04 mm)	6.914 in (175.64 mm)	8.477 in (215.30 mm)	8.523 in (216.50 mm)	8.126 in (206.40 mm)	8.165 in (207.40 mm)	N/A	8.111 in (206.00 mm)	8.157 in (207.20 mm)
7.625	29.70	0.375	TenarisHydril MS XT/XC™	Standard	6.750	API Standard Drift	5.26 in (133.6 mm)	1.92 in (48.6 mm)	6.864 in (174.34 mm)	6.887 in (174.92 mm)	7.625 in (193.68 mm)	7.701 in (195.60 mm)	5.26 in (133.6 mm)	2.03 in (51.6 mm)	10.571 in (268.50 mm)	10.767 in (273.50 mm)	6.817 in (173.16 mm)	6.840 in (173.74 mm)	8.477 in (215.30 mm)	8.523 in (216.50 mm)	8.146 in (206.90 mm)	8.185 in (207.90 mm)	N/A	8.111 in (206.00 mm)	8.157 in (207.20 mm)
7.625	33.70	0.430	TenarisHydril MS XT/XC™	Standard	6.640	API Standard Drift	5.26 in (133.6 mm)	1.92 in (48.6 mm)	6.754 in (171.54 mm)	6.776 in (172.12 mm)	7.625 in (193.68 mm)	7.701 in (195.60 mm)	5.26 in (133.6 mm)	2.03 in (51.6 mm)	10.571 in (268.50 mm)	10.767 in (273.50 mm)	6.727 in (170.86 mm)	6.750 in (171.46 mm)	8.477 in (215.30 mm)	8.523 in (216.50 mm)	8.237 in (209.20 mm)	8.275 in (210.20 mm)	N/A	8.111 in (206.00 mm)	8.157 in (207.20 mm)
7.625	39.00	0.500	TenarisHydril MS XT/XC™	Standard	6.500	API Standard Drift	5.26 in (133.6 mm)	1.92 in (48.6 mm)	6.614 in (167.98 mm)	6.637 in (168.58 mm)	7.625 in (193.68 mm)	7.701 in (195.60 mm)	5.26 in (133.6 mm)	2.03 in (51.6 mm)	10.571 in (268.50 mm)	10.767 in (273.50 mm)	6.615 in (168.00 mm)	6.637 in (168.60 mm)	8.477 in (215.30 mm)	8.523 in (216.50 mm)	8.351 in (212.10 mm)	8.389 in (213.10 mm)	N/A	8.111 in (206.00 mm)	8.157 in (207.20 mm)
7.625	42.80	0.562	TenarisHydril MS XT/XC™	Standard	6.376	API Standard Drift	5.26 in (133.6 mm)	1.92 in (48.6 mm)	6.490 in (164.84 mm)	6.512 in (165.42 mm)	7.625 in (193.68 mm)	7.701 in (195.60 mm)	5.26 in (133.6 mm)	2.03 in (51.6 mm)	10.571 in (268.50 mm)	10.767 in (273.50 mm)	6.491 in (164.86 mm)	6.514 in (165.46 mm)	8.477 in (215.30 mm)	8.523 in (216.50 mm)	8.449 in (214.60 mm)	8.488 in (215.60 mm)	N/A	8.111 in (206.00 mm)	8.157 in (207.20 mm)
7.625	45.30	0.595	TenarisHydril MS XT/XC™	Standard	6.310	API Standard Drift	5.26 in (133.6 mm)	1.92 in (48.6 mm)	6.424 in (163.16 mm)	6.446 in (163.74 mm)	7.625 in (193.68 mm)	7.701 in (195.60 mm)	5.26 in (133.6 mm)	2.03 in (51.6 mm)	10.571 in (268.50 mm)	10.767 in (273.50 mm)	6.425 in (163.18 mm)	6.448 in (163.78 mm)	8.477 in (215.30 mm)	8.523 in (216.50 mm)	8.500 in (215.90 mm)	8.539 in (216.90 mm)	N/A	8.111 in (206.00 mm)	8.157 in (207.20 mm)
7.625	47.10	0.625	TenarisHydril MS XT/XC™	Standard	6.250	API Standard Drift	5.26 in (133.6 mm)	1.92 in (48.6 mm)	6.364 in (161.64 mm)	6.387 in (162.22 mm)	7.625 in (193.68 mm)	7.701 in (195.60 mm)	5.26 in (133.6 mm)	2.03 in (51.6 mm)	10.571 in (268.50 mm)	10.767 in (273.50 mm)	6.364 in (161.64 mm)	6.387 in (162.24 mm)	8.477 in (215.30 mm)	8.523 in (216.50 mm)	8.544 in (217.00 mm)	8.582 in (218.00 mm)	N/A	8.111 in (206.00 mm)	8.157 in (207.20 mm)
7.750	46.10	0.595	TenarisHydril MS XT/XC™	Standard	6.435	API Standard Drift	5.26 in (133.6 mm)	1.92 in (48.6 mm)	6.549 in (166.32 mm)	6.571 in (166.92 mm)	7.750 in (196.86 mm)	7.828 in (198.82 mm)	5.26 in (133.6 mm)	2.03 in (51.6 mm)	11.398 in (289.50 mm)	11.594 in (294.50 mm)	6.551 in (166.38 mm)	6.574 in (166.98 mm)	8.611 in (218.70 mm)	8.657 in (219.90 mm)	8.626 in (219.10 mm)	8.665 in (220.10 mm)	N/A	N/A	N/A
8.625	32.00	0.352	TenarisHydril MS XT/XC™	Standard	7.796	API Standard Drift	5.38 in (136.6 mm)	1.92 in (48.6 mm)	7.910 in (200.90 mm)	7.932 in (201.48 mm)	8.625 in (219.08 mm)	8.711 in (221.24 mm)	5.38 in (136.6 mm)	2.03 in (51.6 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	8.744 in (199.22 mm)	8.766 in (199.82 mm)	9.603 in (243.90 mm)	9.649 in (245.10 mm)	9.126 in (231.80 mm)	9.165 in (232.80 mm)	N/A	9.111 in (231.40 mm)	9.157 in (232.60 mm)
8.625	32.00	0.352	TenarisHydril MS XT/XC™	Standard	7.875	Alternative API Drift	5.38 in (136.6 mm)	1.92 in (48.6 mm)	7.910 in (200.90 mm)	7.932 in (201.48 mm)	8.625 in (219.08 mm)	8.711 in (221.24 mm)	5.38 in (136.6 mm)	2.03 in (51.6 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	8.744 in (199.22 mm)	8.766 in (199.82 mm)	9.603 in (243.90 mm)	9.649 in (245.10 mm)	9.126 in (231.80 mm)	9.165 in (232.80 mm)	N/A	9.111 in (231.40 mm)	9.157 in (232.60 mm)
8.625	36.00	0.400	TenarisHydril MS XT/XC™	Standard	7.700	API Standard Drift	5.38 in (136.6 mm)	1.92 in (48.6 mm)	7.814 in (198.46 mm)	7.837 in (199.06 mm)	8.625 in (219.08 mm)	8.711 in (221.24 mm)	5.38 in (136.6 mm)	2.03 in (51.6 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	7.767 in (197.28 mm)	7.790 in (197.88 mm)	9.603 in (243.90 mm)	9.649 in (245.10 mm)	9.186 in (233.30 mm)	9.224 in (234.30 mm)	N/A	9.111 in (231.40 mm)	9.157 in (232.60 mm)
8.625	40.00	0.450	TenarisHydril MS XT/XC™	Standard	7.600	API Standard Drift	5.38 in (136.6 mm)	1.92 in (48.6 mm)	7.714 in (195.92 mm)	7.737 in (196.52 mm)	8.625 in (219.08 mm)	8.711 in (221.24 mm)	5.38 in (136.6 mm)	2.03 in (51.6 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	7.687 in (195.24 mm)	7.710 in (195.84 mm)	9.603 in (243.90 mm)	9.649 in (245.10 mm)	9.272 in (235.50 mm)	9.311 in (236.50 mm)	N/A	9.111 in (231.40 mm)	9.157 in (232.60 mm)
8.625	40.00	0.450	TenarisHydril MS XT/XC™	Standard	7.625	Alternative API Drift	5.38 in (136.6 mm)	1.92 in (48.6 mm)	7.714 in (195.92 mm)	7.737 in (196.52 mm)	8.625 in (219.08 mm)	8.711 in (221.24 mm)	5.38 in (136.6 mm)	2.03 in (51.6 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	7.687 in (195.24 mm)	7.710 in (195.84 mm)	9.603 in (243.90 mm)	9.649 in (245.10 mm)	9.272 in (235.50 mm)	9.311 in (236.50 mm)	N/A	9.111 in (231.40 mm)	9.157 in (232.60 mm)
8.625	44.00	0.500	TenarisHydril MS XT/XC™	Standard	7.500	API Standard Drift	5.38 in (136.6 mm)	1.92 in (48.6 mm)	7.614 in (193.38 mm)	7.637 in (193.98 mm)	8.625 in (219.08 mm)	8.711 in (221.24 mm)	5.38 in (136.6 mm)	2.03 in (51.6 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	7.615 in (193.40 mm)	7.637 in (194.00 mm)	9.603 in (243.90 mm)	9.649 in (245.10 mm)	9.355 in (237.60 mm)	9.393 in (238.60 mm)	N/A	9.111 in (231.40 mm)	9.157 in (232.60 mm)
8.625	49.00	0.557	TenarisHydril MS XT/XC™	Standard	7.386	API Standard Drift	5.38 in (136.6 mm)	1.92 in (48.6 mm)	7.500 in (190.48 mm)	7.522 in (191.08 mm)	8.625 in (219.08 mm)	8.711 in (221.24 mm)	5.38 in (136.6 mm)	2.03 in (51.6 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	7.500 in (190.50 mm)	7.523 in (191.10 mm)	9.603 in (243.90 mm)	9.649 in (245.10 mm)	9.445 in (239.90 mm)	9.484 in (240.90 mm)	N/A	9.111 in (231.40 mm)	9.157 in (232.60 mm)
9.625	36.00	0.352	TenarisHydril MS XT/XC™	Standard	8.765	API Standard Drift	5.38 in (136.6 mm)	1.92 in (48.6 mm)	8.905 in (226.18 mm)	8.928 in (226.78 mm)	9.625 in (244.48 mm)	9.721 in (246.90 mm)	5.38 in (136.6 mm)	2.03 in (51.6 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	8.813 in (223.84 mm)	8.835 in (224.42 mm)	10.597 in (269.16 mm)	10.655 in (270.64 mm)	10.126 in (257.20 mm)	10.165 in (258.20 mm)	N/A	10.111 in (256.80 mm)	10.157 in (258.00 mm)
9.625	40.00	0.395	TenarisHydril MS XT/XC™	Standard	8.679	API Standard Drift	5.38 in (136.6 mm)	1.92 in (48.6 mm)	8.824 in (224.12 mm)	8.846 in (224.72 mm)	9.625 in (244.48 mm)	9.721 in (246.90 mm)	5.38 in (136.6 mm)	2.03 in (51.6 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	8.727 in (222.24 mm)	8.750 in (222.82 mm)	10.597 in (269.16 mm)	10.655 in (270.64 mm)	10.182 in (258.60 mm)	10.220 in (259.60 mm)	N/A	10.111 in (256.80 mm)	10.157 in (258.00 mm)
9.625	40.00	0.395	TenarisHydril MS XT/XC™	Standard	8.750	Alternative API Drift	5.38 in (136.6 mm)	1.92 in (48.6 mm)	8.824 in (224.12 mm)	8.846 in (224.72 mm)	9.625 in (244.48 mm)	9.721 in (246.90 mm)	5.38 in (136.6 mm)	2.03 in (51.6 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	8.727 in (222.24 mm)	8.750 in (222.82 mm)	10.597 in (269.16 mm)	10.655 in (270.64 mm)	10.182 in (258.60 mm)	10.220 in (259.60 mm)	N/A	10.111 in (256.80 mm)	10.157 in (258.00 mm)
9.625	43.50	0.435	TenarisHydril MS XT/XC™	Standard	8.599	API Standard Drift	5.38 in (136.6 mm)	1.92 in (48.6 mm)	8.744 in (222.08 mm)	8.766 in (222.68 mm)	9.625 in (244.48 mm)	9.721 in (246.90 mm)	5.38 in (136.6 mm)	2.03 in (51.6 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	8.666 in (220.12 mm)	8.689 in (220.70 mm)	10.597 in (269.16 mm)	10.655 in (270.64 mm)	10.252 in (260.40 mm)	10.291 in (261.40 mm)	N/A	10.111 in (256.80 mm)	10.157 in (258.00 mm)
9.625	43.50	0.435	TenarisHydril MS XT/XC™	Standard	8.625	Special Drift	5.38 in (136.6 mm)	1.92 in (48.6 mm)	8.744 in (222.08 mm)	8.766 in (222.68 mm)	9.625 in (244.48 mm)	9.721 in (246.90 mm)	5.38 in (136.6 mm)	2.03 in (51.6 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	8.666 in (220.12 mm)	8.689 in (220.70 mm)	10.597 in (269.16 mm)	10.655 in (270.64 mm)	10.252 in (260.40 mm)	10.291 in (261.40 mm)	N/A	10.111 in (256.80 mm)	10.157 in (258.00 mm)
9.625	47.00	0.472	TenarisHydril MS XT/XC™	Standard	8.525	API Standard Drift	5.38 in (136.6 mm)	1.92 in (48.6 mm)	8.670 in (220.20 mm)	8.692 in (220.80 mm)	9.625 in (244.48 mm)	9.721 in (246.90 mm)	5.38 in (136.6 mm)	2.03 in (51.6 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	8.612 in (218.74 mm)	8.635 in (219.34 mm)	10.597 in (269.16 mm)	10.655 in (270.64 mm)	10.315 in (262.00 mm)	10.354 in (263.00 mm)	N/A	10.111 in (256.80 mm)	10.157 in (258.00 mm)
9.625	53.50	0.545	TenarisHydril MS XT/XC™	Standard	8.379	API Standard Drift	5.38 in (136.6 mm)	1.92 in (48.6 mm)	8.524 in (216.50 mm)	8.546 in (217.08 mm)	9.625 in (244.48 mm)	9.721 in (246.90 mm)	5.38 in (136.6 mm)	2.03 in (51.6 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	8.525 in (216.52 mm)	8.548 in (217.12 mm)	10.597 in (269.16 mm)	10.655 in (270.64 mm)	10.438 in (265.10 mm)	10.476 in (266.10 mm)	N/A	10.111 in (256.80 mm)	10.157 in (258.00 mm)
9.625	53.50	0.545	TenarisHydril MS XT/XC™	Standard	8.500	Alternative API Drift	5.38 in (136.6 mm)	1.92 in (48.6 mm)	8.524 in (216.50 mm)	8.546 in (217.08 mm)	9.625 in (244.48 mm)	9.721 in (246.90 mm)	5.38 in (136.6 mm)	2.03 in (51.6 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	8.535 in (216.78 mm)	8.548 in (217.12 mm)	10.597 in (269.16 mm)	10.655 in (270.64 mm)	10.438 in (265.10 mm)	10.476 in (266.10 mm)	N/A	10.111 in (256.80 mm)	10.157 in (258.00 mm)
9.625	58.40	0.595	TenarisHydril MS XT/XC™	Standard	8.279	API Standard Drift	5.38 in (136.6 mm)	1.92 in (48.6 mm)	8.424 in (213.96 mm)	8.446 in (214.54 mm)	9.625 in (244.48 mm)	9.721 in (246.90 mm)	5.38 in (136.6 mm)	2.03 in (51.6 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	8.449 in (214.58 mm)	8.471 in (215.18 mm)	10.597 in (269.16 mm)	10.655 in (270.64 mm)	10.516 in (267.10 mm)	10.555 in (268.10 mm)	N/A	10.111 in (256.80 mm)	10.157 in (258.00 mm)
9.625	58.40	0.595	TenarisHydril MS XT/XC™	Standard	8.375	Alternative API Drift	5.38 in (136.6 mm)	1.92 in (48.6 mm)	8.424 in (213.96 mm)	8.446 in (214.54 mm)	9.625 in (244.48 mm)	9.721 in (246.90 mm)	5.38 in (136.6 mm)	2.03 in (51.6 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	8.449 in (214.58 mm)	8.471 in (215.18 mm)	10.597 in (269.16 mm)	10.655 in (270.64 mm)	10.516 in (267.10 mm)	10.555 in (268			

TenarisHydril MS XT/XC™ Blanking Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, recopied, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections B.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request therefore. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyrighted 2019 as an unpublished work. ALL RIGHTS RESERVED.

SIZE (IN)	WEIGHT (LB/FT)	WALL (IN)	CONNECTION				PIN						BOX												
			PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH	RECUT LENGTH	INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH	RECUT LENGTH	COUPLING LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER - REGULAR		OUTSIDE DIAMETER - MATCHED STRENGTH		OUTSIDE DIAMETER - SPECIAL CLEARANCE		
									MIN	MAX	MIN	MAX			MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN
9.875	67.30	0.668	TenarisHydril MS XT/XC™	Standard	8.383	API Standard Drift	5.38 in (136.6 mm)	1.92 in (48.6 mm)	8.528 in (216.60 mm)	8.550 in (217.18 mm)	9.875 in (250.84 mm)	9.974 in (253.32 mm)	5.38 in (136.6 mm)	2.03 in (51.6 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	8.526 in (216.56 mm)	8.549 in (217.16 mm)	10.955 in (278.26 mm)	11.013 in (279.74 mm)	10.886 in (276.50 mm)	10.925 in (277.50 mm)	N/A	N/A	N/A
9.875	67.30	0.668	TenarisHydril MS XT/XC™	Standard	8.500	Special Drift	5.38 in (136.6 mm)	1.92 in (48.6 mm)	8.528 in (216.60 mm)	8.550 in (217.18 mm)	9.875 in (250.84 mm)	9.974 in (253.32 mm)	5.38 in (136.6 mm)	2.03 in (51.6 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	8.549 in (217.16 mm)	8.526 in (216.56 mm)	10.955 in (278.26 mm)	11.013 in (279.74 mm)	10.886 in (276.50 mm)	10.925 in (277.50 mm)	N/A	N/A	N/A
9.875	68.80	0.700	TenarisHydril MS XT/XC™	Standard	8.319	API Standard Drift	5.38 in (136.6 mm)	1.92 in (48.6 mm)	8.464 in (214.98 mm)	8.487 in (215.56 mm)	9.875 in (250.84 mm)	9.974 in (253.32 mm)	5.38 in (136.6 mm)	2.03 in (51.6 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	8.463 in (214.94 mm)	8.485 in (215.54 mm)	10.955 in (278.26 mm)	11.013 in (279.74 mm)	10.934 in (277.70 mm)	10.972 in (278.70 mm)	N/A	N/A	N/A
9.875	68.80	0.700	TenarisHydril MS XT/XC™	Standard	8.375	Special Drift	5.38 in (136.6 mm)	1.92 in (48.6 mm)	8.464 in (214.98 mm)	8.487 in (215.56 mm)	9.875 in (250.84 mm)	9.974 in (253.32 mm)	5.38 in (136.6 mm)	2.03 in (51.6 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	8.485 in (214.94 mm)	8.485 in (215.54 mm)	10.955 in (278.26 mm)	11.013 in (279.74 mm)	10.934 in (277.70 mm)	10.972 in (278.70 mm)	N/A	N/A	N/A
9.875	70.40	0.707	TenarisHydril MS XT/XC™	Standard	8.305	API Standard Drift	5.38 in (136.6 mm)	1.92 in (48.6 mm)	8.450 in (214.62 mm)	8.472 in (215.20 mm)	9.875 in (250.84 mm)	9.974 in (253.32 mm)	5.38 in (136.6 mm)	2.03 in (51.6 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	8.449 in (214.58 mm)	8.471 in (215.18 mm)	10.955 in (278.26 mm)	11.013 in (279.74 mm)	10.945 in (278.00 mm)	10.984 in (279.00 mm)	N/A	N/A	N/A
9.875	72.10	0.725	TenarisHydril MS XT/XC™	Standard	8.269	API Standard Drift	5.38 in (136.6 mm)	1.92 in (48.6 mm)	8.414 in (213.70 mm)	8.437 in (214.30 mm)	9.875 in (250.84 mm)	9.974 in (253.32 mm)	5.38 in (136.6 mm)	2.03 in (51.6 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	8.412 in (213.66 mm)	8.435 in (214.26 mm)	10.955 in (278.26 mm)	11.013 in (279.74 mm)	10.973 in (278.70 mm)	11.011 in (279.70 mm)	N/A	N/A	N/A
9.875	72.10	0.725	TenarisHydril MS XT/XC™	Standard	8.375	Special Drift	5.38 in (136.6 mm)	1.92 in (48.6 mm)	8.414 in (213.70 mm)	8.437 in (214.30 mm)	9.875 in (250.84 mm)	9.974 in (253.32 mm)	5.38 in (136.6 mm)	2.03 in (51.6 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	8.412 in (213.66 mm)	8.435 in (214.26 mm)	10.955 in (278.26 mm)	11.013 in (279.74 mm)	10.973 in (278.70 mm)	11.011 in (279.70 mm)	N/A	N/A	N/A
10.750	40.50	0.350	TenarisHydril MS XT/XC™	Standard	9.894	API Standard Drift	5.38 in (136.6 mm)	1.92 in (48.6 mm)	10.034 in (254.84 mm)	10.056 in (255.44 mm)	10.750 in (273.06 mm)	10.858 in (275.78 mm)	5.38 in (136.6 mm)	2.03 in (51.6 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	9.942 in (252.52 mm)	9.964 in (253.10 mm)	11.719 in (297.66 mm)	11.777 in (299.14 mm)	11.252 in (285.80 mm)	11.291 in (286.80 mm)	N/A	11.237 in (285.40 mm)	11.283 in (286.60 mm)
10.750	45.50	0.400	TenarisHydril MS XT/XC™	Standard	9.794	API Standard Drift	5.38 in (136.6 mm)	1.92 in (48.6 mm)	9.939 in (252.44 mm)	9.961 in (253.02 mm)	10.750 in (273.06 mm)	10.858 in (275.78 mm)	5.38 in (136.6 mm)	2.03 in (51.6 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	9.862 in (250.48 mm)	9.884 in (251.06 mm)	11.719 in (297.66 mm)	11.777 in (299.14 mm)	11.323 in (287.60 mm)	11.362 in (288.60 mm)	N/A	11.237 in (285.40 mm)	11.283 in (286.60 mm)
10.750	45.50	0.400	TenarisHydril MS XT/XC™	Standard	9.875	Alternative API Drift	5.38 in (136.6 mm)	1.92 in (48.6 mm)	9.939 in (252.44 mm)	9.961 in (253.02 mm)	10.750 in (273.06 mm)	10.858 in (275.78 mm)	5.38 in (136.6 mm)	2.03 in (51.6 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	9.862 in (250.48 mm)	9.884 in (251.06 mm)	11.719 in (297.66 mm)	11.777 in (299.14 mm)	11.323 in (287.60 mm)	11.362 in (288.60 mm)	N/A	11.237 in (285.40 mm)	11.283 in (286.60 mm)
10.750	51.00	0.450	TenarisHydril MS XT/XC™	Standard	9.694	API Standard Drift	5.38 in (136.6 mm)	1.92 in (48.6 mm)	9.839 in (249.90 mm)	9.861 in (250.48 mm)	10.750 in (273.06 mm)	10.858 in (275.78 mm)	5.38 in (136.6 mm)	2.03 in (51.6 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	9.781 in (248.44 mm)	9.804 in (249.02 mm)	11.719 in (297.66 mm)	11.777 in (299.14 mm)	11.410 in (289.80 mm)	11.448 in (290.80 mm)	N/A	11.237 in (285.40 mm)	11.283 in (286.60 mm)
10.750	55.50	0.495	TenarisHydril MS XT/XC™	Standard	9.604	API Standard Drift	5.38 in (136.6 mm)	1.92 in (48.6 mm)	9.749 in (247.60 mm)	9.771 in (248.20 mm)	10.750 in (273.06 mm)	10.858 in (275.78 mm)	5.38 in (136.6 mm)	2.03 in (51.6 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	9.751 in (247.66 mm)	9.774 in (248.26 mm)	11.719 in (297.66 mm)	11.777 in (299.14 mm)	11.485 in (291.70 mm)	11.523 in (292.70 mm)	N/A	11.237 in (285.40 mm)	11.283 in (286.60 mm)
10.750	55.50	0.495	TenarisHydril MS XT/XC™	Standard	9.625	Alternative API Drift	5.38 in (136.6 mm)	1.92 in (48.6 mm)	9.749 in (247.60 mm)	9.771 in (248.20 mm)	10.750 in (273.06 mm)	10.858 in (275.78 mm)	5.38 in (136.6 mm)	2.03 in (51.6 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	9.751 in (247.66 mm)	9.774 in (248.26 mm)	11.719 in (297.66 mm)	11.777 in (299.14 mm)	11.485 in (291.70 mm)	11.523 in (292.70 mm)	N/A	11.237 in (285.40 mm)	11.283 in (286.60 mm)
10.750	60.70	0.545	TenarisHydril MS XT/XC™	Standard	9.504	API Standard Drift	5.38 in (136.6 mm)	1.92 in (48.6 mm)	9.649 in (245.06 mm)	9.671 in (245.66 mm)	10.750 in (273.06 mm)	10.858 in (275.78 mm)	5.38 in (136.6 mm)	2.03 in (51.6 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	9.651 in (245.12 mm)	9.674 in (245.72 mm)	11.719 in (297.66 mm)	11.777 in (299.14 mm)	11.571 in (293.90 mm)	11.610 in (294.90 mm)	N/A	11.237 in (285.40 mm)	11.283 in (286.60 mm)
10.750	65.70	0.595	TenarisHydril MS XT/XC™	Standard	9.404	API Standard Drift	5.38 in (136.6 mm)	1.92 in (48.6 mm)	9.549 in (242.52 mm)	9.571 in (243.12 mm)	10.750 in (273.06 mm)	10.858 in (275.78 mm)	5.38 in (136.6 mm)	2.03 in (51.6 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	9.551 in (242.58 mm)	9.574 in (243.18 mm)	11.719 in (297.66 mm)	11.777 in (299.14 mm)	11.654 in (296.00 mm)	11.692 in (297.00 mm)	N/A	11.237 in (285.40 mm)	11.283 in (286.60 mm)
10.750	65.70	0.595	TenarisHydril MS XT/XC™	Standard	9.504	Special Drift	5.38 in (136.6 mm)	1.92 in (48.6 mm)	9.549 in (242.52 mm)	9.571 in (243.12 mm)	10.750 in (273.06 mm)	10.858 in (275.78 mm)	5.38 in (136.6 mm)	2.03 in (51.6 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	9.551 in (242.58 mm)	9.574 in (243.18 mm)	11.719 in (297.66 mm)	11.777 in (299.14 mm)	11.654 in (296.00 mm)	11.692 in (297.00 mm)	N/A	11.237 in (285.40 mm)	11.283 in (286.60 mm)
11.750	47.00	0.375	TenarisHydril MS XT/XC™	Standard	10.844	API Standard Drift	5.38 in (136.6 mm)	1.92 in (48.6 mm)	10.981 in (278.90 mm)	11.019 in (279.90 mm)	11.750 in (298.46 mm)	11.868 in (301.44 mm)	5.38 in (136.6 mm)	2.03 in (51.6 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	10.903 in (276.94 mm)	10.942 in (277.92 mm)	12.723 in (323.16 mm)	12.781 in (324.64 mm)	12.284 in (312.00 mm)	12.322 in (313.00 mm)	N/A	N/A	N/A
11.750	54.00	0.435	TenarisHydril MS XT/XC™	Standard	10.724	API Standard Drift	5.38 in (136.6 mm)	1.92 in (48.6 mm)	10.861 in (275.86 mm)	10.899 in (276.84 mm)	11.750 in (298.46 mm)	11.868 in (301.44 mm)	5.38 in (136.6 mm)	2.03 in (51.6 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	10.783 in (273.88 mm)	10.822 in (274.88 mm)	12.723 in (323.16 mm)	12.781 in (324.64 mm)	12.394 in (314.80 mm)	12.433 in (315.80 mm)	N/A	N/A	N/A
11.750	60.00	0.489	TenarisHydril MS XT/XC™	Standard	10.625	API Standard Drift	5.38 in (136.6 mm)	1.92 in (48.6 mm)	10.753 in (273.12 mm)	10.791 in (274.10 mm)	11.750 in (298.46 mm)	11.868 in (301.44 mm)	5.38 in (136.6 mm)	2.03 in (51.6 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	10.694 in (271.62 mm)	10.732 in (272.60 mm)	12.723 in (323.16 mm)	12.781 in (324.64 mm)	12.485 in (317.10 mm)	12.523 in (318.10 mm)	N/A	N/A	N/A
11.750	65.00	0.534	TenarisHydril MS XT/XC™	Standard	10.526	API Standard Drift	5.38 in (136.6 mm)	1.92 in (48.6 mm)	10.663 in (270.82 mm)	10.701 in (271.82 mm)	11.750 in (298.46 mm)	11.868 in (301.44 mm)	5.38 in (136.6 mm)	2.03 in (51.6 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	10.665 in (270.88 mm)	10.703 in (271.86 mm)	12.723 in (323.16 mm)	12.781 in (324.64 mm)	12.563 in (319.10 mm)	12.602 in (320.10 mm)	N/A	N/A	N/A
13.375	54.50	0.380	TenarisHydril MS XT/XC™	Standard	12.459	API Standard Drift	5.38 in (136.6 mm)	1.92 in (48.6 mm)	12.596 in (319.92 mm)	12.634 in (320.92 mm)	13.375 in (339.74 mm)	13.509 in (343.12 mm)	5.38 in (136.6 mm)	2.03 in (51.6 mm)	12.988 in (330.00 mm)	12.998 in (331.00 mm)	12.499 in (317.46 mm)	12.499 in (318.46 mm)	14.403 in (364.36 mm)	14.403 in (365.84 mm)	14.008 in (355.80 mm)	14.047 in (356.80 mm)	N/A	N/A	N/A
13.375	61.00	0.430	TenarisHydril MS XT/XC™	Standard	12.359	API Standard Drift	5.38 in (136.6 mm)	1.92 in (48.6 mm)	12.496 in (317.38 mm)	12.534 in (318.38 mm)	13.375 in (339.74 mm)	13.509 in (343.12 mm)	5.38 in (136.6 mm)	2.03 in (51.6 mm)	12.988 in (330.00 mm)	12.998 in (331.00 mm)	12.419 in (315.42 mm)	12.457 in (316.42 mm)	14.345 in (364.36 mm)	14.345 in (365.84 mm)	14.008 in (355.80 mm)	14.047 in (356.80 mm)	N/A	N/A	N/A
13.375	68.00	0.480	TenarisHydril MS XT/XC™	Standard	12.259	API Standard Drift	5.38 in (136.6 mm)	1.92 in (48.6 mm)	12.396 in (314.84 mm)	12.434 in (315.84 mm)	13.375 in (339.74 mm)	13.509 in (343.12 mm)	5.38 in (136.6 mm)	2.03 in (51.6 mm)	12.988 in (330.00 mm)	12.998 in (331.00 mm)	12.377 in (313.38 mm)	12.377 in (314.38 mm)	14.345 in (364.36 mm)	14.345 in (365.84 mm)	14.095 in (358.00 mm)	14.133 in (359.00 mm)	N/A	N/A	N/A
13.375	72.00	0.514	TenarisHydril MS XT/XC™	Standard	12.191	API Standard Drift	5.38 in (136.6 mm)	1.92 in (48.6 mm)	12.328 in (313.12 mm)	12.366 in (314.10 mm)	13.375 in (339.74 mm)	13.509 in (343.12 mm)	5.38 in (136.6 mm)	2.03 in (51.6 mm)	12.988 in (330.00 mm)	12.998 in (331.00 mm)	12.326 in (313.08 mm)	12.365 in (314.08 mm)	14.345 in (364.36 mm)	14.345 in (365.84 mm)	14.154 in (359.50 mm)	14.192 in (360.50 mm)	N/A	N/A	N/A
13.375	72.00	0.514	TenarisHydril MS XT/XC™	Standard	12.250	Alternative API Drift	5.38 in (136.6 mm)	1.92 in (48.6 mm)	12.328 in (313.12 mm)	12.366 in (314.10 mm)	13.375 in (339.74 mm)	13.509 in (343.12 mm)	5.38 in (136.6 mm)	2.03 in (51.6 mm)	12.988 in (330.00 mm)	12.998 in (331.00 mm)	12.326 in (313.08 mm)	12.365 in (314.08 mm)	14.345 in (364.36 mm)	14.345 in (365.84 mm)	14.154 in (359.50 mm)	14.192 in (360.50 mm)	N/A	N/A	N/A
13.625	88.20	0.625	TenarisHydril MS XT/XC™	Standard	12.188	API Standard Drift	5.38 in (136.6 mm)	1.92 in (48.6 mm)	12.356 in (313.84 mm)	12.394 in (314.82 mm)	13.625 in (346.08 mm)	13.761 in (349.52 mm)	5.38 in (136.6 mm)	2.03 in (51.6 mm)	12.988 in (330.00 mm)	12.998 in (331.00 mm)	12.356 in (313.84 mm)	12.395 in (314.84 mm)	14.597 in (372.24 mm)	14.655 in (373.24 mm)	14.599 in (370.80 mm)	14.637 in (371.80 mm)	N/A	N/A	N/A
13.625	88.20	0.625	TenarisHydril MS XT/XC™	Standard	12.250	Special Drift	5.38 in (136.6 mm)	1.92 in (48.6 mm)	12.356 in (313.84 mm)	12.394 in (314.82 mm)	13.625 in (346.08 mm)	13.761 in (349.52 mm)	5.38 in (136.6 mm)	2.03 in (51.6 mm)	12.988 in (330.00 mm)	12.998 in (331.00 mm)	12.356 in (313.84 mm)	12.395 in (314.84 mm)	14.597 in (372.24 mm)	14.655 in (373.24 mm)	14.599 in (370.80 mm)	14.637 in (371.80 mm)	N/A	N/A	N/A

Dimensions provided do not include length required for tongs for making up assemblies. Please take this into consideration when designing and machining your accessory.

BLANK OD and ID: The nominal blank ODs and IDs in the Pin Diameters and Box Diameters columns are finished product dimensions. When this minimum material is supplied, the blank OD and the blank ID must be true to each other within 0.010" TIR (Total Indicator Reading).

BLANK Min Length includes 0.02" (0.5mm) extra material for facing.

Contact Tenaris Manufacturing Services at blankingdimensions@tenaris.com for details.

These Blanking Dimensions are NOT applicable For Handling & lifting plug, HydroTest Caps & HydroTest Plugs.

N/A: Not Applicable