

TenarisHydril Blue® Max TenarisHydril Blue® Max Dopeless® Blanking Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, recopied, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections S.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request therefore. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyrighted 2021 as an unpublished work. ALL RIGHTS RESERVED.

CONNECTION						PIN						BOX														
SIZE (IN)	WEIGHT (LB/FT)	WALL (IN)	PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH	RECUT LENGTH	INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH	RECUT LENGTH	COUPLING LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER - REGULAR		OUTSIDE DIAMETER - SPECIAL CLEARANCE #1			OUTSIDE DIAMETER - SPECIAL CLEARANCE #2		
							MIN	MIN	MIN	MAX	MIN	MAX	MIN	MIN	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	EFFICIEN CY	MIN	MAX	EFFICIEN CY
7.000	35.00	0.498	TenarisHydril Blue® Max	Standard	5.879	Standard API Drift	6.13 in (155.6 mm)	1.86 in (47.2 mm)	5.944 in (150.98 mm)	5.967 in (151.56 mm)	7.000 in (177.80 mm)	7.070 in (179.56 mm)	6.13 in (155.6 mm)	2.11 in (53.6 mm)	12.418 in (315.40 mm)	12.614 in (320.40 mm)	5.913 in (150.18 mm)	5.935 in (150.76 mm)	7.825 in (198.76 mm)	7.864 in (199.74 mm)	85.0	7.689 in (195.30 mm)	7.728 in (196.30 mm)	N/A	N/A	N/A
7.000	35.00	0.498	TenarisHydril Blue® Max	ExxonMobil CTP ALL	5.879	Standard API Drift	6.13 in (155.6 mm)	1.86 in (47.2 mm)	5.944 in (150.98 mm)	5.967 in (151.56 mm)	7.000 in (177.80 mm)	7.070 in (179.56 mm)	6.13 in (155.6 mm)	2.11 in (53.6 mm)	12.418 in (315.40 mm)	12.614 in (320.40 mm)	5.913 in (150.18 mm)	5.935 in (150.76 mm)	7.825 in (198.76 mm)	7.864 in (199.74 mm)	85.0	7.689 in (195.30 mm)	7.728 in (196.30 mm)	N/A	N/A	N/A
7.000	38.00	0.540	TenarisHydril Blue® Max	Standard	5.795	Standard API Drift	6.13 in (155.6 mm)	1.86 in (47.2 mm)	5.860 in (148.84 mm)	5.883 in (149.44 mm)	7.000 in (177.80 mm)	7.070 in (179.56 mm)	6.13 in (155.6 mm)	2.11 in (53.6 mm)	12.418 in (315.40 mm)	12.614 in (320.40 mm)	5.829 in (148.04 mm)	5.851 in (148.64 mm)	7.914 in (201.00 mm)	7.952 in (202.00 mm)	85.0	7.768 in (197.30 mm)	7.807 in (198.30 mm)	N/A	N/A	N/A
7.000	41.00	0.590	TenarisHydril Blue® Max	Standard	5.695	Standard API Drift	6.13 in (155.6 mm)	1.86 in (47.2 mm)	5.760 in (146.30 mm)	5.783 in (146.88 mm)	7.000 in (177.80 mm)	7.070 in (179.56 mm)	6.13 in (155.6 mm)	2.11 in (53.6 mm)	12.418 in (315.40 mm)	12.614 in (320.40 mm)	5.728 in (145.50 mm)	5.751 in (146.08 mm)	7.977 in (202.60 mm)	8.015 in (203.60 mm)	85.0	7.823 in (198.70 mm)	7.862 in (199.70 mm)	N/A	N/A	N/A
7.750	38.75	0.500	TenarisHydril Blue® Max	Standard	6.625	Standard API Drift	6.61 in (168.0 mm)	1.86 in (47.2 mm)	6.690 in (169.92 mm)	6.713 in (170.52 mm)	7.750 in (196.86 mm)	7.828 in (198.82 mm)	6.61 in (168.0 mm)	2.12 in (53.8 mm)	13.394 in (340.20 mm)	13.590 in (345.20 mm)	6.659 in (169.12 mm)	6.681 in (169.72 mm)	8.544 in (217.00 mm)	8.582 in (218.00 mm)	85.0	8.406 in (213.50 mm)	8.444 in (214.50 mm)	N/A	N/A	N/A
7.750	46.10	0.595	TenarisHydril Blue® Max	Standard	6.435	Standard API Drift	5.92 in (150.2 mm)	1.86 in (47.2 mm)	6.549 in (166.34 mm)	6.572 in (166.92 mm)	7.750 in (196.86 mm)	7.828 in (198.82 mm)	5.92 in (150.2 mm)	2.11 in (53.6 mm)	12.004 in (304.90 mm)	12.200 in (309.90 mm)	6.534 in (165.96 mm)	6.557 in (166.54 mm)	8.804 in (223.60 mm)	8.842 in (224.60 mm)	85.0	8.638 in (219.40 mm)	8.677 in (220.40 mm)	N/A	N/A	N/A
7.750	46.10	0.595	TenarisHydril Blue® Max	Standard	6.500	Special Drift	5.92 in (150.2 mm)	1.86 in (47.2 mm)	6.549 in (166.34 mm)	6.572 in (166.92 mm)	7.750 in (196.86 mm)	7.828 in (198.82 mm)	5.92 in (150.2 mm)	2.11 in (53.6 mm)	12.004 in (304.90 mm)	12.200 in (309.90 mm)	6.534 in (165.96 mm)	6.557 in (166.54 mm)	8.804 in (223.60 mm)	8.842 in (224.60 mm)	85.0	8.638 in (219.40 mm)	8.677 in (220.40 mm)	N/A	N/A	N/A
8.125	54.60	0.679	TenarisHydril Blue® Max	Standard	6.642	Standard API Drift	6.18 in (156.8 mm)	1.86 in (47.2 mm)	6.718 in (170.62 mm)	6.740 in (171.22 mm)	8.125 in (206.38 mm)	8.206 in (208.42 mm)	6.18 in (156.8 mm)	2.08 in (53.0 mm)	12.520 in (318.00 mm)	12.716 in (323.00 mm)	6.684 in (169.76 mm)	6.707 in (170.36 mm)	9.245 in (234.80 mm)	9.283 in (235.80 mm)	85.0	9.063 in (230.20 mm)	9.102 in (231.20 mm)	N/A	N/A	N/A
8.125	54.60	0.679	TenarisHydril Blue® Max	Standard	6.650	Special Drift	6.18 in (156.8 mm)	1.86 in (47.2 mm)	6.718 in (170.62 mm)	6.740 in (171.22 mm)	8.125 in (206.38 mm)	8.206 in (208.42 mm)	6.18 in (156.8 mm)	2.08 in (53.0 mm)	12.520 in (318.00 mm)	12.716 in (323.00 mm)	6.684 in (169.76 mm)	6.707 in (170.36 mm)	9.245 in (234.80 mm)	9.283 in (235.80 mm)	85.0	9.063 in (230.20 mm)	9.102 in (231.20 mm)	N/A	N/A	N/A
9.625	53.50	0.545	TenarisHydril Blue® Max	Standard	8.379	Standard API Drift	5.73 in (145.6 mm)	1.86 in (47.2 mm)	8.524 in (216.50 mm)	8.547 in (217.10 mm)	9.625 in (244.48 mm)	9.721 in (246.90 mm)	5.73 in (145.6 mm)	2.09 in (53.2 mm)	11.638 in (295.60 mm)	11.834 in (300.60 mm)	8.534 in (216.76 mm)	8.557 in (217.34 mm)	10.638 in (270.20 mm)	10.677 in (271.20 mm)	85.0	10.481 in (266.20 mm)	10.519 in (267.20 mm)	N/A	N/A	N/A
9.625	53.50	0.545	TenarisHydril Blue® Max	Standard	8.500	Special Drift	5.73 in (145.6 mm)	1.86 in (47.2 mm)	8.530 in (216.66 mm)	8.553 in (217.24 mm)	9.625 in (244.48 mm)	9.721 in (246.90 mm)	5.73 in (145.6 mm)	2.09 in (53.2 mm)	11.638 in (295.60 mm)	11.834 in (300.60 mm)	8.534 in (216.76 mm)	8.557 in (217.34 mm)	10.638 in (270.20 mm)	10.677 in (271.20 mm)	85.0	10.481 in (266.20 mm)	10.519 in (267.20 mm)	N/A	N/A	N/A
9.875	62.80	0.625	TenarisHydril Blue® Max	Standard	8.469	Standard API Drift	6.68 in (169.6 mm)	1.86 in (47.2 mm)	8.573 in (217.76 mm)	8.596 in (218.34 mm)	9.875 in (250.84 mm)	9.974 in (253.32 mm)	6.68 in (169.6 mm)	2.08 in (52.8 mm)	13.528 in (343.60 mm)	13.724 in (348.60 mm)	8.534 in (216.76 mm)	8.557 in (217.34 mm)	11.085 in (279.00 mm)	11.023 in (280.00 mm)	85.0	10.804 in (274.40 mm)	10.842 in (275.40 mm)	N/A	N/A	N/A
9.875	62.80	0.625	TenarisHydril Blue® Max	Standard	8.500	Special Drift	6.68 in (169.6 mm)	1.86 in (47.2 mm)	8.573 in (217.76 mm)	8.596 in (218.34 mm)	9.875 in (250.84 mm)	9.974 in (253.32 mm)	6.68 in (169.6 mm)	2.08 in (52.8 mm)	13.528 in (343.60 mm)	13.724 in (348.60 mm)	8.534 in (216.76 mm)	8.557 in (217.34 mm)	11.085 in (279.00 mm)	11.023 in (280.00 mm)	85.0	10.804 in (274.40 mm)	10.842 in (275.40 mm)	N/A	N/A	N/A
9.875	66.90	0.668	TenarisHydril Blue® Max	Standard	8.383	Standard API Drift	6.68 in (169.6 mm)	1.86 in (47.2 mm)	8.528 in (216.60 mm)	8.550 in (217.18 mm)	9.875 in (250.84 mm)	9.974 in (253.32 mm)	6.68 in (169.6 mm)	2.08 in (52.8 mm)	13.528 in (343.60 mm)	13.724 in (348.60 mm)	8.534 in (216.76 mm)	8.557 in (217.34 mm)	11.060 in (280.90 mm)	11.098 in (281.90 mm)	85.0	10.871 in (276.10 mm)	10.909 in (277.10 mm)	N/A	N/A	N/A
9.875	66.90	0.668	TenarisHydril Blue® Max	Standard	8.500	Special Drift	6.68 in (169.6 mm)	1.86 in (47.2 mm)	8.530 in (216.66 mm)	8.553 in (217.24 mm)	9.875 in (250.84 mm)	9.974 in (253.32 mm)	6.68 in (169.6 mm)	2.08 in (52.8 mm)	13.528 in (343.60 mm)	13.724 in (348.60 mm)	8.534 in (216.76 mm)	8.557 in (217.34 mm)	11.060 in (280.90 mm)	11.098 in (281.90 mm)	85.0	10.871 in (276.10 mm)	10.909 in (277.10 mm)	N/A	N/A	N/A
9.875	68.80	0.700	TenarisHydril Blue® Max	Standard	8.319	Standard API Drift	7.14 in (181.4 mm)	1.86 in (47.2 mm)	8.464 in (214.98 mm)	8.487 in (215.56 mm)	9.875 in (250.84 mm)	9.974 in (253.32 mm)	7.14 in (181.4 mm)	2.12 in (54.0 mm)	14.445 in (366.90 mm)	14.641 in (371.90 mm)	8.534 in (216.76 mm)	8.557 in (217.34 mm)	11.178 in (283.90 mm)	11.216 in (284.90 mm)	85.0	10.985 in (279.00 mm)	11.023 in (280.00 mm)	N/A	N/A	N/A
9.875	68.80	0.700	TenarisHydril Blue® Max	Standard	8.500	Special Drift	7.14 in (181.4 mm)	1.86 in (47.2 mm)	8.562 in (217.46 mm)	8.584 in (218.04 mm)	9.875 in (250.84 mm)	9.974 in (253.32 mm)	7.14 in (181.4 mm)	2.12 in (54.0 mm)	14.445 in (366.90 mm)	14.641 in (371.90 mm)	8.534 in (216.76 mm)	8.557 in (217.34 mm)	11.178 in (283.90 mm)	11.216 in (284.90 mm)	85.0	10.985 in (279.00 mm)	11.023 in (280.00 mm)	N/A	N/A	N/A
10.000	67.70	0.678	TenarisHydril Blue® Max	Standard	8.488	Standard API Drift	7.53 in (191.2 mm)	1.86 in (47.2 mm)	8.562 in (217.46 mm)	8.584 in (218.04 mm)	10.000 in (254.00 mm)	10.100 in (256.54 mm)	7.53 in (191.2 mm)	2.12 in (54.0 mm)	15.229 in (386.80 mm)	15.425 in (391.80 mm)	8.534 in (216.76 mm)	8.557 in (217.34 mm)	11.142 in (283.00 mm)	11.181 in (284.00 mm)	85.0	10.953 in (278.20 mm)	10.992 in (279.20 mm)	N/A	N/A	N/A
10.000	67.70	0.678	TenarisHydril Blue® Max	Standard	8.500	Special Drift	7.53 in (191.2 mm)	1.86 in (47.2 mm)	8.562 in (217.46 mm)	8.584 in (218.04 mm)	10.000 in (254.00 mm)	10.100 in (256.54 mm)	7.53 in (191.2 mm)	2.12 in (54.0 mm)	15.229 in (386.80 mm)	15.425 in (391.80 mm)	8.534 in (216.76 mm)	8.557 in (217.34 mm)	11.142 in (283.00 mm)	11.181 in (284.00 mm)	85.0	10.953 in (278.20 mm)	10.992 in (279.20 mm)	N/A	N/A	N/A
10.000	68.90	0.688	TenarisHydril Blue® Max	Standard	8.468	Standard API Drift	7.53 in (191.2 mm)	1.86 in (47.2 mm)	8.562 in (217.46 mm)	8.584 in (218.04 mm)	10.000 in (254.00 mm)	10.100 in (256.54 mm)	7.53 in (191.2 mm)	2.12 in (54.0 mm)	15.229 in (386.80 mm)	15.425 in (391.80 mm)	8.534 in (216.76 mm)	8.557 in (217.34 mm)	11.142 in (283.00 mm)	11.181 in (284.00 mm)	85.0	10.953 in (278.20 mm)	10.992 in (279.20 mm)	N/A	N/A	N/A
10.000	68.90	0.688	TenarisHydril Blue® Max	Standard	8.500	Special Drift	7.53 in (191.2 mm)	1.86 in (47.2 mm)	8.562 in (217.46 mm)	8.584 in (218.04 mm)	10.000 in (254.00 mm)	10.100 in (256.54 mm)	7.53 in (191.2 mm)	2.12 in (54.0 mm)	15.229 in (386.80 mm)	15.425 in (391.80 mm)	8.534 in (216.76 mm)	8.557 in (217.34 mm)	11.142 in (283.00 mm)	11.181 in (284.00 mm)	85.0	10.953 in (278.20 mm)	10.992 in (279.20 mm)	N/A	N/A	N/A
10.000	73.90	0.732	TenarisHydril Blue® Max	Standard	8.380	Standard API Drift	7.53 in (191.2 mm)	1.86 in (47.2 mm)	8.525 in (216.52 mm)	8.548 in (217.12 mm)	10.000 in (254.00 mm)	10.100 in (256.54 mm)	7.53 in (191.2 mm)	2.12 in (54.0 mm)	15.229 in (386.80 mm)	15.425 in (391.80 mm)	8.534 in (216.76 mm)	8.557 in (217.34 mm)	11.209 in (284.70 mm)	11.248 in (285.70 mm)	85.0	11.012 in (279.70 mm)	11.051 in (280.70 mm)	N/A	N/A	N/A
10.000	73.90	0.732	TenarisHydril Blue® Max	Standard	8.500	Special Drift	7.53 in (191.2 mm)	1.86 in (47.2 mm)	8.562 in (217.46 mm)	8.584 in (218.04 mm)	10.000 in (254.00 mm)	10.130 in (257.30 mm)	7.53 in (191.2 mm)	2.12 in (54.0 mm)	15.229 in (386.80 mm)	15.425 in (391.80 mm)	8.534 in (216.76 mm)	8.557 in (217.34 mm)	11.209 in (284.70 mm)	11.248 in (285.70 mm)	85.0	11.012 in (279.70 mm)	11.051 in (280.70 mm)	N/A	N/A	N/A
10.125	79.30	0.795	TenarisHydril Blue® Max	Standard	8.379	Standard API Drift	7.12 in (181.0 mm)	1.86 in (47.2 mm)	8.524 in (216.50 mm)	8.547 in (217.10 mm)	10.125 in (257.18 mm)	10.226 in (259.74 mm)	7.12 in (181.0 mm)	2.08 in (52.8 mm)	14.414 in (366.10 mm)	14.610 in (371.10 mm)	8.534 in (216.76 mm)	8.557 in (217.34 mm)	11.556 in (293.50 mm)	11.594 in (294.50 mm)	85.0	11.335 in (287.90 mm)	11.374 in (288.90 mm)	N/A	N/A	N/A
10.125	79.30	0.795	TenarisHydril Blue® Max	SC80	8.379	Standard API Drift	7.12 in (181.0 mm)	1.86 in (47.2 mm)	8.524 in (216.50 mm)	8.547 in (217.10 mm)	10.125 in (257.18 mm)	10.226 in (259.74 mm)	7.12 in (181.0 mm)	2.08 in (52.8 mm)	14.414 in (366.10 mm)	14.610 in (371.10 mm)	8.534 in (216.76 mm)	8.557 in (217.34 mm)	N/A	N/A	80.0	11.256 in (28				

TenarisHydril Blue® Max TenarisHydril Blue® Max Dopeless® Blanking Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, recopied, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections S.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request therefore. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is accepted by acceptance of this document. Copyrighted 2021 as an unpublished work. ALL RIGHTS RESERVED.

CONNECTION							PIN								BOX													
SIZE (IN)	WEIGHT (LB/FT)	WALL (IN)	PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH		RECUT LENGTH		COUPLING LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER - REGULAR		OUTSIDE DIAMETER - SPECIAL CLEARANCE #1			OUTSIDE DIAMETER - SPECIAL CLEARANCE #2		
							MIN	MIN	MIN	MAX	MIN	MAX	MIN	MIN	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	EFFICIEN CY	MIN	MAX	EFFICIEN CY	MIN	MAX
13.375	72.00	0.514	TenarisHydril Blue® Max	Standard	12.191	Standard API Drift	6.77 in (172.0 mm)	1.86 in (47.2 mm)	12.336 in (313.32 mm)	12.358 in (313.90 mm)	13.375 in (339.74 mm)	13.509 in (343.12 mm)	6.77 in (172.0 mm)	2.15 in (54.6 mm)	13.713 in (348.30 mm)	13.909 in (353.30 mm)	12.284 in (312.00 mm)	12.307 in (312.60 mm)	14.292 in (363.00 mm)	14.330 in (364.00 mm)	85.0	14.142 in (359.20 mm)	14.181 in (360.20 mm)	N/A	N/A	N/A		
13.375	72.00	0.514	TenarisHydril Blue® Max	Standard	12.250	Alternative API Drift	6.77 in (172.0 mm)	1.86 in (47.2 mm)	12.336 in (313.32 mm)	12.358 in (313.90 mm)	13.375 in (339.74 mm)	13.509 in (343.12 mm)	6.77 in (172.0 mm)	2.15 in (54.6 mm)	13.713 in (348.30 mm)	13.909 in (353.30 mm)	12.284 in (312.00 mm)	12.307 in (312.60 mm)	14.292 in (363.00 mm)	14.330 in (364.00 mm)	85.0	14.142 in (359.20 mm)	14.181 in (360.20 mm)	N/A	N/A	N/A		
13.625	88.20	0.625	TenarisHydril Blue® Max	Standard	12.188	Standard API Drift	7.45 in (189.2 mm)	1.86 in (47.2 mm)	12.319 in (312.90 mm)	12.342 in (313.50 mm)	13.625 in (346.08 mm)	13.761 in (349.52 mm)	7.45 in (189.2 mm)	2.15 in (54.6 mm)	15.075 in (382.90 mm)	15.271 in (387.90 mm)	12.284 in (312.00 mm)	12.307 in (312.60 mm)	14.843 in (377.00 mm)	14.881 in (378.00 mm)	85.0	14.642 in (371.90 mm)	14.681 in (372.90 mm)	N/A	N/A	N/A		
13.625	88.20	0.625	TenarisHydril Blue® Max	SC100	12.188	Standard API Drift	7.45 in (189.2 mm)	1.86 in (47.2 mm)	12.319 in (312.90 mm)	12.342 in (313.50 mm)	13.625 in (346.08 mm)	13.761 in (349.52 mm)	7.45 in (189.2 mm)	2.15 in (54.6 mm)	15.075 in (382.90 mm)	15.271 in (387.90 mm)	12.284 in (312.00 mm)	12.307 in (312.60 mm)	N/A	N/A	100.0	14.749 in (374.60 mm)	14.787 in (375.60 mm)	N/A	N/A	N/A		
13.625	88.20	0.625	TenarisHydril Blue® Max	Standard	12.250	Special Drift	7.45 in (189.2 mm)	1.86 in (47.2 mm)	12.319 in (312.90 mm)	12.342 in (313.50 mm)	13.625 in (346.08 mm)	13.761 in (349.52 mm)	7.45 in (189.2 mm)	2.15 in (54.6 mm)	15.075 in (382.90 mm)	15.271 in (387.90 mm)	12.284 in (312.00 mm)	12.307 in (312.60 mm)	14.843 in (377.00 mm)	14.881 in (378.00 mm)	85.0	14.642 in (371.90 mm)	14.681 in (372.90 mm)	N/A	N/A	N/A		
13.625	88.20	0.625	TenarisHydril Blue® Max	SC100	12.250	Special Drift	7.45 in (189.2 mm)	1.86 in (47.2 mm)	12.319 in (312.90 mm)	12.342 in (313.50 mm)	13.625 in (346.08 mm)	13.761 in (349.52 mm)	7.45 in (189.2 mm)	2.15 in (54.6 mm)	15.075 in (382.90 mm)	15.271 in (387.90 mm)	12.284 in (312.00 mm)	12.307 in (312.60 mm)	N/A	N/A	100.0	14.749 in (374.60 mm)	14.787 in (375.60 mm)	N/A	N/A	N/A		
14.000	82.50	0.562	TenarisHydril Blue® Max	Standard	12.689	Standard API Drift	6.73 in (170.8 mm)	1.86 in (47.2 mm)	12.865 in (326.76 mm)	12.888 in (327.36 mm)	14.000 in (355.60 mm)	14.140 in (359.14 mm)	6.73 in (170.8 mm)	2.15 in (54.6 mm)	13.619 in (345.90 mm)	13.814 in (350.90 mm)	12.844 in (326.22 mm)	12.866 in (326.82 mm)	15.111 in (383.80 mm)	15.149 in (384.80 mm)	85.0	14.938 in (379.40 mm)	14.976 in (380.40 mm)	N/A	N/A	N/A		
14.000	82.50	0.562	TenarisHydril Blue® Max	Standard	12.810	Special Drift	6.73 in (170.8 mm)	1.86 in (47.2 mm)	12.865 in (326.76 mm)	12.888 in (327.36 mm)	14.000 in (355.60 mm)	14.140 in (359.14 mm)	6.73 in (170.8 mm)	2.15 in (54.6 mm)	13.619 in (345.90 mm)	13.814 in (350.90 mm)	12.844 in (326.22 mm)	12.866 in (326.82 mm)	15.111 in (383.80 mm)	15.149 in (384.80 mm)	85.0	14.938 in (379.40 mm)	14.976 in (380.40 mm)	N/A	N/A	N/A		
14.000	82.50	0.562	TenarisHydril Blue® Max	ExxonMobil CTP ALL	12.810	Special Drift	6.73 in (170.8 mm)	1.86 in (47.2 mm)	12.865 in (326.76 mm)	12.888 in (327.36 mm)	14.000 in (355.60 mm)	14.140 in (359.14 mm)	6.73 in (170.8 mm)	2.15 in (54.6 mm)	13.619 in (345.90 mm)	13.814 in (350.90 mm)	12.844 in (326.22 mm)	12.866 in (326.82 mm)	15.111 in (383.80 mm)	15.149 in (384.80 mm)	85.0	14.938 in (379.40 mm)	14.976 in (380.40 mm)	N/A	N/A	N/A		
14.000	93.00	0.650	TenarisHydril Blue® Max	Standard	12.512	Standard API Drift	7.88 in (200.2 mm)	1.86 in (47.2 mm)	12.497 in (319.90 mm)	12.519 in (320.50 mm)	14.000 in (355.60 mm)	14.140 in (359.14 mm)	7.88 in (200.2 mm)	2.15 in (54.6 mm)	15.934 in (404.70 mm)	16.129 in (409.70 mm)	12.447 in (316.14 mm)	12.470 in (316.74 mm)	15.252 in (387.40 mm)	15.330 in (389.40 mm)	85.0	15.044 in (382.10 mm)	15.082 in (383.10 mm)	N/A	N/A	N/A		
14.000	100.00	0.700	TenarisHydril Blue® Max	Standard	12.413	Standard API Drift	7.88 in (200.2 mm)	1.86 in (47.2 mm)	12.497 in (319.90 mm)	12.519 in (320.50 mm)	14.000 in (355.60 mm)	14.140 in (359.14 mm)	7.88 in (200.2 mm)	2.15 in (54.6 mm)	15.934 in (404.70 mm)	16.129 in (409.70 mm)	12.447 in (316.14 mm)	12.470 in (316.74 mm)	15.252 in (387.40 mm)	15.330 in (389.40 mm)	85.0	15.044 in (382.10 mm)	15.082 in (383.10 mm)	N/A	N/A	N/A		
14.000	110.00	0.772	TenarisHydril Blue® Max	Standard	12.269	Standard API Drift	7.88 in (200.2 mm)	1.86 in (47.2 mm)	12.445 in (316.08 mm)	12.467 in (316.68 mm)	14.000 in (355.60 mm)	14.140 in (359.14 mm)	7.88 in (200.2 mm)	2.15 in (54.6 mm)	15.934 in (404.70 mm)	16.129 in (409.70 mm)	12.406 in (315.12 mm)	12.429 in (315.70 mm)	15.351 in (389.90 mm)	15.429 in (391.90 mm)	85.0	15.130 in (384.30 mm)	15.169 in (385.30 mm)	N/A	N/A	N/A		
14.000	114.00	0.800	TenarisHydril Blue® Max	Standard	12.213	Standard API Drift	7.88 in (200.2 mm)	1.86 in (47.2 mm)	12.389 in (314.66 mm)	12.411 in (315.26 mm)	14.000 in (355.60 mm)	14.140 in (359.14 mm)	7.88 in (200.2 mm)	2.15 in (54.6 mm)	15.934 in (404.70 mm)	16.129 in (409.70 mm)	12.402 in (315.00 mm)	12.425 in (315.60 mm)	15.371 in (390.40 mm)	15.448 in (392.40 mm)	85.0	15.146 in (384.70 mm)	15.185 in (385.70 mm)	N/A	N/A	N/A		
14.000	114.00	0.800	TenarisHydril Blue® Max	Standard	12.250	Special Drift	7.88 in (200.2 mm)	1.86 in (47.2 mm)	12.389 in (314.66 mm)	12.411 in (315.26 mm)	14.000 in (355.60 mm)	14.140 in (359.14 mm)	7.88 in (200.2 mm)	2.15 in (54.6 mm)	15.934 in (404.70 mm)	16.129 in (409.70 mm)	12.402 in (315.00 mm)	12.425 in (315.60 mm)	15.371 in (390.40 mm)	15.448 in (392.40 mm)	85.0	15.146 in (384.70 mm)	15.185 in (385.70 mm)	N/A	N/A	N/A		
14.000	115.00	0.812	TenarisHydril Blue® Max	Standard	12.189	Standard API Drift	7.88 in (200.2 mm)	1.86 in (47.2 mm)	12.365 in (314.06 mm)	12.388 in (314.66 mm)	14.000 in (355.60 mm)	14.140 in (359.14 mm)	7.88 in (200.2 mm)	2.15 in (54.6 mm)	15.934 in (404.70 mm)	16.129 in (409.70 mm)	12.402 in (315.00 mm)	12.425 in (315.60 mm)	15.485 in (393.30 mm)	15.562 in (395.30 mm)	85.0	15.245 in (387.20 mm)	15.283 in (388.20 mm)	N/A	N/A	N/A		
14.000	115.00	0.812	TenarisHydril Blue® Max	Standard	12.250	Special Drift	7.88 in (200.2 mm)	1.86 in (47.2 mm)	12.365 in (314.06 mm)	12.388 in (314.66 mm)	14.000 in (355.60 mm)	14.140 in (359.14 mm)	7.88 in (200.2 mm)	2.15 in (54.6 mm)	15.934 in (404.70 mm)	16.129 in (409.70 mm)	12.402 in (315.00 mm)	12.425 in (315.60 mm)	15.485 in (393.30 mm)	15.562 in (395.30 mm)	85.0	15.245 in (387.20 mm)	15.283 in (388.20 mm)	N/A	N/A	N/A		
14.000	116.00	0.820	TenarisHydril Blue® Max	Standard	12.173	Standard API Drift	7.88 in (200.2 mm)	1.86 in (47.2 mm)	12.349 in (313.64 mm)	12.371 in (314.24 mm)	14.000 in (355.60 mm)	14.140 in (359.14 mm)	7.88 in (200.2 mm)	2.15 in (54.6 mm)	15.934 in (404.70 mm)	16.129 in (409.70 mm)	12.402 in (315.00 mm)	12.425 in (315.60 mm)	15.500 in (393.70 mm)	15.578 in (395.70 mm)	85.0	15.256 in (387.50 mm)	15.295 in (388.50 mm)	80.0	15.197 in (386.00 mm)	15.236 in (387.00 mm)		
14.000	116.00	0.820	TenarisHydril Blue® Max	Standard	12.250	Special Drift	7.88 in (200.2 mm)	1.86 in (47.2 mm)	12.349 in (313.64 mm)	12.371 in (314.24 mm)	14.000 in (355.60 mm)	14.140 in (359.14 mm)	7.88 in (200.2 mm)	2.15 in (54.6 mm)	15.934 in (404.70 mm)	16.129 in (409.70 mm)	12.402 in (315.00 mm)	12.425 in (315.60 mm)	15.500 in (393.70 mm)	15.578 in (395.70 mm)	85.0	15.256 in (387.50 mm)	15.295 in (388.50 mm)	80.0	15.197 in (386.00 mm)	15.236 in (387.00 mm)		
16.000	84.00	0.495	TenarisHydril Blue® Max	Standard	14.823	Standard API Drift	6.85 in (173.8 mm)	1.86 in (47.2 mm)	14.906 in (378.62 mm)	14.929 in (379.20 mm)	16.000 in (406.40 mm)	16.160 in (410.46 mm)	6.85 in (173.8 mm)	2.15 in (54.6 mm)	13.863 in (352.10 mm)	14.059 in (357.10 mm)	14.857 in (377.36 mm)	14.879 in (377.94 mm)	16.949 in (430.50 mm)	16.988 in (431.50 mm)	85.0	16.796 in (426.60 mm)	16.834 in (427.60 mm)	N/A	N/A	N/A		
16.000	96.00	0.575	TenarisHydril Blue® Max	Standard	14.663	Standard API Drift	6.85 in (173.8 mm)	1.86 in (47.2 mm)	14.834 in (376.76 mm)	14.856 in (377.36 mm)	16.000 in (406.40 mm)	16.160 in (410.46 mm)	6.85 in (173.8 mm)	2.15 in (54.6 mm)	13.863 in (352.10 mm)	14.059 in (357.10 mm)	14.784 in (375.50 mm)	14.807 in (376.10 mm)	17.111 in (434.60 mm)	17.149 in (435.60 mm)	85.0	16.934 in (430.10 mm)	16.972 in (431.10 mm)	N/A	N/A	N/A		
16.000	96.00	0.575	TenarisHydril Blue® Max	Standard	14.750	Special Drift	6.85 in (173.8 mm)	1.86 in (47.2 mm)	14.834 in (376.76 mm)	14.856 in (377.36 mm)	16.000 in (406.40 mm)	16.160 in (410.46 mm)	6.85 in (173.8 mm)	2.15 in (54.6 mm)	13.863 in (352.10 mm)	14.059 in (357.10 mm)	14.784 in (375.50 mm)	14.807 in (376.10 mm)	17.111 in (434.60 mm)	17.149 in (435.60 mm)	85.0	16.934 in (430.10 mm)	16.972 in (431.10 mm)	N/A	N/A	N/A		
16.000	109.00	0.656	TenarisHydril Blue® Max	Standard	14.501	Standard API Drift	7.91 in (201.0 mm)	1.86 in (47.2 mm)	14.645 in (371.98 mm)	14.668 in (372.58 mm)	16.000 in (406.40 mm)	16.160 in (410.46 mm)	7.91 in (201.0 mm)	2.15 in (54.6 mm)	15.993 in (406.20 mm)	16.188 in (411.20 mm)	14.596 in (370.72 mm)	14.618 in (371.32 mm)	17.138 in (435.30 mm)	17.177 in (436.30 mm)	85.0	16.945 in (430.40 mm)	16.984 in (431.40 mm)	N/A	N/A	N/A		
16.000	118.00	0.715	TenarisHydril Blue® Max	Standard	14.383	Standard API Drift	7.91 in (201.0 mm)	1.86 in (47.2 mm)	14.559 in (369.78 mm)	14.581 in (370.38 mm)	16.000 in (406.40 mm)	16.160 in (410.46 mm)	7.91 in (201.0 mm)	2.15 in (54.6 mm)	15.993 in (406.20 mm)	16.188 in (411.20 mm)	14.516 in (368.70 mm)	14.539 in (369.30 mm)	17.249 in (438.10 mm)	17.287 in (439.10 mm)	85.0	17.040 in (432.80 mm)	17.078 in (433.80 mm)	N/A	N/A	N/A		
16.264	114.40	0.687	TenarisHydril Blue® Max	Standard	14.703	Standard API Drift	8.53 in (216.8 mm)	1.86 in (47.2 mm)	14.834 in (376.76 mm)	14.856 in (377.36 mm)	16.264 in (413.12 mm)	16.427 in (417.24 mm)	8.53 in (216.8 mm)	2.15 in (54.6 mm)	17.237 in (437.80 mm)	17.433 in (442.80 mm)	14.784 in (375.50 mm)	14.807 in (376.10 mm)	17.461 in (443.50 mm)	17.500 in (444.50 mm)	85.0	17.256 in (438.30 mm)	17.295 in (439.30 mm)	N/A	N/A	N/A		
16.264	114.40	0.687	TenarisHydril Blue® Max	Standard	14.750	Special Drift	8.53 in (216.8 mm)	1.86 in (47.2 mm)	14.834 in (376.76 mm)																			