

# TenarisHydril Blue® Blanking Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, recycled, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections B.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request hereafter. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyright © 2019 by an unpublished work. ALL RIGHTS RESERVED.

SIZE (IN)	WEIGHT (LB/FT)	WALL (IN)	CONNECTION				PIN										BOX																
			PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH		RECUT LENGTH		COUPLING LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER - REGULAR		OUTSIDE DIAMETER - MATCHED STRENGTH		OUTSIDE DIAMETER - SPECIAL CLEARANCE #1		OUTSIDE DIAMETER - SPECIAL CLEARANCE #2		OUTSIDE DIAMETER - SPECIAL CLEARANCE #3				
							MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	EFFICIENCY	MIN	MAX	EFFICIENCY	MIN
2.375	4.60	0.190	FenarisHydril® Blue	Standard	1.901	Standard API Drift	3.31 (84.0 mm)	1.55 (39.4 mm)	1.949 (49.50 mm)	1.972 (50.10 mm)	2.375 (60.34 mm)	2.406 (61.10 mm)	3.31 (84.0 mm)	2.08 (52.8 mm)	5.808 (147.50 mm)	6.003 (152.50 mm)	1.936 (49.16 mm)	1.958 (49.74 mm)	2.756 (70.00 mm)	2.795 (71.00 mm)	2.705 (68.70 mm)	2.744 (69.70 mm)	85.0	2.646 (67.20 mm)	2.685 (68.20 mm)	80.0	2.638 (67.00 mm)	2.677 (68.00 mm)	N/A	N/A	N/A	N/A	N/A
2.375	5.10	0.218	FenarisHydril® Blue	Standard	1.845	Standard API Drift	3.31 (84.0 mm)	1.55 (39.4 mm)	1.918 (48.70 mm)	1.940 (49.30 mm)	2.375 (60.34 mm)	2.406 (61.10 mm)	3.31 (84.0 mm)	2.08 (52.8 mm)	5.808 (147.50 mm)	6.003 (152.50 mm)	1.904 (48.94 mm)	1.927 (49.49 mm)	2.756 (70.00 mm)	2.795 (71.00 mm)	2.745 (68.70 mm)	2.783 (69.70 mm)	86.0	2.682 (68.10 mm)	2.720 (69.10 mm)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
2.375	5.80	0.254	FenarisHydril® Blue	Standard	1.773	Standard API Drift	3.31 (84.0 mm)	1.55 (39.4 mm)	1.856 (47.12 mm)	1.878 (47.72 mm)	2.375 (60.34 mm)	2.406 (61.10 mm)	3.31 (84.0 mm)	2.08 (52.8 mm)	5.808 (147.50 mm)	6.003 (152.50 mm)	1.857 (47.16 mm)	1.879 (47.74 mm)	2.808 (71.30 mm)	2.846 (72.30 mm)	2.796 (71.00 mm)	2.834 (72.00 mm)	85.0	2.721 (69.10 mm)	2.759 (70.10 mm)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
2.375	6.30	0.280	FenarisHydril® Blue	Standard	1.721	Standard API Drift	3.31 (84.0 mm)	1.55 (39.4 mm)	1.804 (45.80 mm)	1.826 (46.40 mm)	2.375 (60.34 mm)	2.406 (61.10 mm)	3.31 (84.0 mm)	2.08 (52.8 mm)	5.808 (147.50 mm)	6.003 (152.50 mm)	1.821 (46.84 mm)	1.844 (47.40 mm)	2.827 (71.80 mm)	2.866 (72.80 mm)	2.831 (71.90 mm)	2.870 (72.90 mm)	85.0	2.752 (69.90 mm)	2.791 (70.90 mm)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
2.375	6.60	0.295	FenarisHydril® Blue	Standard	1.691	Standard API Drift	3.31 (84.0 mm)	1.55 (39.4 mm)	1.774 (45.04 mm)	1.796 (45.64 mm)	2.375 (60.34 mm)	2.406 (61.10 mm)	3.31 (84.0 mm)	2.08 (52.8 mm)	5.808 (147.50 mm)	6.003 (152.50 mm)	1.825 (46.94 mm)	1.848 (47.50 mm)	2.843 (72.20 mm)	2.881 (73.20 mm)	2.851 (72.40 mm)	2.889 (73.40 mm)	85.0	2.768 (70.30 mm)	2.807 (71.30 mm)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
2.375	7.35	0.336	FenarisHydril® Blue	Standard	1.609	Standard API Drift	3.31 (84.0 mm)	1.55 (39.4 mm)	1.692 (42.96 mm)	1.714 (43.56 mm)	2.375 (60.34 mm)	2.406 (61.10 mm)	3.31 (84.0 mm)	2.08 (52.8 mm)	5.808 (147.50 mm)	6.003 (152.50 mm)	1.786 (46.50 mm)	1.809 (47.10 mm)	2.894 (73.50 mm)	2.933 (74.50 mm)	2.902 (73.70 mm)	2.940 (74.70 mm)	85.0	2.812 (71.40 mm)	2.850 (72.40 mm)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
2.875	6.40	0.217	FenarisHydril® Blue	Standard	2.347	Standard API Drift	3.86 (98.0 mm)	1.55 (39.4 mm)	2.410 (61.20 mm)	2.433 (61.80 mm)	2.875 (73.04 mm)	2.906 (73.80 mm)	3.86 (98.0 mm)	2.12 (53.8 mm)	7.107 (180.50 mm)	7.303 (185.50 mm)	2.417 (61.40 mm)	2.439 (62.00 mm)	3.288 (83.50 mm)	3.326 (84.50 mm)	3.229 (82.00 mm)	3.267 (83.00 mm)	85.0	3.162 (80.30 mm)	3.200 (81.30 mm)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
2.875	7.80	0.276	FenarisHydril® Blue	Standard	2.229	Standard API Drift	3.86 (98.0 mm)	1.55 (39.4 mm)	2.312 (58.70 mm)	2.334 (59.30 mm)	2.875 (73.04 mm)	2.906 (73.80 mm)	3.86 (98.0 mm)	2.12 (53.8 mm)	7.107 (180.50 mm)	7.303 (185.50 mm)	2.327 (59.10 mm)	2.350 (59.70 mm)	3.327 (84.50 mm)	3.366 (85.50 mm)	3.319 (84.30 mm)	3.358 (85.30 mm)	85.0	3.237 (82.20 mm)	3.275 (83.20 mm)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
2.875	8.60	0.308	FenarisHydril® Blue	Standard	2.165	Standard API Drift	3.86 (98.0 mm)	1.55 (39.4 mm)	2.248 (57.08 mm)	2.270 (57.68 mm)	2.875 (73.04 mm)	2.906 (73.80 mm)	3.86 (98.0 mm)	2.12 (53.8 mm)	7.107 (180.50 mm)	7.303 (185.50 mm)	2.264 (57.50 mm)	2.287 (58.10 mm)	3.405 (86.50 mm)	3.444 (87.50 mm)	3.367 (85.50 mm)	3.405 (86.50 mm)	85.0	3.276 (83.10 mm)	3.314 (84.20 mm)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
2.875	9.35	0.340	FenarisHydril® Blue	Standard	2.101	Standard API Drift	3.86 (98.0 mm)	1.55 (39.4 mm)	2.184 (55.46 mm)	2.206 (56.06 mm)	2.875 (73.04 mm)	2.906 (73.80 mm)	3.86 (98.0 mm)	2.12 (53.8 mm)	7.107 (180.50 mm)	7.303 (185.50 mm)	2.212 (56.30 mm)	2.235 (56.90 mm)	3.456 (87.80 mm)	3.495 (88.80 mm)	3.410 (87.60 mm)	3.448 (88.60 mm)	85.0	3.312 (84.10 mm)	3.350 (85.10 mm)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
2.875	9.80	0.362	FenarisHydril® Blue	Standard	2.057	Standard API Drift	3.86 (98.0 mm)	1.55 (39.4 mm)	2.140 (54.34 mm)	2.162 (54.94 mm)	2.875 (73.04 mm)	2.906 (73.80 mm)	3.86 (98.0 mm)	2.12 (53.8 mm)	7.107 (180.50 mm)	7.303 (185.50 mm)	2.197 (56.40 mm)	2.220 (57.00 mm)	3.430 (88.10 mm)	3.468 (89.10 mm)	3.438 (88.30 mm)	3.476 (89.30 mm)	85.0	3.335 (84.70 mm)	3.374 (85.70 mm)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
2.875	10.50	0.392	FenarisHydril® Blue	Standard	1.997	Standard API Drift	3.86 (98.0 mm)	1.55 (39.4 mm)	2.080 (52.82 mm)	2.102 (53.40 mm)	2.875 (73.04 mm)	2.906 (73.80 mm)	3.86 (98.0 mm)	2.12 (53.8 mm)	7.107 (180.50 mm)	7.303 (185.50 mm)	2.174 (55.80 mm)	2.196 (56.40 mm)	3.469 (89.10 mm)	3.507 (90.10 mm)	3.477 (88.30 mm)	3.515 (89.30 mm)	85.0	3.371 (85.60 mm)	3.409 (86.60 mm)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
2.875	10.70	0.405	FenarisHydril® Blue	Standard	1.971	Standard API Drift	3.86 (98.0 mm)	1.55 (39.4 mm)	2.054 (52.16 mm)	2.076 (52.74 mm)	2.875 (73.04 mm)	2.906 (73.80 mm)	3.86 (98.0 mm)	2.12 (53.8 mm)	7.107 (180.50 mm)	7.303 (185.50 mm)	2.150 (55.20 mm)	2.173 (55.80 mm)	3.485 (89.50 mm)	3.523 (90.50 mm)	3.493 (88.70 mm)	3.531 (89.70 mm)	85.0	3.382 (85.90 mm)	3.421 (86.90 mm)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
3.500	7.70	0.216	FenarisHydril® Blue	Standard	2.943	Standard API Drift	4.27 (108.4 mm)	1.55 (39.4 mm)	3.020 (76.70 mm)	3.043 (77.30 mm)	3.500 (88.90 mm)	3.531 (89.68 mm)	4.27 (108.4 mm)	2.09 (53.2 mm)	8.130 (206.50 mm)	8.326 (211.50 mm)	3.004 (76.90 mm)	3.027 (77.50 mm)	3.918 (99.50 mm)	3.956 (100.50 mm)	3.843 (97.60 mm)	3.881 (98.60 mm)	85.0	3.772 (95.80 mm)	3.811 (96.80 mm)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
3.500	9.20	0.254	FenarisHydril® Blue	Standard	2.867	Standard API Drift	4.27 (108.4 mm)	1.55 (39.4 mm)	2.996 (75.50 mm)	3.019 (76.10 mm)	3.500 (88.90 mm)	3.531 (89.68 mm)	4.27 (108.4 mm)	2.09 (53.2 mm)	8.130 (206.50 mm)	8.326 (211.50 mm)	2.981 (75.10 mm)	2.999 (75.70 mm)	3.959 (99.50 mm)	3.997 (100.50 mm)	3.906 (97.60 mm)	3.944 (98.60 mm)	85.0	3.823 (97.10 mm)	3.861 (98.10 mm)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
3.500	10.20	0.289	FenarisHydril® Blue	Standard	2.797	Standard API Drift	4.27 (108.4 mm)	1.55 (39.4 mm)	2.910 (73.90 mm)	2.933 (74.50 mm)	3.500 (88.90 mm)	3.531 (89.68 mm)	4.27 (108.4 mm)	2.09 (53.2 mm)	8.130 (206.50 mm)	8.326 (211.50 mm)	2.894 (74.10 mm)	2.917 (74.70 mm)	4.035 (101.50 mm)	4.073 (102.50 mm)	3.961 (100.60 mm)	3.999 (101.60 mm)	85.0	3.871 (98.30 mm)	3.909 (99.30 mm)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
3.500	12.70	0.375	FenarisHydril® Blue	Standard	2.625	Standard API Drift	4.27 (108.4 mm)	1.55 (39.4 mm)	2.739 (69.56 mm)	2.761 (70.14 mm)	3.500 (88.90 mm)	3.531 (89.68 mm)	4.27 (108.4 mm)	2.09 (53.2 mm)	8.130 (206.50 mm)	8.326 (211.50 mm)	2.788 (71.40 mm)	2.811 (72.00 mm)	4.130 (104.90 mm)	4.169 (105.90 mm)	4.087 (103.80 mm)	4.125 (104.80 mm)	85.0	3.977 (101.00 mm)	4.015 (102.00 mm)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
3.500	12.70	0.375	FenarisHydril® Blue	ExxonMobil CTP ALL	2.625	Standard API Drift	4.27 (108.4 mm)	1.55 (39.4 mm)	2.739 (69.56 mm)	2.761 (70.14 mm)	3.500 (88.90 mm)	3.531 (89.68 mm)	4.27 (108.4 mm)	2.09 (53.2 mm)	8.130 (206.50 mm)	8.326 (211.50 mm)	2.788 (71.40 mm)	2.811 (72.00 mm)	4.130 (104.90 mm)	4.169 (105.90 mm)	4.087 (103.80 mm)	4.125 (104.80 mm)	85.0	3.977 (101.00 mm)	4.015 (102.00 mm)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
3.500	13.70	0.413	FenarisHydril® Blue	Standard	2.549	Standard API Drift	4.27 (108.4 mm)	1.55 (39.4 mm)	2.663 (67.62 mm)	2.685 (68.22 mm)	3.500 (88.90 mm)	3.531 (89.68 mm)	4.27 (108.4 mm)	2.09 (53.2 mm)	8.130 (206.50 mm)	8.326 (211.50 mm)	2.793 (70.70 mm)	2.816 (71.30 mm)	4.130 (104.90 mm)	4.169 (105.90 mm)	4.095 (105.10 mm)	4.133 (106.10 mm)	85.0	4.020 (102.00 mm)	4.058 (103.00 mm)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
3.500	14.30	0.430	FenarisHydril® Blue	Standard	2.515	Standard API Drift	4.27 (108.4 mm)	1.55 (39.4 mm)	2.629 (66.76 mm)	2.651 (67.36 mm)	3.500 (88.90 mm)	3.531 (89.68 mm)	4.27 (108.4 mm)	2.09 (53.2 mm)	8.130 (206.50 mm)	8.326 (211.50 mm)	2.725 (69.20 mm)	2.748 (69.80 mm)	4.150 (105.40 mm)	4.188 (106.40 mm)	N/A	N/A	85.0	4.036 (102.50 mm)	4.074 (103.50 mm)	N/A	N/A	N/A	N/A	N/A	N/A		
3.500	14.70	0.449	FenarisHydril® Blue	Standard	2.477	Standard API Drift	4.27 (108.4 mm)	1.55 (39.4 mm)	2.591 (65.80 mm)	2.613 (66.38 mm)	3.500 (88.90 mm)	3.531 (89.68 mm)	4.27 (108.4 mm)	2.09 (53.2 mm)	8.130 (206.50 mm)	8.326 (211.50 mm)	2.709 (68.80 mm)	2.732 (69.40 mm)	4.174 (106.00 mm)	4.212 (107.00 mm)	N/A	N/A	85.0	4.060 (103.10 mm)	4.098 (104.10 mm)	N/A	N/A	N/A	N/A	N/A	N/A		
3.500	15.50	0.476	FenarisHydril® Blue	Standard	2.423	Standard API Drift	4.27 (108.4 mm)	1.55 (39.4 mm)	2.537 (64.42 mm)	2.559 (65.02 mm)	3.500 (88.90 mm)	3.531 (89.68 mm)	4.27 (108.4 mm)	2.09 (53.2 mm)	8.130 (206.50 mm)	8.326 (211.50 mm)	2.709 (68.80 mm)	2.732 (69.40 mm)	4.209 (106.90 mm)	4.248 (107.90 mm)	N/A	N/A	85.0	4.087 (103.80 mm)	4.125 (104.80 mm)	N/A	N/A	N/A	N/A	N/A	N/A		
4.000	8.20	0.190	FenarisHydril® Blue	Standard	3.495	Standard API Drift	4.46 (113.2 mm)	1.55 (39.4 mm)	3.544 (90.60 mm)	3.566 (91.20 mm)	4.000 (101.60 mm)	4.031 (102.38 mm)	4.46 (113.2 mm)	2.11 (53.6 mm)	8.682 (220.50 mm)	8.877 (225.50 mm)	3.526 (89.56 mm)	3.549 (90.14 mm)	4.422 (113.20 mm)	4.460 (114.20 mm)	4.300 (109.20 mm)	4.338 (110.20 mm)	97.0	4.276 (108.50 mm)	4.314 (109.50 mm)	N/A	N/A	N/A	N/A	N/A	N/A		
4.000	9.50	0.226	FenarisHydril® Blue	Standard	3.423	Standard API Drift	4.46 (113.2 mm)	1.55 (39.4 mm)	3.481 (88.40 mm)	3.503 (89.00 mm)	4.000 (101.60 mm)	4.031 (102.38 mm)	4.46 (113.2 mm)	2.11 (53.6 mm)	8.682 (220.50 mm)	8.877 (225.50 mm)	3.486 (88.54 mm)	3.488 (89.12 mm)	4.422 (113.20 mm)	4.460 (114.20 mm)	4.363 (110.80 mm)	4.401 (111.80 mm)	85.0	4.288 (108.90 mm)	4.326 (109.90 mm)	N/A	N/A	N/A	N/A	N/A	N/A		
4.000	10.90	0.262	FenarisHydril® Blue	Standard	3.351	Standard API Drift	4.46 (113.2 mm)	1.55 (39.4 mm)	3.438 (87.30 mm)	3.460 (87.90 mm)	4.000 (101.60 mm)	4.031 (102.38 mm)	4.46 (113.2 mm)	2.11 (53.6 mm)	8.682 (220.50 mm)	8.877 (225.50 mm)	3.420 (87.44 mm)	3.442 (88.02 mm)	4.422 (113.20 mm)	4.460 (114.20 mm)	4.4												

# TenarisHydril Blue® Blanking Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, recopied, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections B.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and/or are to be returned upon request. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyrighted 2019 by an unpublished work. ALL RIGHTS RESERVED.

SIZE (IN)	WEIGHT (LB/FT)	WALL (IN)	CONNECTION				PIN										BOX																
			PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH		RECUT LENGTH		COUPLING LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER - REGULAR		OUTSIDE DIAMETER - MATCHED STRENGTH		OUTSIDE DIAMETER - SPECIAL CLEARANCE #1		OUTSIDE DIAMETER - SPECIAL CLEARANCE #2		OUTSIDE DIAMETER - SPECIAL CLEARANCE #3				
							MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN
4.500	17.00	0.380	FenarisHydril® Blue	Standard	3.615	Standard API Drift	4.67 (118.6 mm)	1.55 (39.4 mm)	3.725 (94.70 mm)	3.751 (95.30 mm)	4.500 (114.30 mm)	4.545 (115.44 mm)	4.67 (118.6 mm)	2.11 (53.6 mm)	9.115 (231.50 mm)	9.311 (236.50 mm)	9.311 (236.50 mm)	9.115 (231.50 mm)	3.780 (96.00 mm)	3.803 (96.60 mm)	5.095 (129.40 mm)	5.133 (130.40 mm)	N/A	N/A	85.0	4.993 (126.80 mm)	5.031 (127.80 mm)	N/A	N/A	N/A	N/A	N/A	N/A
4.500	17.70	0.402	FenarisHydril® Blue	Standard	3.571	Standard API Drift	4.67 (118.6 mm)	1.55 (39.4 mm)	3.685 (93.58 mm)	3.707 (94.18 mm)	4.500 (114.30 mm)	4.545 (115.44 mm)	4.67 (118.6 mm)	2.11 (53.6 mm)	9.311 (231.50 mm)	9.311 (236.50 mm)	9.311 (236.50 mm)	9.115 (231.50 mm)	3.756 (96.00 mm)	3.779 (96.00 mm)	5.126 (130.20 mm)	5.165 (131.20 mm)	N/A	N/A	85.0	5.020 (127.50 mm)	5.059 (128.50 mm)	N/A	N/A	N/A	N/A	N/A	N/A
4.500	18.90	0.430	FenarisHydril® Blue	Standard	3.515	Standard API Drift	4.67 (118.6 mm)	1.55 (39.4 mm)	3.629 (92.16 mm)	3.651 (92.76 mm)	4.500 (114.30 mm)	4.545 (115.44 mm)	4.67 (118.6 mm)	2.11 (53.6 mm)	9.311 (231.50 mm)	9.311 (236.50 mm)	9.311 (236.50 mm)	9.115 (231.50 mm)	3.729 (94.70 mm)	3.751 (95.30 mm)	5.170 (132.30 mm)	5.208 (133.20 mm)	N/A	N/A	85.0	5.052 (128.30 mm)	5.090 (129.30 mm)	N/A	N/A	N/A	N/A	N/A	N/A
4.500	21.50	0.500	FenarisHydril® Blue	Standard	3.375	Standard API Drift	4.67 (118.6 mm)	1.55 (39.4 mm)	3.489 (88.60 mm)	3.511 (89.20 mm)	4.500 (114.30 mm)	4.545 (115.44 mm)	4.67 (118.6 mm)	2.11 (53.6 mm)	9.311 (231.50 mm)	9.311 (236.50 mm)	9.311 (236.50 mm)	9.115 (231.50 mm)	3.591 (91.20 mm)	3.614 (91.80 mm)	5.268 (133.80 mm)	5.307 (134.80 mm)	N/A	N/A	85.0	5.138 (130.50 mm)	5.177 (131.50 mm)	N/A	N/A	N/A	N/A	N/A	N/A
5.000	13.00	0.253	FenarisHydril® Blue	Standard	4.369	Standard API Drift	5.23 (132.8 mm)	1.55 (39.4 mm)	4.480 (112.50 mm)	4.452 (112.10 mm)	5.000 (127.00 mm)	5.050 (128.26 mm)	5.23 (132.8 mm)	2.06 (52.4 mm)	10.453 (265.50 mm)	10.649 (270.50 mm)	10.649 (270.50 mm)	10.453 (265.50 mm)	4.410 (112.60 mm)	4.433 (113.60 mm)	5.493 (140.50 mm)	5.531 (141.50 mm)	5.382 (136.70 mm)	5.392 (137.70 mm)	90.0	5.315 (135.00 mm)	5.354 (136.00 mm)	N/A	N/A	N/A	N/A	N/A	N/A
5.000	15.00	0.296	FenarisHydril® Blue	Standard	4.283	Standard API Drift	5.23 (132.8 mm)	1.55 (39.4 mm)	4.359 (110.70 mm)	4.381 (111.30 mm)	5.000 (127.00 mm)	5.050 (128.26 mm)	5.23 (132.8 mm)	2.06 (52.4 mm)	10.453 (265.50 mm)	10.649 (270.50 mm)	10.649 (270.50 mm)	10.453 (265.50 mm)	4.339 (110.80 mm)	4.362 (111.80 mm)	5.493 (140.50 mm)	5.531 (141.50 mm)	5.459 (136.00 mm)	5.492 (137.00 mm)	85.0	5.355 (136.00 mm)	5.393 (137.00 mm)	N/A	N/A	N/A	N/A	N/A	N/A
5.000	18.00	0.362	FenarisHydril® Blue	Standard	4.151	Standard API Drift	5.23 (132.8 mm)	1.55 (39.4 mm)	4.265 (108.30 mm)	4.287 (108.90 mm)	5.000 (127.00 mm)	5.050 (128.26 mm)	5.23 (132.8 mm)	2.06 (52.4 mm)	10.453 (265.50 mm)	10.649 (270.50 mm)	10.649 (270.50 mm)	10.453 (265.50 mm)	4.252 (108.00 mm)	4.275 (109.00 mm)	5.611 (142.50 mm)	5.649 (143.50 mm)	5.563 (138.50 mm)	5.602 (139.50 mm)	85.0	5.445 (138.30 mm)	5.484 (139.30 mm)	N/A	N/A	N/A	N/A	N/A	N/A
5.000	20.30	0.408	FenarisHydril® Blue	Standard	4.059	Standard API Drift	5.23 (132.8 mm)	1.55 (39.4 mm)	4.173 (105.98 mm)	4.195 (106.56 mm)	5.000 (127.00 mm)	5.050 (128.26 mm)	5.23 (132.8 mm)	2.06 (52.4 mm)	10.453 (265.50 mm)	10.649 (270.50 mm)	10.649 (270.50 mm)	10.453 (265.50 mm)	4.197 (107.20 mm)	4.220 (108.20 mm)	5.630 (143.00 mm)	5.669 (144.00 mm)	5.634 (141.30 mm)	5.673 (142.30 mm)	85.0	5.508 (139.90 mm)	5.547 (140.90 mm)	N/A	N/A	N/A	N/A	N/A	N/A
5.000	20.30	0.408	FenarisHydril® Blue	Standard	4.125	Special Drift	5.23 (132.8 mm)	1.55 (39.4 mm)	4.173 (105.98 mm)	4.195 (106.56 mm)	5.000 (127.00 mm)	5.050 (128.26 mm)	5.23 (132.8 mm)	2.06 (52.4 mm)	10.453 (265.50 mm)	10.649 (270.50 mm)	10.649 (270.50 mm)	10.453 (265.50 mm)	4.197 (107.20 mm)	4.220 (108.20 mm)	5.630 (143.00 mm)	5.669 (144.00 mm)	5.634 (141.30 mm)	5.673 (142.30 mm)	85.0	5.508 (139.90 mm)	5.547 (140.90 mm)	N/A	N/A	N/A	N/A	N/A	N/A
5.000	20.80	0.422	FenarisHydril® Blue	Standard	4.031	Standard API Drift	5.23 (132.8 mm)	1.55 (39.4 mm)	4.145 (105.26 mm)	4.167 (105.86 mm)	5.000 (127.00 mm)	5.050 (128.26 mm)	5.23 (132.8 mm)	2.06 (52.4 mm)	10.453 (265.50 mm)	10.649 (270.50 mm)	10.649 (270.50 mm)	10.453 (265.50 mm)	4.182 (106.20 mm)	4.204 (107.20 mm)	5.654 (143.60 mm)	5.692 (144.60 mm)	5.658 (143.70 mm)	5.696 (144.70 mm)	85.0	5.524 (140.30 mm)	5.562 (141.30 mm)	N/A	N/A	N/A	N/A	N/A	N/A
5.000	20.80	0.422	FenarisHydril® Blue	ExxonMobil CTP ALL	4.031	Standard API Drift	5.23 (132.8 mm)	1.55 (39.4 mm)	4.145 (105.26 mm)	4.167 (105.86 mm)	5.000 (127.00 mm)	5.050 (128.26 mm)	5.23 (132.8 mm)	2.06 (52.4 mm)	10.453 (265.50 mm)	10.649 (270.50 mm)	10.649 (270.50 mm)	10.453 (265.50 mm)	4.182 (106.20 mm)	4.204 (107.20 mm)	5.654 (143.60 mm)	5.692 (144.60 mm)	5.658 (143.70 mm)	5.696 (144.70 mm)	85.0	5.524 (140.30 mm)	5.562 (141.30 mm)	N/A	N/A	N/A	N/A	N/A	N/A
5.000	21.40	0.437	FenarisHydril® Blue	Standard	4.001	Standard API Drift	5.23 (132.8 mm)	1.55 (39.4 mm)	4.115 (104.50 mm)	4.137 (105.10 mm)	5.000 (127.00 mm)	5.050 (128.26 mm)	5.23 (132.8 mm)	2.06 (52.4 mm)	10.453 (265.50 mm)	10.649 (270.50 mm)	10.649 (270.50 mm)	10.453 (265.50 mm)	4.174 (106.00 mm)	4.196 (107.00 mm)	5.674 (144.10 mm)	5.712 (145.10 mm)	5.678 (144.20 mm)	5.716 (145.20 mm)	85.0	5.544 (140.80 mm)	5.582 (141.80 mm)	N/A	N/A	N/A	N/A	N/A	N/A
5.000	23.20	0.478	FenarisHydril® Blue	Standard	3.919	Standard API Drift	5.23 (132.8 mm)	1.55 (39.4 mm)	4.033 (102.42 mm)	4.055 (103.02 mm)	5.000 (127.00 mm)	5.050 (128.26 mm)	5.23 (132.8 mm)	2.06 (52.4 mm)	10.453 (265.50 mm)	10.649 (270.50 mm)	10.649 (270.50 mm)	10.453 (265.50 mm)	4.123 (104.70 mm)	4.145 (105.70 mm)	5.737 (146.70 mm)	5.775 (147.70 mm)	5.741 (145.80 mm)	5.779 (146.80 mm)	85.0	5.595 (142.10 mm)	5.633 (143.10 mm)	N/A	N/A	N/A	N/A	N/A	N/A
5.000	23.20	0.478	FenarisHydril® Blue	Shell B	3.919	Standard API Drift	5.23 (132.8 mm)	1.55 (39.4 mm)	4.033 (102.42 mm)	4.055 (103.02 mm)	5.000 (127.00 mm)	5.050 (128.26 mm)	5.23 (132.8 mm)	2.06 (52.4 mm)	10.453 (265.50 mm)	10.649 (270.50 mm)	10.649 (270.50 mm)	10.453 (265.50 mm)	4.123 (104.70 mm)	4.145 (105.70 mm)	5.737 (146.70 mm)	5.775 (147.70 mm)	5.741 (145.80 mm)	5.779 (146.80 mm)	85.0	5.595 (142.10 mm)	5.633 (143.10 mm)	N/A	N/A	N/A	N/A	N/A	N/A
5.000	24.10	0.500	FenarisHydril® Blue	Standard	3.875	Standard API Drift	5.23 (132.8 mm)	1.55 (39.4 mm)	3.989 (101.30 mm)	4.011 (101.90 mm)	5.000 (127.00 mm)	5.050 (128.26 mm)	5.23 (132.8 mm)	2.06 (52.4 mm)	10.453 (265.50 mm)	10.649 (270.50 mm)	10.649 (270.50 mm)	10.453 (265.50 mm)	4.102 (103.60 mm)	4.124 (104.60 mm)	5.807 (145.50 mm)	5.845 (146.50 mm)	5.811 (144.60 mm)	5.849 (145.60 mm)	85.0	5.623 (142.80 mm)	5.661 (143.80 mm)	N/A	N/A	N/A	N/A	N/A	N/A
5.000	26.70	0.562	FenarisHydril® Blue	Standard	3.751	Standard API Drift	5.23 (132.8 mm)	1.55 (39.4 mm)	3.865 (98.16 mm)	3.887 (98.74 mm)	5.000 (127.00 mm)	5.050 (128.26 mm)	5.23 (132.8 mm)	2.06 (52.4 mm)	10.453 (265.50 mm)	10.649 (270.50 mm)	10.649 (270.50 mm)	10.453 (265.50 mm)	3.957 (101.10 mm)	3.980 (102.10 mm)	5.855 (148.70 mm)	5.893 (149.70 mm)	5.859 (148.80 mm)	5.897 (149.80 mm)	85.0	5.693 (144.60 mm)	5.732 (145.60 mm)	N/A	N/A	N/A	N/A	N/A	N/A
5.000	15.50	0.275	FenarisHydril® Blue	Standard	4.825	Standard API Drift	5.33 (135.4 mm)	1.55 (39.4 mm)	4.922 (125.00 mm)	4.944 (125.60 mm)	5.500 (141.00 mm)	5.555 (142.14 mm)	5.33 (135.4 mm)	2.12 (53.8 mm)	10.650 (270.50 mm)	10.846 (275.50 mm)	10.846 (275.50 mm)	10.650 (270.50 mm)	4.900 (124.46 mm)	4.923 (125.46 mm)	6.044 (153.50 mm)	6.082 (154.50 mm)	5.926 (150.50 mm)	5.964 (151.50 mm)	85.0	5.831 (148.10 mm)	5.870 (149.10 mm)	N/A	N/A	N/A	N/A	N/A	N/A
5.500	17.00	0.304	FenarisHydril® Blue	Standard	4.767	Standard API Drift	5.33 (135.4 mm)	1.55 (39.4 mm)	4.871 (123.70 mm)	4.893 (124.30 mm)	5.500 (141.00 mm)	5.555 (142.14 mm)	5.33 (135.4 mm)	2.12 (53.8 mm)	10.650 (270.50 mm)	10.846 (275.50 mm)	10.846 (275.50 mm)	10.650 (270.50 mm)	4.849 (123.16 mm)	4.872 (124.16 mm)	6.044 (153.50 mm)	6.082 (154.50 mm)	5.973 (150.70 mm)	6.011 (151.70 mm)	85.0	5.875 (149.20 mm)	5.914 (150.20 mm)	N/A	N/A	N/A	N/A	N/A	N/A
5.500	20.00	0.361	FenarisHydril® Blue	Standard	4.653	Standard API Drift	5.33 (135.4 mm)	1.55 (39.4 mm)	4.767 (121.06 mm)	4.789 (121.66 mm)	5.500 (141.00 mm)	5.555 (142.14 mm)	5.33 (135.4 mm)	2.12 (53.8 mm)	10.650 (270.50 mm)	10.846 (275.50 mm)	10.846 (275.50 mm)	10.650 (270.50 mm)	4.778 (121.36 mm)	4.801 (122.36 mm)	6.122 (154.50 mm)	6.160 (155.50 mm)	6.067 (151.20 mm)	6.106 (152.20 mm)	85.0	5.953 (151.20 mm)	5.992 (152.20 mm)	N/A	N/A	N/A	N/A	N/A	N/A
5.500	23.00	0.415	FenarisHydril® Blue	Standard	4.545	Standard API Drift	5.33 (135.4 mm)	1.55 (39.4 mm)	4.659 (118.32 mm)	4.681 (118.92 mm)	5.500 (141.00 mm)	5.555 (142.14 mm)	5.33 (135.4 mm)	2.12 (53.8 mm)	10.650 (270.50 mm)	10.846 (275.50 mm)	10.846 (275.50 mm)	10.650 (270.50 mm)	4.684 (119.54 mm)	4.706 (120.54 mm)	6.162 (156.50 mm)	6.200 (157.50 mm)	6.158 (156.40 mm)	6.196 (157.40 mm)	85.0	6.024 (154.00 mm)	6.062 (155.00 mm)	N/A	N/A	N/A	N/A	N/A	N/A
5.500	23.00	0.415	FenarisHydril® Blue	ExxonMobil CTP ALL	4.545	Standard API Drift	5.33 (135.4 mm)	1.55 (39.4 mm)	4.659 (118.32 mm)	4.681 (118.92 mm)	5.500 (141.00 mm)	5.555 (142.14 mm)	5.33 (135.4 mm)	2.12 (53.8 mm)	10.650 (270.50 mm)	10.846 (275.50 mm)	10.846 (275.50 mm)	10.650 (270.50 mm)	4.684 (119.54 mm)	4.706 (120.54 mm)	6.162 (156.50 mm)	6.200 (157.50 mm)	6.158 (156.40 mm)	6.196 (157.40 mm)	85.0	6.024 (154.00 mm)	6.062 (155.00 mm)	N/A	N/A	N/A	N/A	N/A	N/A
5.500	26.00	0.476	FenarisHydril® Blue	Standard	4.423	Standard API Drift	5.33 (135.4 mm)	1.55 (39.4 mm)	4.537 (115.22 mm)	4.559 (115.82 mm)	5.500 (141.00 mm)	5.555 (142.14 mm)	5.33 (135.4 mm)	2.12 (53.8 mm)	10.650 (270.50 mm)	10.846 (275.50 mm)	10.846 (275.50 mm)	10.650 (270.50 mm)	4.605 (116.96 mm)	4.627 (117.96 mm)	6.288 (159.70 mm)	6.326 (160.70 mm)	6.221 (158.00 mm)	6.259 (159.00 mm)	85.0	6.103 (155.00 mm)	6.141 (156.00 mm)	N/A	N/A	N/A	N/A	N/A	N/A
5.500	26.00	0.476	FenarisHydril® Blue	ExxonMobil CTP ALL	4.423	Standard API Drift	5.33 (135.4 mm)	1.55 (39.4 mm)	4.537 (115.22 mm)	4.559 (115.82 mm)	5.500 (141.00 mm)	5.555 (142.14 mm)	5.33 (135.4 mm)	2.12 (53.8 mm)	10.650 (270.50 mm)	10.846 (275.50 mm)	10.846 (275.50 mm)	10.650 (270.50 mm)	4.605 (116.96 mm)	4.627 (117.96 mm)	6.288 (159.70 mm)	6.326 (160.70 mm)											



# TenarisHydril Blue® Blanking Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, recycled, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connectors B.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request thereafter. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyrighted 2019 as an unpublished work. ALL RIGHTS RESERVED.

SIZE (IN)	WEIGHT (LB/FT)	WALL (IN)	CONNECTION					PIN										BOX														
			PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH		RECUT LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH	RECUT LENGTH	COUPLING LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER - REGULAR		OUTSIDE DIAMETER - MATCHED STRENGTH		OUTSIDE DIAMETER - SPECIAL CLEARANCE #1		OUTSIDE DIAMETER - SPECIAL CLEARANCE #2		OUTSIDE DIAMETER - SPECIAL CLEARANCE #3			
							MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX			MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX
8.625	44.00	0.500	FenarisHydril® Blue	Standard	7.500	Standard API Drift	5.72 (145.2 mm)	1.60 (40.8 mm)	7.614 (193.38 mm)	7.637 (193.98 mm)	8.625 (219.08 mm)	8.711 (221.24 mm)	5.72 (145.2 mm)	2.08 (52.8 mm)	11.995 (304.50 mm)	11.791 (299.50 mm)	7.638 (194.00 mm)	7.661 (194.60 mm)	9.469 (240.50 mm)	9.507 (241.50 mm)	9.418 (239.20 mm)	9.456 (240.20 mm)	85.0	9.252 (235.00 mm)	9.291 (236.00 mm)	N/A	N/A	N/A	N/A	N/A	N/A	N/A
8.625	49.00	0.557	FenarisHydril® Blue	Standard	7.386	Standard API Drift	5.72 (145.2 mm)	1.60 (40.8 mm)	7.500 (190.48 mm)	7.522 (191.08 mm)	8.625 (219.08 mm)	8.711 (221.24 mm)	5.72 (145.2 mm)	2.08 (52.8 mm)	11.995 (304.50 mm)	11.791 (299.50 mm)	7.524 (191.10 mm)	7.547 (191.70 mm)	9.607 (244.00 mm)	9.645 (245.00 mm)	9.512 (241.60 mm)	9.551 (242.60 mm)	85.0	9.331 (237.00 mm)	9.370 (238.00 mm)	N/A	N/A	N/A	N/A	N/A	N/A	N/A
8.625	52.00	0.595	FenarisHydril® Blue	Standard	7.310	Standard API Drift	5.72 (145.2 mm)	1.60 (40.8 mm)	7.424 (188.56 mm)	7.446 (189.16 mm)	8.625 (219.08 mm)	8.711 (221.24 mm)	5.72 (145.2 mm)	2.08 (52.8 mm)	11.995 (304.50 mm)	11.791 (299.50 mm)	7.485 (190.10 mm)	7.507 (190.70 mm)	9.607 (244.00 mm)	9.645 (245.00 mm)	9.575 (243.20 mm)	9.614 (244.20 mm)	85.0	9.382 (238.30 mm)	9.421 (239.30 mm)	N/A	N/A	N/A	N/A	N/A	N/A	N/A
8.625	54.00	0.625	FenarisHydril® Blue	Standard	7.250	Standard API Drift	5.72 (145.2 mm)	1.60 (40.8 mm)	7.364 (187.04 mm)	7.387 (187.64 mm)	8.625 (219.08 mm)	8.711 (221.24 mm)	5.72 (145.2 mm)	2.08 (52.8 mm)	11.995 (304.50 mm)	11.791 (299.50 mm)	7.426 (188.60 mm)	7.448 (189.20 mm)	9.619 (244.30 mm)	9.657 (245.30 mm)	N/A	N/A	85.0	9.422 (239.30 mm)	9.460 (240.30 mm)	N/A	N/A	N/A	N/A	N/A	N/A	N/A
8.625	58.70	0.687	FenarisHydril® Blue	Standard	7.126	Standard API Drift	5.72 (145.2 mm)	1.60 (40.8 mm)	7.240 (183.88 mm)	7.262 (184.48 mm)	8.625 (219.08 mm)	8.711 (221.24 mm)	5.72 (145.2 mm)	2.10 (53.4 mm)	11.995 (304.50 mm)	11.791 (299.50 mm)	7.378 (187.40 mm)	7.401 (188.00 mm)	9.717 (246.80 mm)	9.755 (247.80 mm)	N/A	N/A	85.0	9.504 (241.40 mm)	9.543 (242.40 mm)	N/A	N/A	N/A	N/A	N/A	N/A	N/A
9.625	36.00	0.352	FenarisHydril® Blue	Standard	8.765	Standard API Drift	5.72 (145.2 mm)	1.60 (40.8 mm)	8.847 (224.70 mm)	8.870 (225.30 mm)	9.625 (244.48 mm)	9.711 (246.90 mm)	5.72 (145.2 mm)	5.34 (136.4 mm)	11.995 (304.50 mm)	11.791 (299.50 mm)	8.817 (223.96 mm)	8.840 (224.54 mm)	10.607 (269.40 mm)	10.645 (270.40 mm)	10.166 (258.20 mm)	10.204 (259.20 mm)	91.0	10.075 (256.00 mm)	10.114 (257.00 mm)	N/A	N/A	N/A	N/A	N/A	N/A	N/A
9.625	40.00	0.395	FenarisHydril® Blue	Standard	8.679	Standard API Drift	5.72 (145.2 mm)	1.60 (40.8 mm)	8.800 (223.50 mm)	8.822 (224.10 mm)	9.625 (244.48 mm)	9.711 (246.90 mm)	5.72 (145.2 mm)	5.34 (136.4 mm)	11.995 (304.50 mm)	11.791 (299.50 mm)	8.770 (222.76 mm)	8.793 (223.34 mm)	10.607 (269.40 mm)	10.645 (270.40 mm)	10.123 (257.10 mm)	10.161 (258.10 mm)	87.0	10.123 (257.10 mm)	10.161 (258.10 mm)	N/A	N/A	N/A	N/A	N/A	N/A	N/A
9.625	40.00	0.395	FenarisHydril® Blue	Standard	8.750	Alternative API Drift	5.72 (145.2 mm)	1.60 (40.8 mm)	8.804 (223.60 mm)	8.822 (224.10 mm)	9.625 (244.48 mm)	9.711 (246.90 mm)	5.72 (145.2 mm)	5.34 (136.4 mm)	11.995 (304.50 mm)	11.791 (299.50 mm)	8.774 (222.86 mm)	8.793 (223.34 mm)	10.607 (269.40 mm)	10.645 (270.40 mm)	10.123 (257.10 mm)	10.161 (258.10 mm)	87.0	10.123 (257.10 mm)	10.161 (258.10 mm)	N/A	N/A	N/A	N/A	N/A	N/A	N/A
9.625	43.50	0.435	FenarisHydril® Blue	Standard	8.599	Standard API Drift	5.72 (145.2 mm)	1.60 (40.8 mm)	8.729 (221.70 mm)	8.751 (222.30 mm)	9.625 (244.48 mm)	9.711 (246.90 mm)	5.72 (145.2 mm)	5.34 (136.4 mm)	11.995 (304.50 mm)	11.791 (299.50 mm)	8.699 (220.96 mm)	8.722 (211.54 mm)	10.607 (269.40 mm)	10.645 (270.40 mm)	10.166 (258.20 mm)	10.204 (259.20 mm)	85.0	10.166 (258.20 mm)	10.204 (259.20 mm)	N/A	N/A	N/A	N/A	N/A	N/A	N/A
9.625	43.50	0.435	FenarisHydril® Blue	Standard	8.625	Special Drift	5.72 (145.2 mm)	1.60 (40.8 mm)	8.721 (221.70 mm)	8.743 (222.30 mm)	9.625 (244.48 mm)	9.711 (246.90 mm)	5.72 (145.2 mm)	5.34 (136.4 mm)	11.995 (304.50 mm)	11.791 (299.50 mm)	8.717 (220.96 mm)	8.740 (211.54 mm)	10.607 (269.40 mm)	10.645 (270.40 mm)	10.166 (258.20 mm)	10.204 (259.20 mm)	85.0	10.166 (258.20 mm)	10.204 (259.20 mm)	N/A	N/A	N/A	N/A	N/A	N/A	N/A
9.625	47.00	0.472	FenarisHydril® Blue	Standard	8.525	Standard API Drift	5.72 (145.2 mm)	1.60 (40.8 mm)	8.670 (220.20 mm)	8.692 (220.80 mm)	9.625 (244.48 mm)	9.711 (246.90 mm)	5.72 (145.2 mm)	5.34 (136.4 mm)	11.995 (304.50 mm)	11.791 (299.50 mm)	8.648 (219.66 mm)	8.671 (220.24 mm)	10.607 (269.40 mm)	10.645 (270.40 mm)	10.127 (259.50 mm)	10.165 (260.50 mm)	85.0	10.127 (259.50 mm)	10.165 (260.50 mm)	N/A	N/A	N/A	N/A	N/A	N/A	N/A
9.625	47.00	0.472	FenarisHydril® Blue	ExxonMobil CTP ALL	8.525	Standard API Drift	5.72 (145.2 mm)	1.60 (40.8 mm)	8.670 (220.20 mm)	8.692 (220.80 mm)	9.625 (244.48 mm)	9.711 (246.90 mm)	5.72 (145.2 mm)	5.34 (136.4 mm)	11.995 (304.50 mm)	11.791 (299.50 mm)	8.648 (219.66 mm)	8.671 (220.24 mm)	10.607 (269.40 mm)	10.645 (270.40 mm)	10.127 (259.50 mm)	10.165 (260.50 mm)	85.0	10.127 (259.50 mm)	10.165 (260.50 mm)	N/A	N/A	N/A	N/A	N/A	N/A	N/A
9.625	47.00	0.472	FenarisHydril® Blue	Standard	8.614	Special Drift	5.72 (145.2 mm)	1.60 (40.8 mm)	8.670 (220.20 mm)	8.692 (220.80 mm)	9.625 (244.48 mm)	9.711 (246.90 mm)	5.72 (145.2 mm)	5.34 (136.4 mm)	11.995 (304.50 mm)	11.791 (299.50 mm)	8.648 (219.66 mm)	8.671 (220.24 mm)	10.607 (269.40 mm)	10.645 (270.40 mm)	10.127 (259.50 mm)	10.165 (260.50 mm)	85.0	10.127 (259.50 mm)	10.165 (260.50 mm)	N/A	N/A	N/A	N/A	N/A	N/A	N/A
9.625	53.50	0.545	FenarisHydril® Blue	Standard	8.379	Standard API Drift	5.72 (145.2 mm)	1.60 (40.8 mm)	8.524 (216.50 mm)	8.546 (217.10 mm)	9.625 (244.48 mm)	9.711 (246.90 mm)	5.72 (145.2 mm)	5.34 (136.4 mm)	11.995 (304.50 mm)	11.791 (299.50 mm)	8.534 (216.76 mm)	8.557 (217.34 mm)	10.607 (269.40 mm)	10.645 (270.40 mm)	10.504 (262.80 mm)	10.543 (263.80 mm)	85.0	10.523 (262.20 mm)	10.562 (263.20 mm)	N/A	N/A	N/A	N/A	N/A	N/A	N/A
9.625	53.50	0.545	FenarisHydril® Blue	Standard	8.500	Alternative API Drift	5.72 (145.2 mm)	1.60 (40.8 mm)	8.524 (216.50 mm)	8.546 (217.10 mm)	9.625 (244.48 mm)	9.711 (246.90 mm)	5.72 (145.2 mm)	5.34 (136.4 mm)	11.995 (304.50 mm)	11.791 (299.50 mm)	8.534 (216.76 mm)	8.557 (217.34 mm)	10.607 (269.40 mm)	10.645 (270.40 mm)	10.504 (262.80 mm)	10.543 (263.80 mm)	85.0	10.523 (262.20 mm)	10.562 (263.20 mm)	N/A	N/A	N/A	N/A	N/A	N/A	N/A
9.625	58.40	0.595	FenarisHydril® Blue	Standard	8.279	Standard API Drift	5.72 (145.2 mm)	1.60 (40.8 mm)	8.424 (213.96 mm)	8.446 (214.54 mm)	9.625 (244.48 mm)	9.711 (246.90 mm)	5.72 (145.2 mm)	5.34 (136.4 mm)	11.995 (304.50 mm)	11.791 (299.50 mm)	8.483 (215.46 mm)	8.505 (216.04 mm)	10.607 (269.40 mm)	10.645 (270.40 mm)	10.394 (264.00 mm)	10.433 (265.00 mm)	85.0	10.394 (264.00 mm)	10.433 (265.00 mm)	N/A	N/A	N/A	N/A	N/A	N/A	N/A
9.625	58.40	0.595	FenarisHydril® Blue	Standard	8.375	Alternative API Drift	5.72 (145.2 mm)	1.60 (40.8 mm)	8.424 (213.96 mm)	8.446 (214.54 mm)	9.625 (244.48 mm)	9.711 (246.90 mm)	5.72 (145.2 mm)	5.34 (136.4 mm)	11.995 (304.50 mm)	11.791 (299.50 mm)	8.483 (215.46 mm)	8.505 (216.04 mm)	10.607 (269.40 mm)	10.645 (270.40 mm)	10.394 (264.00 mm)	10.433 (265.00 mm)	85.0	10.394 (264.00 mm)	10.433 (265.00 mm)	N/A	N/A	N/A	N/A	N/A	N/A	N/A
9.625	59.40	0.609	FenarisHydril® Blue	Standard	8.251	Standard API Drift	5.72 (145.2 mm)	1.60 (40.8 mm)	8.396 (213.24 mm)	8.418 (213.84 mm)	9.625 (244.48 mm)	9.711 (246.90 mm)	5.72 (145.2 mm)	5.34 (136.4 mm)	11.995 (304.50 mm)	11.791 (299.50 mm)	8.542 (216.96 mm)	8.564 (217.54 mm)	10.607 (269.40 mm)	10.645 (270.40 mm)	N/A	N/A	85.0	10.410 (264.40 mm)	10.448 (265.40 mm)	N/A	N/A	N/A	N/A	N/A	N/A	
9.625	61.10	0.625	FenarisHydril® Blue	Standard	8.219	Standard API Drift	5.72 (145.2 mm)	1.60 (40.8 mm)	8.361 (212.44 mm)	8.383 (213.04 mm)	9.625 (244.48 mm)	9.711 (246.90 mm)	5.72 (145.2 mm)	5.34 (136.4 mm)	11.995 (304.50 mm)	11.791 (299.50 mm)	8.517 (216.26 mm)	8.539 (216.84 mm)	10.607 (269.40 mm)	10.645 (270.40 mm)	N/A	N/A	85.0	10.434 (265.00 mm)	10.472 (266.00 mm)	N/A	N/A	N/A	N/A	N/A	N/A	
9.625	64.90	0.672	FenarisHydril® Blue	Standard	8.125	Standard API Drift	5.72 (145.2 mm)	1.60 (40.8 mm)	8.270 (210.04 mm)	8.292 (210.64 mm)	9.625 (244.48 mm)	9.711 (246.90 mm)	5.72 (145.2 mm)	5.34 (136.4 mm)	11.995 (304.50 mm)	11.791 (299.50 mm)	8.424 (213.96 mm)	8.446 (214.54 mm)	10.709 (272.00 mm)	10.748 (273.00 mm)	N/A	N/A	85.0	10.497 (266.60 mm)	10.535 (267.60 mm)	N/A	N/A	N/A	N/A	N/A	N/A	
9.625	70.30	0.734	FenarisHydril® Blue	Standard	8.001	Standard API Drift	5.72 (145.2 mm)	1.60 (40.8 mm)	8.146 (206.90 mm)	8.168 (207.48 mm)	9.625 (244.48 mm)	9.711 (246.90 mm)	5.72 (145.2 mm)	5.34 (136.4 mm)	11.995 (304.50 mm)	11.791 (299.50 mm)	8.345 (211.96 mm)	8.368 (212.54 mm)	10.808 (274.50 mm)	10.846 (275.50 mm)	N/A	N/A	85.0	10.579 (268.70 mm)	10.618 (269.70 mm)	N/A	N/A	N/A	N/A	N/A	N/A	
9.875	62.80	0.625	FenarisHydril® Blue	Standard	8.469	Standard API Drift	5.72 (145.2 mm)	1.60 (40.8 mm)	8.614 (218.78 mm)	8.637 (219.38 mm)	9.875 (250.84 mm)	9.974 (253.32 mm)	5.72 (145.2 mm)	5.12 (130.2 mm)	11.995 (304.50 mm)	11.791 (299.50 mm)	8.680 (220.46 mm)	8.702 (221.04 mm)	10.965 (278.50 mm)	11.003 (279.50 mm)	10.859 (275.80 mm)	10.897 (276.80 mm)	85.0	10.654 (270.60 mm)	10.692 (271.60 mm)	N/A	N/A	N/A	N/A	N/A	N/A	
9.875	62.80	0.625	FenarisHydril® Blue	Standard	8.469	Standard API Drift	5.72 (145.2 mm)	1.60 (40.8 mm)	8.614 (218.78 mm)	8.637 (219.38 mm)	9.875 (250.84 mm)	9.974 (253.32 mm)	5.72 (145.2 mm)	5.12 (130.2 mm)	11.995 (304.50 mm)	11.791 (299.50 mm)	8.680 (220.46 mm)	8.702 (221.04 mm)	10.965 (278.50 mm)	11.003 (279.50 mm)	10.859 (275.80 mm)	10.897 (276.80 mm)	85.0	10.654 (270.60 mm)	10.692 (271.60 mm)	N/A	N/A	N/A	N/A	N/A	N/A	
9.875	62.80	0.625	FenarisHydril® Blue	Standard	8.500	Special Drift	5.72 (145.2 mm)	1.60 (40.8 mm)	8.614 (218.78 mm)	8.637 (219.38 mm)	9.875 (250.84 mm)	9.974 (253.32 mm)	5.72 (145.2 mm)	5.12 (130.2 mm)	11.995 (304.50 mm)	11.791 (299.50 mm)	8.680 (220.46 mm)	8.702 (221.04 mm)	10.965 (278.50 mm)	11.003 (279.50 mm)	10.859 (275.80 mm)	10.897 (276.80 mm)	85.0	10.654 (270.60 mm)	10.692 (271.60 mm)	N/A	N/A	N/A	N/A	N/A	N/A	
9.875	65.30	0.650	Fenaris																													



# TenarisHydril Blue® Blanking Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections B.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request therefore. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyrighted 2019 by an unpublished work. ALL RIGHTS RESERVED.

SIZE (IN)	WEIGHT (LB/FT)	CONNECTION					PIN										BOX																
		WALL (IN)	PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH		RECT LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH		RECT LENGTH		COUPLING LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER - REGULAR		OUTSIDE DIAMETER - MATCHED STRENGTH		OUTSIDE DIAMETER - SPECIAL CLEARANCE #1		OUTSIDE DIAMETER - SPECIAL CLEARANCE #2		OUTSIDE DIAMETER - SPECIAL CLEARANCE #3		
							MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN
10.750	45.50	0.400	FenarisHydril® Blue	Standard	9.794	Standard API Drift	5.72 (145.2 mm)	1.60 (40.8 mm)	9.10 (231.7 mm)	9.93 (252.3 mm)	10.750 (273.0 mm)	10.858 (275.7 mm)	5.72 (145.2 mm)	2.05 (52.0 mm)	11.995 (304.5 mm)	11.791 (299.5 mm)	9.873 (251.3 mm)	9.896 (252.0 mm)	11.556 (293.5 mm)	11.594 (294.5 mm)	11.394 (289.4 mm)	11.433 (290.4 mm)	85.0	11.256 (285.9 mm)	11.295 (286.9 mm)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

# TenarisHydril Blue® Blanking Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, recycled, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections B.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request therefore. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyrighted 2019 as an unpublished work. ALL RIGHTS RESERVED.

CONNECTION							PIN								BOX																
SIZE (IN)	WEIGHT (LB/FT)	WALL (IN)	PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH	RECUT LENGTH	INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH	RECUT LENGTH	COUPLING LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER - REGULAR		OUTSIDE DIAMETER - MATCHED STRENGTH		OUTSIDE DIAMETER - SPECIAL CLEARANCE #1			OUTSIDE DIAMETER - SPECIAL CLEARANCE #2			OUTSIDE DIAMETER - SPECIAL CLEARANCE #3		
							MIN	MIN	MIN	MAX	MIN	MAX	MIN	MIN	MIN	MAX	MIN	MIN	MIN	MAX	MIN	MAX	MIN	MAX	EFFICIENCY	MIN	MAX	EFFICIENCY	MIN	MAX	EFFICIENCY
13.500	81.40	0.580	TenarisHydril® Blue	Standard	12.153	Standard API Drift	6.37 in (161.8 mm)	1.60 in (40.8 mm)	12.329 in (313.14 mm)	12.351 in (313.74 mm)	13.500 in (342.90 mm)	13.635 in (346.32 mm)	6.37 in (161.8 mm)	2.36 in (59.8 mm)	12.894 in (327.50 mm)	13.090 in (332.50 mm)	12.388 in (314.66 mm)	12.411 in (315.24 mm)	14.469 in (367.50 mm)	14.507 in (368.50 mm)	14.441 in (366.80 mm)	14.480 in (367.80 mm)	85.0	14.283 in (362.78 mm)	14.322 in (363.78 mm)	N/A	N/A	N/A	N/A	N/A	N/A
13.500	81.40	0.580	TenarisHydril® Blue	Standard	12.250	Special Drift	6.37 in (161.8 mm)	1.60 in (40.8 mm)	12.329 in (313.14 mm)	12.351 in (313.74 mm)	13.500 in (342.90 mm)	13.635 in (346.32 mm)	6.37 in (161.8 mm)	2.36 in (59.8 mm)	12.894 in (327.50 mm)	13.090 in (332.50 mm)	12.388 in (314.66 mm)	12.411 in (315.24 mm)	14.469 in (367.50 mm)	14.507 in (368.50 mm)	14.441 in (366.80 mm)	14.480 in (367.80 mm)	85.0	14.283 in (362.78 mm)	14.322 in (363.78 mm)	N/A	N/A	N/A	N/A	N/A	N/A
13.625	79.10	0.555	TenarisHydril® Blue	Standard	12.328	Standard API Drift	6.37 in (161.8 mm)	1.60 in (40.8 mm)	12.504 in (317.58 mm)	12.526 in (318.18 mm)	13.625 in (346.08 mm)	13.761 in (349.52 mm)	6.37 in (161.8 mm)	2.08 in (52.8 mm)	12.894 in (327.50 mm)	13.090 in (332.50 mm)	12.467 in (316.66 mm)	12.490 in (317.24 mm)	14.646 in (372.00 mm)	14.685 in (373.00 mm)	14.593 in (370.66 mm)	14.631 in (371.64 mm)	85.0	14.425 in (366.38 mm)	14.463 in (367.38 mm)	N/A	N/A	N/A	N/A	N/A	N/A
13.625	88.20	0.625	TenarisHydril® Blue	Standard	12.188	Standard API Drift	6.37 in (161.8 mm)	1.60 in (40.8 mm)	12.364 in (314.04 mm)	12.387 in (314.62 mm)	13.625 in (346.08 mm)	13.761 in (349.52 mm)	6.37 in (161.8 mm)	2.08 in (52.8 mm)	12.894 in (327.50 mm)	13.090 in (332.50 mm)	12.411 in (315.22 mm)	12.433 in (315.82 mm)	14.646 in (372.00 mm)	14.685 in (373.00 mm)	14.634 in (371.70 mm)	14.673 in (372.70 mm)	85.0	14.422 in (366.30 mm)	14.460 in (367.30 mm)	N/A	N/A	N/A	N/A	N/A	N/A
13.625	88.20	0.625	TenarisHydril® Blue	COP Norway	12.188	Standard API Drift	6.37 in (161.8 mm)	1.60 in (40.8 mm)	12.364 in (314.04 mm)	12.387 in (314.62 mm)	13.625 in (346.08 mm)	13.761 in (349.52 mm)	6.37 in (161.8 mm)	2.08 in (52.8 mm)	12.894 in (327.50 mm)	13.090 in (332.50 mm)	12.411 in (315.22 mm)	12.433 in (315.82 mm)	N/A	N/A	N/A	N/A	85.0	14.422 in (366.30 mm)	14.460 in (367.30 mm)	N/A	N/A	N/A	N/A	N/A	N/A
13.625	88.20	0.625	TenarisHydril® Blue	Standard	12.250	Special Drift	6.37 in (161.8 mm)	1.60 in (40.8 mm)	12.364 in (314.04 mm)	12.387 in (314.62 mm)	13.625 in (346.08 mm)	13.761 in (349.52 mm)	6.37 in (161.8 mm)	2.08 in (52.8 mm)	12.894 in (327.50 mm)	13.090 in (332.50 mm)	12.411 in (315.22 mm)	12.433 in (315.82 mm)	14.646 in (372.00 mm)	14.685 in (373.00 mm)	14.634 in (371.70 mm)	14.673 in (372.70 mm)	85.0	14.422 in (366.30 mm)	14.460 in (367.30 mm)	N/A	N/A	N/A	N/A	N/A	N/A

Dimensions provided do not include length required for tongs for making up assemblies. Please take this into consideration when designing and machining your accessory.  
 BLANK OD and ID: The nominal blank ODs and IDs in the Pin Diameters and Box Diameters columns are finished product dimensions. When this minimum material is supplied, the blank OD and the blank ID must be true to each other within 0.010" TIR (Total Indicator Reading).  
 BLANK Min Length includes 0.02" (0.5mm) extra material for facing.  
 Contact Tenaris Manufacturing Services at [blankingdimensions@tenaris.com](mailto:blankingdimensions@tenaris.com) for details.  
 These Blanking Dimensions are NOT applicable For Handling & lifting plug, HydroTest Caps & HydroTest Plugs.  
 N/A: Not Applicable