

TenarisHydril Wedge 667® Blanking Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, recopied, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections B.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request therefore. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyrighted 2020 as an unpublished work. ALL RIGHTS RESERVED.

CONNECTION							PIN						BOX															
SIZE (IN)	WEIGHT (LB/FT)	WALL (IN)	PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH	RECUT LENGTH	INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH	RECUT LENGTH	COUPLING LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER - REGULAR		OUTSIDE DIAMETER - MATCHED STRENGTH		OUTSIDE DIAMETER - SPECIAL CLEARANCE		OUTSIDE DIAMETER - AS ROLLED			
							MIN	MIN	MIN	MAX	MIN	MAX	MIN	MIN	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX*	EFFICIENCY	MIN	MAX*	MIN	MAX*	
7.625	39.00	0.500	TenarisHydril Wedge 667*	Standard	6.500	Standard API Drift	7.51 in (190.8 mm)	2.73 in (69.2 mm)	6.556 in (166.54 mm)	6.576 in (167.02 mm)	7.625 in (193.68 mm)	7.701 in (195.60 mm)	8.01 in (203.4 mm)	2.73 in (69.2 mm)	15.120 in (384.06 mm)	15.640 in (397.24 mm)	6.526 in (165.78 mm)	6.546 in (166.26 mm)	N/A	N/A	8.146 in (206.92 mm)	8.186 in (207.92 mm)	N/A	7.972 in (202.50 mm)	8.012 in (203.50 mm)	N/A	N/A	
7.625	39.00	0.500	TenarisHydril Wedge 667*	Shell Level A,B	6.500	Standard API Drift	7.51 in (190.8 mm)	2.73 in (69.2 mm)	6.556 in (166.54 mm)	6.576 in (167.02 mm)	7.625 in (193.68 mm)	7.701 in (195.60 mm)	8.01 in (203.4 mm)	2.73 in (69.2 mm)	15.120 in (384.06 mm)	15.640 in (397.24 mm)	6.526 in (165.78 mm)	6.546 in (166.26 mm)	N/A	N/A	8.146 in (206.92 mm)	8.186 in (207.92 mm)	N/A	7.972 in (202.50 mm)	8.012 in (203.50 mm)	N/A	N/A	
7.625	47.10	0.625	TenarisHydril Wedge 667*	Standard	6.250	Standard API Drift	8.66 in (220.0 mm)	2.17 in (55.0 mm)	6.306 in (160.18 mm)	6.326 in (160.68 mm)	7.625 in (193.68 mm)	7.701 in (195.60 mm)	9.17 in (233.0 mm)	2.17 in (55.0 mm)	17.440 in (442.98 mm)	18.030 in (457.96 mm)	6.276 in (159.42 mm)	6.296 in (159.90 mm)	N/A	N/A	8.266 in (209.96 mm)	8.306 in (210.96 mm)	N/A	N/A	N/A	N/A	N/A	N/A
7.625	47.10	0.625	TenarisHydril Wedge 667*	Shell Level A & B	6.250	Standard API Drift	8.66 in (220.0 mm)	2.17 in (55.0 mm)	6.306 in (160.18 mm)	6.326 in (160.68 mm)	7.625 in (193.68 mm)	7.701 in (195.60 mm)	9.17 in (233.0 mm)	2.17 in (55.0 mm)	17.440 in (442.98 mm)	18.030 in (457.96 mm)	6.276 in (159.42 mm)	6.296 in (159.90 mm)	N/A	N/A	8.266 in (209.96 mm)	8.306 in (210.96 mm)	N/A	N/A	N/A	N/A	N/A	N/A
8.625	44.00	0.500	TenarisHydril Wedge 667*	Standard	7.500	Standard API Drift	7.88 in (200.2 mm)	2.53 in (64.2 mm)	7.565 in (192.16 mm)	7.585 in (192.64 mm)	8.625 in (219.08 mm)	8.711 in (221.24 mm)	8.38 in (213.0 mm)	2.19 in (55.8 mm)	15.870 in (403.10 mm)	16.410 in (416.80 mm)	7.531 in (191.30 mm)	7.551 in (191.78 mm)	N/A	N/A	N/A	N/A	100.0	8.974 in (227.94 mm)	9.014 in (228.94 mm)	N/A	N/A	
8.625	44.00	0.500	TenarisHydril Wedge 667*	Shell Level A,B	7.500	Standard API Drift	7.88 in (200.2 mm)	2.53 in (64.2 mm)	7.565 in (192.16 mm)	7.585 in (192.64 mm)	8.625 in (219.08 mm)	8.711 in (221.24 mm)	8.38 in (213.0 mm)	2.19 in (55.8 mm)	15.870 in (403.10 mm)	16.410 in (416.80 mm)	7.531 in (191.30 mm)	7.551 in (191.78 mm)	N/A	N/A	N/A	N/A	100.0	8.974 in (227.94 mm)	9.014 in (228.94 mm)	N/A	N/A	
8.625	57.40	0.656	TenarisHydril Wedge 667*	Standard	7.250	Special Drift	8.76 in (222.4 mm)	2.60 in (66.0 mm)	7.293 in (185.26 mm)	7.313 in (185.74 mm)	8.615 in (218.84 mm)	8.635 in (219.32 mm)	8.68 in (220.4 mm)	2.66 in (67.6 mm)	16.500 in (419.10 mm)	17.050 in (433.06 mm)	7.281 in (184.94 mm)	7.301 in (185.44 mm)	N/A	N/A	N/A	N/A	80.0	8.965 in (227.72 mm)	8.985 in (228.20 mm)	N/A	N/A	
10.750	65.70	0.595	TenarisHydril Wedge 667*	Standard	9.500	Special Drift	8.76 in (222.6 mm)	2.17 in (55.0 mm)	9.550 in (242.58 mm)	9.570 in (243.06 mm)	10.750 in (273.06 mm)	10.858 in (275.78 mm)	9.25 in (234.8 mm)	2.17 in (55.0 mm)	17.590 in (446.80 mm)	18.180 in (461.76 mm)	9.535 in (242.20 mm)	9.555 in (242.68 mm)	11.730 in (297.96 mm)	11.770 in (298.94 mm)	11.419 in (290.06 mm)	11.459 in (291.04 mm)	N/A	N/A	N/A	11.688 in (296.88 mm)	11.867 in (301.42 mm)	
10.750	65.70	0.595	TenarisHydril Wedge 667*	Standard	9.504	Special Drift	8.76 in (222.6 mm)	2.17 in (55.0 mm)	9.550 in (242.58 mm)	9.570 in (243.06 mm)	10.750 in (273.06 mm)	10.858 in (275.78 mm)	9.25 in (234.8 mm)	2.17 in (55.0 mm)	17.590 in (446.80 mm)	18.180 in (461.76 mm)	9.535 in (242.20 mm)	9.555 in (242.68 mm)	11.730 in (297.96 mm)	11.770 in (298.94 mm)	11.419 in (290.06 mm)	11.459 in (291.04 mm)	N/A	N/A	N/A	11.688 in (296.88 mm)	11.867 in (301.42 mm)	

Dimensions provided do not include length required for tongs for making up assemblies. Please take this into consideration when designing and machining your accessory.
 BLANK OD and ID: The nominal blank ODs and IDs in the Pin Diameters and Box Diameters columns are finished product dimensions. When this minimum material is supplied, the blank OD and the blank ID must be true to each other within 0.010" TIR (Total Indicator Reading).
 BLANK Min Length includes 0.02" (0.5mm) extra material for facing.
 Contact Tenaris Manufacturing Services at blankingdimensions@tenaris.com for details.
 These Blanking Dimensions are NOT applicable For Handling & lifting plug, HydroTest Caps & HydroTest Plugs.
 N/A: Not Applicable

Yellow - Shaded corresponds to modified from previous document revision.