

# TenarisHydril Blue® Dopeless® Blanking Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, recopied, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections B.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request therefore. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyrighted 2020 as an unpublished work. ALL RIGHTS RESERVED.

SIZE (IN)	WEIGHT (LB/FT)	WALL (IN)	CONNECTION				PIN										BOX									
			PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH		RECUR LENGTH	COUPLING LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER - REGULAR		OUTSIDE DIAMETER - MATCHED STRENGTH		OUTSIDE DIAMETER - SPECIAL CLEARANCE #1		
							MIN	MIN	MIN	MAX	MIN	MAX	MIN	MIN		MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN
3.500	7.70	0.216	TenarisHydril Blue® Dopeless®	Standard	2.943	Standard API Drift	4.27 in (108.4 mm)	1.55 in (39.4 mm)	3.020 in (76.70 mm)	3.043 in (77.30 mm)	3.500 in (88.90 mm)	3.531 in (89.68 mm)	4.27 in (108.4 mm)	2.09 in (53.2 mm)	8.130 in (206.50 mm)	8.326 in (211.50 mm)	3.004 in (76.30 mm)	3.027 in (76.90 mm)	3.918 in (99.50 mm)	3.956 in (100.50 mm)	3.843 in (97.60 mm)	3.881 in (98.60 mm)	85.0	3.772 in (95.80 mm)	3.811 in (96.80 mm)	
3.500	9.20	0.254	TenarisHydril Blue® Dopeless®	Standard	2.867	Standard API Drift	4.27 in (108.4 mm)	1.55 in (39.4 mm)	2.973 in (75.50 mm)	2.996 in (76.10 mm)	3.500 in (88.90 mm)	3.531 in (89.68 mm)	4.27 in (108.4 mm)	2.09 in (53.2 mm)	8.130 in (206.50 mm)	8.326 in (211.50 mm)	2.906 in (73.80 mm)	2.929 in (74.40 mm)	3.918 in (99.50 mm)	3.956 in (100.50 mm)	3.906 in (99.20 mm)	3.944 in (100.20 mm)	85.0	3.823 in (97.10 mm)	3.862 in (98.10 mm)	
3.500	9.20	0.254	TenarisHydril Blue® Dopeless®	Standard	2.900	Special Drift	4.27 in (108.4 mm)	1.55 in (39.4 mm)	2.973 in (75.50 mm)	2.996 in (76.10 mm)	3.500 in (88.90 mm)	3.531 in (89.68 mm)	4.27 in (108.4 mm)	2.09 in (53.2 mm)	8.130 in (206.50 mm)	8.326 in (211.50 mm)	2.934 in (74.50 mm)	2.944 in (74.80 mm)	3.918 in (99.50 mm)	3.956 in (100.50 mm)	3.906 in (99.20 mm)	3.944 in (100.20 mm)	85.0	3.823 in (97.10 mm)	3.862 in (98.10 mm)	
3.500	10.20	0.289	TenarisHydril Blue® Dopeless®	Standard	2.797	Standard API Drift	4.27 in (108.4 mm)	1.55 in (39.4 mm)	2.910 in (73.90 mm)	2.933 in (74.50 mm)	3.500 in (88.90 mm)	3.531 in (89.68 mm)	4.27 in (108.4 mm)	2.09 in (53.2 mm)	8.130 in (206.50 mm)	8.326 in (211.50 mm)	2.835 in (72.00 mm)	2.858 in (72.60 mm)	3.997 in (101.50 mm)	4.035 in (102.50 mm)	3.961 in (100.60 mm)	4.000 in (101.60 mm)	85.0	3.871 in (98.30 mm)	3.909 in (99.30 mm)	
3.500	12.70	0.375	TenarisHydril Blue® Dopeless®	Standard	2.625	Standard API Drift	4.27 in (108.4 mm)	1.55 in (39.4 mm)	2.739 in (69.56 mm)	2.761 in (70.14 mm)	3.500 in (88.90 mm)	3.531 in (89.68 mm)	4.27 in (108.4 mm)	2.09 in (53.2 mm)	8.130 in (206.50 mm)	8.326 in (211.50 mm)	2.709 in (68.80 mm)	2.732 in (69.40 mm)	4.130 in (104.90 mm)	4.169 in (105.90 mm)	4.087 in (103.80 mm)	4.125 in (104.80 mm)	85.0	3.977 in (101.00 mm)	4.015 in (102.00 mm)	
3.500	13.70	0.413	TenarisHydril Blue® Dopeless®	Standard	2.549	Standard API Drift	4.27 in (108.4 mm)	1.55 in (39.4 mm)	2.663 in (67.62 mm)	2.685 in (68.22 mm)	3.500 in (88.90 mm)	3.531 in (89.68 mm)	4.27 in (108.4 mm)	2.09 in (53.2 mm)	8.130 in (206.50 mm)	8.326 in (211.50 mm)	2.678 in (68.00 mm)	2.700 in (68.60 mm)	4.130 in (104.90 mm)	4.169 in (105.90 mm)	4.138 in (105.10 mm)	4.177 in (106.10 mm)	85.0	4.020 in (102.10 mm)	4.059 in (103.10 mm)	
3.500	14.30	0.430	TenarisHydril Blue® Dopeless®	Standard	2.515	Standard API Drift	4.27 in (108.4 mm)	1.55 in (39.4 mm)	2.629 in (66.76 mm)	2.651 in (67.36 mm)	3.500 in (88.90 mm)	3.531 in (89.68 mm)	4.27 in (108.4 mm)	2.09 in (53.2 mm)	8.130 in (206.50 mm)	8.326 in (211.50 mm)	2.634 in (66.90 mm)	2.657 in (67.50 mm)	4.150 in (105.40 mm)	4.188 in (106.40 mm)	N/A	N/A	85.0	4.036 in (102.50 mm)	4.074 in (103.50 mm)	
3.500	14.70	0.449	TenarisHydril Blue® Dopeless®	Standard	2.477	Standard API Drift	4.27 in (108.4 mm)	1.55 in (39.4 mm)	2.591 in (65.80 mm)	2.613 in (66.38 mm)	3.500 in (88.90 mm)	3.531 in (89.68 mm)	4.27 in (108.4 mm)	2.09 in (53.2 mm)	8.130 in (206.50 mm)	8.326 in (211.50 mm)	2.617 in (66.46 mm)	2.639 in (67.04 mm)	4.174 in (106.00 mm)	4.212 in (107.00 mm)	N/A	N/A	85.0	4.060 in (103.10 mm)	4.098 in (104.10 mm)	
3.500	15.50	0.476	TenarisHydril Blue® Dopeless®	Standard	2.423	Standard API Drift	4.27 in (108.4 mm)	1.55 in (39.4 mm)	2.537 in (64.42 mm)	2.559 in (65.02 mm)	3.500 in (88.90 mm)	3.531 in (89.68 mm)	4.27 in (108.4 mm)	2.09 in (53.2 mm)	8.130 in (206.50 mm)	8.326 in (211.50 mm)	2.617 in (66.46 mm)	2.639 in (67.04 mm)	4.209 in (106.90 mm)	4.248 in (107.90 mm)	N/A	N/A	85.0	4.087 in (103.80 mm)	4.125 in (104.80 mm)	
4.000	8.20	0.190	TenarisHydril Blue® Dopeless®	Standard	3.495	Standard API Drift	4.46 in (113.2 mm)	1.55 in (39.4 mm)	3.544 in (90.00 mm)	3.566 in (90.60 mm)	4.000 in (101.60 mm)	4.031 in (102.38 mm)	4.46 in (113.2 mm)	2.11 in (53.6 mm)	8.682 in (220.50 mm)	8.877 in (225.50 mm)	3.526 in (89.56 mm)	3.549 in (90.14 mm)	4.422 in (112.30 mm)	4.460 in (113.30 mm)	4.300 in (109.20 mm)	4.338 in (110.20 mm)	97.0	4.276 in (108.60 mm)	4.314 in (109.60 mm)	
4.000	9.50	0.226	TenarisHydril Blue® Dopeless®	Standard	3.423	Standard API Drift	4.46 in (113.2 mm)	1.55 in (39.4 mm)	3.481 in (88.40 mm)	3.503 in (89.00 mm)	4.000 in (101.60 mm)	4.031 in (102.38 mm)	4.46 in (113.2 mm)	2.11 in (53.6 mm)	8.682 in (220.50 mm)	8.877 in (225.50 mm)	3.486 in (88.54 mm)	3.486 in (88.54 mm)	4.422 in (112.30 mm)	4.460 in (113.30 mm)	4.363 in (110.80 mm)	4.410 in (111.80 mm)	85.0	4.288 in (109.30 mm)	4.326 in (109.90 mm)	
4.000	10.90	0.262	TenarisHydril Blue® Dopeless®	Standard	3.351	Standard API Drift	4.46 in (113.2 mm)	1.55 in (39.4 mm)	3.438 in (87.30 mm)	3.460 in (87.90 mm)	4.000 in (101.60 mm)	4.031 in (102.38 mm)	4.46 in (113.2 mm)	2.11 in (53.6 mm)	8.682 in (220.50 mm)	8.877 in (225.50 mm)	3.413 in (86.10 mm)	3.413 in (86.10 mm)	4.422 in (112.30 mm)	4.460 in (113.30 mm)	4.422 in (112.30 mm)	4.460 in (113.30 mm)	85.0	4.385 in (110.10 mm)	4.374 in (111.10 mm)	
4.000	13.20	0.330	TenarisHydril Blue® Dopeless®	Standard	3.215	Standard API Drift	4.46 in (113.2 mm)	1.55 in (39.4 mm)	3.329 in (84.54 mm)	3.351 in (85.14 mm)	4.000 in (101.60 mm)	4.031 in (102.38 mm)	4.46 in (113.2 mm)	2.11 in (53.6 mm)	8.682 in (220.50 mm)	8.877 in (225.50 mm)	3.280 in (83.30 mm)	3.303 in (83.90 mm)	4.548 in (115.50 mm)	4.586 in (116.50 mm)	4.528 in (115.00 mm)	4.566 in (116.00 mm)	85.0	4.426 in (112.40 mm)	4.464 in (113.40 mm)	
4.000	14.85	0.380	TenarisHydril Blue® Dopeless®	Standard	3.115	Standard API Drift	4.46 in (113.2 mm)	1.55 in (39.4 mm)	3.229 in (82.00 mm)	3.251 in (82.60 mm)	4.000 in (101.60 mm)	4.031 in (102.38 mm)	4.46 in (113.2 mm)	2.11 in (53.6 mm)	8.682 in (220.50 mm)	8.877 in (225.50 mm)	3.191 in (81.06 mm)	3.214 in (81.64 mm)	4.591 in (116.60 mm)	4.629 in (117.60 mm)	N/A	N/A	85.0	4.489 in (114.00 mm)	4.527 in (115.00 mm)	
4.000	16.10	0.415	TenarisHydril Blue® Dopeless®	Standard	3.045	Standard API Drift	4.46 in (113.2 mm)	1.55 in (39.4 mm)	3.159 in (80.22 mm)	3.181 in (80.82 mm)	4.000 in (101.60 mm)	4.031 in (102.38 mm)	4.46 in (113.2 mm)	2.11 in (53.6 mm)	8.682 in (220.50 mm)	8.877 in (225.50 mm)	3.168 in (80.46 mm)	3.190 in (81.04 mm)	4.642 in (117.90 mm)	4.681 in (118.90 mm)	N/A	N/A	85.0	4.532 in (115.10 mm)	4.570 in (116.10 mm)	
4.000	16.50	0.430	TenarisHydril Blue® Dopeless®	Standard	3.015	Standard API Drift	4.46 in (113.2 mm)	1.55 in (39.4 mm)	3.129 in (79.46 mm)	3.151 in (80.06 mm)	4.000 in (101.60 mm)	4.031 in (102.38 mm)	4.46 in (113.2 mm)	2.11 in (53.6 mm)	8.682 in (220.50 mm)	8.877 in (225.50 mm)	3.159 in (79.66 mm)	3.159 in (80.24 mm)	4.662 in (118.40 mm)	4.700 in (119.40 mm)	N/A	N/A	85.0	4.548 in (115.50 mm)	4.586 in (116.50 mm)	
4.000	18.90	0.500	TenarisHydril Blue® Dopeless®	Standard	2.875	Standard API Drift	4.46 in (113.2 mm)	1.55 in (39.4 mm)	2.989 in (75.90 mm)	3.011 in (76.50 mm)	4.000 in (101.60 mm)	4.031 in (102.38 mm)	4.46 in (113.2 mm)	2.11 in (53.6 mm)	8.682 in (220.50 mm)	8.877 in (225.50 mm)	2.967 in (75.36 mm)	2.990 in (75.94 mm)	4.756 in (120.80 mm)	4.795 in (121.80 mm)	N/A	N/A	85.0	4.630 in (117.60 mm)	4.669 in (118.60 mm)	
4.500	10.50	0.224	TenarisHydril Blue® Dopeless®	Standard	3.927	Standard API Drift	4.67 in (118.6 mm)	1.55 in (39.4 mm)	4.004 in (101.70 mm)	4.027 in (102.30 mm)	4.500 in (114.30 mm)	4.545 in (115.44 mm)	4.67 in (118.6 mm)	2.11 in (53.6 mm)	9.115 in (231.50 mm)	9.311 in (236.50 mm)	3.985 in (101.20 mm)	4.007 in (102.50 mm)	4.902 in (124.50 mm)	4.940 in (125.50 mm)	4.855 in (123.30 mm)	4.893 in (124.30 mm)	85.0	4.780 in (121.40 mm)	4.818 in (122.40 mm)	
4.500	11.60	0.250	TenarisHydril Blue® Dopeless®	Standard	3.875	Standard API Drift	4.67 in (118.6 mm)	1.55 in (39.4 mm)	3.965 in (100.70 mm)	3.988 in (101.30 mm)	4.500 in (114.30 mm)	4.545 in (115.44 mm)	4.67 in (118.6 mm)	2.11 in (53.6 mm)	9.115 in (231.50 mm)	9.311 in (236.50 mm)	3.918 in (99.50 mm)	3.940 in (100.10 mm)	4.902 in (124.50 mm)	4.940 in (125.50 mm)	4.898 in (124.40 mm)	4.937 in (125.40 mm)	85.0	4.815 in (122.30 mm)	4.854 in (123.30 mm)	
4.500	12.60	0.271	TenarisHydril Blue® Dopeless®	Standard	3.833	Standard API Drift	4.67 in (118.6 mm)	1.55 in (39.4 mm)	3.926 in (99.70 mm)	3.948 in (100.30 mm)	4.500 in (114.30 mm)	4.545 in (115.44 mm)	4.67 in (118.6 mm)	2.11 in (53.6 mm)	9.115 in (231.50 mm)	9.311 in (236.50 mm)	3.875 in (98.40 mm)	3.897 in (99.00 mm)	4.941 in (125.50 mm)	4.980 in (126.50 mm)	4.934 in (125.30 mm)	4.972 in (126.30 mm)	85.0	4.847 in (123.10 mm)	4.885 in (124.10 mm)	
4.500	13.50	0.290	TenarisHydril Blue® Dopeless®	Standard	3.795	Standard API Drift	4.67 in (118.6 mm)	1.55 in (39.4 mm)	3.886 in (98.70 mm)	3.909 in (99.30 mm)	4.500 in (114.30 mm)	4.545 in (115.44 mm)	4.67 in (118.6 mm)	2.11 in (53.6 mm)	9.115 in (231.50 mm)	9.311 in (236.50 mm)	3.835 in (97.40 mm)	3.858 in (98.00 mm)	4.981 in (126.50 mm)	5.019 in (127.50 mm)	4.965 in (126.10 mm)	5.003 in (127.10 mm)	85.0	4.871 in (123.70 mm)	4.909 in (124.70 mm)	
4.500	15.20	0.337	TenarisHydril Blue® Dopeless®	Standard	3.701	Standard API Drift	4.67 in (118.6 mm)	1.55 in (39.4 mm)	3.815 in (96.88 mm)	3.837 in (97.48 mm)	4.500 in (114.30 mm)	4.545 in (115.44 mm)	4.67 in (118.6 mm)	2.11 in (53.6 mm)	9.115 in (231.50 mm)	9.311 in (236.50 mm)	3.745 in (95.10 mm)	3.767 in (95.70 mm)	5.028 in (127.70 mm)	5.066 in (128.70 mm)	N/A	N/A	85.0	4.934 in (125.30 mm)	4.972 in (126.30 mm)	
4.500	15.20	0.337	TenarisHydril Blue® Dopeless®	Standard	3.750	Special Drift	4.67 in (118.6 mm)	1.55 in (39.4 mm)	3.831 in (97.30 mm)	3.854 in (97.90 mm)	4.500 in (114.30 mm)	4.545 in (115.44 mm)	4.67 in (118.6 mm)	2.11 in (53.6 mm)	9.115 in (231.50 mm)	9.311 in (236.50 mm)	3.784 in (96.10 mm)	3.795 in (96.40 mm)	5.028 in (127.70 mm)	5.066 in (128.70 mm)	N/A	N/A	85.0	4.934 in (125.30 mm)	4.972 in (126.30 mm)	
4.500	16.60	0.375	TenarisHydril Blue® Dopeless®	Standard	3.625	Standard API Drift	4.67 in (118.6 mm)	1.55 in (39.4 mm)	3.739 in (94.96 mm)	3.761 in (95.54 mm)	4.500 in (114.30 mm)	4.545 in (115.44 mm)	4.67 in (118.6 mm)	2.11 in (53.6 mm)	9.115 in (231.50 mm)	9.311 in (236.50 mm)	3.709 in (94.20 mm)	3.732 in (94.80 mm)	5.087 in (129.20 mm)	5.125 in (130.20 mm)	N/A	N/A	85.0	4.993 in (126.80 mm)	5.031 in (127.80 mm)	
4.500	17.00	0.380	TenarisHydril Blue® Dopeless®	Standard	3.615	Standard API Drift	4.67 in (118.6 mm)	1.55 in (39.4 mm)	3.729 in (94.70 mm)	3.751 in (95.30 mm)	4.500 in (114.30 mm)	4.545 in (115.44 mm)	4.67 in (118.6 mm)	2.11 in (53.6 mm)	9.115 in (231.50 mm)	9.311 in (236.50 mm)	3.699 in (94.54 mm)	3.722 in (95.14 mm)	5.095 in (129.40 mm)	5.133 in (130.40 mm)	N/A	N/A	85.0	4.993 in (126.80 mm)	5.031 in (127.80 mm)	
4.500	17.70	0.402	TenarisHydril Blue® Dopeless®	Standard	3.571	Standard API Drift	4.67 in (118.6 mm)	1.55 in (39.4 mm)	3.685 in (93.58 mm)	3.707 in (94.18 mm)	4.500 in (114.30 mm)	4.545 in (115.44 mm)	4.67 in (118.6 mm)	2.11 in (53.6 mm)	9.115 in (231.50 mm)	9.311 in (236.50 mm)	3.672 in (93.26 mm)	3.694 in (93.84 mm)	5.126 in (130.20 mm)	5.165 in (131.20 mm)	N/A	N/A	85.0	5.020 in (127.50 mm)	5.059 in (128.50 mm)	
4.500	18.90	0.430	TenarisHydril Blue® Dopeless®	Standard	3.515	Standard API Drift	4.67 in (118.6 mm)	1.55 in (39.4 mm)	3.629 in (92.16 mm)	3.651 in (92.76 mm)	4.500 in (114.30 mm)	4.545 in (115.44 mm)	4.67 in (118.6 mm)	2.11 in (53.6 mm)	9.115 in (231.50 mm)	9.311 in (236.50 mm)	3.640 in (92.46 mm)	3.663 in (93.04 mm)	5							

# TenarisHydril Blue® Dopeless® Blanking Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, recopied, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections B.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request therefore. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyrighted 2020 as an unpublished work. ALL RIGHTS RESERVED.

SIZE (IN)	WEIGHT (LB/FT)	WALL (IN)	CONNECTION				PIN										BOX									
			PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH	RECUT LENGTH	COUPLING LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER - REGULAR		OUTSIDE DIAMETER - MATCHED STRENGTH		OUTSIDE DIAMETER - SPECIAL CLEARANCE #1			
							MIN	MIN	MIN	MAX	MIN	MAX			MIN	MIN	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX
5.000	21.40	0.437	TenarisHydril Blue® Dopeless®	Standard	4.001	Standard API Drift	5.23 in (132.8 mm)	1.55 in (39.4 mm)	4.115 in (104.50 mm)	4.137 in (105.10 mm)	5.000 in (127.00 mm)	5.050 in (128.26 mm)	5.23 in (132.8 mm)	2.06 in (52.4 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	4.087 in (103.80 mm)	4.110 in (104.40 mm)	5.674 in (144.10 mm)	5.712 in (145.10 mm)	5.678 in (144.20 mm)	5.716 in (145.20 mm)	85.0	5.544 in (140.80 mm)	5.582 in (141.80 mm)	
5.000	23.20	0.478	TenarisHydril Blue® Dopeless®	Standard	3.919	Standard API Drift	5.23 in (132.8 mm)	1.55 in (39.4 mm)	4.033 in (102.42 mm)	4.055 in (103.02 mm)	5.000 in (127.00 mm)	5.050 in (128.26 mm)	5.23 in (132.8 mm)	2.06 in (52.4 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	4.026 in (102.26 mm)	4.049 in (102.84 mm)	5.737 in (145.70 mm)	5.775 in (146.70 mm)	5.741 in (145.80 mm)	5.779 in (146.80 mm)	85.0	5.595 in (142.10 mm)	5.633 in (143.10 mm)	
5.000	24.10	0.500	TenarisHydril Blue® Dopeless®	Standard	3.875	Standard API Drift	5.23 in (132.8 mm)	1.55 in (39.4 mm)	3.989 in (101.30 mm)	4.011 in (101.90 mm)	5.000 in (127.00 mm)	5.050 in (128.26 mm)	5.23 in (132.8 mm)	2.06 in (52.4 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	3.975 in (100.96 mm)	3.998 in (101.54 mm)	5.768 in (146.50 mm)	5.807 in (147.50 mm)	5.772 in (146.60 mm)	5.811 in (147.60 mm)	85.0	5.623 in (142.80 mm)	5.661 in (143.80 mm)	
5.000	26.70	0.562	TenarisHydril Blue® Dopeless®	Standard	3.751	Standard API Drift	5.23 in (132.8 mm)	1.55 in (39.4 mm)	3.865 in (98.16 mm)	3.887 in (98.74 mm)	5.000 in (127.00 mm)	5.050 in (128.26 mm)	5.23 in (132.8 mm)	2.06 in (52.4 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	3.831 in (97.30 mm)	3.854 in (97.90 mm)	5.855 in (148.70 mm)	5.893 in (149.70 mm)	5.859 in (148.80 mm)	5.897 in (149.80 mm)	85.0	5.693 in (144.60 mm)	5.732 in (145.60 mm)	
5.500	15.50	0.275	TenarisHydril Blue® Dopeless®	Standard	4.825	Standard API Drift	5.33 in (135.4 mm)	1.55 in (39.4 mm)	4.922 in (125.00 mm)	4.944 in (125.60 mm)	5.500 in (139.70 mm)	5.555 in (141.08 mm)	5.33 in (135.4 mm)	2.12 in (53.8 mm)	10.650 in (270.50 mm)	10.846 in (275.50 mm)	4.871 in (123.70 mm)	4.893 in (124.30 mm)	6.044 in (153.50 mm)	6.082 in (154.50 mm)	6.082 in (154.50 mm)	6.111 in (155.10 mm)	85.0	5.831 in (148.10 mm)	5.870 in (149.10 mm)	
5.500	17.00	0.304	TenarisHydril Blue® Dopeless®	Standard	4.767	Standard API Drift	5.33 in (135.4 mm)	1.55 in (39.4 mm)	4.871 in (123.70 mm)	4.893 in (124.30 mm)	5.500 in (139.70 mm)	5.555 in (141.08 mm)	5.33 in (135.4 mm)	2.12 in (53.8 mm)	10.650 in (270.50 mm)	10.846 in (275.50 mm)	4.812 in (122.20 mm)	4.834 in (122.80 mm)	6.044 in (153.50 mm)	6.082 in (154.50 mm)	6.082 in (154.50 mm)	6.111 in (155.10 mm)	85.0	5.875 in (149.20 mm)	5.913 in (150.20 mm)	
5.500	20.00	0.361	TenarisHydril Blue® Dopeless®	Standard	4.653	Standard API Drift	5.33 in (135.4 mm)	1.55 in (39.4 mm)	4.767 in (121.06 mm)	4.789 in (121.66 mm)	5.500 in (139.70 mm)	5.555 in (141.08 mm)	5.33 in (135.4 mm)	2.12 in (53.8 mm)	10.650 in (270.50 mm)	10.846 in (275.50 mm)	4.707 in (119.56 mm)	4.730 in (120.14 mm)	6.083 in (154.50 mm)	6.122 in (155.50 mm)	6.122 in (155.50 mm)	6.161 in (156.10 mm)	85.0	5.953 in (151.20 mm)	5.992 in (152.20 mm)	
5.500	23.00	0.415	TenarisHydril Blue® Dopeless®	Standard	4.545	Standard API Drift	5.33 in (135.4 mm)	1.55 in (39.4 mm)	4.659 in (118.32 mm)	4.681 in (118.92 mm)	5.500 in (139.70 mm)	5.555 in (141.08 mm)	5.33 in (135.4 mm)	2.12 in (53.8 mm)	10.650 in (270.50 mm)	10.846 in (275.50 mm)	4.599 in (116.80 mm)	4.622 in (117.40 mm)	6.162 in (156.50 mm)	6.200 in (157.50 mm)	6.158 in (156.40 mm)	6.196 in (157.40 mm)	85.0	6.024 in (153.00 mm)	6.062 in (154.00 mm)	
5.500	26.00	0.476	TenarisHydril Blue® Dopeless®	Standard	4.423	Standard API Drift	5.33 in (135.4 mm)	1.55 in (39.4 mm)	4.537 in (115.22 mm)	4.559 in (115.82 mm)	5.500 in (139.70 mm)	5.555 in (141.08 mm)	5.33 in (135.4 mm)	2.12 in (53.8 mm)	10.650 in (270.50 mm)	10.846 in (275.50 mm)	4.544 in (115.40 mm)	4.566 in (116.00 mm)	6.288 in (159.70 mm)	6.326 in (160.70 mm)	6.326 in (160.70 mm)	6.361 in (161.70 mm)	85.0	6.103 in (155.00 mm)	6.141 in (156.00 mm)	
5.500	26.80	0.500	TenarisHydril Blue® Dopeless®	Standard	4.375	Standard API Drift	5.33 in (135.4 mm)	1.55 in (39.4 mm)	4.489 in (114.00 mm)	4.511 in (114.60 mm)	5.500 in (139.70 mm)	5.555 in (141.08 mm)	5.33 in (135.4 mm)	2.12 in (53.8 mm)	10.650 in (270.50 mm)	10.846 in (275.50 mm)	4.475 in (113.66 mm)	4.498 in (114.24 mm)	6.288 in (159.70 mm)	6.326 in (160.70 mm)	6.326 in (160.70 mm)	6.361 in (161.70 mm)	85.0	6.134 in (155.80 mm)	6.173 in (156.80 mm)	
5.500	28.40	0.530	TenarisHydril Blue® Dopeless®	Standard	4.315	Standard API Drift	5.33 in (135.4 mm)	1.55 in (39.4 mm)	4.429 in (112.48 mm)	4.451 in (113.08 mm)	5.500 in (139.70 mm)	5.555 in (141.08 mm)	5.33 in (135.4 mm)	2.12 in (53.8 mm)	10.650 in (270.50 mm)	10.846 in (275.50 mm)	4.404 in (111.86 mm)	4.427 in (112.44 mm)	6.331 in (160.80 mm)	6.370 in (161.80 mm)	6.331 in (161.80 mm)	6.370 in (162.80 mm)	85.0	6.170 in (157.00 mm)	6.208 in (158.00 mm)	
5.500	29.70	0.562	TenarisHydril Blue® Dopeless®	Standard	4.251	Standard API Drift	5.33 in (135.4 mm)	1.55 in (39.4 mm)	4.365 in (110.86 mm)	4.387 in (111.44 mm)	5.500 in (139.70 mm)	5.555 in (141.08 mm)	5.33 in (135.4 mm)	2.12 in (53.8 mm)	10.650 in (270.50 mm)	10.846 in (275.50 mm)	4.376 in (111.16 mm)	4.399 in (111.74 mm)	6.363 in (161.60 mm)	6.401 in (162.60 mm)	N/A	N/A	85.0	6.209 in (157.70 mm)	6.248 in (158.70 mm)	
5.500	32.60	0.625	TenarisHydril Blue® Dopeless®	Standard	4.125	Standard API Drift	5.33 in (135.4 mm)	1.55 in (39.4 mm)	4.239 in (107.66 mm)	4.261 in (108.24 mm)	5.500 in (139.70 mm)	5.555 in (141.08 mm)	5.33 in (135.4 mm)	2.12 in (53.8 mm)	10.650 in (270.50 mm)	10.846 in (275.50 mm)	4.284 in (108.80 mm)	4.307 in (109.40 mm)	6.449 in (163.80 mm)	6.488 in (164.80 mm)	N/A	N/A	85.0	6.284 in (159.60 mm)	6.322 in (160.60 mm)	
5.500	35.30	0.687	TenarisHydril Blue® Dopeless®	Standard	4.001	Standard API Drift	5.33 in (135.4 mm)	1.55 in (39.4 mm)	4.115 in (104.50 mm)	4.137 in (105.10 mm)	5.500 in (139.70 mm)	5.555 in (141.08 mm)	5.33 in (135.4 mm)	2.12 in (53.8 mm)	10.650 in (270.50 mm)	10.846 in (275.50 mm)	4.044 in (102.70 mm)	4.066 in (103.30 mm)	6.532 in (166.90 mm)	6.570 in (167.90 mm)	N/A	N/A	N/A	N/A	N/A	
6.625	20.00	0.288	TenarisHydril Blue® Dopeless®	Standard	5.924	Standard API Drift	5.13 in (130.4 mm)	1.60 in (40.8 mm)	5.985 in (152.00 mm)	6.007 in (152.60 mm)	6.625 in (168.28 mm)	6.691 in (169.94 mm)	5.13 in (130.4 mm)	2.05 in (52.0 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	5.962 in (151.42 mm)	5.985 in (152.02 mm)	7.264 in (184.50 mm)	7.303 in (185.50 mm)	7.264 in (184.60 mm)	7.311 in (185.60 mm)	94.0	7.020 in (178.30 mm)	7.059 in (179.30 mm)	
6.625	23.20	0.330	TenarisHydril Blue® Dopeless®	Standard	5.840	Standard API Drift	5.13 in (130.4 mm)	1.60 in (40.8 mm)	5.906 in (150.00 mm)	5.929 in (150.60 mm)	6.625 in (168.28 mm)	6.691 in (169.94 mm)	5.13 in (130.4 mm)	2.05 in (52.0 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	5.906 in (149.42 mm)	5.929 in (150.02 mm)	7.264 in (184.50 mm)	7.303 in (185.50 mm)	7.264 in (184.60 mm)	7.311 in (185.60 mm)	88.0	7.052 in (179.10 mm)	7.090 in (180.10 mm)	
6.625	24.00	0.352	TenarisHydril Blue® Dopeless®	Standard	5.796	Standard API Drift	5.13 in (130.4 mm)	1.60 in (40.8 mm)	5.867 in (149.00 mm)	5.889 in (149.60 mm)	6.625 in (168.28 mm)	6.691 in (169.94 mm)	5.13 in (130.4 mm)	2.05 in (52.0 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	5.844 in (148.42 mm)	5.866 in (149.02 mm)	7.264 in (184.50 mm)	7.303 in (185.50 mm)	7.264 in (184.60 mm)	7.311 in (185.60 mm)	85.0	7.063 in (179.40 mm)	7.102 in (180.40 mm)	
6.625	28.00	0.417	TenarisHydril Blue® Dopeless®	Standard	5.666	Standard API Drift	5.13 in (130.4 mm)	1.60 in (40.8 mm)	5.760 in (146.30 mm)	5.783 in (146.90 mm)	6.625 in (168.28 mm)	6.691 in (169.94 mm)	5.13 in (130.4 mm)	2.05 in (52.0 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	5.738 in (145.72 mm)	5.760 in (146.32 mm)	7.371 in (187.20 mm)	7.409 in (188.20 mm)	7.292 in (187.30 mm)	7.330 in (188.20 mm)	85.0	7.158 in (181.80 mm)	7.196 in (182.80 mm)	
6.625	32.00	0.475	TenarisHydril Blue® Dopeless®	Standard	5.550	Standard API Drift	5.13 in (130.4 mm)	1.60 in (40.8 mm)	5.664 in (143.86 mm)	5.687 in (144.44 mm)	6.625 in (168.28 mm)	6.691 in (169.94 mm)	5.13 in (130.4 mm)	2.05 in (52.0 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	5.667 in (143.92 mm)	5.689 in (144.52 mm)	7.390 in (187.70 mm)	7.429 in (188.70 mm)	7.386 in (188.60 mm)	7.425 in (188.60 mm)	85.0	7.237 in (183.80 mm)	7.275 in (184.80 mm)	
6.625	35.00	0.525	TenarisHydril Blue® Dopeless®	Standard	5.450	Standard API Drift	5.13 in (130.4 mm)	1.60 in (40.8 mm)	5.564 in (141.32 mm)	5.587 in (141.90 mm)	6.625 in (168.28 mm)	6.691 in (169.94 mm)	5.13 in (130.4 mm)	2.05 in (52.0 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	5.608 in (142.42 mm)	5.630 in (143.02 mm)	7.473 in (189.80 mm)	7.511 in (190.80 mm)	7.465 in (189.60 mm)	7.503 in (190.60 mm)	85.0	7.300 in (185.40 mm)	7.338 in (186.40 mm)	
6.625	36.70	0.562	TenarisHydril Blue® Dopeless®	Standard	5.376	Standard API Drift	5.13 in (130.4 mm)	1.60 in (40.8 mm)	5.490 in (139.44 mm)	5.512 in (140.02 mm)	6.625 in (168.28 mm)	6.691 in (169.94 mm)	5.13 in (130.4 mm)	2.05 in (52.0 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	5.612 in (142.52 mm)	5.634 in (143.12 mm)	7.520 in (191.00 mm)	7.559 in (192.00 mm)	7.520 in (191.00 mm)	7.559 in (192.00 mm)	85.0	7.347 in (186.60 mm)	7.385 in (187.60 mm)	
7.000	23.00	0.317	TenarisHydril Blue® Dopeless®	Standard	6.241	Standard API Drift	5.13 in (130.4 mm)	1.60 in (40.8 mm)	6.300 in (160.00 mm)	6.322 in (160.60 mm)	7.000 in (177.80 mm)	7.070 in (179.56 mm)	5.13 in (130.4 mm)	2.09 in (53.0 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	6.276 in (159.40 mm)	6.299 in (160.00 mm)	7.658 in (194.50 mm)	7.696 in (195.50 mm)	7.658 in (194.60 mm)	7.696 in (195.60 mm)	91.0	7.410 in (188.20 mm)	7.448 in (189.20 mm)	
7.000	23.00	0.317	TenarisHydril Blue® Dopeless®	Standard	6.250	Alternative API Drift	5.13 in (130.4 mm)	1.60 in (40.8 mm)	6.300 in (160.00 mm)	6.322 in (160.60 mm)	7.000 in (177.80 mm)	7.070 in (179.56 mm)	5.13 in (130.4 mm)	2.09 in (53.0 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	6.276 in (159.40 mm)	6.299 in (160.00 mm)	7.658 in (194.50 mm)	7.696 in (195.50 mm)	7.658 in (194.60 mm)	7.696 in (195.60 mm)	91.0	7.410 in (188.20 mm)	7.448 in (189.20 mm)	
7.000	24.75	0.343	TenarisHydril Blue® Dopeless®	Standard	6.189	Standard API Drift	5.13 in (130.4 mm)	1.60 in (40.8 mm)	6.241 in (158.50 mm)	6.263 in (159.10 mm)	7.000 in (177.80 mm)	7.070 in (179.56 mm)	5.13 in (130.4 mm)	2.09 in (53.0 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	6.217 in (157.90 mm)	6.240 in (158.50 mm)	7.658 in (194.50 mm)	7.696 in (195.50 mm)	7.532 in (191.30 mm)	7.570 in (192.30 mm)	85.0	7.414 in (188.30 mm)	7.452 in (189.30 mm)	
7.000	26.00	0.362	TenarisHydril Blue® Dopeless®	Standard	6.151	Standard API Drift	5.13 in (130.4 mm)	1.60 in (40.8 mm)	6.201 in (157.50 mm)	6.224 in (158.10 mm)	7.000 in (177.80 mm)	7.070 in (179.56 mm)	5.13 in (130.4 mm)	2.09 in (53.0 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	6.178 in (156.90 mm)	6.200 in (157.50 mm)	7.658 in (194.50 mm)	7.696 in (195.50 mm)	7.563 in (192.10 mm)	7.602 in (193.10 mm)	85.0	7.441 in (189.00 mm)	7.480 in (190.00 mm)	
7.000	26.00	0.362	TenarisHydril Blue® Dopeless®	RNGE	6.151	Standard API Drift	5.13 in (130.4 mm)	1.60 in (40.8 mm)	6.201 in (157.50 mm)	6.224 in (158.10 mm)	7.000 in (177.80 mm)	7.070 in (179.56 mm)	5.13 in (130.4 mm)	2.09 in (53.0 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	6.178 in (156.90 mm)	6.200 in (157.50 mm)	N/A	N/A	N/A	N/A	100.0	7.375 in (187.30 mm)	7.413 in (	

# TenarisHydril Blue® Dopeless® Blanking Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, recopied, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections B.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request therefore. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyrighted 2020 as an unpublished work. ALL RIGHTS RESERVED.

SIZE (IN)	WEIGHT (LB/FT)	WALL (IN)	CONNECTION				PIN										BOX									
			PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH		RECUT LENGTH	COUPLING LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER - REGULAR		OUTSIDE DIAMETER - MATCHED STRENGTH		OUTSIDE DIAMETER - SPECIAL CLEARANCE #1		
							MIN	MIN	MIN	MAX	MIN	MAX	MIN	MIN		MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN
7.000	38.00	0.540	TenarisHydril Blue® Dopeless®	Standard	5.875	Special Drift	5.13 in (130.4 mm)	1.60 in (40.8 mm)	5.909 in (150.08 mm)	5.931 in (150.66 mm)	7.000 in (177.80 mm)	7.070 in (179.56 mm)	5.13 in (130.4 mm)	2.09 in (53.0 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	5.957 in (151.30 mm)	5.980 in (151.90 mm)	7.851 in (199.40 mm)	7.889 in (200.40 mm)	N/A	N/A	85.0	7.686 in (195.20 mm)	7.724 in (196.20 mm)	
7.000	41.00	0.590	TenarisHydril Blue® Dopeless®	Standard	5.695	Standard API Drift	5.13 in (130.4 mm)	1.60 in (40.8 mm)	5.809 in (147.54 mm)	5.831 in (148.12 mm)	7.000 in (177.80 mm)	7.070 in (179.56 mm)	5.13 in (130.4 mm)	2.09 in (53.0 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	5.878 in (149.30 mm)	5.901 in (149.90 mm)	7.930 in (201.40 mm)	7.968 in (202.40 mm)	N/A	N/A	85.0	7.749 in (196.80 mm)	7.787 in (197.80 mm)	
7.000	44.00	0.640	TenarisHydril Blue® Dopeless®	Standard	5.595	Standard API Drift	5.13 in (130.4 mm)	1.60 in (40.8 mm)	5.709 in (145.00 mm)	5.731 in (145.58 mm)	7.000 in (177.80 mm)	7.070 in (179.56 mm)	5.13 in (130.4 mm)	2.09 in (53.0 mm)	10.453 in (265.50 mm)	10.649 in (270.50 mm)	5.835 in (148.20 mm)	5.858 in (148.80 mm)	8.004 in (203.30 mm)	8.043 in (204.30 mm)	7.973 in (202.50 mm)	8.011 in (203.50 mm)	85.0	7.815 in (198.50 mm)	7.854 in (199.50 mm)	
7.250	41.80	0.578	TenarisHydril Blue® Dopeless®	Standard	5.969	Standard API Drift	5.16 in (131.2 mm)	1.60 in (40.8 mm)	6.083 in (154.50 mm)	6.105 in (155.08 mm)	7.250 in (184.16 mm)	7.323 in (186.00 mm)	5.16 in (131.2 mm)	2.32 in (59.0 mm)	10.493 in (266.50 mm)	10.688 in (271.50 mm)	6.087 in (154.60 mm)	6.110 in (155.20 mm)	8.158 in (207.20 mm)	8.196 in (208.20 mm)	8.142 in (206.80 mm)	8.181 in (207.80 mm)	85.0	8.000 in (203.20 mm)	8.039 in (204.20 mm)	
7.250	41.80	0.578	TenarisHydril Blue® Dopeless®	Standard	6.000	Special Drift	5.16 in (131.2 mm)	1.60 in (40.8 mm)	6.083 in (154.50 mm)	6.105 in (155.08 mm)	7.250 in (184.16 mm)	7.323 in (186.00 mm)	5.16 in (131.2 mm)	2.32 in (59.0 mm)	10.493 in (266.50 mm)	10.688 in (271.50 mm)	6.087 in (154.60 mm)	6.110 in (155.20 mm)	8.158 in (207.20 mm)	8.196 in (208.20 mm)	8.142 in (206.80 mm)	8.181 in (207.80 mm)	85.0	8.000 in (203.20 mm)	8.039 in (204.20 mm)	
7.625	29.70	0.375	TenarisHydril Blue® Dopeless®	Standard	6.750	Standard API Drift	5.21 in (132.2 mm)	1.60 in (40.8 mm)	6.815 in (173.10 mm)	6.838 in (173.70 mm)	7.625 in (193.68 mm)	7.701 in (195.60 mm)	5.21 in (132.2 mm)	2.09 in (53.0 mm)	10.571 in (268.50 mm)	10.767 in (273.50 mm)	6.790 in (172.46 mm)	6.812 in (173.04 mm)	8.406 in (213.50 mm)	8.444 in (214.50 mm)	8.201 in (208.30 mm)	8.240 in (209.30 mm)	85.0	8.075 in (205.10 mm)	8.114 in (206.10 mm)	
7.625	33.70	0.430	TenarisHydril Blue® Dopeless®	Standard	6.640	Standard API Drift	5.21 in (132.2 mm)	1.60 in (40.8 mm)	6.713 in (170.50 mm)	6.736 in (171.10 mm)	7.625 in (193.68 mm)	7.701 in (195.60 mm)	5.21 in (132.2 mm)	2.09 in (53.0 mm)	10.571 in (268.50 mm)	10.767 in (273.50 mm)	6.688 in (169.86 mm)	6.710 in (170.44 mm)	8.445 in (214.50 mm)	8.484 in (215.50 mm)	8.296 in (210.70 mm)	8.334 in (211.70 mm)	85.0	8.154 in (207.10 mm)	8.192 in (208.10 mm)	
7.625	35.80	0.465	TenarisHydril Blue® Dopeless®	Standard	6.570	Standard API Drift	5.21 in (132.2 mm)	1.60 in (40.8 mm)	6.674 in (169.50 mm)	6.696 in (170.10 mm)	7.625 in (193.68 mm)	7.701 in (195.60 mm)	5.21 in (132.2 mm)	2.09 in (53.0 mm)	10.571 in (268.50 mm)	10.767 in (273.50 mm)	6.648 in (168.86 mm)	6.671 in (169.44 mm)	8.445 in (214.50 mm)	8.484 in (215.50 mm)	8.355 in (212.20 mm)	8.393 in (213.20 mm)	85.0	8.201 in (208.30 mm)	8.240 in (209.30 mm)	
7.625	39.00	0.500	TenarisHydril Blue® Dopeless®	Standard	6.500	Standard API Drift	5.21 in (132.2 mm)	1.60 in (40.8 mm)	6.614 in (167.98 mm)	6.637 in (168.58 mm)	7.625 in (193.68 mm)	7.701 in (195.60 mm)	5.21 in (132.2 mm)	2.09 in (53.0 mm)	10.571 in (268.50 mm)	10.767 in (273.50 mm)	6.593 in (168.86 mm)	6.616 in (169.44 mm)	8.477 in (214.50 mm)	8.515 in (215.50 mm)	8.414 in (213.20 mm)	8.452 in (214.20 mm)	85.0	8.252 in (209.60 mm)	8.291 in (210.60 mm)	
7.625	42.80	0.562	TenarisHydril Blue® Dopeless®	Standard	6.376	Standard API Drift	5.21 in (132.2 mm)	1.60 in (40.8 mm)	6.490 in (164.84 mm)	6.512 in (165.44 mm)	7.625 in (193.68 mm)	7.701 in (195.60 mm)	5.21 in (132.2 mm)	2.09 in (53.0 mm)	10.571 in (268.50 mm)	10.767 in (273.50 mm)	6.542 in (166.16 mm)	6.564 in (166.74 mm)	8.520 in (216.40 mm)	8.559 in (217.40 mm)	8.512 in (216.20 mm)	8.551 in (217.20 mm)	85.0	8.335 in (211.70 mm)	8.374 in (212.70 mm)	
7.625	45.30	0.595	TenarisHydril Blue® Dopeless®	Standard	6.310	Standard API Drift	5.21 in (132.2 mm)	1.60 in (40.8 mm)	6.424 in (163.16 mm)	6.446 in (163.74 mm)	7.625 in (193.68 mm)	7.701 in (195.60 mm)	5.21 in (132.2 mm)	2.09 in (53.0 mm)	10.571 in (268.50 mm)	10.767 in (273.50 mm)	6.550 in (166.36 mm)	6.572 in (166.94 mm)	8.571 in (217.70 mm)	8.610 in (218.70 mm)	8.563 in (217.50 mm)	8.602 in (218.50 mm)	85.0	8.418 in (212.80 mm)	8.417 in (213.80 mm)	
7.750	46.10	0.595	TenarisHydril Blue® Dopeless®	Standard	6.435	Standard API Drift	5.62 in (142.8 mm)	1.60 in (40.8 mm)	6.549 in (166.32 mm)	6.571 in (166.92 mm)	7.750 in (196.86 mm)	7.828 in (198.82 mm)	5.62 in (142.8 mm)	2.08 in (53.0 mm)	11.398 in (289.50 mm)	11.594 in (294.50 mm)	6.680 in (169.66 mm)	6.702 in (170.24 mm)	8.721 in (221.50 mm)	8.759 in (222.50 mm)	8.678 in (220.40 mm)	8.716 in (221.40 mm)	85.0	8.489 in (215.60 mm)	8.527 in (216.60 mm)	
7.750	46.10	0.595	TenarisHydril Blue® Dopeless®	COP Norway	6.435	Standard API Drift	5.62 in (142.8 mm)	1.60 in (40.8 mm)	6.549 in (166.32 mm)	6.571 in (166.92 mm)	7.750 in (196.86 mm)	7.828 in (198.82 mm)	5.62 in (142.8 mm)	2.08 in (53.0 mm)	11.398 in (289.50 mm)	11.594 in (294.50 mm)	6.680 in (169.66 mm)	6.702 in (170.24 mm)	8.721 in (221.50 mm)	8.759 in (222.50 mm)	N/A	N/A	85.0	8.489 in (215.60 mm)	8.527 in (216.60 mm)	
7.750	46.10	0.595	TenarisHydril Blue® Dopeless®	Standard	6.500	Alternative API Drift	5.62 in (142.8 mm)	1.60 in (40.8 mm)	6.549 in (166.32 mm)	6.571 in (166.92 mm)	7.750 in (196.86 mm)	7.828 in (198.82 mm)	5.62 in (142.8 mm)	2.08 in (53.0 mm)	11.398 in (289.50 mm)	11.594 in (294.50 mm)	6.680 in (169.66 mm)	6.702 in (170.24 mm)	8.721 in (221.50 mm)	8.759 in (222.50 mm)	8.678 in (220.40 mm)	8.716 in (221.40 mm)	85.0	8.489 in (215.60 mm)	8.527 in (216.60 mm)	
7.750	46.10	0.595	TenarisHydril Blue® Dopeless®	COP Norway	6.500	Alternative API Drift	5.62 in (142.8 mm)	1.60 in (40.8 mm)	6.549 in (166.32 mm)	6.571 in (166.92 mm)	7.750 in (196.86 mm)	7.828 in (198.82 mm)	5.62 in (142.8 mm)	2.08 in (53.0 mm)	11.398 in (289.50 mm)	11.594 in (294.50 mm)	6.680 in (169.66 mm)	6.702 in (170.24 mm)	8.721 in (221.50 mm)	8.759 in (222.50 mm)	N/A	N/A	85.0	8.489 in (215.60 mm)	8.527 in (216.60 mm)	
7.750	47.60	0.625	TenarisHydril Blue® Dopeless®	Standard	6.375	Standard API Drift	5.62 in (142.8 mm)	1.60 in (40.8 mm)	6.489 in (164.80 mm)	6.511 in (165.40 mm)	7.750 in (196.86 mm)	7.828 in (198.82 mm)	5.62 in (142.8 mm)	2.08 in (53.0 mm)	11.398 in (289.50 mm)	11.594 in (294.50 mm)	6.621 in (168.16 mm)	6.643 in (168.74 mm)	8.721 in (221.50 mm)	8.759 in (222.50 mm)	8.725 in (221.60 mm)	8.763 in (222.60 mm)	85.0	8.528 in (216.60 mm)	8.566 in (217.60 mm)	
7.750	48.60	0.640	TenarisHydril Blue® Dopeless®	Standard	6.345	Standard API Drift	5.62 in (142.8 mm)	1.60 in (40.8 mm)	6.459 in (164.04 mm)	6.481 in (164.64 mm)	7.750 in (196.86 mm)	7.828 in (198.82 mm)	5.62 in (142.8 mm)	2.08 in (53.0 mm)	11.398 in (289.50 mm)	11.594 in (294.50 mm)	6.589 in (167.34 mm)	6.612 in (167.94 mm)	8.752 in (222.30 mm)	8.791 in (223.30 mm)	8.745 in (222.10 mm)	8.783 in (223.10 mm)	85.0	8.548 in (217.10 mm)	8.586 in (218.10 mm)	
7.750	51.80	0.687	TenarisHydril Blue® Dopeless®	Standard	6.251	Standard API Drift	5.62 in (142.8 mm)	1.60 in (40.8 mm)	6.365 in (161.66 mm)	6.387 in (162.24 mm)	7.750 in (196.86 mm)	7.828 in (198.82 mm)	5.62 in (142.8 mm)	2.08 in (53.0 mm)	11.398 in (289.50 mm)	11.594 in (294.50 mm)	6.495 in (165.54 mm)	6.517 in (166.14 mm)	8.823 in (224.10 mm)	8.862 in (225.10 mm)	8.819 in (224.00 mm)	8.858 in (225.00 mm)	85.0	8.607 in (218.60 mm)	8.645 in (219.60 mm)	
7.750	56.10	0.750	TenarisHydril Blue® Dopeless®	Standard	6.125	Standard API Drift	5.62 in (142.8 mm)	1.60 in (40.8 mm)	6.239 in (158.46 mm)	6.261 in (159.04 mm)	7.750 in (196.86 mm)	7.828 in (198.82 mm)	5.62 in (142.8 mm)	2.08 in (53.0 mm)	11.398 in (289.50 mm)	11.594 in (294.50 mm)	6.369 in (161.76 mm)	6.391 in (162.34 mm)	8.918 in (226.50 mm)	8.956 in (227.50 mm)	8.910 in (226.30 mm)	8.948 in (227.30 mm)	85.0	8.686 in (220.60 mm)	8.724 in (221.60 mm)	
8.625	36.00	0.400	TenarisHydril Blue® Dopeless®	Standard	7.700	Standard API Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	7.804 in (198.20 mm)	7.826 in (198.80 mm)	8.625 in (219.08 mm)	8.711 in (221.24 mm)	5.72 in (145.2 mm)	2.08 in (52.8 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	7.776 in (197.50 mm)	7.799 in (198.10 mm)	9.469 in (240.50 mm)	9.507 in (241.50 mm)	9.245 in (234.80 mm)	9.283 in (235.80 mm)	87.0	9.126 in (231.80 mm)	9.165 in (232.80 mm)	
8.625	40.00	0.450	TenarisHydril Blue® Dopeless®	Standard	7.600	Standard API Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	7.714 in (195.92 mm)	7.737 in (196.52 mm)	8.625 in (219.08 mm)	8.711 in (221.24 mm)	5.72 in (145.2 mm)	2.08 in (52.8 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	7.697 in (195.50 mm)	7.720 in (196.10 mm)	9.469 in (240.50 mm)	9.507 in (241.50 mm)	9.331 in (237.00 mm)	9.370 in (238.00 mm)	85.0	9.182 in (233.20 mm)	9.220 in (234.20 mm)	
8.625	40.00	0.450	TenarisHydril Blue® Dopeless®	Standard	7.625	Alternative API Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	7.714 in (195.92 mm)	7.737 in (196.52 mm)	8.625 in (219.08 mm)	8.711 in (221.24 mm)	5.72 in (145.2 mm)	2.08 in (52.8 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	7.697 in (195.50 mm)	7.720 in (196.10 mm)	9.469 in (240.50 mm)	9.507 in (241.50 mm)	9.331 in (237.00 mm)	9.370 in (238.00 mm)	85.0	9.182 in (233.20 mm)	9.220 in (234.20 mm)	
8.625	44.00	0.500	TenarisHydril Blue® Dopeless®	Standard	7.500	Standard API Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	7.614 in (193.38 mm)	7.637 in (193.98 mm)	8.625 in (219.08 mm)	8.711 in (221.24 mm)	5.72 in (145.2 mm)	2.08 in (52.8 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	7.638 in (194.00 mm)	7.661 in (194.60 mm)	9.469 in (240.50 mm)	9.507 in (241.50 mm)	9.418 in (239.20 mm)	9.456 in (240.20 mm)	85.0	9.252 in (235.00 mm)	9.291 in (236.00 mm)	
8.625	49.00	0.557	TenarisHydril Blue® Dopeless®	Standard	7.386	Standard API Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	7.500 in (190.48 mm)	7.522 in (191.08 mm)	8.625 in (219.08 mm)	8.711 in (221.24 mm)	5.72 in (145.2 mm)	2.08 in (52.8 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	7.524 in (191.10 mm)	7.547 in (191.70 mm)	9.607 in (244.00 mm)	9.645 in (245.00 mm)	9.512 in (241.60 mm)	9.551 in (242.60 mm)	85.0	9.331 in (237.00 mm)	9.370 in (238.00 mm)	
8.625	52.00	0.595	TenarisHydril Blue® Dopeless®	Standard	7.310	Standard API Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	7.424 in (188.56 mm)	7.446 in (189.14 mm)	8.625 in (219.08 mm)	8.711 in (221.24 mm)	5.72 in (145.2 mm)	2.08 in (52.8 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	7.485 in (190.10 mm)	7.507 in (190.70 mm)	9.607 in (244.00 mm)	9.645 in (245.00 mm)	9.575 in (243.20 mm)	9.614 in (244.20 mm)	85.0	9.382 in (238.30 mm)	9.421 in (239.30 mm)	
8.625	54.00	0.625	TenarisHydril Blue® Dopeless®	Standard	7.250	Standard API Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	7.364 in (187.04 mm)	7.387 in (187.62 mm)	8.625 in (219.08 mm)	8.711 in (221.24 mm)	5.72 in (145.2 mm)	2.08 in (52.8 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	7.426 in (188.60 mm)	7.448 in (189.20 mm)	9.619 in (244.30 mm)	9.657 in (245.30 mm)	N/A					

# TenarisHydril Blue® Dopeless® Blanking Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, recopied, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections B.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request therefore. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyrighted 2020 as an unpublished work. ALL RIGHTS RESERVED.

SIZE (IN)	WEIGHT (LB/FT)	WALL (IN)	CONNECTION				PIN										BOX									
			PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH		RECUT LENGTH	COUPLING LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER - REGULAR		OUTSIDE DIAMETER - MATCHED STRENGTH		OUTSIDE DIAMETER - SPECIAL CLEARANCE #1		
							MIN	MIN	MIN	MAX	MIN	MAX	MIN	MIN		MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN
9.625	47.00	0.472	TenarisHydril Blue® Dopeless®	Standard	8.540	Special Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	8.670 in (220.2 mm)	8.692 in (220.8 mm)	9.625 in (244.48 mm)	9.721 in (246.90 mm)	5.72 in (145.2 mm)	2.10 in (53.4 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	8.648 in (219.66 mm)	8.671 in (220.24 mm)	10.607 in (269.40 mm)	10.645 in (270.40 mm)	10.378 in (263.60 mm)	10.417 in (264.60 mm)	85.0	10.217 in (259.50 mm)	10.255 in (260.50 mm)	
9.625	47.00	0.472	TenarisHydril Blue® Dopeless®	Standard	8.614	Special Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	8.670 in (220.2 mm)	8.692 in (220.8 mm)	9.625 in (244.48 mm)	9.721 in (246.90 mm)	5.72 in (145.2 mm)	2.10 in (53.4 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	8.648 in (219.66 mm)	8.671 in (220.24 mm)	10.607 in (269.40 mm)	10.645 in (270.40 mm)	10.378 in (263.60 mm)	10.417 in (264.60 mm)	85.0	10.217 in (259.50 mm)	10.255 in (260.50 mm)	
9.625	53.50	0.545	TenarisHydril Blue® Dopeless®	Standard	8.379	Standard API Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	8.524 in (216.50 mm)	8.546 in (217.08 mm)	9.625 in (244.48 mm)	9.721 in (246.90 mm)	5.72 in (145.2 mm)	2.10 in (53.4 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	8.534 in (216.76 mm)	8.557 in (217.34 mm)	10.607 in (269.40 mm)	10.645 in (270.40 mm)	10.504 in (266.80 mm)	10.543 in (267.80 mm)	85.0	10.323 in (262.20 mm)	10.362 in (263.20 mm)	
9.625	53.50	0.545	TenarisHydril Blue® Dopeless®	Standard	8.500	Alternative API Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	8.524 in (216.50 mm)	8.546 in (217.08 mm)	9.625 in (244.48 mm)	9.721 in (246.90 mm)	5.72 in (145.2 mm)	2.10 in (53.4 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	8.534 in (216.76 mm)	8.557 in (217.34 mm)	10.607 in (269.40 mm)	10.645 in (270.40 mm)	10.504 in (266.80 mm)	10.543 in (267.80 mm)	85.0	10.323 in (262.20 mm)	10.362 in (263.20 mm)	
9.625	53.50	0.545	TenarisHydril Blue® Dopeless®	Statoil	8.508	Special Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	8.571 in (217.70 mm)	8.586 in (218.10 mm)	9.625 in (244.48 mm)	9.745 in (247.52 mm)	5.72 in (145.2 mm)	2.10 in (53.4 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	8.542 in (216.96 mm)	8.557 in (217.34 mm)	10.607 in (269.40 mm)	10.645 in (270.40 mm)	10.504 in (266.80 mm)	10.543 in (267.80 mm)	85.0	10.323 in (262.20 mm)	10.362 in (263.20 mm)	
9.625	58.40	0.595	TenarisHydril Blue® Dopeless®	Standard	8.279	Standard API Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	8.424 in (213.96 mm)	8.446 in (214.54 mm)	9.625 in (244.48 mm)	9.721 in (246.90 mm)	5.72 in (145.2 mm)	2.10 in (53.4 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	8.483 in (215.46 mm)	8.505 in (216.04 mm)	10.607 in (269.40 mm)	10.645 in (270.40 mm)	10.587 in (268.90 mm)	10.625 in (269.90 mm)	85.0	10.394 in (264.00 mm)	10.433 in (265.00 mm)	
9.625	58.40	0.595	TenarisHydril Blue® Dopeless®	Standard	8.375	Alternative API Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	8.424 in (213.96 mm)	8.446 in (214.54 mm)	9.625 in (244.48 mm)	9.721 in (246.90 mm)	5.72 in (145.2 mm)	2.10 in (53.4 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	8.483 in (215.46 mm)	8.505 in (216.04 mm)	10.607 in (269.40 mm)	10.645 in (270.40 mm)	10.587 in (268.90 mm)	10.625 in (269.90 mm)	85.0	10.394 in (264.00 mm)	10.433 in (265.00 mm)	
9.625	59.40	0.609	TenarisHydril Blue® Dopeless®	Standard	8.251	Standard API Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	8.396 in (213.24 mm)	8.418 in (213.84 mm)	9.625 in (244.48 mm)	9.721 in (246.90 mm)	5.72 in (145.2 mm)	2.10 in (53.4 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	8.542 in (216.96 mm)	8.564 in (217.54 mm)	10.607 in (269.40 mm)	10.645 in (270.40 mm)	N/A	N/A	85.0	10.410 in (264.00 mm)	10.448 in (265.40 mm)	
9.625	61.10	0.625	TenarisHydril Blue® Dopeless®	Standard	8.219	Standard API Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	8.364 in (212.44 mm)	8.387 in (213.02 mm)	9.625 in (244.48 mm)	9.721 in (246.90 mm)	5.72 in (145.2 mm)	2.10 in (53.4 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	8.502 in (216.96 mm)	8.525 in (217.54 mm)	10.634 in (270.10 mm)	10.673 in (271.10 mm)	N/A	N/A	85.0	10.434 in (265.00 mm)	10.472 in (266.00 mm)	
9.625	64.90	0.672	TenarisHydril Blue® Dopeless®	Standard	8.125	Standard API Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	8.270 in (210.04 mm)	8.292 in (210.62 mm)	9.625 in (244.48 mm)	9.721 in (246.90 mm)	5.72 in (145.2 mm)	2.10 in (53.4 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	8.424 in (213.96 mm)	8.446 in (214.54 mm)	10.709 in (272.00 mm)	10.748 in (273.00 mm)	N/A	N/A	85.0	10.497 in (266.60 mm)	10.535 in (267.60 mm)	
9.625	70.30	0.734	TenarisHydril Blue® Dopeless®	Standard	8.001	Standard API Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	8.146 in (206.90 mm)	8.168 in (207.48 mm)	9.625 in (244.48 mm)	9.721 in (246.90 mm)	5.72 in (145.2 mm)	2.10 in (53.4 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	8.345 in (212.54 mm)	8.368 in (213.12 mm)	10.808 in (274.50 mm)	10.846 in (275.50 mm)	N/A	N/A	85.0	10.579 in (268.70 mm)	10.618 in (269.70 mm)	
9.875	62.80	0.625	TenarisHydril Blue® Dopeless®	Standard	8.469	Standard API Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	8.614 in (218.78 mm)	8.637 in (219.38 mm)	9.875 in (250.84 mm)	9.974 in (253.32 mm)	5.72 in (145.2 mm)	2.02 in (51.2 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	8.680 in (220.46 mm)	8.702 in (221.04 mm)	10.965 in (278.50 mm)	11.003 in (279.50 mm)	10.859 in (275.80 mm)	10.897 in (276.80 mm)	85.0	10.654 in (270.60 mm)	10.692 in (271.60 mm)	
9.875	62.80	0.625	TenarisHydril Blue® Dopeless®	Standard	8.500	Special Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	8.614 in (218.78 mm)	8.637 in (219.38 mm)	9.875 in (250.84 mm)	9.974 in (253.32 mm)	5.72 in (145.2 mm)	2.02 in (51.2 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	8.680 in (220.46 mm)	8.702 in (221.04 mm)	10.965 in (278.50 mm)	11.003 in (279.50 mm)	10.859 in (275.80 mm)	10.897 in (276.80 mm)	85.0	10.654 in (270.60 mm)	10.692 in (271.60 mm)	
9.875	65.30	0.650	TenarisHydril Blue® Dopeless®	Standard	8.500	Special Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	8.564 in (217.52 mm)	8.587 in (218.10 mm)	9.875 in (250.84 mm)	9.974 in (253.32 mm)	5.72 in (145.2 mm)	2.02 in (51.2 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	8.647 in (219.62 mm)	8.670 in (220.22 mm)	10.965 in (278.50 mm)	11.003 in (279.50 mm)	10.859 in (275.80 mm)	10.897 in (276.80 mm)	85.0	10.693 in (271.60 mm)	10.732 in (272.60 mm)	
9.875	66.90	0.668	TenarisHydril Blue® Dopeless®	Standard	8.383	Standard API Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	8.528 in (217.52 mm)	8.550 in (218.10 mm)	9.875 in (250.84 mm)	9.974 in (253.32 mm)	5.72 in (145.2 mm)	2.02 in (51.2 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	8.635 in (219.32 mm)	8.658 in (219.92 mm)	10.965 in (278.50 mm)	11.003 in (279.50 mm)	10.890 in (276.60 mm)	10.929 in (277.60 mm)	85.0	10.717 in (272.20 mm)	10.755 in (273.20 mm)	
9.875	66.90	0.668	TenarisHydril Blue® Dopeless®	Standard	8.500	Special Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	8.528 in (217.52 mm)	8.550 in (218.10 mm)	9.875 in (250.84 mm)	9.974 in (253.32 mm)	5.72 in (145.2 mm)	2.02 in (51.2 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	8.635 in (219.32 mm)	8.658 in (219.92 mm)	10.965 in (278.50 mm)	11.003 in (279.50 mm)	10.890 in (276.60 mm)	10.929 in (277.60 mm)	85.0	10.717 in (272.20 mm)	10.755 in (273.20 mm)	
9.875	68.80	0.700	TenarisHydril Blue® Dopeless®	Standard	8.319	Standard API Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	8.464 in (214.98 mm)	8.487 in (215.56 mm)	9.875 in (250.84 mm)	9.974 in (253.32 mm)	5.72 in (145.2 mm)	2.02 in (51.2 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	8.581 in (218.54 mm)	8.604 in (219.12 mm)	10.965 in (278.50 mm)	11.003 in (279.50 mm)	N/A	N/A	85.0	10.756 in (273.20 mm)	10.795 in (274.20 mm)	
9.875	68.80	0.700	TenarisHydril Blue® Dopeless®	COP UK	8.500	Special Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	8.562 in (217.48 mm)	8.585 in (218.06 mm)	9.925 in (252.10 mm)	10.073 in (255.84 mm)	5.72 in (145.2 mm)	2.02 in (51.2 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	8.581 in (217.96 mm)	8.604 in (218.54 mm)	10.965 in (278.50 mm)	11.003 in (279.50 mm)	N/A	N/A	85.0	10.756 in (273.20 mm)	10.795 in (274.20 mm)	
9.875	70.40	0.707	TenarisHydril Blue® Dopeless®	Standard	8.305	Standard API Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	8.450 in (214.62 mm)	8.472 in (215.20 mm)	9.875 in (250.84 mm)	9.974 in (253.32 mm)	5.72 in (145.2 mm)	2.02 in (51.2 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	8.597 in (218.36 mm)	8.620 in (218.94 mm)	10.965 in (278.50 mm)	11.003 in (279.50 mm)	N/A	N/A	85.0	10.768 in (273.50 mm)	10.807 in (274.50 mm)	
9.875	72.10	0.725	TenarisHydril Blue® Dopeless®	Standard	8.269	Standard API Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	8.414 in (213.70 mm)	8.437 in (214.30 mm)	9.875 in (250.84 mm)	9.974 in (253.32 mm)	5.72 in (145.2 mm)	2.02 in (51.2 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	8.562 in (217.46 mm)	8.584 in (218.04 mm)	11.012 in (279.70 mm)	11.051 in (280.70 mm)	N/A	N/A	85.0	10.792 in (274.10 mm)	10.830 in (275.10 mm)	
10.250	82.00	0.800	TenarisHydril Blue® Dopeless®	Standard	8.494	Standard API Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	8.639 in (219.42 mm)	8.661 in (220.00 mm)	10.250 in (260.36 mm)	10.353 in (262.96 mm)	5.72 in (145.2 mm)	2.34 in (59.4 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	8.859 in (225.00 mm)	8.881 in (225.60 mm)	11.560 in (293.60 mm)	11.598 in (294.60 mm)	11.528 in (292.80 mm)	11.566 in (293.80 mm)	85.0	11.331 in (287.80 mm)	11.370 in (288.80 mm)	
10.250	82.00	0.800	TenarisHydril Blue® Dopeless®	Standard	8.500	Special Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	8.639 in (219.42 mm)	8.661 in (220.00 mm)	10.250 in (260.36 mm)	10.353 in (262.96 mm)	5.72 in (145.2 mm)	2.34 in (59.4 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	8.859 in (225.00 mm)	8.881 in (225.60 mm)	11.560 in (293.60 mm)	11.598 in (294.60 mm)	11.528 in (292.80 mm)	11.566 in (293.80 mm)	85.0	11.331 in (287.80 mm)	11.370 in (288.80 mm)	
10.750	40.50	0.350	TenarisHydril Blue® Dopeless®	Standard	9.894	Standard API Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	9.989 in (253.70 mm)	10.011 in (254.30 mm)	10.750 in (273.06 mm)	10.858 in (275.78 mm)	5.72 in (145.2 mm)	2.05 in (52.0 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	9.952 in (252.78 mm)	9.975 in (253.36 mm)	11.556 in (293.50 mm)	11.594 in (294.50 mm)	11.304 in (287.10 mm)	11.342 in (288.10 mm)	91.0	11.217 in (284.90 mm)	11.255 in (285.90 mm)	
10.750	45.50	0.400	TenarisHydril Blue® Dopeless®	Standard	9.794	Standard API Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	9.910 in (251.70 mm)	9.933 in (252.30 mm)	10.750 in (273.06 mm)	10.858 in (275.78 mm)	5.72 in (145.2 mm)	2.05 in (52.0 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	9.873 in (250.78 mm)	9.896 in (251.36 mm)	11.556 in (293.50 mm)	11.594 in (294.50 mm)	11.394 in (289.40 mm)	11.433 in (290.40 mm)	85.0	11.256 in (285.90 mm)	11.295 in (286.90 mm)	
10.750	45.50	0.400	TenarisHydril Blue® Dopeless®	Standard	9.875	Alternative API Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	9.946 in (252.62 mm)	9.971 in (253.20 mm)	10.750 in (273.06 mm)	10.858 in (275.78 mm)	5.72 in (145.2 mm)	2.05 in (52.0 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	9.909 in (251.68 mm)	9.920 in (252.26 mm)	11.556 in (293.50 mm)	11.594 in (294.50 mm)	11.394 in (289.40 mm)	11.433 in (290.40 mm)	85.0	11.256 in (285.90 mm)	11.295 in (286.90 mm)	
10.750	51.00	0.450	TenarisHydril Blue® Dopeless®	Standard	9.694	Standard API Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	9.831 in (249.70 mm)	9.854 in (250.30 mm)	10.750 in (273.06 mm)	10.858 in (275.78 mm)	5.72 in (145.2 mm)	2.05 in (52.0 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	9.795 in (248.78 mm)	9.817 in (249.36 mm)								



# TenarisHydril Blue® Dopeless® Blanking Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, recopied, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections B.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request therefore. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyrighted 2020 as an unpublished work. ALL RIGHTS RESERVED.

SIZE (IN)	WEIGHT (LB/FT)	WALL (IN)	CONNECTION				PIN								BOX										
			PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH	RECUT LENGTH	COUPLING LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER - REGULAR		OUTSIDE DIAMETER - MATCHED STRENGTH		OUTSIDE DIAMETER - SPECIAL CLEARANCE #1		
							MIN	MIN	MIN	MAX	MIN	MAX			MIN	MIN	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN
10.750	60.70	0.545	TenarisHydril Blue® Dopeless®	Standard	9.604	Special Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	9.649 in (245.06 mm)	9.671 in (245.66 mm)	10.750 in (273.06 mm)	10.890 in (276.60 mm)	5.72 in (145.2 mm)	2.05 in (52.0 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	9.680 in (245.88 mm)	9.703 in (246.46 mm)	11.729 in (297.90 mm)	11.767 in (298.90 mm)	11.650 in (295.90 mm)	11.688 in (296.90 mm)	85.0	11.469 in (291.30 mm)	11.507 in (292.30 mm)
10.750	65.70	0.595	TenarisHydril Blue® Dopeless®	Standard	9.404	Standard API Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	9.549 in (242.52 mm)	9.571 in (243.12 mm)	10.750 in (273.06 mm)	10.858 in (275.78 mm)	5.72 in (145.2 mm)	2.05 in (52.0 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	9.621 in (244.38 mm)	9.644 in (244.96 mm)	11.871 in (301.50 mm)	11.909 in (302.50 mm)	11.737 in (298.10 mm)	11.775 in (299.10 mm)	85.0	11.540 in (293.10 mm)	11.578 in (294.10 mm)
10.750	65.70	0.595	TenarisHydril Blue® Dopeless®	COP Norway	9.404	Standard API Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	9.549 in (242.52 mm)	9.571 in (243.12 mm)	10.750 in (273.06 mm)	10.858 in (275.78 mm)	5.72 in (145.2 mm)	2.05 in (52.0 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	9.621 in (244.38 mm)	9.644 in (244.96 mm)	N/A	N/A	N/A	N/A	85.0	11.540 in (293.10 mm)	11.578 in (294.10 mm)
10.750	65.70	0.595	TenarisHydril Blue® Dopeless®	Standard	9.500	Special Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	9.549 in (242.52 mm)	9.571 in (243.12 mm)	10.750 in (273.06 mm)	10.858 in (275.78 mm)	5.72 in (145.2 mm)	2.05 in (52.0 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	9.621 in (244.38 mm)	9.644 in (244.96 mm)	11.871 in (301.50 mm)	11.909 in (302.50 mm)	11.737 in (298.10 mm)	11.775 in (299.10 mm)	85.0	11.540 in (293.10 mm)	11.578 in (294.10 mm)
10.750	65.70	0.595	TenarisHydril Blue® Dopeless®	COP Norway	9.500	Special Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	9.549 in (242.52 mm)	9.571 in (243.12 mm)	10.750 in (273.06 mm)	10.858 in (275.78 mm)	5.72 in (145.2 mm)	2.05 in (52.0 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	9.621 in (244.38 mm)	9.644 in (244.96 mm)	N/A	N/A	N/A	N/A	85.0	11.540 in (293.10 mm)	11.578 in (294.10 mm)
10.750	65.70	0.595	TenarisHydril Blue® Dopeless®	Standard	9.504	Special Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	9.549 in (242.52 mm)	9.571 in (243.12 mm)	10.750 in (273.06 mm)	10.858 in (275.78 mm)	5.72 in (145.2 mm)	2.05 in (52.0 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	9.621 in (244.38 mm)	9.644 in (244.96 mm)	11.871 in (301.50 mm)	11.909 in (302.50 mm)	11.737 in (298.10 mm)	11.775 in (299.10 mm)	85.0	11.540 in (293.10 mm)	11.578 in (294.10 mm)
10.750	65.70	0.595	TenarisHydril Blue® Dopeless®	PETROBRAS	9.504	Special Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	9.549 in (242.52 mm)	9.571 in (243.12 mm)	10.750 in (273.06 mm)	10.858 in (275.78 mm)	5.72 in (145.2 mm)	2.05 in (52.0 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	9.621 in (244.38 mm)	9.644 in (244.96 mm)	N/A	N/A	N/A	N/A	80.0	11.489 in (291.80 mm)	11.527 in (292.80 mm)
10.750	65.70	0.595	TenarisHydril Blue® Dopeless®	COP Norway	9.504	Special Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	9.549 in (242.52 mm)	9.571 in (243.12 mm)	10.750 in (273.06 mm)	10.858 in (275.78 mm)	5.72 in (145.2 mm)	2.05 in (52.0 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	9.621 in (244.38 mm)	9.644 in (244.96 mm)	N/A	N/A	N/A	N/A	85.0	11.540 in (293.10 mm)	11.578 in (294.10 mm)
10.750	65.70	0.595	TenarisHydril Blue® Dopeless®	SPR.0026 - ADNOC	9.404	Standard API Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	9.549 in (242.52 mm)	9.571 in (243.12 mm)	10.750 in (273.06 mm)	10.858 in (275.78 mm)	5.72 in (145.2 mm)	2.05 in (52.0 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	9.621 in (244.38 mm)	9.644 in (244.96 mm)	11.871 in (301.50 mm)	11.909 in (302.50 mm)	11.737 in (298.10 mm)	11.775 in (299.10 mm)	85.0	11.540 in (293.10 mm)	11.578 in (294.10 mm)
10.750	71.10	0.650	TenarisHydril Blue® Dopeless®	Standard	9.294	Standard API Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	9.439 in (239.74 mm)	9.461 in (240.32 mm)	10.750 in (273.06 mm)	10.858 in (275.78 mm)	5.72 in (145.2 mm)	2.05 in (52.0 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	9.558 in (242.78 mm)	9.581 in (243.36 mm)	11.871 in (301.50 mm)	11.909 in (302.50 mm)	11.784 in (299.30 mm)	11.822 in (300.30 mm)	85.0	11.615 in (295.00 mm)	11.653 in (296.00 mm)
10.750	73.20	0.672	TenarisHydril Blue® Dopeless®	Standard	9.250	Standard API Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	9.395 in (238.62 mm)	9.417 in (239.20 mm)	10.750 in (273.06 mm)	10.858 in (275.78 mm)	5.72 in (145.2 mm)	2.05 in (52.0 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	9.547 in (242.48 mm)	9.569 in (243.06 mm)	11.910 in (302.50 mm)	11.948 in (303.50 mm)	11.863 in (301.30 mm)	11.901 in (302.30 mm)	85.0	11.646 in (295.80 mm)	11.685 in (296.80 mm)
10.750	76.60	0.700	TenarisHydril Blue® Dopeless®	Standard	9.194	Standard API Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	9.339 in (237.20 mm)	9.361 in (237.78 mm)	10.750 in (273.06 mm)	10.858 in (275.78 mm)	5.72 in (145.2 mm)	2.05 in (52.0 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	9.491 in (241.08 mm)	9.514 in (241.66 mm)	11.910 in (302.50 mm)	11.948 in (303.50 mm)	N/A	N/A	85.0	11.686 in (296.80 mm)	11.724 in (297.80 mm)
10.750	79.20	0.734	TenarisHydril Blue® Dopeless®	Standard	9.126	Standard API Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	9.271 in (235.46 mm)	9.293 in (236.04 mm)	10.750 in (273.06 mm)	10.858 in (275.78 mm)	5.72 in (145.2 mm)	2.05 in (52.0 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	9.440 in (239.78 mm)	9.463 in (240.36 mm)	11.965 in (303.90 mm)	12.003 in (304.90 mm)	N/A	N/A	85.0	11.729 in (297.90 mm)	11.767 in (298.90 mm)
11.750	54.00	0.435	TenarisHydril Blue® Dopeless®	Standard	10.724	Standard API Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	10.869 in (276.06 mm)	10.891 in (276.64 mm)	11.750 in (298.46 mm)	11.868 in (301.44 mm)	5.72 in (145.2 mm)	2.08 in (53.0 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	10.938 in (277.82 mm)	10.961 in (278.42 mm)	12.733 in (323.40 mm)	12.771 in (324.40 mm)	12.669 in (316.70 mm)	12.507 in (317.70 mm)	85.0	12.319 in (312.90 mm)	12.358 in (313.90 mm)
11.750	60.00	0.489	TenarisHydril Blue® Dopeless®	Standard	10.616	Standard API Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	10.761 in (273.32 mm)	10.783 in (273.90 mm)	11.750 in (298.46 mm)	11.868 in (301.44 mm)	5.72 in (145.2 mm)	2.08 in (53.0 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	10.820 in (274.82 mm)	10.843 in (275.42 mm)	12.733 in (323.40 mm)	12.771 in (324.40 mm)	12.567 in (319.20 mm)	12.606 in (320.20 mm)	85.0	12.398 in (314.90 mm)	12.437 in (315.90 mm)
11.750	60.00	0.489	TenarisHydril Blue® Dopeless®	Standard	10.625	Alternative API Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	10.761 in (273.32 mm)	10.783 in (273.90 mm)	11.750 in (298.46 mm)	11.868 in (301.44 mm)	5.72 in (145.2 mm)	2.08 in (53.0 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	10.820 in (274.82 mm)	10.843 in (275.42 mm)	12.733 in (323.40 mm)	12.771 in (324.40 mm)	12.567 in (319.20 mm)	12.606 in (320.20 mm)	85.0	12.398 in (314.90 mm)	12.437 in (315.90 mm)
11.750	65.00	0.534	TenarisHydril Blue® Dopeless®	Standard	10.526	Standard API Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	10.671 in (271.02 mm)	10.693 in (271.62 mm)	11.750 in (298.46 mm)	11.868 in (301.44 mm)	5.72 in (145.2 mm)	2.08 in (53.0 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	10.741 in (272.82 mm)	10.764 in (273.42 mm)	12.733 in (323.40 mm)	12.771 in (324.40 mm)	12.646 in (321.20 mm)	12.685 in (322.20 mm)	85.0	12.465 in (316.60 mm)	12.503 in (317.60 mm)
11.750	65.00	0.534	TenarisHydril Blue® Dopeless®	Standard	10.625	Alternative API Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	10.671 in (271.02 mm)	10.693 in (271.62 mm)	11.750 in (298.46 mm)	11.868 in (301.44 mm)	5.72 in (145.2 mm)	2.08 in (53.0 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	10.741 in (272.82 mm)	10.764 in (273.42 mm)	12.733 in (323.40 mm)	12.771 in (324.40 mm)	12.646 in (321.20 mm)	12.685 in (322.20 mm)	85.0	12.465 in (316.60 mm)	12.503 in (317.60 mm)
11.750	71.00	0.582	TenarisHydril Blue® Dopeless®	Standard	10.430	Standard API Drift	5.72 in (145.2 mm)	1.60 in (40.8 mm)	10.575 in (268.58 mm)	10.597 in (269.18 mm)	11.750 in (298.46 mm)	11.868 in (301.44 mm)	5.72 in (145.2 mm)	2.08 in (53.0 mm)	11.595 in (294.50 mm)	11.791 in (299.50 mm)	10.659 in (270.72 mm)	10.681 in (271.32 mm)	12.733 in (323.40 mm)	12.771 in (324.40 mm)	12.729 in (323.30 mm)	12.767 in (324.30 mm)	85.0	12.532 in (318.30 mm)	12.570 in (319.30 mm)
11.875	58.80	0.470	TenarisHydril Blue® Dopeless®	Standard	10.779	Standard API Drift	6.02 in (152.8 mm)	1.60 in (40.8 mm)	10.924 in (277.46 mm)	10.946 in (278.04 mm)	11.875 in (301.64 mm)	11.994 in (304.64 mm)	6.02 in (152.8 mm)	2.06 in (52.2 mm)	12.186 in (309.50 mm)	12.381 in (314.50 mm)	10.962 in (278.42 mm)	10.985 in (279.02 mm)	12.835 in (326.00 mm)	12.874 in (327.00 mm)	12.638 in (321.00 mm)	12.677 in (322.00 mm)	85.0	12.473 in (316.80 mm)	12.511 in (317.80 mm)
11.875	71.80	0.582	TenarisHydril Blue® Dopeless®	Standard	10.555	Standard API Drift	6.02 in (152.8 mm)	1.60 in (40.8 mm)	10.700 in (271.76 mm)	10.722 in (272.36 mm)	11.875 in (301.64 mm)	11.994 in (304.64 mm)	6.02 in (152.8 mm)	2.06 in (52.2 mm)	12.186 in (309.50 mm)	12.381 in (314.50 mm)	10.867 in (276.62 mm)	10.890 in (277.22 mm)	12.835 in (326.00 mm)	12.874 in (327.00 mm)	12.835 in (326.00 mm)	12.874 in (327.00 mm)	85.0	12.638 in (321.00 mm)	12.677 in (322.00 mm)
13.375	54.50	0.380	TenarisHydril Blue® Dopeless®	Standard	12.459	Standard API Drift	6.37 in (161.8 mm)	1.60 in (40.8 mm)	12.548 in (318.70 mm)	12.570 in (319.30 mm)	13.375 in (339.74 mm)	13.509 in (343.12 mm)	6.37 in (161.8 mm)	2.08 in (53.0 mm)	12.934 in (328.50 mm)	13.129 in (333.50 mm)	12.509 in (317.72 mm)	12.532 in (318.32 mm)	14.154 in (359.50 mm)	14.192 in (360.50 mm)	13.957 in (354.50 mm)	13.996 in (355.50 mm)	90.0	13.859 in (352.00 mm)	13.897 in (353.00 mm)
13.375	61.00	0.430	TenarisHydril Blue® Dopeless®	Standard	12.359	Standard API Drift	6.37 in (161.8 mm)	1.60 in (40.8 mm)	12.469 in (316.70 mm)	12.492 in (317.30 mm)	13.375 in (339.74 mm)	13.509 in (343.12 mm)	6.37 in (161.8 mm)	2.08 in (53.0 mm)	12.934 in (328.50 mm)	13.129 in (333.50 mm)	12.430 in (315.72 mm)	12.453 in (316.32 mm)	14.154 in (359.50 mm)	14.192 in (360.50 mm)	14.052 in (356.90 mm)	14.090 in (357.90 mm)	85.0	13.898 in (353.00 mm)	13.937 in (354.00 mm)
13.375	68.00	0.480	TenarisHydril Blue® Dopeless®	Standard	12.259	Standard API Drift	6.37 in (161.8 mm)	1.60 in (40.8 mm)	12.398 in (314.90 mm)	12.421 in (315.50 mm)	13.375 in (339.74 mm)	13.509 in (343.12 mm)	6.37 in (161.8 mm)	2.08 in (53.0 mm)	12.934 in (328.50 mm)	13.129 in (333.50 mm)	12.360 in (313.92 mm)	12.382 in (314.52 mm)	14.233 in (361.50 mm)	14.271 in (362.50 mm)	14.142 in (359.20 mm)	14.181 in (360.20 mm)	85.0	13.977 in (355.00 mm)	14.015 in (356.00 mm)
13.375	72.00	0.514	TenarisHydril Blue® Dopeless®	Standard	12.191	Standard API Drift	6.37 in (161.8 mm)	1.60 in (40.8 mm)	12.336 in (313.32 mm)	12.358 in (313.90 mm)	13.375 in (339.74 mm)	13.509 in (343.12 mm)	6.37 in (161.8 mm)	2.08 in (53.0 mm)	12.934 in (328.50 mm)	13.129 in (333.50 mm)	12.300 in (312.42 mm)	12.323 in (313.02 mm)	14.233 in (361.50 mm)	14.271 in (362.50 mm)	14.205 in (360.80 mm)	14.244 in (361.80 mm)	85.0	14.028 in (356.30 mm)	14.066 in (357.30 mm)
13.375	72.00	0.514	TenarisHydril Blue® Dopeless®	Standard	12.250	Alternative API Drift	6.37 in (161.8 mm)	1.60 in (40.8 mm)	12.336 in (313.32 mm)	12.358 in (313.90 mm)	13.375 in (339.74 mm)	13.509 in (343.12 mm)	6.37 in (161.8 mm)	2.08 in (53.0 mm)	12.934 in (328.5										

# TenarisHydril Blue® Dopeless® Blanking Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, recopied, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections B.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request therefore. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyrighted 2020 as an unpublished work. ALL RIGHTS RESERVED.

SIZE (IN)	WEIGHT (LB/FT)	WALL (IN)	CONNECTION				PIN								BOX										
			PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH	RECUR LENGTH	INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH	RECUR LENGTH	COUPLING LENGTH		INSIDE DIAMETER		OUTSIDE DIAMETER - REGULAR		OUTSIDE DIAMETER - MATCHED STRENGTH		OUTSIDE DIAMETER - SPECIAL CLEARANCE #1		
									MIN	MAX	MIN	MAX			MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN
13.500	81.40	0.580	TenarisHydril Blue® Dopeless®	Standard	12.250	Special Drift	6.37 in (161.8 mm)	1.60 in (40.8 mm)	12.329 in (313.14 mm)	12.351 in (313.74 mm)	13.500 in (342.90 mm)	13.635 in (346.32 mm)	6.37 in (161.8 mm)	2.36 in (59.8 mm)	12.894 in (327.50 mm)	13.090 in (332.50 mm)	12.388 in (314.66 mm)	12.411 in (315.24 mm)	14.469 in (367.50 mm)	14.507 in (368.50 mm)	14.440 in (366.76 mm)	14.478 in (367.76 mm)	85.0	14.283 in (362.78 mm)	14.322 in (363.78 mm)
13.625	79.10	0.555	TenarisHydril Blue® Dopeless®	Standard	12.328	Standard API Drift	6.37 in (161.8 mm)	1.60 in (40.8 mm)	12.504 in (317.58 mm)	12.526 in (318.18 mm)	13.625 in (346.08 mm)	13.761 in (349.52 mm)	6.37 in (161.8 mm)	2.08 in (52.8 mm)	12.894 in (327.50 mm)	13.090 in (332.50 mm)	12.467 in (316.66 mm)	12.490 in (317.24 mm)	14.646 in (373.00 mm)	14.685 in (373.00 mm)	14.593 in (370.66 mm)	14.631 in (371.64 mm)	85.0	14.425 in (366.38 mm)	14.463 in (367.38 mm)
13.625	88.20	0.625	TenarisHydril Blue® Dopeless®	Standard	12.188	Standard API Drift	6.37 in (161.8 mm)	1.60 in (40.8 mm)	12.364 in (314.04 mm)	12.387 in (314.62 mm)	13.625 in (346.08 mm)	13.761 in (349.52 mm)	6.37 in (161.8 mm)	2.08 in (52.8 mm)	12.894 in (327.50 mm)	13.090 in (332.50 mm)	12.411 in (315.22 mm)	12.433 in (315.82 mm)	14.646 in (373.00 mm)	14.685 in (373.00 mm)	14.634 in (371.70 mm)	14.673 in (372.70 mm)	85.0	14.422 in (366.30 mm)	14.460 in (367.30 mm)
13.625	88.20	0.625	TenarisHydril Blue® Dopeless®	Standard	12.250	Special Drift	6.37 in (161.8 mm)	1.60 in (40.8 mm)	12.364 in (314.04 mm)	12.387 in (314.62 mm)	13.625 in (346.08 mm)	13.761 in (349.52 mm)	6.37 in (161.8 mm)	2.08 in (52.8 mm)	12.894 in (327.50 mm)	13.090 in (332.50 mm)	12.411 in (315.22 mm)	12.433 in (315.82 mm)	14.646 in (373.00 mm)	14.685 in (373.00 mm)	14.634 in (371.70 mm)	14.673 in (372.70 mm)	85.0	14.422 in (366.30 mm)	14.460 in (367.30 mm)
14.000	82.50	0.562	TenarisHydril Blue® Dopeless®	Standard	12.689	Standard API Drift	7.10 in (180.2 mm)	1.60 in (40.8 mm)	12.865 in (326.76 mm)	12.887 in (327.34 mm)	14.000 in (355.60 mm)	14.140 in (359.14 mm)	7.10 in (180.2 mm)	2.09 in (53.0 mm)	14.359 in (364.70 mm)	14.555 in (369.70 mm)	12.919 in (328.14 mm)	12.942 in (328.72 mm)	14.867 in (377.60 mm)	14.905 in (378.60 mm)	14.839 in (376.90 mm)	14.877 in (377.90 mm)	85.0	14.686 in (373.00 mm)	14.724 in (374.00 mm)
14.000	86.00	0.600	TenarisHydril Blue® Dopeless®	Standard	12.613	Standard API Drift	7.10 in (180.2 mm)	1.60 in (40.8 mm)	12.789 in (324.82 mm)	12.811 in (325.42 mm)	14.000 in (355.60 mm)	14.140 in (359.14 mm)	7.10 in (180.2 mm)	2.09 in (53.0 mm)	14.359 in (364.70 mm)	14.555 in (369.70 mm)	12.878 in (327.08 mm)	12.900 in (327.68 mm)	14.934 in (379.30 mm)	14.972 in (380.30 mm)	14.906 in (378.60 mm)	14.944 in (379.60 mm)	85.0	14.741 in (374.40 mm)	14.779 in (375.40 mm)
14.000	93.00	0.650	TenarisHydril Blue® Dopeless®	Standard	12.513	Standard API Drift	7.10 in (180.2 mm)	1.60 in (40.8 mm)	12.689 in (322.28 mm)	12.711 in (322.88 mm)	14.000 in (355.60 mm)	14.140 in (359.14 mm)	7.10 in (180.2 mm)	2.09 in (53.0 mm)	14.359 in (364.70 mm)	14.555 in (369.70 mm)	12.823 in (325.70 mm)	12.846 in (326.30 mm)	15.024 in (381.60 mm)	15.062 in (382.60 mm)	14.989 in (380.70 mm)	15.027 in (381.70 mm)	85.0	14.815 in (376.30 mm)	14.854 in (377.30 mm)
14.000	94.80	0.656	TenarisHydril Blue® Dopeless®	Standard	12.500	Standard API Drift	7.10 in (180.2 mm)	1.60 in (40.8 mm)	12.677 in (321.98 mm)	12.700 in (322.58 mm)	14.000 in (355.60 mm)	14.140 in (359.14 mm)	7.10 in (180.2 mm)	2.09 in (53.0 mm)	14.359 in (364.70 mm)	14.555 in (369.70 mm)	12.817 in (325.54 mm)	12.839 in (326.12 mm)	15.036 in (381.90 mm)	15.074 in (382.90 mm)	15.000 in (381.00 mm)	15.039 in (382.00 mm)	85.0	14.823 in (376.50 mm)	14.862 in (377.50 mm)
14.000	99.30	0.688	TenarisHydril Blue® Dopeless®	Standard	12.437	Standard API Drift	7.10 in (180.2 mm)	1.60 in (40.8 mm)	12.613 in (320.36 mm)	12.635 in (320.94 mm)	14.000 in (355.60 mm)	14.140 in (359.14 mm)	7.10 in (180.2 mm)	2.09 in (53.0 mm)	14.359 in (364.70 mm)	14.555 in (369.70 mm)	12.782 in (324.66 mm)	12.805 in (325.24 mm)	15.091 in (383.30 mm)	15.129 in (384.30 mm)	15.056 in (382.40 mm)	15.094 in (383.40 mm)	85.0	14.871 in (377.70 mm)	14.909 in (378.70 mm)
14.000	100.00	0.700	TenarisHydril Blue® Dopeless®	Standard	12.413	Standard API Drift	7.10 in (180.2 mm)	1.60 in (40.8 mm)	12.589 in (319.74 mm)	12.611 in (320.34 mm)	14.000 in (355.60 mm)	14.140 in (359.14 mm)	7.10 in (180.2 mm)	2.09 in (53.0 mm)	14.359 in (364.70 mm)	14.555 in (369.70 mm)	12.769 in (324.32 mm)	12.792 in (324.92 mm)	15.115 in (383.90 mm)	15.153 in (384.90 mm)	15.075 in (382.90 mm)	15.114 in (383.90 mm)	85.0	14.886 in (378.10 mm)	14.925 in (379.10 mm)
14.000	104.20	0.734	TenarisHydril Blue® Dopeless®	Standard	12.344	Standard API Drift	7.10 in (180.2 mm)	1.60 in (40.8 mm)	12.521 in (318.02 mm)	12.543 in (318.60 mm)	14.000 in (355.60 mm)	14.140 in (359.14 mm)	7.10 in (180.2 mm)	2.09 in (53.0 mm)	14.359 in (364.70 mm)	14.555 in (369.70 mm)	12.732 in (323.40 mm)	12.755 in (323.98 mm)	15.174 in (385.40 mm)	15.212 in (386.40 mm)	15.130 in (384.30 mm)	15.169 in (385.30 mm)	85.0	14.938 in (379.40 mm)	14.976 in (380.40 mm)
14.000	106.00	0.750	TenarisHydril Blue® Dopeless®	Standard	12.313	Standard API Drift	7.10 in (180.2 mm)	1.60 in (40.8 mm)	12.489 in (317.20 mm)	12.511 in (317.80 mm)	14.000 in (355.60 mm)	14.140 in (359.14 mm)	7.10 in (180.2 mm)	2.09 in (53.0 mm)	14.359 in (364.70 mm)	14.555 in (369.70 mm)	12.715 in (322.96 mm)	12.738 in (323.54 mm)	15.201 in (386.10 mm)	15.240 in (387.10 mm)	15.158 in (385.00 mm)	15.196 in (386.00 mm)	85.0	14.961 in (380.00 mm)	15.000 in (381.00 mm)
14.000	110.00	0.772	TenarisHydril Blue® Dopeless®	Standard	12.269	Standard API Drift	7.10 in (180.2 mm)	1.60 in (40.8 mm)	12.445 in (316.08 mm)	12.467 in (316.68 mm)	14.000 in (355.60 mm)	14.140 in (359.14 mm)	7.10 in (180.2 mm)	2.09 in (53.0 mm)	14.359 in (364.70 mm)	14.555 in (369.70 mm)	12.691 in (322.36 mm)	12.714 in (322.94 mm)	15.237 in (387.00 mm)	15.275 in (388.00 mm)	15.193 in (385.90 mm)	15.232 in (386.90 mm)	85.0	14.989 in (380.70 mm)	15.027 in (381.70 mm)
14.000	111.00	0.779	TenarisHydril Blue® Dopeless®	Standard	12.254	Standard API Drift	7.10 in (180.2 mm)	1.60 in (40.8 mm)	12.431 in (315.74 mm)	12.453 in (316.32 mm)	14.000 in (355.60 mm)	14.140 in (359.14 mm)	7.10 in (180.2 mm)	2.09 in (53.0 mm)	14.359 in (364.70 mm)	14.555 in (369.70 mm)	12.682 in (322.12 mm)	12.705 in (322.72 mm)	15.249 in (388.30 mm)	15.287 in (389.30 mm)	15.205 in (386.20 mm)	15.244 in (387.20 mm)	85.0	15.000 in (381.00 mm)	15.039 in (382.00 mm)
14.000	112.60	0.797	TenarisHydril Blue® Dopeless®	Standard	12.219	Standard API Drift	7.10 in (180.2 mm)	1.60 in (40.8 mm)	12.395 in (314.82 mm)	12.417 in (315.40 mm)	14.000 in (355.60 mm)	14.140 in (359.14 mm)	7.10 in (180.2 mm)	2.09 in (53.0 mm)	14.359 in (364.70 mm)	14.555 in (369.70 mm)	12.665 in (321.68 mm)	12.687 in (322.26 mm)	15.280 in (388.10 mm)	15.318 in (389.10 mm)	15.233 in (386.90 mm)	15.271 in (387.90 mm)	85.0	15.024 in (381.60 mm)	15.062 in (382.60 mm)
14.000	114.00	0.800	TenarisHydril Blue® Dopeless®	Standard	12.213	Standard API Drift	7.10 in (180.2 mm)	1.60 in (40.8 mm)	12.389 in (314.66 mm)	12.411 in (315.26 mm)	14.000 in (355.60 mm)	14.140 in (359.14 mm)	7.10 in (180.2 mm)	2.09 in (53.0 mm)	14.359 in (364.70 mm)	14.555 in (369.70 mm)	12.662 in (321.60 mm)	12.684 in (322.18 mm)	15.284 in (388.20 mm)	15.322 in (389.20 mm)	15.241 in (387.10 mm)	15.279 in (388.10 mm)	85.0	15.032 in (381.80 mm)	15.070 in (382.80 mm)
14.000	114.00	0.800	TenarisHydril Blue® Dopeless®	Standard	12.250	Special Drift	7.10 in (180.2 mm)	1.60 in (40.8 mm)	12.389 in (314.66 mm)	12.411 in (315.26 mm)	14.000 in (355.60 mm)	14.140 in (359.14 mm)	7.10 in (180.2 mm)	2.09 in (53.0 mm)	14.359 in (364.70 mm)	14.555 in (369.70 mm)	12.662 in (321.60 mm)	12.684 in (322.18 mm)	15.284 in (388.20 mm)	15.322 in (389.20 mm)	15.241 in (387.10 mm)	15.279 in (388.10 mm)	85.0	15.032 in (381.80 mm)	15.070 in (382.80 mm)

Dimensions provided do not include length required for tongs for making up assemblies. Please take this into consideration when designing and machining your accessory.  
 BLANK OD and ID: The nominal blank ODs and IDs in the Pin Diameters and Box Diameters columns are finished product dimensions. When this minimum material is supplied, the blank OD and the blank ID must be true to each other within 0.010" TIR (Total Indicator Reading).  
 BLANK Min Length includes 0.02" (0.5mm) extra material for facing.  
 Contact Tenaris Manufacturing Services at blankingdimensions@tenaris.com for details.  
 These Blanking Dimensions are NOT applicable For Handling & lifting plug, HydroTest Caps & HydroTest Plugs.  
 N/A: Not Applicable

Yellow - Shaded corresponds to modified from previous document revision.