

TenarisHydril Wedge 521® Blanking Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, recopied, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections B.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request therefore. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyrighted 2020 as an unpublished work. ALL RIGHTS RESERVED.

CONNECTION							PIN						BOX					
SIZE (IN)	WEIGHT (LB/FT)	WALL (IN)	PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH	RECUT LENGTH	INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH	RECUT LENGTH	INSIDE DIAMETER		OUTSIDE DIAMETER - MACHINED OD	
							MIN	MIN	MIN	MAX	MIN	MAX	MIN	MIN	MIN	MAX	MIN	MAX*
4.000	9.50	0.226	TenarisHydril Wedge 521®	Standard	3.423	Standard API Drift	4.47 in (113.6 mm)	1.77 in (45.0 mm)	3.447 in (87.56 mm)	3.467 in (88.06 mm)	3.990 in (101.36 mm)	4.010 in (101.84 mm)	4.40 in (111.6 mm)	1.77 in (45.0 mm)	3.538 in (89.88 mm)	3.558 in (90.36 mm)	4.093 in (103.98 mm)	4.113 in (104.46 mm)
4.000	11.00	0.262	TenarisHydril Wedge 521®	Standard	3.351	Standard API Drift	4.47 in (113.6 mm)	1.77 in (45.0 mm)	3.391 in (86.14 mm)	3.411 in (86.62 mm)	3.990 in (101.36 mm)	4.010 in (101.84 mm)	4.40 in (111.6 mm)	1.77 in (45.0 mm)	3.466 in (88.04 mm)	3.486 in (88.54 mm)	4.152 in (105.48 mm)	4.172 in (105.96 mm)
4.000	11.60	0.286	TenarisHydril Wedge 521®	Standard	3.303	Standard API Drift	4.47 in (113.6 mm)	1.77 in (45.0 mm)	3.343 in (84.92 mm)	3.363 in (85.42 mm)	3.990 in (101.36 mm)	4.010 in (101.84 mm)	4.40 in (111.6 mm)	1.77 in (45.0 mm)	3.418 in (86.82 mm)	3.438 in (87.32 mm)	4.190 in (106.44 mm)	4.210 in (106.92 mm)
4.500	9.50	0.205	TenarisHydril Wedge 521®	Standard	3.965	Standard API Drift	3.60 in (91.4 mm)	1.63 in (41.4 mm)	4.030 in (102.38 mm)	4.050 in (102.86 mm)	4.490 in (114.06 mm)	4.510 in (114.54 mm)	3.52 in (89.4 mm)	1.63 in (41.4 mm)	4.080 in (103.64 mm)	4.100 in (104.14 mm)	4.619 in (117.34 mm)	4.639 in (117.82 mm)
4.500	10.50	0.224	TenarisHydril Wedge 521®	Standard	3.927	Standard API Drift	4.47 in (113.6 mm)	1.77 in (45.0 mm)	3.966 in (100.74 mm)	3.986 in (101.24 mm)	4.490 in (114.06 mm)	4.510 in (114.54 mm)	4.40 in (111.6 mm)	1.77 in (45.0 mm)	4.042 in (102.68 mm)	4.062 in (103.16 mm)	4.641 in (117.90 mm)	4.661 in (118.38 mm)
4.500	11.00	0.237	TenarisHydril Wedge 521®	Standard	3.901	Standard API Drift	4.47 in (113.6 mm)	1.77 in (45.0 mm)	3.966 in (100.74 mm)	3.986 in (101.24 mm)	4.490 in (114.06 mm)	4.510 in (114.54 mm)	4.40 in (111.6 mm)	1.77 in (45.0 mm)	4.016 in (102.02 mm)	4.036 in (102.50 mm)	4.663 in (118.46 mm)	4.683 in (118.94 mm)
4.500	11.60	0.250	TenarisHydril Wedge 521®	Standard	3.875	Standard API Drift	4.47 in (113.6 mm)	1.77 in (45.0 mm)	3.950 in (100.34 mm)	3.970 in (100.82 mm)	4.490 in (114.06 mm)	4.510 in (114.54 mm)	4.40 in (111.6 mm)	1.77 in (45.0 mm)	3.990 in (101.36 mm)	4.010 in (101.84 mm)	4.685 in (119.00 mm)	4.705 in (119.50 mm)
4.500	12.60	0.271	TenarisHydril Wedge 521®	Standard	3.833	Standard API Drift	4.47 in (113.6 mm)	1.77 in (45.0 mm)	3.908 in (99.28 mm)	3.928 in (99.76 mm)	4.490 in (114.06 mm)	4.510 in (114.54 mm)	4.40 in (111.6 mm)	1.77 in (45.0 mm)	3.948 in (100.28 mm)	3.968 in (100.78 mm)	4.719 in (119.88 mm)	4.739 in (120.36 mm)
4.500	13.50	0.290	TenarisHydril Wedge 521®	Standard	3.795	Standard API Drift	4.47 in (113.6 mm)	1.77 in (45.0 mm)	3.870 in (98.30 mm)	3.890 in (98.80 mm)	4.490 in (114.06 mm)	4.510 in (114.54 mm)	4.40 in (111.6 mm)	1.77 in (45.0 mm)	3.910 in (99.32 mm)	3.930 in (99.82 mm)	4.749 in (120.64 mm)	4.769 in (121.12 mm)
5.000	13.00	0.253	TenarisHydril Wedge 521®	Standard	4.369	Standard API Drift	4.47 in (113.6 mm)	1.79 in (45.6 mm)	4.434 in (112.64 mm)	4.454 in (113.12 mm)	4.990 in (126.76 mm)	5.010 in (127.24 mm)	4.40 in (111.6 mm)	1.79 in (45.6 mm)	4.484 in (113.90 mm)	4.504 in (114.40 mm)	5.175 in (131.46 mm)	5.195 in (131.94 mm)
5.000	15.00	0.296	TenarisHydril Wedge 521®	Standard	4.283	Standard API Drift	4.47 in (113.6 mm)	1.79 in (45.6 mm)	4.348 in (110.44 mm)	4.368 in (110.94 mm)	4.990 in (126.76 mm)	5.010 in (127.24 mm)	4.40 in (111.6 mm)	1.79 in (45.6 mm)	4.398 in (111.72 mm)	4.418 in (112.20 mm)	5.245 in (133.24 mm)	5.265 in (133.72 mm)
5.000	18.00	0.362	TenarisHydril Wedge 521®	Standard	4.151	Standard API Drift	4.47 in (113.6 mm)	1.79 in (45.6 mm)	4.216 in (107.10 mm)	4.236 in (107.58 mm)	4.990 in (126.76 mm)	5.010 in (127.24 mm)	4.40 in (111.6 mm)	1.79 in (45.6 mm)	4.266 in (108.36 mm)	4.286 in (108.86 mm)	5.349 in (135.88 mm)	5.369 in (136.36 mm)
5.000	18.00	0.362	TenarisHydril Wedge 521®	ExxonMobil CTP3	4.151	Standard API Drift	4.47 in (113.6 mm)	1.79 in (45.6 mm)	4.216 in (107.10 mm)	4.236 in (107.58 mm)	4.990 in (126.76 mm)	5.010 in (127.24 mm)	4.40 in (111.6 mm)	1.79 in (45.6 mm)	4.266 in (108.36 mm)	4.286 in (108.86 mm)	5.349 in (135.88 mm)	5.369 in (136.36 mm)
5.500	14.00	0.244	TenarisHydril Wedge 521®	Standard	4.887	Standard API Drift	4.47 in (113.6 mm)	1.79 in (45.6 mm)	4.937 in (125.40 mm)	4.957 in (125.90 mm)	5.490 in (139.46 mm)	5.510 in (139.94 mm)	4.40 in (111.6 mm)	1.79 in (45.6 mm)	5.002 in (127.06 mm)	5.022 in (127.54 mm)	5.650 in (143.52 mm)	5.670 in (144.00 mm)
5.500	15.50	0.275	TenarisHydril Wedge 521®	Standard	4.825	Standard API Drift	4.47 in (113.6 mm)	1.79 in (45.6 mm)	4.890 in (124.22 mm)	4.910 in (124.70 mm)	5.490 in (139.46 mm)	5.510 in (139.94 mm)	4.40 in (111.6 mm)	1.79 in (45.6 mm)	4.940 in (125.48 mm)	4.960 in (125.98 mm)	5.703 in (144.86 mm)	5.723 in (145.36 mm)
5.500	17.00	0.304	TenarisHydril Wedge 521®	Standard	4.767	Standard API Drift	4.47 in (113.6 mm)	1.79 in (45.6 mm)	4.832 in (122.74 mm)	4.852 in (123.24 mm)	5.490 in (139.46 mm)	5.510 in (139.94 mm)	4.40 in (111.6 mm)	1.79 in (45.6 mm)	4.882 in (124.02 mm)	4.902 in (124.50 mm)	5.751 in (146.08 mm)	5.771 in (146.58 mm)
5.500	17.00	0.304	TenarisHydril Wedge 521®	ExxonMobil CTP3	4.767	Standard API Drift	4.47 in (113.6 mm)	1.79 in (45.6 mm)	4.832 in (122.74 mm)	4.852 in (123.24 mm)	5.490 in (139.46 mm)	5.510 in (139.94 mm)	4.40 in (111.6 mm)	1.79 in (45.6 mm)	4.882 in (124.02 mm)	4.902 in (124.50 mm)	5.751 in (146.08 mm)	5.771 in (146.58 mm)
5.500	20.00	0.361	TenarisHydril Wedge 521®	Standard	4.653	Standard API Drift	4.47 in (113.6 mm)	1.79 in (45.6 mm)	4.718 in (119.84 mm)	4.738 in (120.34 mm)	5.490 in (139.46 mm)	5.510 in (139.94 mm)	4.40 in (111.6 mm)	1.79 in (45.6 mm)	4.768 in (121.12 mm)	4.788 in (121.60 mm)	5.842 in (148.40 mm)	5.862 in (148.88 mm)
5.500	23.00	0.415	TenarisHydril Wedge 521®	Standard	4.545	Standard API Drift	4.47 in (113.6 mm)	1.79 in (45.6 mm)	4.610 in (117.10 mm)	4.630 in (117.60 mm)	5.490 in (139.46 mm)	5.510 in (139.94 mm)	4.40 in (111.6 mm)	1.79 in (45.6 mm)	4.660 in (118.38 mm)	4.680 in (118.86 mm)	5.926 in (150.54 mm)	5.946 in (151.02 mm)
5.500	23.00	0.415	TenarisHydril Wedge 521®	ExxonMobil CTP ALL	4.545	Standard API Drift	4.47 in (113.6 mm)	1.79 in (45.6 mm)	4.610 in (117.10 mm)	4.630 in (117.60 mm)	5.490 in (139.46 mm)	5.510 in (139.94 mm)	4.40 in (111.6 mm)	1.79 in (45.6 mm)	4.660 in (118.38 mm)	4.680 in (118.86 mm)	5.926 in (150.54 mm)	5.946 in (151.02 mm)
6.625	20.00	0.288	TenarisHydril Wedge 521®	Standard	5.924	Standard API Drift	4.56 in (115.8 mm)	2.03 in (51.6 mm)	5.989 in (152.14 mm)	6.009 in (152.62 mm)	6.615 in (168.04 mm)	6.635 in (168.52 mm)	4.49 in (114.0 mm)	2.03 in (51.6 mm)	6.039 in (153.40 mm)	6.059 in (153.88 mm)	6.808 in (172.94 mm)	6.828 in (173.42 mm)
6.625	24.00	0.352	TenarisHydril Wedge 521®	Standard	5.796	Standard API Drift	4.56 in (115.8 mm)	2.03 in (51.6 mm)	5.861 in (148.88 mm)	5.881 in (149.36 mm)	6.615 in (168.04 mm)	6.635 in (168.52 mm)	4.49 in (114.0 mm)	2.03 in (51.6 mm)	5.911 in (150.14 mm)	5.931 in (150.64 mm)	6.915 in (175.66 mm)	6.935 in (176.14 mm)
6.625	24.00	0.352	TenarisHydril Wedge 521®	ExxonMobil CTP ALL	5.796	Standard API Drift	4.56 in (115.8 mm)	2.03 in (51.6 mm)	5.861 in (148.88 mm)	5.881 in (149.36 mm)	6.615 in (168.04 mm)	6.635 in (168.52 mm)	4.49 in (114.0 mm)	2.03 in (51.6 mm)	5.911 in (150.14 mm)	5.931 in (150.64 mm)	6.915 in (175.66 mm)	6.935 in (176.14 mm)

TenarisHydril Wedge 521® Blanking Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, recopied, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections B.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request therefore. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyrighted 2020 as an unpublished work. ALL RIGHTS RESERVED.

CONNECTION							PIN						BOX					
SIZE (IN)	WEIGHT (LB/FT)	WALL (IN)	PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH	RECUT LENGTH	INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH	RECUT LENGTH	INSIDE DIAMETER		OUTSIDE DIAMETER - MACHINED OD	
							MIN	MIN	MIN	MAX	MIN	MAX	MIN	MIN	MIN	MAX	MIN	MAX*
6.625	28.00	0.417	TenarisHydril Wedge 521®	Standard	5.666	Standard API Drift	4.56 in (115.8 mm)	2.03 in (51.6 mm)	5.731 in (145.58 mm)	5.751 in (146.06 mm)	6.615 in (168.04 mm)	6.635 in (168.52 mm)	4.49 in (114.0 mm)	2.03 in (51.6 mm)	5.781 in (146.84 mm)	5.801 in (147.34 mm)	7.019 in (178.30 mm)	7.039 in (178.78 mm)
6.625	32.00	0.475	TenarisHydril Wedge 521®	Standard	5.550	Standard API Drift	4.56 in (115.8 mm)	2.03 in (51.6 mm)	5.615 in (142.64 mm)	5.635 in (143.12 mm)	6.615 in (168.04 mm)	6.635 in (168.52 mm)	4.49 in (114.0 mm)	2.03 in (51.6 mm)	5.665 in (143.90 mm)	5.685 in (144.38 mm)	7.110 in (180.60 mm)	7.130 in (181.10 mm)
6.625	32.00	0.475	TenarisHydril Wedge 521®	ExxonMobil CTP ALL	5.550	Standard API Drift	4.56 in (115.8 mm)	2.03 in (51.6 mm)	5.615 in (142.64 mm)	5.635 in (143.12 mm)	6.615 in (168.04 mm)	6.635 in (168.52 mm)	4.49 in (114.0 mm)	2.03 in (51.6 mm)	5.665 in (143.90 mm)	5.685 in (144.38 mm)	7.110 in (180.60 mm)	7.130 in (181.10 mm)
7.000	20.00	0.272	TenarisHydril Wedge 521®	Standard	6.331	Standard API Drift	4.56 in (115.8 mm)	2.03 in (51.6 mm)	6.371 in (161.84 mm)	6.391 in (162.32 mm)	6.990 in (177.56 mm)	7.010 in (178.04 mm)	4.49 in (114.0 mm)	2.03 in (51.6 mm)	6.446 in (163.74 mm)	6.466 in (164.22 mm)	7.138 in (181.32 mm)	7.158 in (181.80 mm)
7.000	23.00	0.317	TenarisHydril Wedge 521®	Standard	6.250	Alternative API Drift	4.56 in (115.8 mm)	2.03 in (51.6 mm)	6.281 in (159.54 mm)	6.301 in (160.04 mm)	6.990 in (177.56 mm)	7.010 in (178.04 mm)	4.49 in (114.0 mm)	2.03 in (51.6 mm)	6.356 in (161.46 mm)	6.376 in (161.94 mm)	7.215 in (183.28 mm)	7.235 in (183.76 mm)
7.000	23.00	0.317	TenarisHydril Wedge 521®	ExxonMobil CTP ALL	6.250	Standard API Drift	4.56 in (115.8 mm)	2.03 in (51.6 mm)	6.281 in (159.54 mm)	6.301 in (160.04 mm)	6.990 in (177.56 mm)	7.010 in (178.04 mm)	4.49 in (114.0 mm)	2.03 in (51.6 mm)	6.356 in (161.46 mm)	6.376 in (161.94 mm)	7.215 in (183.28 mm)	7.235 in (183.76 mm)
7.000	26.00	0.362	TenarisHydril Wedge 521®	Standard	6.151	Standard API Drift	4.56 in (115.8 mm)	2.03 in (51.6 mm)	6.191 in (157.26 mm)	6.211 in (157.74 mm)	6.990 in (177.56 mm)	7.010 in (178.04 mm)	4.49 in (114.0 mm)	2.03 in (51.6 mm)	6.266 in (159.16 mm)	6.286 in (159.66 mm)	7.290 in (185.18 mm)	7.310 in (185.66 mm)
7.000	26.00	0.362	TenarisHydril Wedge 521®	ExxonMobil CTP3	6.151	Standard API Drift	4.56 in (115.8 mm)	2.03 in (51.6 mm)	6.191 in (157.26 mm)	6.211 in (157.74 mm)	6.990 in (177.56 mm)	7.010 in (178.04 mm)	4.49 in (114.0 mm)	2.03 in (51.6 mm)	6.266 in (159.16 mm)	6.286 in (159.66 mm)	7.290 in (185.18 mm)	7.310 in (185.66 mm)
7.000	29.00	0.408	TenarisHydril Wedge 521®	Standard	6.059	Standard API Drift	4.56 in (115.8 mm)	2.03 in (51.6 mm)	6.099 in (154.92 mm)	6.119 in (155.42 mm)	6.990 in (177.56 mm)	7.010 in (178.04 mm)	4.49 in (114.0 mm)	2.03 in (51.6 mm)	6.174 in (156.82 mm)	6.194 in (157.32 mm)	7.365 in (187.08 mm)	7.385 in (187.56 mm)
7.000	32.00	0.453	TenarisHydril Wedge 521®	Standard	6.000	Alternative API Drift	4.56 in (115.8 mm)	2.03 in (51.6 mm)	6.040 in (153.42 mm)	6.060 in (153.92 mm)	6.990 in (177.56 mm)	7.010 in (178.04 mm)	4.49 in (114.0 mm)	2.03 in (51.6 mm)	6.084 in (154.54 mm)	6.104 in (155.04 mm)	7.437 in (188.90 mm)	7.457 in (189.40 mm)
7.625	26.40	0.328	TenarisHydril Wedge 521®	Standard	6.844	Standard API Drift	4.56 in (115.8 mm)	2.03 in (51.6 mm)	6.884 in (174.86 mm)	6.904 in (175.36 mm)	7.615 in (193.44 mm)	7.635 in (193.92 mm)	4.49 in (114.0 mm)	2.03 in (51.6 mm)	6.959 in (176.76 mm)	6.979 in (177.26 mm)	7.858 in (199.60 mm)	7.878 in (200.10 mm)
7.625	29.70	0.375	TenarisHydril Wedge 521®	Standard	6.750	Standard API Drift	4.56 in (115.8 mm)	2.03 in (51.6 mm)	6.790 in (172.48 mm)	6.810 in (172.96 mm)	7.615 in (193.44 mm)	7.635 in (193.92 mm)	4.49 in (114.0 mm)	2.03 in (51.6 mm)	6.865 in (174.38 mm)	6.885 in (174.86 mm)	7.937 in (201.60 mm)	7.957 in (202.10 mm)
7.625	33.70	0.430	TenarisHydril Wedge 521®	Standard	6.640	Standard API Drift	4.56 in (115.8 mm)	2.03 in (51.6 mm)	6.680 in (169.68 mm)	6.700 in (170.18 mm)	7.615 in (193.44 mm)	7.635 in (193.92 mm)	4.49 in (114.0 mm)	2.03 in (51.6 mm)	6.755 in (171.58 mm)	6.775 in (172.08 mm)	8.027 in (203.90 mm)	8.047 in (204.38 mm)
7.625	39.00	0.500	TenarisHydril Wedge 521®	Standard	6.500	Standard API Drift	4.56 in (115.8 mm)	2.03 in (51.6 mm)	6.540 in (166.12 mm)	6.560 in (166.62 mm)	7.615 in (193.44 mm)	7.635 in (193.92 mm)	4.49 in (114.0 mm)	2.03 in (51.6 mm)	6.615 in (168.04 mm)	6.635 in (168.52 mm)	8.138 in (206.72 mm)	8.158 in (207.20 mm)
7.625	51.20	0.687	TenarisHydril Wedge 521®	Standard	6.126	Standard API Drift	5.81 in (147.6 mm)	1.93 in (49.2 mm)	6.166 in (156.62 mm)	6.186 in (157.12 mm)	7.615 in (193.44 mm)	7.635 in (193.92 mm)	5.76 in (146.4 mm)	1.93 in (49.2 mm)	6.241 in (158.54 mm)	6.261 in (159.02 mm)	8.070 in (204.98 mm)	8.090 in (205.48 mm)
7.625	52.80	0.712	TenarisHydril Wedge 521®	Standard	6.076	Standard API Drift	5.81 in (147.6 mm)	1.93 in (49.2 mm)	6.116 in (155.36 mm)	6.136 in (155.84 mm)	7.615 in (193.44 mm)	7.635 in (193.92 mm)	5.76 in (146.4 mm)	1.93 in (49.2 mm)	6.191 in (157.26 mm)	6.211 in (157.74 mm)	8.070 in (204.98 mm)	8.090 in (205.48 mm)
8.625	32.00	0.352	TenarisHydril Wedge 521®	Standard	7.875	Alternative API Drift	4.56 in (115.8 mm)	2.03 in (51.6 mm)	7.914 in (201.02 mm)	7.934 in (201.52 mm)	8.615 in (218.84 mm)	8.635 in (219.32 mm)	4.49 in (114.0 mm)	2.03 in (51.6 mm)	7.911 in (200.94 mm)	7.931 in (201.44 mm)	8.879 in (225.54 mm)	8.899 in (226.02 mm)
8.625	36.00	0.400	TenarisHydril Wedge 521®	Standard	7.700	Standard API Drift	4.56 in (115.8 mm)	2.03 in (51.6 mm)	7.740 in (196.60 mm)	7.760 in (197.10 mm)	8.615 in (218.84 mm)	8.635 in (219.32 mm)	4.49 in (114.0 mm)	2.03 in (51.6 mm)	7.815 in (198.52 mm)	7.835 in (199.00 mm)	8.960 in (227.60 mm)	8.980 in (228.08 mm)
8.625	40.00	0.450	TenarisHydril Wedge 521®	Standard	7.625	Alternative API Drift	4.56 in (115.8 mm)	2.03 in (51.6 mm)	7.664 in (194.68 mm)	7.684 in (195.16 mm)	8.615 in (218.84 mm)	8.635 in (219.32 mm)	4.49 in (114.0 mm)	2.03 in (51.6 mm)	7.715 in (195.98 mm)	7.735 in (196.46 mm)	9.043 in (229.70 mm)	9.063 in (230.20 mm)
8.625	44.00	0.500	TenarisHydril Wedge 521®	Standard	7.500	Standard API Drift	4.56 in (115.8 mm)	2.03 in (51.6 mm)	7.540 in (191.52 mm)	7.560 in (192.02 mm)	8.615 in (218.84 mm)	8.635 in (219.32 mm)	4.49 in (114.0 mm)	2.03 in (51.6 mm)	7.615 in (193.44 mm)	7.635 in (193.92 mm)	9.124 in (231.76 mm)	9.144 in (232.24 mm)
9.625	36.00	0.352	TenarisHydril Wedge 521®	Standard	8.765	Standard API Drift	4.56 in (115.8 mm)	2.03 in (51.6 mm)	8.836 in (224.44 mm)	8.856 in (224.94 mm)	9.615 in (244.24 mm)	9.635 in (244.72 mm)	4.49 in (114.0 mm)	2.03 in (51.6 mm)	8.911 in (226.34 mm)	8.931 in (226.84 mm)	9.873 in (250.78 mm)	9.893 in (251.28 mm)
9.625	40.00	0.395	TenarisHydril Wedge 521®	Standard	8.750	Alternative API Drift	4.56 in (115.8 mm)	2.03 in (51.6 mm)	8.789 in (223.26 mm)	8.809 in (223.74 mm)	9.615 in (244.24 mm)	9.635 in (244.72 mm)	4.49 in (114.0 mm)	2.03 in (51.6 mm)	8.825 in (224.16 mm)	8.845 in (224.66 mm)	9.947 in (252.66 mm)	9.967 in (253.16 mm)
9.625	43.50	0.435	TenarisHydril Wedge 521®	Standard	8.599	Standard API Drift	4.56 in (115.8 mm)	2.03 in (51.6 mm)	8.670 in (220.22 mm)	8.690 in (220.72 mm)	9.615 in (244.24 mm)	9.635 in (244.72 mm)	4.49 in (114.0 mm)	2.03 in (51.6 mm)	8.745 in (222.14 mm)	8.765 in (222.62 mm)	10.015 in (254.40 mm)	10.035 in (254.88 mm)

TenarisHydril Wedge 521® Blanking Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, recopied, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections B.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request therefore. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyrighted 2020 as an unpublished work. ALL RIGHTS RESERVED.

CONNECTION							PIN						BOX					
SIZE (IN)	WEIGHT (LB/FT)	WALL (IN)	PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH	RECUT LENGTH	INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH	RECUT LENGTH	INSIDE DIAMETER		OUTSIDE DIAMETER - MACHINED OD	
							MIN	MIN	MIN	MAX	MIN	MAX	MIN	MIN	MIN	MAX	MIN	MAX*
9.625	47.00	0.472	TenarisHydril Wedge 521®	Standard	8.525	Standard API Drift	4.56 in (115.8 mm)	2.03 in (51.6 mm)	8.596 in (218.34 mm)	8.616 in (218.84 mm)	9.615 in (244.24 mm)	9.635 in (244.72 mm)	4.49 in (114.0 mm)	2.03 in (51.6 mm)	8.671 in (220.26 mm)	8.691 in (220.74 mm)	10.077 in (255.96 mm)	10.097 in (256.46 mm)
9.625	53.50	0.545	TenarisHydril Wedge 521®	Standard	8.500	Alternative API Drift	4.56 in (115.8 mm)	2.03 in (51.6 mm)	8.525 in (216.54 mm)	8.545 in (217.04 mm)	9.615 in (244.24 mm)	9.635 in (244.72 mm)	4.49 in (114.0 mm)	2.03 in (51.6 mm)	8.525 in (216.54 mm)	8.545 in (217.04 mm)	10.196 in (258.98 mm)	10.216 in (259.48 mm)
10.750	40.50	0.350	TenarisHydril Wedge 521®	Standard	9.894	Standard API Drift	4.99 in (126.8 mm)	2.22 in (56.2 mm)	9.965 in (253.12 mm)	9.985 in (253.60 mm)	10.740 in (272.80 mm)	10.760 in (273.30 mm)	4.93 in (125.2 mm)	2.22 in (56.2 mm)	10.040 in (255.02 mm)	10.060 in (255.52 mm)	10.853 in (275.68 mm)	10.873 in (276.16 mm)
10.750	45.50	0.400	TenarisHydril Wedge 521®	Standard	9.875	Alternative API Drift	4.99 in (126.8 mm)	2.22 in (56.2 mm)	9.916 in (251.88 mm)	9.936 in (252.36 mm)	10.740 in (272.80 mm)	10.760 in (273.30 mm)	4.93 in (125.2 mm)	2.22 in (56.2 mm)	9.940 in (252.48 mm)	9.960 in (252.98 mm)	10.940 in (277.88 mm)	10.960 in (278.38 mm)
10.750	51.00	0.450	TenarisHydril Wedge 521®	Standard	9.694	Standard API Drift	4.99 in (126.8 mm)	2.22 in (56.2 mm)	9.765 in (248.04 mm)	9.785 in (248.52 mm)	10.740 in (272.80 mm)	10.760 in (273.30 mm)	4.93 in (125.2 mm)	2.22 in (56.2 mm)	9.840 in (249.94 mm)	9.860 in (250.44 mm)	11.027 in (280.10 mm)	11.047 in (280.58 mm)
10.750	55.50	0.495	TenarisHydril Wedge 521®	Standard	9.625	Alternative API Drift	5.81 in (147.6 mm)	1.95 in (49.6 mm)	9.675 in (245.76 mm)	9.695 in (246.24 mm)	10.740 in (272.80 mm)	10.760 in (273.30 mm)	5.76 in (146.4 mm)	1.95 in (49.6 mm)	9.750 in (247.66 mm)	9.770 in (248.14 mm)	11.000 in (279.40 mm)	11.020 in (279.90 mm)
10.750	60.70	0.545	TenarisHydril Wedge 521®	Standard	9.504	Standard API Drift	5.81 in (147.6 mm)	1.95 in (49.6 mm)	9.575 in (243.22 mm)	9.595 in (243.70 mm)	10.740 in (272.80 mm)	10.760 in (273.30 mm)	5.76 in (146.4 mm)	1.95 in (49.6 mm)	9.650 in (245.12 mm)	9.670 in (245.60 mm)	11.084 in (281.54 mm)	11.104 in (282.04 mm)
10.750	65.70	0.595	TenarisHydril Wedge 521®	Standard	9.500	Special Drift	5.81 in (147.6 mm)	1.95 in (49.6 mm)	9.541 in (242.36 mm)	9.561 in (242.84 mm)	10.740 in (272.80 mm)	10.760 in (273.30 mm)	5.76 in (146.4 mm)	1.95 in (49.6 mm)	9.550 in (242.58 mm)	9.570 in (243.06 mm)	11.167 in (283.66 mm)	11.187 in (284.14 mm)
11.750	47.00	0.375	TenarisHydril Wedge 521®	Standard	10.844	Standard API Drift	4.99 in (126.8 mm)	2.22 in (56.2 mm)	10.915 in (277.26 mm)	10.935 in (277.74 mm)	11.740 in (298.20 mm)	11.760 in (298.70 mm)	4.93 in (125.2 mm)	2.22 in (56.2 mm)	10.990 in (279.16 mm)	11.010 in (279.64 mm)	11.882 in (301.82 mm)	11.902 in (302.30 mm)
11.750	54.00	0.435	TenarisHydril Wedge 521®	Standard	10.724	Standard API Drift	4.99 in (126.8 mm)	2.22 in (56.2 mm)	10.795 in (274.20 mm)	10.815 in (274.70 mm)	11.740 in (298.20 mm)	11.760 in (298.70 mm)	4.93 in (125.2 mm)	2.22 in (56.2 mm)	10.870 in (276.10 mm)	10.890 in (276.60 mm)	11.988 in (304.50 mm)	12.008 in (305.00 mm)
11.750	60.00	0.489	TenarisHydril Wedge 521®	Standard	10.625	Alternative API Drift	5.81 in (147.6 mm)	1.95 in (49.6 mm)	10.677 in (271.20 mm)	10.697 in (271.70 mm)	11.740 in (298.20 mm)	11.760 in (298.70 mm)	5.76 in (146.4 mm)	1.95 in (49.6 mm)	10.762 in (273.36 mm)	10.782 in (273.86 mm)	11.918 in (302.72 mm)	11.938 in (303.22 mm)
11.750	65.00	0.534	TenarisHydril Wedge 521®	Standard	10.625	Alternative API Drift	5.81 in (147.6 mm)	1.95 in (49.6 mm)	10.666 in (270.92 mm)	10.686 in (271.42 mm)	11.740 in (298.20 mm)	11.760 in (298.70 mm)	5.76 in (146.4 mm)	1.95 in (49.6 mm)	10.672 in (271.08 mm)	10.692 in (271.56 mm)	11.955 in (303.66 mm)	11.975 in (304.16 mm)
11.750	71.00	0.582	TenarisHydril Wedge 521®	Standard	10.430	Standard API Drift	5.81 in (147.6 mm)	1.95 in (49.6 mm)	10.491 in (266.48 mm)	10.511 in (266.96 mm)	11.740 in (298.20 mm)	11.760 in (298.70 mm)	5.76 in (146.4 mm)	1.95 in (49.6 mm)	10.576 in (268.64 mm)	10.596 in (269.12 mm)	12.115 in (307.74 mm)	12.135 in (308.22 mm)
11.750	73.60	0.609	TenarisHydril Wedge 521®	Standard	10.376	Standard API Drift	5.81 in (147.6 mm)	1.95 in (49.6 mm)	10.437 in (265.10 mm)	10.457 in (265.60 mm)	11.740 in (298.20 mm)	11.760 in (298.70 mm)	5.76 in (146.4 mm)	1.95 in (49.6 mm)	10.522 in (267.26 mm)	10.542 in (267.76 mm)	12.160 in (308.88 mm)	12.180 in (309.36 mm)
11.750	80.50	0.672	TenarisHydril Wedge 521®	Standard	10.250	Standard API Drift	5.81 in (147.6 mm)	1.95 in (49.6 mm)	10.311 in (261.90 mm)	10.331 in (262.40 mm)	11.740 in (298.20 mm)	11.760 in (298.70 mm)	5.76 in (146.4 mm)	1.95 in (49.6 mm)	10.396 in (264.06 mm)	10.416 in (264.56 mm)	12.264 in (311.52 mm)	12.284 in (312.00 mm)
11.875	71.80	0.582	TenarisHydril Wedge 521®	Standard	10.625	Special Drift	5.81 in (147.6 mm)	1.95 in (49.6 mm)	10.666 in (270.92 mm)	10.686 in (271.42 mm)	11.865 in (301.38 mm)	11.885 in (301.86 mm)	5.76 in (146.4 mm)	1.95 in (49.6 mm)	10.701 in (271.82 mm)	10.721 in (272.30 mm)	12.259 in (311.38 mm)	12.279 in (311.88 mm)
13.375	54.50	0.380	TenarisHydril Wedge 521®	Standard	12.459	Standard API Drift	5.49 in (139.6 mm)	2.54 in (64.4 mm)	12.530 in (318.28 mm)	12.550 in (318.76 mm)	13.365 in (339.48 mm)	13.385 in (339.96 mm)	5.44 in (138.2 mm)	2.54 in (64.4 mm)	12.605 in (320.18 mm)	12.625 in (320.66 mm)	13.521 in (343.44 mm)	13.541 in (343.94 mm)
13.375	61.00	0.430	TenarisHydril Wedge 521®	Standard	12.359	Standard API Drift	5.49 in (139.6 mm)	2.54 in (64.4 mm)	12.430 in (315.74 mm)	12.450 in (316.22 mm)	13.365 in (339.48 mm)	13.385 in (339.96 mm)	5.44 in (138.2 mm)	2.54 in (64.4 mm)	12.505 in (316.64 mm)	12.525 in (317.12 mm)	13.610 in (345.70 mm)	13.630 in (346.20 mm)
13.375	68.00	0.480	TenarisHydril Wedge 521®	Standard	12.259	Standard API Drift	5.49 in (139.6 mm)	2.54 in (64.4 mm)	12.330 in (313.20 mm)	12.350 in (313.68 mm)	13.365 in (339.48 mm)	13.385 in (339.96 mm)	5.44 in (138.2 mm)	2.54 in (64.4 mm)	12.405 in (315.10 mm)	12.425 in (315.58 mm)	13.697 in (347.92 mm)	13.717 in (348.40 mm)
13.375	72.00	0.514	TenarisHydril Wedge 521®	Standard	12.250	Alternative API Drift	5.49 in (139.6 mm)	2.54 in (64.4 mm)	12.307 in (312.60 mm)	12.327 in (313.10 mm)	13.365 in (339.48 mm)	13.385 in (339.96 mm)	5.44 in (138.2 mm)	2.54 in (64.4 mm)	12.337 in (313.36 mm)	12.357 in (313.86 mm)	13.756 in (349.42 mm)	13.776 in (349.90 mm)
13.375	77.00	0.550	TenarisHydril Wedge 521®	Standard	12.119	Standard API Drift	6.43 in (163.4 mm)	2.37 in (60.0 mm)	12.190 in (309.64 mm)	12.210 in (310.12 mm)	13.365 in (339.48 mm)	13.385 in (339.96 mm)	6.40 in (162.6 mm)	2.37 in (60.0 mm)	12.265 in (311.54 mm)	12.285 in (312.02 mm)	13.676 in (347.38 mm)	13.696 in (347.86 mm)
13.375	80.70	0.580	TenarisHydril Wedge 521®	Standard	12.059	Standard API Drift	6.43 in (163.4 mm)	2.37 in (60.0 mm)	12.130 in (308.12 mm)	12.150 in (308.60 mm)	13.365 in (339.48 mm)	13.385 in (339.96 mm)	6.40 in (162.6 mm)	2.37 in (60.0 mm)	12.205 in (310.02 mm)	12.225 in (310.50 mm)	13.728 in (348.70 mm)	13.748 in (349.18 mm)
13.375	85.00	0.608	TenarisHydril Wedge 521®	Standard	12.003	Standard API Drift	6.43 in (163.4 mm)	2.37 in (60.0 mm)	12.074 in (306.68 mm)	12.094 in (307.18 mm)	13.365 in (339.48 mm)	13.385 in (339.96 mm)	6.40 in (162.6 mm)	2.37 in (60.0 mm)	12.149 in (308.60 mm)	12.169 in (309.08 mm)	13.775 in (349.90 mm)	13.795 in (350.38 mm)

TenarisHydril Wedge 521® Blanking Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, recopied, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections B.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request therefore. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyrighted 2020 as an unpublished work. ALL RIGHTS RESERVED.

CONNECTION							PIN						BOX					
SIZE (IN)	WEIGHT (LB/FT)	WALL (IN)	PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH	RECUT LENGTH	INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH	RECUT LENGTH	INSIDE DIAMETER		OUTSIDE DIAMETER - MACHINED OD	
							MIN	MIN	MIN	MAX	MIN	MAX	MIN	MIN	MIN	MAX	MIN	MAX*
13.375	86.00	0.625	TenarisHydril Wedge 521®	Standard	11.969	Standard API Drift	6.43 in (163.4 mm)	2.37 in (60.0 mm)	12.040 in (305.82 mm)	12.060 in (306.32 mm)	13.365 in (339.48 mm)	13.385 in (339.96 mm)	6.40 in (162.6 mm)	2.37 in (60.0 mm)	12.115 in (307.74 mm)	12.135 in (308.22 mm)	13.804 in (350.64 mm)	13.824 in (351.12 mm)
13.500	81.40	0.580	TenarisHydril Wedge 521®	Standard	12.250	Special Drift	6.43 in (163.4 mm)	2.37 in (60.0 mm)	12.305 in (312.56 mm)	12.325 in (313.04 mm)	13.490 in (342.66 mm)	13.510 in (343.14 mm)	6.40 in (162.6 mm)	2.37 in (60.0 mm)	12.330 in (313.20 mm)	12.350 in (313.68 mm)	13.930 in (353.84 mm)	13.950 in (354.32 mm)
13.625	88.20	0.625	TenarisHydril Wedge 521®	Standard	12.250	Special Drift	6.43 in (163.4 mm)	2.37 in (60.0 mm)	12.295 in (312.30 mm)	12.315 in (312.80 mm)	13.615 in (345.84 mm)	13.635 in (346.32 mm)	6.40 in (162.6 mm)	2.37 in (60.0 mm)	12.365 in (314.08 mm)	12.385 in (314.56 mm)	13.930 in (353.84 mm)	13.950 in (354.32 mm)
15.000	77.50	0.500	TenarisHydril Wedge 521®	Standard	13.812	Standard API Drift	5.49 in (139.6 mm)	2.56 in (65.0 mm)	13.865 in (352.18 mm)	13.885 in (352.66 mm)	14.990 in (380.76 mm)	15.010 in (381.24 mm)	5.44 in (138.2 mm)	2.56 in (65.0 mm)	13.990 in (355.36 mm)	14.010 in (355.84 mm)	15.139 in (384.54 mm)	15.159 in (385.02 mm)
16.000	65.00	0.375	TenarisHydril Wedge 521®	Standard	15.062	Standard API Drift	5.49 in (139.6 mm)	2.56 in (65.0 mm)	15.112 in (383.86 mm)	15.132 in (384.34 mm)	15.990 in (406.16 mm)	16.010 in (406.64 mm)	5.44 in (138.2 mm)	2.56 in (65.0 mm)	15.240 in (387.10 mm)	15.260 in (387.60 mm)	16.115 in (409.34 mm)	16.135 in (409.82 mm)
16.000	75.00	0.438	TenarisHydril Wedge 521®	Standard	14.936	Standard API Drift	5.49 in (139.6 mm)	2.56 in (65.0 mm)	15.039 in (382.00 mm)	15.059 in (382.48 mm)	15.990 in (406.16 mm)	16.010 in (406.64 mm)	5.44 in (138.2 mm)	2.56 in (65.0 mm)	15.114 in (383.90 mm)	15.134 in (384.40 mm)	16.145 in (410.10 mm)	16.165 in (410.58 mm)
16.000	84.00	0.495	TenarisHydril Wedge 521®	Standard	14.822	Standard API Drift	5.49 in (139.6 mm)	2.56 in (65.0 mm)	14.925 in (379.10 mm)	14.945 in (379.60 mm)	15.990 in (406.16 mm)	16.010 in (406.64 mm)	5.44 in (138.2 mm)	2.56 in (65.0 mm)	15.000 in (381.00 mm)	15.020 in (381.50 mm)	16.247 in (412.68 mm)	16.267 in (413.18 mm)
16.000	84.00	0.495	TenarisHydril Wedge 521®	ExxonMobil CTP3	14.822	Standard API Drift	5.49 in (139.6 mm)	2.56 in (65.0 mm)	14.925 in (379.10 mm)	14.945 in (379.60 mm)	15.990 in (406.16 mm)	16.010 in (406.64 mm)	5.44 in (138.2 mm)	2.56 in (65.0 mm)	15.000 in (381.00 mm)	15.020 in (381.50 mm)	16.247 in (412.68 mm)	16.267 in (413.18 mm)
16.000	84.80	0.500	TenarisHydril Wedge 521®	Standard	14.812	Standard API Drift	5.49 in (139.6 mm)	2.56 in (65.0 mm)	14.915 in (378.86 mm)	14.935 in (379.34 mm)	15.990 in (406.16 mm)	16.010 in (406.64 mm)	5.44 in (138.2 mm)	2.56 in (65.0 mm)	14.990 in (380.76 mm)	15.010 in (381.24 mm)	16.256 in (412.92 mm)	16.276 in (413.40 mm)
16.000	94.50	0.562	TenarisHydril Wedge 521®	Standard	14.750	Special Drift	5.49 in (139.6 mm)	2.56 in (65.0 mm)	14.799 in (375.90 mm)	14.819 in (376.40 mm)	15.990 in (406.16 mm)	16.010 in (406.64 mm)	5.44 in (138.2 mm)	2.56 in (65.0 mm)	14.866 in (377.60 mm)	14.886 in (378.10 mm)	16.402 in (416.62 mm)	16.422 in (417.10 mm)
16.000	95.00	0.566	TenarisHydril Wedge 521®	Standard	14.750	Special Drift	5.49 in (139.6 mm)	2.56 in (65.0 mm)	14.799 in (375.90 mm)	14.819 in (376.40 mm)	15.990 in (406.16 mm)	16.010 in (406.64 mm)	5.44 in (138.2 mm)	2.56 in (65.0 mm)	14.858 in (377.40 mm)	14.878 in (377.90 mm)	16.387 in (416.24 mm)	16.407 in (416.72 mm)
16.000	96.00	0.575	TenarisHydril Wedge 521®	Standard	14.750	Special Drift	5.49 in (139.6 mm)	2.56 in (65.0 mm)	14.799 in (375.90 mm)	14.819 in (376.40 mm)	15.990 in (406.16 mm)	16.010 in (406.64 mm)	5.44 in (138.2 mm)	2.56 in (65.0 mm)	14.840 in (376.94 mm)	14.860 in (377.44 mm)	16.387 in (416.24 mm)	16.407 in (416.72 mm)
16.000	109.00	0.656	TenarisHydril Wedge 521®	Standard	14.500	Standard API Drift	6.43 in (163.4 mm)	2.39 in (60.6 mm)	14.603 in (370.92 mm)	14.623 in (371.42 mm)	15.990 in (406.16 mm)	16.010 in (406.64 mm)	6.40 in (162.6 mm)	2.39 in (60.6 mm)	14.678 in (372.84 mm)	14.698 in (373.32 mm)	16.455 in (417.96 mm)	16.475 in (418.46 mm)
16.000	118.00	0.715	TenarisHydril Wedge 521®	Standard	14.382	Standard API Drift	6.43 in (163.4 mm)	2.39 in (60.6 mm)	14.485 in (367.92 mm)	14.505 in (368.42 mm)	15.990 in (406.16 mm)	16.010 in (406.64 mm)	6.40 in (162.6 mm)	2.39 in (60.6 mm)	14.560 in (369.84 mm)	14.580 in (370.32 mm)	16.556 in (420.54 mm)	16.576 in (421.02 mm)
16.125	95.60	0.566	TenarisHydril Wedge 521®	Standard	14.805	Standard API Drift	5.49 in (139.6 mm)	2.56 in (65.0 mm)	14.854 in (377.30 mm)	14.874 in (377.78 mm)	16.115 in (409.34 mm)	16.135 in (409.82 mm)	5.44 in (138.2 mm)	2.56 in (65.0 mm)	14.983 in (380.58 mm)	15.003 in (381.06 mm)	16.417 in (417.00 mm)	16.437 in (417.48 mm)
17.000	77.50	0.438	TenarisHydril Wedge 521®	Standard	16.000	Special Drift	5.49 in (139.6 mm)	2.61 in (66.2 mm)	16.057 in (407.86 mm)	16.077 in (408.34 mm)	16.990 in (431.56 mm)	17.010 in (432.04 mm)	5.44 in (138.2 mm)	2.61 in (66.2 mm)	16.114 in (409.30 mm)	16.134 in (409.80 mm)	17.187 in (436.56 mm)	17.207 in (437.04 mm)
17.000	88.10	0.500	TenarisHydril Wedge 521®	Standard	15.812	Standard API Drift	5.49 in (139.6 mm)	2.61 in (66.2 mm)	15.915 in (404.26 mm)	15.935 in (404.74 mm)	16.990 in (431.56 mm)	17.010 in (432.04 mm)	5.44 in (138.2 mm)	2.61 in (66.2 mm)	15.990 in (406.16 mm)	16.010 in (406.64 mm)	17.298 in (439.38 mm)	17.318 in (439.86 mm)
17.000	151.00	0.875	TenarisHydril Wedge 521®	Standard	15.062	Standard API Drift	6.72 in (170.6 mm)	2.05 in (52.0 mm)	15.165 in (385.20 mm)	15.185 in (385.68 mm)	16.990 in (431.56 mm)	17.010 in (432.04 mm)	6.68 in (169.6 mm)	2.05 in (52.0 mm)	15.240 in (387.10 mm)	15.260 in (387.60 mm)	17.663 in (448.66 mm)	17.683 in (449.14 mm)
17.875	93.50	0.500	TenarisHydril Wedge 521®	Standard	16.772	Special Drift	5.49 in (139.6 mm)	2.61 in (66.2 mm)	16.833 in (427.56 mm)	16.853 in (428.06 mm)	17.865 in (453.78 mm)	17.885 in (454.26 mm)	5.44 in (138.2 mm)	2.61 in (66.2 mm)	16.865 in (428.38 mm)	16.885 in (428.86 mm)	17.990 in (456.96 mm)	18.010 in (457.44 mm)
17.875	93.50	0.500	TenarisHydril Wedge 521®	ExxonMobil CTP3	16.772	Special Drift	5.49 in (139.6 mm)	2.61 in (66.2 mm)	16.833 in (427.56 mm)	16.853 in (428.06 mm)	17.865 in (453.78 mm)	17.885 in (454.26 mm)	5.44 in (138.2 mm)	2.61 in (66.2 mm)	16.865 in (428.38 mm)	16.885 in (428.86 mm)	17.990 in (456.96 mm)	18.010 in (457.44 mm)
17.875	105.00	0.562	TenarisHydril Wedge 521®	Standard	16.563	Standard API Drift	6.43 in (163.4 mm)	2.42 in (61.6 mm)	16.618 in (422.10 mm)	16.638 in (422.60 mm)	17.865 in (453.78 mm)	17.885 in (454.26 mm)	6.40 in (162.6 mm)	2.42 in (61.6 mm)	16.741 in (425.24 mm)	16.761 in (425.72 mm)	17.990 in (456.96 mm)	18.010 in (457.44 mm)
17.875	107.00	0.575	TenarisHydril Wedge 521®	Standard	16.563	Special Drift	6.43 in (163.4 mm)	2.42 in (61.6 mm)	16.618 in (422.10 mm)	16.638 in (422.60 mm)	17.865 in (453.78 mm)	17.885 in (454.26 mm)	6.40 in (162.6 mm)	2.42 in (61.6 mm)	16.715 in (424.58 mm)	16.735 in (425.06 mm)	17.990 in (456.96 mm)	18.010 in (457.44 mm)
17.875	106.34	0.575	TenarisHydril Wedge 521®	CHEVRON	16.630	Special Drift	6.43 in (163.4 mm)	2.42 in (61.6 mm)	16.685 in (423.80 mm)	16.705 in (424.30 mm)	17.865 in (453.78 mm)	17.885 in (454.26 mm)	6.40 in (162.6 mm)	2.42 in (61.6 mm)	16.715 in (424.58 mm)	16.735 in (425.06 mm)	17.990 in (456.96 mm)	18.010 in (457.44 mm)

TenarisHydril Wedge 521® Blanking Dimensions



This document as well as the information or data contained herein are confidential and shall not be copied, recopied, reproduced, transmitted, disclosed or distributed to others or otherwise used for any purpose without the express, prior and written permission of Tenaris Connections B.V. and/or Hydril Company. This document as well as the information or data contained herein are the exclusive property of Tenaris, and are to be returned upon request therefore. All rights in proprietary and novel features of the subject matter are expressly reserved by Tenaris. Recipient's agreement to the foregoing is indicated by acceptance of this document. Copyrighted 2020 as an unpublished work. ALL RIGHTS RESERVED.

SIZE (IN)	WEIGHT (LB/FT)	WALL (IN)	CONNECTION				PIN						BOX					
			PRODUCT	TAG	DRIFT (IN)	DRIFT TYPE	LENGTH	RECUT LENGTH	INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH	RECUT LENGTH	INSIDE DIAMETER		OUTSIDE DIAMETER - MACHINED OD	
							MIN	MIN	MIN	MAX	MIN	MAX	MIN	MIN	MIN	MAX	MIN	MAX*
17.875	121.00	0.650	TenarisHydril Wedge 521®	Standard	16.500	Special Drift	6.43 in (163.4 mm)	2.42 in (61.6 mm)	16.555 in (420.50 mm)	16.575 in (421.00 mm)	17.865 in (453.78 mm)	17.885 in (454.26 mm)	6.40 in (162.6 mm)	2.42 in (61.6 mm)	16.565 in (420.76 mm)	16.585 in (421.24 mm)	18.010 in (457.46 mm)	18.030 in (457.96 mm)
18.000	94.00	0.500	TenarisHydril Wedge 521®	Standard	16.812	Standard API Drift	5.49 in (139.6 mm)	2.61 in (66.2 mm)	16.873 in (428.58 mm)	16.893 in (429.08 mm)	17.990 in (456.96 mm)	18.010 in (457.44 mm)	5.44 in (138.2 mm)	2.61 in (66.2 mm)	16.990 in (431.56 mm)	17.010 in (432.04 mm)	18.050 in (458.48 mm)	18.070 in (458.96 mm)
18.000	94.00	0.500	TenarisHydril Wedge 521®	ExxonMobil CTP3	16.812	Standard API Drift	5.49 in (139.6 mm)	2.61 in (66.2 mm)	16.873 in (428.58 mm)	16.893 in (429.08 mm)	17.990 in (456.96 mm)	18.010 in (457.44 mm)	5.44 in (138.2 mm)	2.61 in (66.2 mm)	16.990 in (431.56 mm)	17.010 in (432.04 mm)	18.050 in (458.48 mm)	18.070 in (458.96 mm)
18.000	105.00	0.562	TenarisHydril Wedge 521®	Standard	16.688	Standard API Drift	5.49 in (139.6 mm)	2.61 in (66.2 mm)	16.749 in (425.44 mm)	16.769 in (425.92 mm)	17.990 in (456.96 mm)	18.010 in (457.44 mm)	5.44 in (138.2 mm)	2.61 in (66.2 mm)	16.866 in (428.40 mm)	16.886 in (428.90 mm)	18.125 in (460.38 mm)	18.145 in (460.88 mm)
18.625	87.50	0.435	TenarisHydril Wedge 521®	Standard	17.567	Standard API Drift	5.49 in (139.6 mm)	2.61 in (66.2 mm)	17.628 in (447.76 mm)	17.648 in (448.24 mm)	18.615 in (472.84 mm)	18.635 in (473.32 mm)	5.44 in (138.2 mm)	2.61 in (66.2 mm)	17.745 in (450.74 mm)	17.765 in (451.22 mm)	18.844 in (478.64 mm)	18.864 in (479.14 mm)
18.625	94.50	0.460	TenarisHydril Wedge 521®	Standard	17.517	Standard API Drift	5.49 in (139.6 mm)	2.61 in (66.2 mm)	17.578 in (446.50 mm)	17.598 in (446.98 mm)	18.615 in (472.84 mm)	18.635 in (473.32 mm)	5.44 in (138.2 mm)	2.61 in (66.2 mm)	17.695 in (449.46 mm)	17.715 in (449.96 mm)	18.889 in (479.80 mm)	18.909 in (480.28 mm)
18.625	97.70	0.486	TenarisHydril Wedge 521®	Standard	17.466	Standard API Drift	5.49 in (139.6 mm)	2.61 in (66.2 mm)	17.561 in (446.06 mm)	17.581 in (446.54 mm)	18.615 in (472.84 mm)	18.635 in (473.32 mm)	5.44 in (138.2 mm)	2.61 in (66.2 mm)	17.643 in (448.14 mm)	17.663 in (448.64 mm)	18.936 in (480.98 mm)	18.956 in (481.48 mm)
18.625	97.70	0.486	TenarisHydril Wedge 521®	Standard	17.500	Special Drift	5.49 in (139.6 mm)	2.61 in (66.2 mm)	17.561 in (446.06 mm)	17.581 in (446.54 mm)	18.615 in (472.84 mm)	18.635 in (473.32 mm)	5.44 in (138.2 mm)	2.61 in (66.2 mm)	17.643 in (448.14 mm)	17.663 in (448.64 mm)	18.936 in (480.98 mm)	18.956 in (481.48 mm)
18.625	100.00	0.500	TenarisHydril Wedge 521®	Standard	17.438	Standard API Drift	5.49 in (139.6 mm)	2.61 in (66.2 mm)	17.561 in (446.06 mm)	17.581 in (446.54 mm)	18.615 in (472.84 mm)	18.635 in (473.32 mm)	5.44 in (138.2 mm)	2.61 in (66.2 mm)	17.615 in (447.44 mm)	17.635 in (447.92 mm)	18.961 in (481.62 mm)	18.981 in (482.10 mm)
18.625	100.00	0.500	TenarisHydril Wedge 521®	Standard	17.500	Special Drift	5.49 in (139.6 mm)	2.61 in (66.2 mm)	17.561 in (446.06 mm)	17.581 in (446.54 mm)	18.615 in (472.84 mm)	18.635 in (473.32 mm)	5.44 in (138.2 mm)	2.61 in (66.2 mm)	17.615 in (447.44 mm)	17.635 in (447.92 mm)	18.961 in (481.62 mm)	18.981 in (482.10 mm)
18.625	101.00	0.510	TenarisHydril Wedge 521®	Standard	17.500	Special Drift	5.49 in (139.6 mm)	2.61 in (66.2 mm)	17.561 in (446.06 mm)	17.581 in (446.54 mm)	18.615 in (472.84 mm)	18.635 in (473.32 mm)	5.44 in (138.2 mm)	2.61 in (66.2 mm)	17.595 in (446.92 mm)	17.615 in (447.42 mm)	18.979 in (482.08 mm)	18.999 in (482.56 mm)
18.625	101.00	0.510	TenarisHydril Wedge 521®	ExxonMobil CTP3	17.500	Special Drift	5.49 in (139.6 mm)	2.61 in (66.2 mm)	17.561 in (446.06 mm)	17.581 in (446.54 mm)	18.615 in (472.84 mm)	18.635 in (473.32 mm)	5.44 in (138.2 mm)	2.61 in (66.2 mm)	17.595 in (446.92 mm)	17.615 in (447.42 mm)	18.979 in (482.08 mm)	18.999 in (482.56 mm)
18.625	109.35	0.563	TenarisHydril Wedge 521®	Standard	17.311	Standard API Drift	6.43 in (163.4 mm)	2.42 in (61.6 mm)	17.377 in (441.38 mm)	17.397 in (441.88 mm)	18.615 in (472.84 mm)	18.635 in (473.32 mm)	6.40 in (162.6 mm)	2.42 in (61.6 mm)	17.489 in (444.24 mm)	17.509 in (444.72 mm)	18.938 in (481.04 mm)	18.958 in (481.52 mm)
18.625	112.00	0.579	TenarisHydril Wedge 521®	Standard	17.279	Standard API Drift	6.43 in (163.4 mm)	2.42 in (61.6 mm)	17.345 in (440.58 mm)	17.365 in (441.06 mm)	18.615 in (472.84 mm)	18.635 in (473.32 mm)	6.40 in (162.6 mm)	2.42 in (61.6 mm)	17.457 in (443.42 mm)	17.477 in (443.90 mm)	18.966 in (481.74 mm)	18.986 in (482.24 mm)

Dimensions provided do not include length required for tongs for making up assemblies. Please take this into consideration when designing and machining your accessory.

BLANK OD and ID: The nominal blank ODs and IDs in the Pin Diameters and Box Diameters columns are finished product dimensions. When this minimum material is supplied, the blank OD and the blank ID must be true to each other within 0.010" TIR (Total Indicator Reading).

BLANK Min Length includes 0.02" (0.5mm) extra material for facing.

Contact Tenaris Manufacturing Services at blankingdimensions@tenaris.com for details.

These Blanking Dimensions are NOT applicable For Handling & lifting plug, HydroTest Caps & HydroTest Plugs.

N/A: Not Applicable

*For OEM Max OD is not restricted.

Yellow - Shaded corresponds to modified from previous document revision.